

Notes 8

cat

- **Usage**
 - Displays the contents of a file.
- **Formula**
 - `cat + option + files to display`
- **Examples**
 - Display the content of a file located in ~/Documents/sample_files/.
 - `cat + ~/Documents/sample_files/Code/helloWorld.py`
 - Display the content of a file with line numbers.
 - `cat + -n + ~/Documents/sample_files/Code/helloWorld.py`
 - Display the content of a file including non printing characters and line endings.
 - `cat + -A + ~/Documents/sample_files/Code/helloWorld.py`

tac

- **Usage**
 - Used for displaying the content of a file in reverse order, in other words it concatenates files and displays the output of the concatenation.
- **Formula**
 - `tac + option + files(s) to display`
- **Examples**
 - Display the content of a file located in ~/Documents/sample_files/ in reverse order.
 - `tac + ~/Documents/sample_files/Code/helloWorld.py`
 - Display the content of multiple files in reverse order.
 - `tac + ~/Documents/sample_files/Code/helloWorld.py +
~/Documents/sample_files/Code/helloWorld.sh`

head

- **Usage**
 - Displays the top N number of lines in a given file.
- **Formula**
 - `head + option + files`
- **Examples**
 - Display the first five lines of the multiple files.
 - `head + -n + 5 + Txt/{dracula,war-and-peace}.txt`
 - Display the first line of multiple files using wildcards.
 - `head + -n + 1 + Csv/*.csv Code/*.py`
 - Display the name of the file in the output.
 - `head + -v + -n + 7 + Json/joke.json`
 - Display a given number of bytes instead of lines.
 - `head + -c + 50 + Txt/dracula.txt`

tail

- **Usage**

- Displays the last N number of lines of a given file. If more than one file name is provided then data from each file is preceded by its file name.

- **Formula**

- `tail + option + file(s)`

- **Examples**

- Display the last 10 lines of a file.
 - `tail + ~/Documents/sample_files/`
- Display the last 5 lines of a file.
 - `tail + -5 + ~/Documents/sample_files/`
- Display a given number of lines of the output of a given command.
 - `ls + -l + ~/cis106/ + | + tail + -n + 2`

cut

- **Usage**

- Used to extract a specific section of each line of a file and display it to the screen.

- **Formula**

- `cut + option + file(s)`

- **Examples**

- Display a list of all the users in your system.
 - `cut + -d + ':' + -f1 + /etc/passwd`
- Cut a range of bytes per line.
 - `cut + -b + 1-5 + usernames.txt`
- Cut a file excluding a given field.
 - `cut + -d + ',' + --complement + -s + -f3 + users.txt`

sort

- **Usage**

- The command is used for sorting files.

- **Formula**

- `sort + option + file`

- **Examples**

- Sort a file
 - `sort + users.lst`
- Sort by column number
 - `sort + -k + 2 + users.txt`
- Check if a file is sorted

- `sort + -c + sorted.lst`

WC

- **Usage**
 - Used for printing the number of lines, characters and bytes in a file.
- **Formula**
 - `wc + option + file(s)`
- **Examples**
 - Display the number of characters in a file.
 - `wc + -m + users.txt`
 - Display the number of lines in a file.
 - `wc + -l + users.txt`
 - Display the number words in a file.
 - `wc + -w + users.txt`