

SOCKET.IO



Agenda

2

- Implement connected oriented web applications
- Discuss techniques
- WebSocket Protocol
- Using Socket.IO

The Challenge: A Chat Application

3

- Polling is expensive
- Long polling is better but still expensive on busy server
- WebSocket is great but
 - ▣ Need modern browser
 - ▣ No built-in support inside Node.js

Web Socket Protocol

4

- Enables two-way communication between browser and server
- Does not rely on opening multiple HTTP connections
- Replacement for older techniques like long polling and forever frame
- A simple abstract over TCP socket
- A totally new application protocol
 - ▣ No HTTP headers
- Managed by IETF

Web Socket API

5

- A JavaScript API
- Is used by the browser to initiate a Web Socket communication with the server
- Is all about the **WebSocket** class
 - ▣ send
 - ▣ close
 - ▣ readyState
 - ▣ onopen, onmessage, onclose, onerror
- Managed by W3C

Getting Started

6

- Create a new **WebSocket** object
- Specify a URL and sub protocols (Optional)
 - ▣ Must use **ws** or **wss** protocols
- Register to **open** and **error** events

```
var ws = new WebSocket("ws://localhost:5481/socket/connect");

ws.onerror = function (e) {
    console.log("ERROR");
    console.log(e);
}

ws.onopen = function (e) {
    console.log("OEPN");
    console.log(e);
}
```

The Handshake

7

- Upon a WebSocket object creation the browser sends an **Upgrade** request to the server

```
GET http://localhost:5481/socket/connect HTTP/1.1
Upgrade: websocket
Connection: Upgrade
Host: localhost:5481
Origin: http://localhost:5481
Sec-WebSocket-Key: rHeA9NhKxIuFX85mxpT0fQ==
Sec-WebSocket-Version: 13
```

- Server must respond with appropriate headers

Server Response

8

```
HTTP/1.1 101 Switching Protocols  
Cache-Control: private  
Upgrade: websocket  
Server: Microsoft-IIS/8.0  
Sec-WebSocket-Accept: JLSwL1hPkGnb4q0J0nYz1957T7I=  
Connection: Upgrade
```

- After a successful handshake, the data transfer part starts
- This is a two-way communication channel where each side can, independently from the other, send data at will

Send and Receive Messages

9

- WebSocket object supports
 - ▣ **send** – Can only be used after **onopen** event was fired
 - ▣ **onmessage**

```
var ws = new WebSocket("ws://localhost:5481/api/socket/connect");

ws.onclose = function (e) {
    ...
}

ws.onopen = function (e) {
    ws.send(message);
}

ws.onmessage = function (e) {
    console.log("MESSAGE: " + e.data);
}
```

Framing

10

- ❑ WebSocket is message based protocol
- ❑ The data being sent by the client is considered a message
- ❑ A message consists of multiple frames
- ❑ Each frame has slight overhead over the original payload
 - ▣ 2 bytes – FIN + Opcode + Payload Length + More
 - ▣ 4 bytes – Masking key
 - ▣ Above is true only for messages ≤ 125 bytes

Socket.IO

11

- Real time bidirectional event based communication
- Supports browser & node platforms
- Uses WebSocket as the transport protocol
- Supports fallbacks
 - ▣ XHR
 - ▣ JSONP
 - ▣ Long Polling
- Must use Socket.IO on both sides

When to use

12

- ❑ Real time analytics
- ❑ Instant messaging
- ❑ Chat
- ❑ Binary streaming

Getting Started

13

- Socket.IO is composed of two parts
- **socket.io**: A server that integrates with Node.js
- **socket.io-client**: A client library that loads on the browser

Server Side

14

□ yarn add express socket.io

Socket.IO does
not connect
directly to
express

```
const express = require('express');
const http = require('http');
const socketIO = require('socket.io');
const path = require("path");

const app = express();
const server = http.Server(app);
const io = socketIO(server);

io.on('connection', function(socket) {
  console.log('A user connected');
});

server.listen(3000, function() {
  console.log('Serve is running on port 3000');
});
```

Client Side

15

- Include the client library
- Start using the global **io** object

```
<body>  
  <script src="socket.io-client/dist/socket.io.dev.js"></script>  
  <script>  
    var socket = io();  
    socket.emit('chat message', 'hello');  
  </script>  
</body>
```

Transmission Types

16

```
// unicast to current client  
socket.emit('message', 'hey there client');  
  
// broadcast to all clients including sender  
io.sockets.emit('message', 'hello everyone!');  
  
// short form, same thing  
io.emit('message', 'hello everyone!');  
  
// broadcast to all clients excluding sender  
socket.broadcast.emit('message', 'surprise party');  
  
// unicast by socketid  
io.to(socketid).emit('message', 'your eyes only');
```


Namespace

17

- Allows for grouping of connections
- By default all clients are part of the default namespace
- Define new namespace

```
const ns = io.of("/chat");  
ns.on('connection', function(socket){  
  socket.on('chat message', function(msg){  
    ns.emit('chat message', msg);  
  });  
});
```

```
var socket = io("/chat");
```

Server vs.
client

Rooms

18

- Within a namespace clients can join/leave rooms
- Rooms are automatically created when a socket join them
- Only the server can add a client to a room

```
ns.on('connection', function(socket){  
  console.log('a user connected', socket.id);  
  
  socket.join("room1");  
});
```

Rooms

19

- The server can decide to send messages only to a specific room

```
socket.on('chat message', function(msg){  
  ns.in("room1").emit('chat message', msg);  
});
```

- As before, the sender can be excluded

```
socket.on('chat message', function(msg){  
  socket.broadcast.to("room1").emit('chat message', msg);  
});
```

Query Clients

20

```
// all connected clients  
io.sockets.clients((err,clients)=>{});  
  
// all clients in namespace 'final-frontier'  
io.of('/final-frontier').clients((err,clients)=>{});  
  
// all users in namespace 'final-frontier' room 'spock'  
io.of('/final-frontier').in("room1").clients((err,clients)=>{});  
  
// all clients in room 'myroom'  
io.in("room1").clients((err,clients)=>{});
```

socket.id

21

- Every connected client has a unique id. For example,
`/chat#jFWs9corXp_9jOF3AAAA`
- Might change because of reconnection
- Can use it to maintain a “session” state table

Clustering

22

- ❑ IE < 11 does not support web socket
- ❑ Socket.IO will use long polling
- ❑ Must use sticky load balancing
- ❑ PM2 does not support that 😞
- ❑ Use fork_mode with different port per process and good balancer like Ngnix

Passing Event Between Nodes

23

- Assuming cluster configuration
- You want to broadcast event to everyone
- Need to implement some IPC infra
- Or use **socket.io-redis**

```
var io = require('socket.io')(3000);  
var redis = require('socket.io-redis');  
io.adapter(redis({ host: 'localhost', port: 6379 }));
```

Summary

24

- Very easy to use
- Not to be confused with WebSocket API