FACILITY TRANSLINK **MAIN** 00MSC **SUB** **IMC** 225405

Material/Process

LONGLIFE ANTIFREEZE

MEDIUM HAZARD

LIQUID

Supplier MAXOL LUBRICANTS LTD

Keyword Anti-Freeze

Contents

Full details of constituents not provided by supplier, Ethane-1,2-diol: 50 - 100%

Signal Word Warning

Exp Limit Ethane-1,2-diol 52mg/m3 Vap8hTWA 10mg/m3 Part8hTWA 104mg/m3 Vap15mSTEL

Health Hazards

May cause damage to organs through prolonged or repeated exposure if swallowed
Harmful if swallowed
Causes serious eye irritation
Causes skin irritation

Considerations

Method Pouring **Area** Outside **Exposure** Up to 1/2 hour per shift

MEDIUM ACUTE RISK - FULL EXPOSURE | **MEDIUM CHRONIC RISK - FULL EXPOSURE**

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY | **MEDIUM CHRONIC RISK**

Control Measures

Spillage

Ventilate area
Wear polythene or nitrile gloves
Suitable eye protection must be worn
Wear respiratory protection for large spills in poorly ventilated areas
Wear protective overalls & chemical proof footwear
Absorb in sand or inert absorbent material
Small spills - wipe up with cloth
Collect into a container, close lid
Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if appropriate

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
Ingestion - do not induce vomiting, wash out mouth with water
Ingestion - give plenty of water in sips, obtain immediate medical attention
Eye - rinse thoroughly with water for 20 minutes - take care not to affect uncontaminated eye. If irritation persists then consult a doctor
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Isolated small scale fire:
Water fog - carbon dioxide - powder - foam
Large fire: evacuate area, call fire brigade or follow site procedure
Wear self-contained breathing apparatus and protective clothing

Activity Comments

Date Printed 11/01/2024