

SUMMARY SHEET

ID# - 4279425

178398

cms.helpdesk@ecoonline.com

FACILITY

TRANSLINK

MAIN

CL

SUB

IMC

Material/Process

NO.21 TAR AND ADHESIVE REMOVER

MEDIUM HAZARD

LIQUID

AUTOGLYM Cleaner (Solvent)

Supplier Keyword

Contents

Naphtha (petroleum), hydrotreated heavy: 60 - 100%, Xylene: 10 - 30%, 1-butoxypropan-2-ol: 5 - 10%

Danger

Xylene 220mg/m3 8hTWA 441mg/m3 15mSTEL WEL, Naphtha (petroleum), hydrotreated heavy 800mg/m3 8hTWA

Signal Word

Exp Limit

Health Hazards

Flammable liquid and vapour

May be fatal if swallowed and enters airways

Causes serious eye irritation

May cause respiratory irritation

Causes skin irritation

May cause damage to organs through prolonged or repeated exposure

Potential for ototoxic effects that may cause hearing loss

May cause drowsiness or dizziness

Toxic to aquatic life with long lasting effects

Considerations

Method

Hand applying

Area

Inside Well Ventilated

Exposure

Up to 1/2 hour per shift

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK

KEEP SKIN COVERED

POLYTHENE OR VITON

BS EN166

WASH AFTER EXPOSURE

IF SOILED

FLAMMABLE / ACUTE

CLOSE ALL CONTAINERS

Sypol

Part of EcoOnline Global

Activity Comments

Date Printed 11/09/2023

Translink

Assessment Reviewed

11/09/2023

Next Review

11/09/2026

Latest SDS Reference

56

23/04/2015