

# Assignment 3 - WebAPI Documentation

Bogdan Alexandru Mezei (293137)

## Adult

An Adult object is sent back and forth as json.

Example:

```
{  
  "JobTitle": "Captain",  
  "ID": 0,  
  "FirstName": "Bogdan",  
  "LastName": "Mezei",  
  "HairColor": "Brown",  
  "EyeColor": "Brown",  
  "Age": 20,  
  "Weight": 75,  
  "Height": 190,  
  "Sex": "M"  
}
```

API	Request	Sub-path	Description	Exceptions
/adult	GET	/id:integer	Will return one Adult based on the ID.  Example: .../adult/3 .../adult/28	Will return error 404 if the adult with the specified ID does not exist.
			Will return the entire list of adults.  Example: .../adult	Will return code 500 internal server error if something fails.
	POST		Will add an Adult object to the list. Its ID will determine the sub-path.	Will return code 500 internal server error if something fails.
	DELETE	/id:integer	Will delete an existing Adult from the list. Provide the ID of the adult to be removed.  Example: .../adult/4	Will return error 404 if the adult with the specified ID does not exist.  Will return code 500 internal server error if something fails.

## User

A User object is sent back and forth as json.

Example:

```
{  
  "FirstName": "Bogdan",  
  "LastName": "Mezei",  
  "Username": "TrashPanda",  
  "Password": "12345",  
}
```

API	Request	Sub-path	Description	Exceptions
/user	GET		Will return the entire list of users.  Example: .../user	Will return code 500 internal server error if something fails.
	POST		Will add an User object to the list. Its ID will determine the sub-path.	Will return code 500 internal server error if something fails.