

P07. Cooperative Control in Eco-Driving of Electric Connected and Autonomous Vehicles in an Un-Signalized Urban Intersection

Vinith Kumar Lakshmanan; Antonio Sciarretta; Ouafae El Ganaoui-Mourlan 2022

AAC 2022 submission / arXiv version PDF pages: 8 Relevance: 81/100

1. 论文全景速览与核心贡献 / High-Level Overview & Core Contributions

研究背景与痛点 / Background & Pain Points

这篇论文位于“Eco-driving optimal speed profile”方向。对你的 JSSP-based Intersection Management 课题，它回答的是高层调度、低层轨迹平滑、安全过滤或真实验证中的一个关键子问题：如何让车辆在路口少停、少冲突、少能耗，同时保持在线可执行。

The paper belongs to the theme of Eco-driving optimal speed profile. For a JSSP-based intersection-management thesis, it illuminates one of the key layers: scheduling, smoothing, safety filtering, or real-world validation.

Narrower single-vehicle/eco-driving emphasis; less detail on high-level scheduling.

核心科学问题 / Core Scientific Question

在无信号交叉口协作中，如何用解析最优控制生成节能、少停顿的速度曲线？

How can Pontryagin-style optimal control generate energy-efficient speed profiles for cooperative CAVs at an unsignalized intersection?

科学贡献 / Scientific Contributions

- 方法贡献 (method contribution): Single-level eco-driving optimization solved with Pontryagin's Minimum Principle for electric CAV speed profiles at an unsignalized intersection.
- 安全/避碰贡献 (safety contribution): Analytical conflict cases and cooperation levels encode interaction safety among CAVs.
- 平滑/停止避免贡献 (smoothing contribution): Focuses directly on optimal speed profiles that reduce energy use and avoid inefficient stop-and-go behavior.
- 创新力度评判 (reviewer judgement): 理论清晰但范围较窄：对 smoother 目标函数很有价值，对高层调度贡献较少。

核心概念对照 / Core Concepts

中文概念	English Concept	Role / 学术作用
自动交叉口管理	Autonomous Intersection Management	把信号控制替换为车辆级调度与控制。
轨迹平滑	Trajectory Smoothing	减少急加减速、停车和能耗峰值。
安全约束	Safety Constraints	把碰撞风险写成距离、时间间隔或屏障函数。
Pontryagin minimum principle eco-driving	PMP 生态驾驶最优控制	该论文的核心方法族。

教材式学习路径 / Textbook–Style Study Path

- 第一遍先读首页截图、摘要与引言，确认研究问题和场景假设。
- 第二遍沿着技术路线图复现模型变量、约束和求解器输入输出。
- 第三遍逐节阅读 section deep reading，对照 PDF 截图检查公式、图表和实验。
- 第四遍只站在审稿人视角重读实验，判断 baseline、公平性、消融和鲁棒性。
- 最后把博士 checklist 写成自己的复现实验或论文拓展计划。

博士阅读 Checklist / Doctoral Reading Checklist

- 能否独立重写核心公式：PMP 速度规划问题 / PMP speed–profile optimal control，并解释每个符号的物理意义？
 - 能否画出输入–模型–算法–控制–验证的数据流程图？
 - 能否指出至少两个强假设，并说明它们在真实交通中何时失效？
 - 能否复述实验基准是否公平，指标是否覆盖效率、安全、能耗和计算时间？
 - 能否提出一个与自己 JSSP/RL/smooth 课题直接相连的拓展实验？
-

关键截图讲解 / PDF Snapshot Explanation

截图来自本地 PDF 的精选页面，用于学习定位和版面理解；请与原 PDF 平行阅读，不把截图视作全文替代。

arXiv:2206.12360v1 [eess.SY] 24 Jun 2022

Cooperative Control in Eco-Driving of Electric Connected and Autonomous Vehicles in an Un-Signalized Urban Intersection

Vinith Kumar Lakshmanan * Antonio Sclaretta **
Ounafe El Ganaoui-Mourlan **

* IEP Energies Nouvelles, Rueil-Malmaison, France (e-mail: name-middlename.surname@ipen.fr)

** IEP Energies Nouvelles, Rueil-Malmaison, France (e-mail: name.surname@ipen.fr)

AbstractThis paper addresses the problem of finding the optimal Eco-Driving (ED) speed profile of an electric connected and automated vehicle in an isolated urban un-signalized intersection. The problem is solved using Pontryagin's Minimum Principle (PMP) and analytical solutions are presented for various conflicts that occur in an intersection. Cooperation is also introduced amongst the CAVs as the ability to share intentions. Two levels of cooperation, namely the cooperative and non-cooperative ED algorithms are evaluated, in a simulation environment, for energy efficiency with Intelligent Driver Model as baseline.

KeywordsEco-driving, cooperation, nonlinear and optimal control, intersection

1. INTRODUCTION

The main goal of Eco-Driving (ED) is to adopt an energy-efficient driving technique and people motivated by this technique are often called hypemilers. In the past decade, ED has been formulated as an optimal control problem, where the vehicle speed is directly controlled or indirectly advised to the driver to minimize energy consumption over a certain horizon (Masami et al. (2016); Wang et al. (2014); Han et al. (2018); Dibi et al. (2011)). ED can be applied to several driving scenarios such as car-following, intersection crossing, eco-acceleration/deceleration, etc.

With the advent of Connected and Automated Vehicles (CAVs), ED can be enforced more easily than with human drivers. Furthermore, in a connected environment, the CAVs can communicate to cooperate amongst each other rather than compete against each other. Cooperation in what follows refers to the sharing of information and the willingness of the CAVs to coordinate their movement for the common good. Based on the amount of information shared and the coordination of movements, cooperation can be categorized into three types, i.e., non-cooperative, cooperative, and centralized cooperative schemes. In the non-cooperative scheme, each CAV selfishly optimizes for itself and shares only its instantaneous control action with its neighbors. In the cooperative scheme, each CAV selfishly optimizes for itself but shares its future intentions with the neighboring CAVs and in the centralized cooperative scheme, the control action of each CAV is such that it optimizes for the entire group. Control schemes of single-CAV optimization (i.e., non-cooperative and cooperative), often fall under the umbrella of decentralized optimization in literature. In this paper, two types of cooperation, namely the *non-cooperative* and *cooperative* schemes are applied to the *intersection crossing* ED scenario.

An intersection is a junction where two or more roads meet and are categorized into two-way, three-way, four-way intersections, roundabouts, etc. They can also be categorized based on traffic control technology as: signalized (traffic lights), stop, yield and un-signalized intersections. An intersection being a shared resource and CAVs wanting to use it simultaneously can cause conflicts leading to either rear-end or lateral collision. In this paper, we consider a single lane, isolated four-way un-signalized intersection. In the literature on un-signalized intersections, the area within the perimeter where CAVs can communicate with each other, or infrastructure is often called the Control Zone (CZ) and the region in the center, where vehicle paths cross, is called the Intersecting Zone (IZ). The lane in the CZ leading to and out of the IZ is called the entry lane and exit lane, respectively. With an intersection being a shared resource it poses two main challenges, namely, scheduling of the CAVs in the IZ and the continuous optimization, involving the motion planning of CAVs.

The scheduling problem determines the priority of CAVs at the intersection. Heuristic or rule-based methods such as First Come First Serve (FCFS) (Dowser and Stone (2008)) or First-In-First-Out (FIFO), right-before-left and nearest to the crossing point, etc. are often used in literature to schedule CAVs crossing an intersection. Scheduling problem can also be cast as an optimization problem with the objective to minimize travel time or energy consumption using tools such as Mixed Integer Linear Programming (MILP) (Jin et al. (2012); Bin Mohamed Nor and Nasirahwan (2019)). The second challenge, motion planning, involves generating paths or trajectories for the

longitudinal and lateral motion of the CAVs. The literature distinguishes path as having a spatial component and trajectory having a temporal component. A path is geometric set of points, $f(x, y, \dots) = 0$, to go from point a to point b and trajectory describes the evolution of path in time, $s(t)$. With a CAV following a predefined fixed path, the problem narrows down to finding the trajectory (i.e., velocity) with respect to a certain objective while respecting constraints such as vehicle dynamics, speed limits, and safety constraints. In our work, we considered a predefined schedule/crossing order and a fixed path.

A rich body of literature is available for intersection scheduling and motion planning. A comprehensive overview of the various heuristic and optimization methods employed can be found in (Rios-Torres and Mallikopoulos (2017); Chen and Englund (2016)). With a focus on trajectory optimization with respect to energy consumption, we review some of the works here. (Bichon and Rakha (2019)) proposes a problem formulation to minimize the trip time and the control effort of a CAV crossing an intersection. Pontryagin's Minimum Principle (PMP) is used to formulate the problem. The authors state that the problem, in theory, could be solved using PMP. However, owing to the difficulty in obtaining analytical solutions, the problem is solved using numerical discrete and convex optimization. Rear-end collision in the CZ is avoided by formulating a position-inequality constraint and lateral collision is avoided by modeling the entire IZ as a collision region. Collision region can also be modelled as a point on the fixed path of the vehicles allowing for more than one vehicle inside the IZ. The red dots in Fig. 1b represent a collision point. In the numerical Model Predictive Control (MPC) proposed by (Huh et al. (2018)), the cost functional directly captures the energy usage of an Electric Vehicle (EV) and the travel time. (Makarem and Gillet (2013); Campos et al. (2014); Kloock et al. (2019)) formulate a quadratic MPC seeking to minimize the control effort and the deviation from the reference velocity.

While numerical methods facilitate the use of non-linear models and complex formulations, analytical methods provide fast and explicable solutions. However, only a handful of research efforts have been made on obtaining analytical closed-form solutions in the optimal control framework of CAVs in an intersection. (Mallikopoulos et al. (2018)) presents a bi-level optimization problem for scheduling and trajectory of CAVs in an intersection without any turns. The upper-level optimization schedules the CAVs by maximizing the throughput under the FIFO policy. The lower-level problem minimizes acceleration, which the authors argue minimizes the transient engine operation and in turn the fuel consumption. With the optimization horizon of the lower-level problem only on the entry lane, the solution to this problem produces an optimal speed profile only until the start of IZ. The vehicles are restricted to a constant velocity thereafter through the intersection. In a follow-up work (Zhang and Constantinou (2019)), the authors extended the problem formulation to consider left and right turning vehicles. The authors present a bi-level optimization solely for the trajectory of the CAVs. Still, under FIFO policy, the upper-level problem has an optimization horizon only for the entry lane jointly minimizing travel time and accelerations. The arrival time

and velocity at the end of the entry lane are then used as input to the second optimization problem. The lower-level problem jointly reduces jolts and accelerations with an optimization horizon only for the IZ. The CAVs are restricted to constant velocity on the exit lane to avoid rear-end collision. The solution to the above formulation leads to one optimal speed profile on the entry lane and a second optimal speed profile inside the IZ followed by a constant velocity.

The main objective of the paper is to obtain analytical solutions to the ED problem of an electric CAV crossing an un-signalized intersection subject to safety constraints, and to explore the benefits of cooperation. The main contributions/ novelty of the paper can be summarised as follows. We formulate a single-level optimization problem to the ED intersection scenario with an optimization horizon that includes the entry lane, the IZ and the exit lane. The analytical objective function used captures directly the energy usage in an EV, and can deal with position and speed constraints, similar to what has already been studied (Lakshmanan et al. (2021a,b); Han et al. (2019)) and experimentally demonstrated (Nego et al. (2022)) for car-following. Cooperation is also introduced amongst the CAVs as the ability to share intentions and two levels of cooperation, namely the cooperative and non-cooperative ED algorithms, are evaluated for performance in terms of energy consumption.

The organization of the paper is as follows. In section 2, the intersection and vehicle model along with its assumptions are presented. The various conflicts in an intersection are also discussed. In section 3, the optimal control problem is formulated along with the various constraints and its solutions are presented. Section 4, details the algorithm and the cooperative nature of the vehicles. The simulation results and its discussions are presented in section 5.

2. INTERSECTION MODEL, VEHICLE MODEL AND CONFLICTS

This section describes the considered intersection and vehicle model along with its various assumptions. The various conflicts that occur in an intersection is also discussed.

2.1 Intersection Model

The intersection considered here is an isolated un-signalized four legged intersection with flat straight roads crossing at right angles to each other. Each leg of the intersection consists of two lanes with traffic flowing in opposite directions. The center of the intersection where two or more paths can intersect, i.e., cause a lateral collision is called the Intersecting Zone (IZ). The roads leading to and away from the IZ, of length l , are called the entry lane and exit lane respectively. The area around the IZ where CAVs can communicate with each other and a coordinator is called the Control Zone (CZ). The point where entry lane meets the IZ is called the Diverging Point (P) and the point where IZ meets the exit lane is called the Merging Point (M). Fig. 1 represents the intersection model considered in this paper.

建模或问题设定页 / Modeling or problem-setup page

p.2 · full_page

这张截图用于把笔记中的抽象概念拉回原论文页面，便于你平行阅读原文、公式、图表和实验设置。

This snapshot anchors the study note to the original PDF page so you can read the explanation alongside the source layout.

与当前课题的连接: Supports the smoothing objective terms for acceleration, energy proxy, and stop avoidance.

首页与摘要 / Title and abstract page

p.1 · full_page

这张截图用于把笔记中的抽象概念拉回原论文页面，便于你平行阅读原文、公式、图表和实验设置。

This snapshot anchors the study note to the original PDF page so you can read the explanation alongside the source layout.

与当前课题的连接： Supports the smoothing objective terms for acceleration, energy proxy, and stop avoidance.

建模或问题设定页 / Modeling or problem-setup page

p.2 · full_page

这张截图用于把笔记中的抽象概念拉回原论文页面，便于你平行阅读原文、公式、图表和实验设置。

This snapshot anchors the study note to the original PDF page so you can read the explanation alongside the source layout.

与当前课题的连接： Supports the smoothing objective terms for acceleration, energy proxy, and stop avoidance.




Figure 2. Four Basic Constraints in an Intersection.

where f , g , and R represent the tyre friction coefficient, gravitational constant and radius of the turn. The latter is different for left and right turning vehicles.

It now remains to obtain the optimal feedback control law $u_i(t)$ for each CAV satisfying the above constraints.

3. OPTIMAL CONTROL PROBLEM FORMULATION IN AN INTERSECTION

This section describes the Optimal Control Problem (OCP) formulation for a CAV i and the mathematical translation of the various conflicts previously discussed. The solution is obtained using Pontryagin's Minimum Principle (PMP).

3.1 Unconstrained Eco-Driving Problem

With the main objective of ED to minimize cumulative energy consumption over a trip and with our work focusing on EVs, the running cost is given by the electrochemical power from the battery $P_b(t)$ defined in (2). With only the main equations summarized here, the readers are referred to (Han et al. (2019); Scharretta and Vahidi (2020)) for a detailed derivation. The optimal control problem reads,

$$a_i(t) = \arg \min_{a_i(t)} \int_0^{T_i} p_b(a_i(t+k) + h) u_i(t+k) + p_i(a_i(t+k) + h)^2 dk \quad (4)$$

subject to state dynamics,

$$\dot{x}_i = v_i(t), \quad \dot{v}_i = a_i(t),$$

and Boundary Conditions (BC),

$$x_i(t_i), \quad v_i(t_i), \quad x_i(T_i) = D_i, \quad v_i(T_i) = V_i,$$

where $x_i(t)$ and $v_i(t)$ are the position and velocity at time t . The desired final time is denoted by T_i and D_i is the length of the path from the start of the entry lane to the end of the exit lane. The desired final speed is V_i . The solution of (4) yields a parabolic speed profile as a function of time,

$$v_i(t+k) = v_i(t) + \left(-\frac{4v_i(t)}{T_i} + \frac{2V_i}{T_i} + \frac{aD_i}{T_i^2} \right) k + \left(\frac{2v_i(t)}{T_i^2} - \frac{6V_i}{T_i^2} + \frac{3V_i^2}{T_i^2} \right) k^2, \quad k \in [0, T_i]. \quad (5)$$

and a cubic position profile as a function of time,

$$x_i(t+k) = x_i(t) + v_i(t)k + \left(-\frac{2v_i(t)}{T_i} - \frac{V_i}{T_i} + \frac{3D_i}{T_i^2} \right) k^2 + \left(\frac{v_i(t)}{T_i^2} - \frac{3D_i}{T_i^2} + \frac{V_i}{T_i^2} \right) k^3, \quad k \in [0, T_i]. \quad (6)$$

The associated energy consumption of the trip E_{E_i} a function of vehicle parameters p_b , p_i , h and boundary conditions, is given by

$$E_{E_i} = p_b h D_i + p_b \frac{V_i^2 - v_i^2(t)}{2} + p_i h^2 T_i + 2p_i h (V_i - v_i(t)) + 4p_i \left(\frac{3D_i^2}{T_i^3} - \frac{3D_i(v_i(t) + V_i)}{T_i^2} + \frac{v_i^2(t) + v_i(t)V_i + V_i^2}{T_i} \right). \quad (7)$$

3.2 Car-Following conflict/Sequential Conflict

Car-following conflict occurs when CAV i and an immediately preceding CAV $p \in CF_i(t)$ have the same path. Such a conflict leads to a potential rear-end collision without adjusting CAV i 's speed. A collision of such type is formulated as a position-inequality constraint. CAV p 's motion is predicted under the assumption of constant acceleration $a_p(t)$ for the entire horizon T_i ,

$$x_i(t+k) \leq x_p(t) + v_p(t)k + \frac{1}{2}a_p(t)k^2 - s_{\min}, \quad (8)$$

where $x_p(t)$, $v_p(t)$ and $a_p(t)$ are the position, velocity and acceleration of CAV p , while $s_{\min}$ denotes the constant safe minimum gap. In the rest of the paper, the term $x_p(t) - s_{\min}$ is lumped into a single term $x_p(t)$ for convenience. The car-following constraint is solved in (Han et al. (2018)) and the main equations are presented here. The optimal speed profile is given as

$$v_i(t+k) = v_i(t) + \left(a_p(t) + \frac{4}{\theta_i} (v_p(t) - v_i(t)) + \frac{\theta_i}{\theta_i^2} (x_p(t) - x_i(t)) \right) k - \left(\frac{\theta_i}{\theta_i^2} (x_p(t) - x_i(t)) \right) k^2, \quad k \in [0, \theta_i], \quad (9)$$

where θ_i denotes the contact time where the position constraint is met ($x_i(t+\theta_i) = x_p(t)$) and is found by solving the cubic equation

In the C-ED, CAV i determines if the higher prioritized vehicles present a conflict or not as soon as it enters the intersection. Cooperation is introduced in amongst CAVs as the ability to share the intentions over a certain horizon. In the presence of a conflict causing a non-avoid collision, the CAVs share their solution to CAV i . In order to be used in the eco-driving control of CAV i , this information is lumped into one "future mean value" $\hat{a}_p$, evaluated over a preview window length L_i as

$$\hat{a}_p(t) = \frac{1}{L_i} \int_{t-L_i}^t a_p(\tau) d\tau, \quad x \in [d, p, e], \quad (18)$$

as in (Lakshmanan et al. (2021a)). The acceleration $\hat{a}_p(t)$, replaces the measured instantaneous acceleration in the non-cooperative scenario, to predict the conflicting CAV's motion. The arrival times K_i^c and k_i are computed from the actual arrival time given by the solution used by CAVs c and i . For example, if CAV c 's solution is given by (5), its arrival time at C_i is computed using (6).

5. SIMULATION

In this section, we evaluate the performance of the proposed NC-ED and C-ED algorithm to cross an urban intersection, in a MATLAB simulation environment. The algorithms are compared to a baseline scenario generated by the traffic simulation software SUMO. The Intelligent Driver Model (IDM) is used to describe the behavior of the CAVs in the baseline. The performance is evaluated, in terms of energy consumption, using a detailed Nissan Leaf electric vehicle model presented in (Dollar et al. (2020)).

We consider an isolated urban intersection where $l = 47$ m and $w = 4$ m. The minimum safety distance $s_{\min} = 7$ m and the safety D to avoid a lateral collision is $2.5 \times$. The initial and final speeds are uniformly distributed in the interval $8.3 \text{ m/s} \leq v \leq 24 \text{ m/s}$. The maximum acceleration and deceleration of the CAVs are set to 4 m/s^2 . A total of 30 CAVs are simulated with a traffic flow rate of 800, 1200, and 1600 veh/hr. The entry time of the CAVs follows an exponential distribution and the lanes and heading directions are assigned using a uniform distribution. Unlike the ED solutions, the IDM cannot enforce a prescribed final time. The final time of CAV i obtained as an output of IDM is used in ED to ensure same average speed for a CAV i across the algorithms. The crossing order is given by the right-before-left criterion in SUMO.

The velocity trajectories of the CAVs, arriving at a flow rate of 800 veh/hr, equipped with IDM, NC-ED and C-ED algorithms are shown in Fig. 5. The CAVs using IDM and NC-ED decelerate to 4 m/s^2 at $D_{\min}$, which is 4.5 m before D . At $D_{\min}$, CAV i checks for merging or crossing conflicts with higher prioritized CAVs and obtains only the instantaneous control input from the conflicting CAVs. In the event of a conflict, the CAV i adjust its speed profile, with some of them coming to an almost complete stop, e.g. the purple CAV at 130 s. On the other hand CAVs with C-ED have less variations in acceleration. CAVs taking left or right turns also decelerate to satisfy turning speed constraints, e.g. CAV 5, green speed profile at around 40 s, is taking a right turn and has a safe speed of 5.24 m/s inside the IZ.




Figure 4. Energy Consumption

Each flow rate is simulated thrice with randomly generated boundary conditions and their energy consumption are given in Fig. 4. It can be seen that the total energy consumption increases with an increase in flow rate. This is due to the increased conflicts amongst the CAVs causing a CAV i to adjust its speed profile. The CAVs in NC-ED consumes 3 % less energy than IDM. With IDM and NC-ED having same information on conflicting vehicles, the energy reduction is caused by the optimal ED speed profiles employed by the CAVs. The C-ED performs best amongst the three, with a reduction of 23.7 % over IDM and 21.3 % over the NC-ED. The CAVs with cooperation have more accurate information about the conflicting vehicles and get this information much earlier (i.e. at $x_i(0) = 0$) than the other two algorithms. This enables better anticipation and hence the CAVs can adjust their speed profiles accordingly.

6. CONCLUSION

The paper addressed the problem of finding the optimal ED speed trajectory for the entire horizon (i.e., entry lane, IZ and exit lane) of an urban isolated intersection. Various conflicts in the intersection were formulated has constraints to the CAV and its solutions were presented. Two levels of cooperation, namely, the non-cooperative and cooperative, were studied and evaluated for energy consumption in comparison to the baseline IDM. The cooperative algorithm performed best indicating that, earlier determination of conflicts with higher prioritized CAVs and better prediction of their arrival time and motion, leads to better energy efficiency.

REFERENCES

- Bishion, Y. and Rakha, H.A. (2019). Real-time optimal intersection control system for automated/responsive vehicles. *International Journal of Transportation Science and Technology*, 8(1), 1–12.
- Bin Mohamed Nor, M.H. and Samerikawa, T. (2019). Optimal control of connected and automated vehicles at intersections with state and control constraints. In *2019 IEEE/ASME International Conference on Advanced Intelligent Mechanisms (AIM)*, 1407–1409.
- Bryson, A.E. and Ho, Y.C. (1969). *Applied Optimal Control*. Blaisdell.

核心方法或算法页 / Core method or algorithm page

p.4 · full_page

这张截图用于把笔记中的抽象概念拉回原论文页面，便于你平行阅读原文、公式、图表和实验设置。

This snapshot anchors the study note to the original PDF page so you can read the explanation alongside the source layout.

与当前课题的连接： Supports the smoothing objective terms for acceleration, energy proxy, and stop avoidance.

实验或结果页 / Experiments or results page

p.7 · full_page

这张截图用于把笔记中的抽象概念拉回原论文页面，便于你平行阅读原文、公式、图表和实验设置。

This snapshot anchors the study note to the original PDF page so you can read the explanation alongside the source layout.

与当前课题的连接： Supports the smoothing objective terms for acceleration, energy proxy, and stop avoidance.




Figure 5. Velocity trajectories of CAVs at 800 veh/hr

Campos, G.R., Falcone, P., Wymerssch, H., Hult, R., and Spöberg, J. (2014). Cooperative receding horizon conflict resolution at traffic intersections. In *2014 IEEE Conference on Decision and Control*, 2032-2037.

Chen, L. and Englund, C. (2016). Cooperative intersection management: A survey. *IEEE Transactions on Intelligent Transportation Systems*, 17(3), 570-586.

Doh, W., Serrao, L., and Sciarretta, A. (2011). Optimal control to minimize trip time and energy consumption in electric vehicles. In *2011 IEEE Vehicle Power and Propulsion Conference*, 1-8.

Dellar, R., Sciarretta, A., and Vahidi, A. (2020). Information and collaboration levels in vehicle strings: A comparative study. *IFAC World Congress*, 2020.

Dresser, K.M. and Stone, P. (2008). A multiagent approach to autonomous intersection management. *J. Artif. Intell. Res.*, 31, 591-656.

Hart, J., Sciarretta, A., Ojeda, L.L., De Nuzzio, G., and Thibault, L. (2018). Safe and co-driving control for connected and automated electric vehicles using analytical state-constrained optimal solution. *IEEE Transactions on Intelligent Vehicles*, 3(2), 163-172.

Hart, J., Vahidi, A., and Sciarretta, A. (2019). Fundamentals of energy efficient driving for combustion engine and electric vehicles: An optimal control perspective. *Automatica*, 103, 568-572.

Hult, R., Zanon, M., Gros, S., and Falcone, P. (2018). Energy-optimal coordination of autonomous vehicles at intersections. In *2018 European Control Conference (ECC)*, 662-667.

Jin, Q., Wu, G., Berthomieu, K., and Barth, M. (2012). Multi-agent intersection management for connected vehicles using an optimal scheduling approach. In *Proceedings of the 2012 International Conference on Connected Vehicles and Expo, ICVE*, 12, 185-190.

Kloock, M., Schelle, P., Marquardt, S., Maciejowski, J., Ahlborn, B., and Kowalewski, S. (2019). Distributed model predictive intersection control of multiple vehicles. In *2019 IEEE Intelligent Transportation Systems Conference (ITSC)*, 1735-1740.

Krajewicz, D. and Erdmann, J. (2013). Road intersection model in simo. 212-220.

Lakshmanan, V.R., Sciarretta, A., and El-Ganaoui-Mourlan, O. (2021a). Cooperative level in eco-driving of electric vehicle platoons. In *2021 IEEE International Intelligent Transportation Systems Conference (ITSC)*, 1153-1158.

Lakshmanan, V.R., Sciarretta, A., and Ganaoui-Mourlan, O.E. (2021b). Cooperative eco-driving of electric vehicle platoons for energy efficiency and string stability. *IFAC-PapersOnLine*, 54(2), 133-139. 16th IFAC Symposium on Control in Transportation Systems CTS 2021.

Maurin, D., Gillet, K., Colin, G., Chamaillard, Y., and Nouillat, C. (2016). Which methodology is more appropriate to solve eco-driving optimal control problem for conventional vehicles? In *2016 IEEE Conference on Control Applications (CCA)*, 1262-1267.

Makarem, L. and Gillet, D. (2013). Model predictive coordination of autonomous vehicles crossing intersections. In *16th International IEEE Conference on Intelligent Transportation Systems (ITIS-2013)*, 1799-1804.

Malkopoulos, A.A., Gossard, C.G., and Zhang, Y.J. (2018). A decentralized energy-optimal control framework for connected automated vehicles at signal-free intersections. *Automatica*, 93, 244-256.

Ney, C., Suet, P.D., Lemaire, O., Egle, M., Nuzzio, G.D., and Sciarretta, A. (2022). Connected strategy for energy-efficient driving of electric vehicle. In *SIA Powertrain and Energy*.

Ros-Torres, J. and Malkopoulos, A.A. (2017). A survey on the coordination of connected and automated vehicles at intersections and merging at highway on-ramps. *IEEE Transactions on Intelligent Transportation Systems*, 18(5), 1066-1077.

Sciarretta, A. and Vahidi, A. (2020). *Energy-Efficient Driving of Road Vehicles*. Springer.

Thompson, M., Kwon, O., and Park, M. (2009). The application of axiomatic design theory and conflict techniques to the design of intersections: Part 1. Paper ICAD-2009.

van Keulen, T., Gillet, J., de Jager, B., and Steinbock, M. (2014). Solution for state constrained optimal control problems applied to power split control for hybrid vehicles. *Automatica*, 50(1), 187-192.

Wang, M., Damm, W., Hoogendoorn, S.P., and van Arem, B. (2014). Rolling horizon control framework for driver assistance systems, part i: Mathematical formulation and non-cooperative systems. *Transportation Research Part C: Emerging Technologies*, 40, 271-288.

Zhang, Y. and Gossard, C.G. (2019). Decentralized optimal control of connected automated vehicles at signal-free intersections including comfort-constrained turns and safety guarantees. *Automatica*, 109, 108563.

补充精读页 / Supplemental close-reading page

p.8 · full_page

这张截图用于把笔记中的抽象概念拉回原论文页面，便于你平行阅读原文、公式、图表和实验设置。

This snapshot anchors the study note to the original PDF page so you can read the explanation alongside the source layout.

与当前课题的连接：Supports the smoothing objective terms for acceleration, energy proxy, and stop avoidance.

章节精读 / Section-by-Section Deep Reading

p.1 · motivation

1. INTRODUCTION

章节目标：建立研究动机：为什么传统信号控制、FCFS 或单车控制不足以处理该论文关注的交叉口协同问题。

Learning goal: Understand why the paper needs a new coordination method rather than a standard signal, FCFS, or single-vehicle controller.

关键论点 / Key argument: 这一部分通常把痛点落到 Eco-driving optimal speed profile: 既要提高效率, 又要保持安全与在线可执行。

技术焦点 / Technical focus: 精读时标出作者批判的 baseline、场景假设、交通参与者类型和隐含优化目标。

审稿追问 / Reviewer question: 作者指出的痛点是否真的需要新方法, 还是可以由更强的优化器/更保守规则解决?

p.2 · model

2. INTERSECTION MODEL, VEHICLE MODEL AND

章节目标：把自然语言交通问题压缩为变量、状态、约束、目标函数或图结构。

Learning goal: Translate the traffic problem into variables, states, constraints, objectives, or graph relations.

关键论点 / Key argument: 本节是复现论文的核心入口, 应与公式“PMP 速度规划问题 / PMP speed-profile optimal control”一起读。

技术焦点 / Technical focus: 逐项检查车辆状态、冲突关系、控制输入、时间/空间索引和安全阈值是否定义完整。

审稿追问 / Reviewer question: 这些建模假设在混合交通、通信延迟、感知误差和高密度车流下是否仍成立?

p.2 · model

2.1 Intersection Model

章节目标：把自然语言交通问题压缩为变量、状态、约束、目标函数或图结构。

Learning goal: Translate the traffic problem into variables, states, constraints, objectives, or graph relations.

关键论点 / Key argument: 本节是复现论文的核心入口, 应与公式“PMP 速度规划问题 / PMP speed-profile optimal control”一起读。

技术焦点 / Technical focus: 逐项检查车辆状态、冲突关系、控制输入、时间/空间索引和安全阈值是否定义完整。

审稿追问 / Reviewer question: 这些建模假设在混合交通、通信延迟、感知误差和高密度车流下是否仍成立?

p.3 · model

2.2 Vehicle Model

章节目标：把自然语言交通问题压缩为变量、状态、约束、目标函数或图结构。

Learning goal: Translate the traffic problem into variables, states, constraints, objectives, or graph relations.

关键论点 / Key argument: 本节是复现论文的核心入口, 应与公式“PMP 速度规划问题 / PMP speed-profile optimal control”一起读。

技术焦点 / Technical focus: 逐项检查车辆状态、冲突关系、控制输入、时间/空间索引和安全阈值是否定义完整。

审稿追问 / Reviewer question: 这些建模假设在混合交通、通信延迟、感知误差和高密度车流下是否仍成立?

p.4 · model

p.4 · model

3. OPTIMAL CONTROL PROBLEM FORMULATION

章节目标：把自然语言交通问题压缩为变量、状态、约束、目标函数或图结构。

Learning goal: Translate the traffic problem into variables, states, constraints, objectives, or graph relations.

关键论点 / Key argument: 本节是复现论文的核心入口，应与公式“PMP 速度规划问题 / PMP speed-profile optimal control”一起读。

技术焦点 / Technical focus: 逐项检查车辆状态、冲突关系、控制输入、时间/空间索引和安全阈值是否定义完整。

审稿追问 / Reviewer question: 这些建模假设在混合交通、通信延迟、感知误差和高密度车流下是否仍成立？

3.1 Unconstrained Eco-Driving Problem

章节目标：把自然语言交通问题压缩为变量、状态、约束、目标函数或图结构。

Learning goal: Translate the traffic problem into variables, states, constraints, objectives, or graph relations.

关键论点 / Key argument: 本节是复现论文的核心入口，应与公式“PMP 速度规划问题 / PMP speed-profile optimal control”一起读。

技术焦点 / Technical focus: 逐项检查车辆状态、冲突关系、控制输入、时间/空间索引和安全阈值是否定义完整。

审稿追问 / Reviewer question: 这些建模假设在混合交通、通信延迟、感知误差和高密度车流下是否仍成立？

p.4 · bridge

3.2 Car-Following conflict/ Sequential Conflict

章节目标：承接前后章节，补充局部定义、案例或实现细节。

Learning goal: Recover implementation details needed for reproduction.

关键论点 / Key argument: 这类章节常常不是主贡献，但决定你能否真正复现方法。

技术焦点 / Technical focus: 检查它是否给出了参数、伪代码、场景划分或实现细节。

审稿追问 / Reviewer question: 跳过该节会不会导致公式或实验无法复现？

p.5 · bridge

3.3 Crossing Conflict

章节目标：承接前后章节，补充局部定义、案例或实现细节。

Learning goal: Recover implementation details needed for reproduction.

关键论点 / Key argument: 这类章节常常不是主贡献，但决定你能否真正复现方法。

技术焦点 / Technical focus: 检查它是否给出了参数、伪代码、场景划分或实现细节。

审稿追问 / Reviewer question: 跳过该节会不会导致公式或实验无法复现？

逐段式导读 / Paragraph-Level Walkthrough

Opening motivation / 开篇动机段

先把作者的痛点翻译成一句博士问题：在无信号交叉口协作中，如何用解析最优控制生成节能、少停顿的速度曲线？读这一段时不要急着接受动机，要追问传统 FCFS、信号灯或保守 MPC 为什么不足。

Turn the opening motivation into one doctoral-level question and test whether the paper truly needs a new method.

Assumption and setting / 假设与场景段

把车辆类型、通信条件、路口类型和动力学假设列成表。该文的关键边界包括：车辆动力学和能耗模型可精确获得。；冲突关系可以预先分类并转成边界/时间约束。；场景规模相对有限。

List vehicle type, communication, intersection setting, and dynamics assumptions before reading the equations.

Model and notation / 模型与符号段

围绕核心公式“PMP 速度规划问题 / PMP speed-profile optimal control”复写符号表，确认每个变量是决策变量、状态变量、参数还是约束阈值。

Rewrite the symbol table around the core formulation and classify variables as states, decisions, parameters, or constraints.

Algorithm mechanism / 算法机制段

把算法读成一条数据流：输入交通状态，执行 Single-level eco-driving optimization solved with Pontryagin's Minimum Principle for electric CAV speed profiles at an unsignalized intersection., 输出可执行通行/控制决策，并检查安全接口。

Read the algorithm as a dataflow from traffic state to executable sequence/control decision, with explicit safety interfaces.

Experiment and evidence / 实验证据段

不要只看作者报告的提升，要检查基准、公平性和指标。本文验证描述为：Simulation comparison of cooperative and non-cooperative eco-driving against IDM baseline.

Go beyond reported gains and inspect baselines, fairness, metrics, and computation time.

Reviewer synthesis / 审稿式总结段

最后把贡献拆成可发表与需补强两部分。对你课题最直接的用途是：Supports the smoothing objective terms for acceleration, energy proxy, and stop avoidance.

Separate publishable contribution from missing evidence, then connect the result to your own thesis architecture.

技术路线图与贡献量评估 / Technical Route & Contribution Matrix

1. 输入 Input 车辆状态、路径/车道、交通需求、信号或协同信息。	2. 建模 Modeling PMP 速度规划问题 / PMP speed-profile optimal control	3. 核心求解 Core solver Single-level eco-driving optimization solved with Pontryagin's Minimum Principle for electric CAV speed profiles at an unsignalized intersection.
4. 安全接口 Safety interface Analytical conflict cases and cooperation levels encode interaction safety among CAVs.	5. 平滑与效率 Smoothing and efficiency Focuses directly on optimal speed profiles that reduce energy use and avoid inefficient stop-and-go behavior.	6. 验证 Validation Simulation comparison of cooperative and non-cooperative eco-driving against IDM baseline.

贡献量评估 / Contribution Strength Matrix

Dimension / 维度	Score / 评分	Comment / 评语
理论贡献 / Theoretical contribution	4/5	PMP 速度规划问题 / PMP speed-profile optimal control
算法贡献 / Algorithmic contribution	4/5	Single-level eco-driving optimization solved with Pontryagin's Minimum Principle for electric CAV speed profiles at an unsignalized intersection.
实验贡献 / Experimental contribution	3/5	Simulation comparison of cooperative and non-cooperative eco-driving against IDM baseline.
工程贡献 / Engineering contribution	3/5	Analytical conflict cases and cooperation levels encode interaction safety among CAVs.
博士课题价值 / PhD relevance	4/5	Supports the smoothing objective terms for acceleration, energy proxy, and stop avoidance.

2. 理论方法论深度解构 / Deep Dive into Methodology & Theoretical Framework

问题数学建模 / Mathematical Formulation

PMP 速度规划问题 / PMP speed-profile optimal control

$$\min_{u(t)} \int_{t_0}^{t_f} \left(\alpha P(v(t), u(t)) + \beta u(t)^2 \right) dt, \quad H = L + \lambda_p v + \lambda_v u$$

Symbol / 符号	含义	Meaning	Role / 建模作用
$P(v, u)$	动力/能耗模型	power or energy model	刻画电动车能量消耗
$u(t)$	加速度	acceleration	连续控制变量
H	哈密顿量	Hamiltonian	PMP 的必要条件核心
λ_p, λ_v	协态变量	costate variables	连接状态约束和最优控制
α, β	能耗与平滑权重	energy and smoothness weights	决定节能与舒适的折中

核心算法架构 / Core Algorithm Layout

论文把路口协作转为有限时域速度曲线优化，用 PMP 推导最优性必要条件，并比较协作与非协作策略。其价值在于给出可解释的低层速度平滑目标。

The paper formulates cooperative eco-driving as a finite-horizon speed-profile problem and uses PMP conditions to derive interpretable optimal-control behavior.

收敛性、稳定性或实时性 / Convergence, Stability, Real-Time Feasibility

解析最优控制比黑盒学习更可解释，但对边界条件和冲突场景分类敏感；实时性取决于求解 shooting/边值问题的效率。

The optimal-control structure is interpretable, but solution quality depends on boundary conditions and conflict-case classification.

潜在假设与边界条件 / Assumptions & Boundary Conditions

- 车辆动力学和能耗模型可精确获得。
- 冲突关系可以预先分类并转成边界/时间约束。
- 场景规模相对有限。

3. 实验验证与结果评判 / Experimental Validation & Result Evaluation

基准对比与环境 / Baselines & Environment

IDM、非协作生态驾驶、固定速度或普通跟驰策略。
Simulation comparison of cooperative and non-cooperative eco-driving against IDM baseline.

核心指标 / Metrics

能耗、速度平滑性、旅行时间、停车次数和安全间隔满足情况。

消融实验 / Ablation

不是典型模块化学习论文，消融较少；更需要权重敏感性和不同协作等级比较。

博士阅读提醒 / Reading Reminder

阅读实验时不要只看平均值；应检查交通密度、车流方向、随机种子、失败案例和计算耗时。For doctoral reading, inspect density regimes, demand patterns, random seeds, failure cases, and computation time rather than only mean improvements.

图表阅读线索 / Figure and Table Reading Cues

PDF extraction detected approximately 14 figure references and 0 table references. Exact captions remain in the original PDF; the bilingual cues below tell you what to inspect first.

图表名称	Figure/Table Name	Reading focus / 阅读重点
系统框架图	system framework diagram	先确认输入、决策层、控制层和安全约束之间的数据流。
控制框架/轨迹曲线图	control-framework or trajectory-profile plots	关注约束激活位置、速度/加速度曲线和安全裕度是否平滑。
实验指标对比图表	experimental metric comparison plots/tables	重点看平均值之外的密度变化、失败场景、计算时间和方差。

4. 审稿人视角：批判性思考与未来方向 / Critical Thinking & Future Directions

论文局限性 / Limitations & Weaknesses

- 高层排序与多车组合爆炸处理不足。
- PMP 推导在复杂约束下可能需要数值求解，工程实现不总是简单。
- 对混合交通和不确定性覆盖有限。

博士课题拓展点 / Research Extensions for PhD

- 把 PMP 低层解作为 JSSP 调度候选动作的可行性 oracle。
- 用神经网络学习 PMP 解的近似映射，加速在线 smoother。
- 在成本中加入 jerk 和舒适性约束，构建更完整的轨迹平滑器。

如何服务当前课题 / Use in This Project

Supports the smoothing objective terms for acceleration, energy proxy, and stop avoidance.

5. 交互式可视化与 PDF 排版蓝图 / Interactive Visualization & PDF Layout Blueprint

动态参数探索 / Parameter Exploration

平滑权重 / Smoothness weight:

平滑权重越大，加速度变化越柔和，但可能增加清空时间。

A larger smoothness weight softens acceleration but may increase clearing time.

HTML 结构化布局建议 / HTML Structuring

- 顶部固定 metadata bar：题名、作者、年份、主题、PDF 页数。
- 左侧目录/section navigator，右侧为五大精读模块。
- 公式卡片使用 `<pre>` 或 LaTeX block，紧跟符号表。
- 审稿人批注用 reviewer-note block，博士拓展用 research-idea list。
- 交互参数用 `input[type=range]` + canvas 曲线，打印 PDF 时隐藏交互控件但保留解释。

来源锚点与逐节阅读路径 / Source Anchors & Section-by-Section Reading Map

以下锚点来自本地 PDF 抽取，用于回到原文复核；笔记不保存论文全文。

Page	Extracted heading
p.1	1. INTRODUCTION
p.4	3. OPTIMAL CONTROL PROBLEM FORMULATION
p.7	5. SIMULATION

p.1 · 1. INTRODUCTION

定位问题背景、研究缺口和为什么现有保守/非协同方法不足。
Frames the motivation, research gap, and limits of conservative or non-cooperative methods.

p.2 · 2. INTERSECTION MODEL, VEHICLE MODEL AND

把交通交互转写为状态、约束、目标或图结构，是精读时最应复现的部分。
Defines states, constraints, objectives, or graph structures; this is the section to reproduce carefully.

p.2 · 2.1 Intersection Model

把交通交互转写为状态、约束、目标或图结构，是精读时最应复现的部分。
Defines states, constraints, objectives, or graph structures; this is the section to reproduce carefully.

p.3 · 2.2 Vehicle Model

把交通交互转写为状态、约束、目标或图结构，是精读时最应复现的部分。
Defines states, constraints, objectives, or graph structures; this is the section to reproduce carefully.

p.4 · 3. OPTIMAL CONTROL PROBLEM FORMULATION

把交通交互转写为状态、约束、目标或图结构，是精读时最应复现的部分。
Defines states, constraints, objectives, or graph structures; this is the section to reproduce carefully.

p.4 · 3.1 Unconstrained Eco-Driving Problem

把交通交互转写为状态、约束、目标或图结构，是精读时最应复现的部分。
Defines states, constraints, objectives, or graph structures; this is the section to reproduce carefully.

p.4 · 3.2 Car-Following conflict/Sequential Conflict

作为局部论证段落阅读，关注它如何服务主问题。

Read as a local argument and ask how it supports the main question.

p.5 · 3.3 Crossing Conflict

作为局部论证段落阅读，关注它如何服务主问题。

Read as a local argument and ask how it supports the main question.
