

LDR

Generated by Doxygen 1.9.6



<b>1 LDR Library Integration Guide</b>	<b>1</b>
1.1 Step 1: Download the library files	1
1.2 Step 2: Add the library files to your project	1
1.2.1 STM32Cube IDE	1
1.2.2 Other IDEs	1
1.3 Step 3: Include the library header in main.c	2
1.4 Step 4: Initialize the LDR in main.c(sets the calibration constants)	2
1.5 Step 5: Read analog light intensity in main.c	2
<b>2 File Index</b>	<b>3</b>
2.1 File List	3
<b>3 File Documentation</b>	<b>5</b>
3.1 ldr.c File Reference	5
3.1.1 Detailed Description	5
3.1.2 Function Documentation	5
3.1.2.1 LDR_Init()	6
3.1.2.2 LDR_ReadADC()	6
3.1.2.3 LDR_ReadAnalogLightIntensity()	6
3.2 ldr.h File Reference	6
3.2.1 Detailed Description	7
3.2.2 Function Documentation	7
3.2.2.1 LDR_Init()	7
3.2.2.2 LDR_ReadADC()	7
3.2.2.3 LDR_ReadAnalogLightIntensity()	8
3.3 ldr.h	8
<b>Index</b>	<b>9</b>



# Chapter 1

## LDR Library Integration Guide

This guide provides instructions on how to integrate the LDR library into your STM32 project using STM32Cube IDE or any other compatible IDE.

### 1.1 Step 1: Download the library files

Download the following LDR library files:

1. `ldr.h` - The header file containing the function prototypes and necessary definitions.
2. `ldr.c` - The source file containing the function implementations.

### 1.2 Step 2: Add the library files to your project

Follow these steps to add the LDR library files to your project:

#### 1.2.1 STM32Cube IDE

1. In STM32Cube IDE, open your STM32 project.
2. Navigate to the project tree in the "Project Explorer" tab.
3. Place the `ldr.h` file into the "Inc" folder (or the folder where header files are stored in your project).
4. Place the `ldr.c` file into the "Src" folder (or the folder where source files are stored in your project).

#### 1.2.2 Other IDEs

1. Open your STM32 project in the IDE you are using.
2. Place the `ldr.h` file in the folder where header files are stored in your project (usually an "include" or "inc" folder).
3. Place the `ldr.c` file in the folder where source files are stored in your project (usually a "source" or "src" folder).

### 1.3 Step 3: Include the library header in main.c

In the `main.c` file of your project, add the following include statement at the beginning of the file, along with other include statements:

```
#include "ldr.h"
```

### 1.4 Step 4: Initialize the LDR in main.c(sets the calibration constants)

In the `main.c` function of your project, call the `LDR_Init()` function to initialize the LDR:

```
int main(void)
{
    // Initialize peripherals, system clock, etc.

    // Initialize LDR
    LDR_Init();

    // Other code
}
```

### 1.5 Step 5: Read analog light intensity in main.c

To read the analog light intensity using the LDR, call the `LDR_ReadAnalogLightIntensity()` function in your code:

```
int main(void)
{
    // Initialize peripherals, system clock, etc.

    // Initialize LDR
    LDR_Init();

    // Read analog light intensity
    float light_intensity = LDR_ReadAnalogLightIntensity(&hadc);

    // Other code
}
```

Again, `hadc` is a handle to the ADC peripheral that you should have already initialized in your project.

## Chapter 2

# File Index

### 2.1 File List

Here is a list of all documented files with brief descriptions:

<a href="#">ldr.c</a>	LDR Library Source . . . . .	<a href="#">5</a>
<a href="#">ldr.h</a>	LDR Library Header . . . . .	<a href="#">6</a>





## Chapter 3

# File Documentation

### 3.1 ldr.c File Reference

LDR Library Source.

```
#include "ldr.h"
```

#### Functions

- void [LDR\\_Init](#) (void)  
*Initialize the LDR with calibration constants.*
- uint32\_t [LDR\\_ReadADC](#) (ADC\_HandleTypeDef \*hadc)  
*Read ADC value from the LDR.*
- float [LDR\\_ReadAnalogLightIntensity](#) (ADC\_HandleTypeDef \*hadc)  
*Read analog light intensity using the LDR.*

#### 3.1.1 Detailed Description

LDR Library Source.

Author

Travimadox Webb @position Embedded Software Engineer @company Imperium LLC

Date

6th of May 2023

#### 3.1.2 Function Documentation

### 3.1.2.1 LDR\_Init()

```
void LDR_Init (
    void )
```

Initialize the LDR with calibration constants.

Initialize the LDR.

### 3.1.2.2 LDR\_ReadADC()

```
uint32_t LDR_ReadADC (
    ADC_HandleTypeDef * hadc )
```

Read ADC value from the LDR.

#### Parameters

<i>hadc</i>	Pointer to an ADC_HandleTypeDef structure that contains the configuration information for the specified ADC
-------------	---

#### Returns

32-bit unsigned integer ADC value

### 3.1.2.3 LDR\_ReadAnalogLightIntensity()

```
float LDR_ReadAnalogLightIntensity (
    ADC_HandleTypeDef * hadc )
```

Read analog light intensity using the LDR.

#### Parameters

<i>hadc</i>	Pointer to an ADC_HandleTypeDef structure that contains the configuration information for the specified ADC
-------------	---

#### Returns

Floating-point light intensity value

## 3.2 Idr.h File Reference

LDR Library Header.

```
#include "stm32f0xx_hal.h"
```

## Functions

- void `LDR_Init` (void)  
*Initialize the LDR.*
- uint32\_t `LDR_ReadADC` (ADC\_HandleTypeDef \*hadc)  
*Read ADC value from the LDR.*
- float `LDR_ReadAnalogLightIntensity` (ADC\_HandleTypeDef \*hadc)  
*Read analog light intensity using the LDR.*

### 3.2.1 Detailed Description

LDR Library Header.

#### Author

Travimadox Webb @position Embedded Software Engineer @company Imperium LLC

#### Date

6th of May 2023

### 3.2.2 Function Documentation

#### 3.2.2.1 LDR\_Init()

```
void LDR_Init (  
    void )
```

Initialize the LDR.

Initialize the LDR.

#### 3.2.2.2 LDR\_ReadADC()

```
uint32_t LDR_ReadADC (  
    ADC_HandleTypeDef * hadc )
```

Read ADC value from the LDR.

#### Parameters

<i>hadc</i>	Pointer to an ADC_HandleTypeDef structure that contains the configuration information for the specified ADC
-------------	---

**Returns**

32-bit unsigned integer ADC value

**3.2.2.3 LDR\_ReadAnalogLightIntensity()**

```
float LDR_ReadAnalogLightIntensity (
    ADC_HandleTypeDef * hadc )
```

Read analog light intensity using the LDR.

**Parameters**

<i>hadc</i>	Pointer to an ADC_HandleTypeDef structure that contains the configuration information for the specified ADC
-------------	---

**Returns**

Floating-point light intensity value

**3.3 ldr.h**

[Go to the documentation of this file.](#)

```
00001
00010 #ifndef LDR_H
00011 #define LDR_H
00012
00013 #include "stm32f0xx_hal.h"
00014
00018 void LDR_Init(void);
00019
00025 uint32_t LDR_ReadADC(ADC_HandleTypeDef *hadc);
00026
00032 float LDR_ReadAnalogLightIntensity(ADC_HandleTypeDef *hadc);
00033
00034 #endif // LDR_H
```

# Index

- ldr.c, [5](#)
  - LDR\_Init, [5](#)
  - LDR\_ReadADC, [6](#)
  - LDR\_ReadAnalogLightIntensity, [6](#)
- ldr.h, [6](#)
  - LDR\_Init, [7](#)
  - LDR\_ReadADC, [7](#)
  - LDR\_ReadAnalogLightIntensity, [8](#)
- LDR\_Init
  - ldr.c, [5](#)
  - ldr.h, [7](#)
- LDR\_ReadADC
  - ldr.c, [6](#)
  - ldr.h, [7](#)
- LDR\_ReadAnalogLightIntensity
  - ldr.c, [6](#)
  - ldr.h, [8](#)