



Quality water Onsite for your Autoclave & Closed Water Systems quickly and affordably

The Ezee Kleen 2.5 is designed for offices in geographic areas having tap water dissolved mineral levels < 100 PPM (mg/L) or offices using low volumes of water. For geographic areas having tap water dissolved mineral levels > 100 PPM (mg/L) or larger offices consider the Ezee Kleen 2.5 HD 4-Stage Ultra Clean Water System.

Contact Oasis Dental Group Inc. for assistance in determining tap water dissolved mineral levels and the appropriate unit for your office.

The Ezee Kleen 2.5 will:

- Produce 1 gallon (4 litres) of autoclave-safe water in approximately 2 minutes!
- Ensure you never run out of water for your autoclaves
- · Eliminate last-minute store runs for water
- Self monitor for consistent water quality (Unlike bottled water)
- Eliminate bulky storage of bottles
- · Reduce maintenance and equipment failure
- Save Money!!!
- Produce onsite, water of the quality necessary to comply with all autoclave manufacturer's TDS level guidelines

Optional Unit Enhancements

- XL DI CARTRIDGE: Reduces change frequency of Ezee Kleen 2.5 DI Cartridges by as much as 3 times.
- SEDIMENT CARTRIDGE: prolongs life of the Ezee Kleen 2.5's DI Cartridges in areas with high suspended solids
- ULTRAVIOLET CARTRIDGE: destroys bacteria, viruses, and other harmful microorganisms when using water in closed water systems
- UNDER COUNTER INSTALLATION

An Innovative product for the cost effective and efficient dental practice of today.



COMPARE EZEEKLEEN 2.5 TO ON-SITE DISTILLATION & BOTTLED DISTILLED WATER

COMPARE DISTILLATION ALTERNATIVE to On-Site Distillation & Bottled Distilled Water	25	On-Site Distiller	Bottled Distilled Water	
Meets & exceeds autoclave manufacturers specifications	Yes ≤ 2.5 PPM (mg/L)	? - possibly, if properly maintained	Inconsistent	
Time required to produce 1 gallon of water	2 minutes	4-8 hours	Time required to pick up water at retail outlet	
Energy requirements Nominal - monitor powered by 12VDC/500mA transformer		4-8 hours of electricity $\approx 5-12$ kWh @ $10\phi = \$0.50-\$1.20/$ gallon ^a	Staff down time - Gas required for vehicle	
Convenience Countertop - wall mounted or under counter		Countertop space needed	Space required to store full & empty bottles	

FEATURES & SPECIFICATIONS

WATER ON DEMAND - NEVER RUN OUT! The Ezee Kleen 2.5 produces water on demand at a flow rate of 1 gallon (4 litres) in 2 minutes eliminating the need for storage of bottles or runs to the store.

MAXIMIZE EFFICIENCY AND LIFE OF AUTOCLAVE EQUIPMENT! The Ezee Kleen 2.5 comes complete with 2 custom mixed bed DI resin cartridges that bring your TDS levels to as low as 0.4 PPM (mg/L) ensuring your equipment does not become clogged with mineral scale that can cause malfunction, increased energy usage and shortened life. (Autoclave manufacturers recommend water quality of less than 5.0 PPM (mg/L) is ideal for maximum efficiency and life.)

FAST SIMPLE INSTALLATION AND USE! Unit comes ready for use with all necessary components for countertop or wall mount installation. Just attach the faucet diverter to your sink spout and the Ezee Kleen 2.5 is ready to use. Sink faucet can still be used as normal or delivered to the Ezee Kleen 2.5 by pulling the diverter pin. For undercounter installation use our optional 9005 & 9007 kits.

NO MORE GUESSING WATER QUALITY! The Ezee Kleen 2.5 self monitoring meter presents a digital read out of water quality. A red light will begin to flash as a secondary indication when levels exceed 2.5 PPM (mg/L) indicating a cartridge change is needed.

SECONDS TO CHANGE CARTRIDGES & NO MESS! Staff members can easily change cartridges. Cartridges are self contained sealed units with quick connect fittings allowing easy cartridge change out that take seconds and no exposure to contaminants.

ENERGY EFFICIENT! Powered by a 12VDC/500mA transformer the Ezee Kleen 2.5 is extremely energy efficient operating for pennies a day. Generates no heat to present hazardous fire concerns or discomfort to staff and patients.

APPROVED COMPONENTRY AND ONE YEAR WARRANTY! All components are UL/CSA approved, made of FDA approved material, and require no MSDS reporting. The Ezee Kleen 2.5 comes complete with one year parts and labour (excluding cartridges) return to depot warranty.

Gallon Production ^b of DI Cartridges based on PPM* (mg/L) of TDS** in Tap Water							
TD	S Levels	Production US Gallons (Litres)		Production with XL DI US Gallons (Litres)			
	30 40 60 80 100 (1)	246 185 123 92 74	(930) (700) (465) (350) (280)	635 476 317 238 190	(2400) (1800) (1200) (900) (720)		



Dimensions: 16"H x 12"W x 6"D/41cm x 30cm x 15cm

Weight - 10lbs/4.54 kg

* PPM = Parts Per Million = mg/L **TDS = Total Dissolved Solids

Actual gallon production from EZEEKLEEN 2.5 DI Cartridges will depend on TDS levels in source tap water and other contaminants.

(1) Ezee Kleen 2.5 HD 4-Stage Ultra Clean Water System (Model: 8000) is typically more cost effective in areas where TDS > 100 PPM (mg/L)

Unit Options

9000 Ezee Kleen 2.5 - 12 VDC 500mA North American format

9000-EUR Ezee Kleen 2.5 Euro - 220V 50hz European format

Installation Options (Undersink Installation) annually 9005 Hard Plumb Kit 9004-0

9007 Permanent Mount Faucet

Replacement Cartridges

9001 DI Cartridges - change when monitor indicates 9001-XL DI Cartridge (Optional) - change with 9001 DI Cartridges when monitor indicates

9002 Sediment Cartridge (Optional) - change annually

9004-01 UV Replacement Lamp (Optional) - change annually

Cartridge Options

9003 Sediment Cartridge Install Kit - removes suspended solids from city water improving the life of 9001 DI Cartridges (includes cartridge)

9004 Ultraviolet Cartridge Install Kit - produces 32,000 - 35,000 (w-sec/cm²) enhancing the microbiological quality of water for closed water system use. (includes lamp)

9001-XL-Kit Extra Large DI Cartridge Kit - Contains all parts to install XL DI Cartridge for the first time (cartridge included.) Replace with 9001-XL