LAB 01

Functions, Control

Mingxiao Wei mingxiaowei@berkeley.edu

Aug 29, 2022

LOGISTICS 🏠

- Lab 00 due Wed 08/31
 - Make sure to finish lab 00 before doing any other assignment!
- Lab 01 also due Wed 08/31
- Homework 01 due Thu 09/01
 - In general, it's recommended to finish lab first, then do the homework
- Look for study buddy or project partners? Talk to your neighbors or check out <u>Ed post #128!</u>
 - The first project is coming soon! You can choose to work alone or in group of 2 ♣ ♣

USING PYTHON 🕹 🖺

- Make sure to navigate to the correct directory ans save your work
- python3 <filename>
 - run the code in the file you provide and return you to the command line
- python3 -i <filename>
 - runs the code in the file, then opens an interactive session where you can run Python code line by line and get immediate feedback.
 - To exit, type exit() into the interpreter prompt. You can also use the keyboard shortcut Ctrl-D on Linux/Mac machines or Ctrl-Z Enter on Windows
- python3 -m doctest <filename>
 - Runs doctests in a particular file. Doctests are surrounded by triple quotes (""") within functions.
 - Each test in the file consists of >>> followed by some Python code and the expected output (though the >>> are not seen in the output of the doctest command).
- python3
 - opens an interactive session without referring to any source file

USING OK

- Make sure to navigate to the correct directory ans save your work
- Most of the time, you don't have to worry about anything other than copying and pasting the ok commands provided in the spec :D
- python3 ok -q <specified function>
 - run tests for a specified function
- python3 ok
 - run all tests; only failed ones will not be shown
- python3 ok -v
 - run all tests and show all results, including the ones that passed
- python3 ok --score
 - run all tests and show your sore
- python3 ok --submit
 - REMEMBER TO RUN THIS EVERY TIME YOU FINISH AN ASSINGMENT!
- print("DEBUG:", <content>)
 - Print content for debugging purposes printed lines that start with
 DEBUG: will be ignored by the ok autograder

KEYBOARD SHORTCUTS

Nothing here is necessary for 61A, but they make your life easier!

- In the terminal, use ↑ or ↓ to retrieve the previous/next command you've entered useful when repeatedly running tests
- Select lines of code and:
 - cmd/ctrl + ? to comment/uncomment the selected lines
 - tab to move them one indentation level inward
 - shift + tab to move them one indentation level outward
- cmd/ctrl + s Save
- cmd/ctrl + z undo
- cmd/ctrl + a select all
- cmd/ctrl + x CUt
- cmd/ctrl + c copy
- cmd/ctrl + v paste

DIVISION, FLOOR DIV, AND MODULO

True Division: / (always returns a decimal number)	Floor Division: // (rounds down to the nearest integer)	Modulo: % (remainder)
>>> 3 / 4	>>> 3 // 4	>>> 3 % 4
0.75	0	3
>>> 6 / 3	>>> 6 // 3	>>> 6 % 3
2.0	2	0
>>> 1 / 0 ZeroDivisionError	>>> 1 // 0 ZeroDivisionError	>>> 1 % 0 ZeroDivisionError

x % y == 0 evaluates to True when x is divisible by y \Rightarrow useful when checking for divisibility or even numbers

FUNCTIONS ?



FUNCTIONS

- Abtraction of some executions
- A function takes some arguments (or no argument), and returns some value, or None if there's no return statement.
- To apply a function to some arguments, we use call expressions

CALL EXPRESSIONS

```
1 def f(x, y):
2  return x * 2 + y * 3
3
4 g = f
5 a, b = 4, 5
6 g(a, b)
7 # operator: g, which evaluates to the function defined above
8 #operands: a and b, which evaluate to 4 and 5, respectively
```

Evaluation rules for call expressions

- 1. Evaluate the operator
- 2. Evaluate the operands from left to right
 - If an operand is a nested call expression, then these steps are applied to that inner operand first in order to evaluate the outer operand.
- 3. Apply the operator to operands

return AND print

- return
 - When Python executes a return statement, the function terminates immediately.
 - If Python reaches the end of the function body without executing a return statement, it will automatically return None
 - If a string is returned, the quote is preserved
- print
 - display values in the Terminal.
 - does not interfere with the execution flow of the function
 - If a string gets printed, print will display the string without quotes

return AND print - CONT.

```
>>> 6
6
>>> print(6)
6
```

```
def what_prints():
    print('Hello World!')
    return 'Exiting this function.'
    print('61A is awesome!')

>>> what_prints()
Hello World!
'Exiting this function.'
```

```
def what_prints():
    'Hello World!'
    return 'Exiting this function.'
    print('61A is awesome!')

>>> what_prints()
'Exiting this function.'
```

CONTROL



BOOLEAN OPERATORS

• Some arithmetic expressions evaluate to boolean values

```
>>> 6+1==7
True
>>> 8>9
False
```

- Python boolean operators: not, and, and or
 - Priority: not > and > or
 - Use parenthesis to make your code more readable!

TRUTHINESS AND FALSINESS

Truthy Values

- Treated as practically "true" in boolean contexts (if/while conditions, and/or/not expressions)
- Everything that's not falsy is truthy

Falsy Values

- Treated as practically "false" in boolean contexts (if/while conditions, and/or/not expressions)
- Including: 0, None, "" (empty string), [] (empty list), etc.
- See <u>here</u> for a comprehensive list

SHORT CIRCUITING

- Short circuit not every operand gets evaluated
- and
 - evalutes from left to right until the first FALSY value or the last value
 - return the last thing that's evaluated
- or
 - evalutes from left to right until the first TRUTHY value or the last value
 - return the last thing that's evaluated

```
>>> True and 1/0
True
>>> True or 1/0
ZeroDivisionError
```

```
>>> 1 and 2 and 3
3
>>> 1 or 2 or 3
1
```

CONDITIONAL STRUCTURES

if STATEMENTS

• Only one of the three cases will be executed.

 Here, more than one case could be executed.

if STATEMENTS - CONT.

```
if 3 > 2:
    print("hello")
elif "huh": # elif is optional
    print("hi")
else: # else is also optional
    print("QAQ")
# output
hi
```

```
if 3 > 2:
        print("hello")
if "huh": # elif is optional
        print("hi")
if 0: # else is also optional
        print("QAQ")
# output
hello
hi
```

while LOOPS

```
while <condition>:
     <do something>
```

• While <condition> is truthy, execute the body of the loop, and evaluate the condition again.

while LOOPS THAT EXECUTE k TIMES

Both are useful templates to remember!

DIGIT MANIPULATION ***

DIGIT MANIPULATION

- num % 10 retrives the last digit of num
- num // 10 removes the last digit of num
- Example: prints the digits of a number n in reverse order

```
while n:
    # isolate the last digit from n and print it
    print (n % 10)
    # removes the last digit from n
    n //= 10 # equivalent to n = n // 10
```

- Get started on the lab and raise your hand whenever you need help!
- Attendance: go.cs61a.org/mingxiao-att
 - By default, password will be released at the end of lab.
 - If you finish early, let me know and I'll check you off.
- Slides: go.cs61a.org/mingxiao-index