

CS 61b: Final Review

Data Structures

Amir Kamil and Jack Sampson

DISCLAIMER

We have **NOT** seen the exam.
We do **NOT** know the format of the exam

What we are presenting is what we
"think is important" for the exam

Amir Kamil and Jack Sampson

Final Review

2

Review Topics

- Inheritance, Method Calls
- Asymptotic Analysis
- Data Structures
 - Binary Search Trees
 - B-Trees
 - Heaps
 - Hash Tables
 - AVL Trees
- Graphs
 - DFS, BFS
 - Topological Sort
 - Strongly Connected Components
- Dijkstra
- Kruskal
- Sorting
- Skip Lists
- Threading, Synchronization
- Scheduling
- Minimax
- B+ Trees
- Threaded Trees

Amir Kamil and Jack Sampson

Final Review

3

Inheritance/Method Calls

- Given the class definitions on the next slide, which lines in class foobarbaz are illegal?

Amir Kamil and Jack Sampson

Final Review

4

Inheritance

```
package foo;
public class foo {
    static void f1() {...}
    protected boolean f2(int x) {...}
    private String f3(String s) {...}
}
```

```
package foo;
public class baz extends foo {
    private String f3(String s) {...}
}
```

```
package bar;
import foo.foo;
public class bar extends foo {
    protected boolean f3(int x) {...}
}
```

```
package foo;
import bar.bar;
public class foobarbaz {
    static void main(String[] args) {
        foo f = new foo();
        bar r = new bar();
        baz z;
        r.f3(3);
        f.f2(3);
        z = (baz) f;
        f = new baz();
        f.f2(3);
        z = (baz) f;
        z.f1();
        r.f1();
        ((foo) r).f1();
    }
}
```

Amir Kamil and Jack Sampson

Final Review

5

Inheritance/Method Calls

- Access table:

	world	package	child	definer
public	X	X	X	X
private				X
protected		X	X	X
<default>		X		X

- Static methods called according to static type
- Child type can be assigned to parent variable without a cast, but the reverse requires one, and the dynamic types must match

Amir Kamil and Jack Sampson

Final Review

6

Inheritance

```
package foo;
public class foo {
    static void f1() {...}
    protected boolean f2(int x) {...}
    private String f3(String s) {...}
}
```

```
package bar;
public class baz extends foo {
    private String f3(String s) {...}
}
```

```
package bar;
import foo.foo;
public class bar extends foo {
    protected boolean f3(int x) {...}
}
```

```
package foo;
import bar.bar;
public class foobarbaz {
    static void main(String[] args) {
        foo f = new foo();
        bar r = new bar();
        baz z;
        r.f3(3); // ILLEGAL
        f.f2(3); // ILLEGAL
        z = (baz) f;
        f = new baz();
        f.f2(3);
        z = (baz) f;
        z.f1();
        r.f1(); // ILLEGAL
        ((foo) r).f1();
    }
}
```

Amir Kamil and Jack Sampson

Final Review

7

Asymptotic Analysis

- O – Upper bound/Worst case
- Ω – Lower bound
- Θ – both
- o – strictly Upper bound

More detail...

Amir Kamil and Jack Sampson


Final Review

8

Asymptotic Analysis

$T(n)$ is $O(f(n))$ if and only if there exists positive constants C and N such that

$$T(n) \leq C f(n) \text{ for all } n \geq N$$



Amir Kamil and Jack Sampson


Final Review

9

Asymptotic Analysis

$T(n)$ is $O(f(n))$ if and only if there exists positive constants C and N such that

$$T(n) \leq C f(n) \text{ for all } n \geq N$$



Amir Kamil and Jack Sampson

Final Review

10

Asymptotic Analysis

$T(n)$ is $O(f(n))$ if and only if there exists positive constants C and N such that

$$T(n) \leq C f(n) \text{ for all } n \geq N$$

$T(n)$ is $\Omega(f(n))$ if and only if there exists positive constants C and N such that

$$T(n) \geq C f(n) \text{ for all } n \geq N$$

Amir Kamil and Jack Sampson

Final Review

11

Asymptotic Analysis

$T(n)$ is $\Theta(f(n))$ if and only if

- $T(n)$ is $O(f(n))$
- and
- $T(n)$ is $\Omega(f(n))$

Examples

$5n^2 + 1$ is $\Theta(n^2)$

$3n$ is $O(n^2)$, but $3n$ is NOT $\Theta(n^2)$ because $3n$ is not $\Omega(n^2)$

Amir Kamil and Jack Sampson

Final Review

12

Asymptotic Analysis Problem

- Find the running time of the following code:

```
int foo(int x) {  
    int ans = 1;  
    for (int i = 0; i < x; i++) {  
        for (int j = 0; j < i; j++) {  
            ans *= (i + j);  
        }  
    }  
    return ans;  
}
```

Amir Kamil and Jack Sampson

Final Review

13

Asymptotic Analysis Solution

- The nested loops give away the answer: the outer loop executes x times, the inner loop an average of $x/2$ times, for a running time of $O(x^2)$.

```
int foo(int x) {  
    int ans = 1;  
    for (int i = 0; i < x; i++) {  
        for (int j = 0; j < i; j++) {  
            ans *= (i + j);  
        }  
    }  
    return ans;  
}
```


Amir Kamil and Jack Sampson

Final Review

14

Trees: Binary Tree

Tree:



Preorder : ABCEGFD
Inorder : CEBAGDF
Postorder: ECBDFGA


Amir Kamil and Jack Sampson

Final Review

15

Trees: BST Problem

- Remove 8 from:




Amir Kamil and Jack Sampson

Final Review

16

Trees: BST Problem

- Remove 8 from:



Replace with successor (left-most node in right subtree)


Amir Kamil and Jack Sampson

Final Review

17

Trees: BST Solution

- Final tree:




Amir Kamil and Jack Sampson

Final Review

18


Trees: B-Tree of Order 4 / 2-3-4 Tree

- Insert 4 and 6 into the following 2-3-4 tree




Trees: B-Tree of Order 4 / 2-3-4 Tree

- Insert 4



Trees: B-Tree of Order 4 / 2-3-4 Tree


- Insert 6



Overflow, so split node and promote middle element

Trees: B-Tree of Order 4 / 2-3-4 Tree


- Insert 6



Overflow, so split node and promote middle element


Trees: B-Tree of Order 4 / 2-3-4 Tree

- Remove 16 from the following 2-3-4 tree



Trees: B-Tree of Order 4 / 2-3-4 Tree


- Remove 16



Underflow, so merge with sibling and demote parent element

Trees: B-Tree of Order 4 / 2-3-4 Tree

- Remove 16



Underflow, so merge with sibling
and demote parent element

Priority Queues – Problem

- Add 9, 76, 54, 3, 33, 21 to a max heap, using only the array based representation

Priority Queues – Insertion

- Insert at the last position in the heap
- Reheapify up: if the element is greater than its parent, swap them and repeat
- For an element at position n , its children are at $2n+1$ and $2n+2$
- For an element at position n , its parent is at $\text{floor}[(n-1)/2]$


Priority Queues – Solution

- Add 9, 76, 54, 3, 33, 21 to a max heap, using only the array based representation




Priority Queues – Solution

- Add 9, 76, 54, 3, 33, 21 to a max heap, using only the array based representation




Priority Queues – Solution

- Add 9, 76, 54, 3, 33, 21 to a max heap, using only the array based representation



Priority Queues – Solution

- Add 9, 76, 54, 3, 33, 21 to a max heap, using only the array based representation




Amir Kamil and Jack Sampson

Final Review

31

Priority Queues – Solution

- Add 9, 76, 54, 3, 33, 21 to a max heap, using only the array based representation




Amir Kamil and Jack Sampson

Final Review

32

Priority Queues – Solution

- Add 9, 76, 54, 3, 33, 21 to a max heap, using only the array based representation



Amir Kamil and Jack Sampson

Final Review

33

Priority Queues – Problem

- Remove the max from the heap



Amir Kamil and Jack Sampson

Final Review

34

Priority Queues – Removal

- Replace the max element with the last element in the heap
- Reheapify down: if one or both of its children is larger than it, swap with the larger of the children and repeat
- For an element at position n , its children are at $2n+1$ and $2n+2$
- For an element at position n , its parent is at $\text{floor}[(n-1)/2]$


Amir Kamil and Jack Sampson

Final Review

35

Priority Queues – Solution

- Remove the max from the heap




Amir Kamil and Jack Sampson

Final Review

36

Priority Queues – Solution

- Remove the max from the heap




Amir Kamil and Jack Sampson

Final Review

37

Priority Queues – Solution

- Remove the max from the heap



Amir Kamil and Jack Sampson

Final Review

38

Hash Table Problem

- Draw the structure of a size 7 hash table after insertion of keys with the following hash codes: 0, 95, 21, 6, 64, 74, 3, 54, 34, 75, 10.

Amir Kamil and Jack Sampson

Final Review

39

Hash Tables

- High-level idea – 2 components
 - Big array called *hash table* of size M
 - Function h which maps keys to integer values
- For (key, item), use $h(\text{key}) \% M$ to find location of item in table
- Linked list in each entry that stores all items that map to that location (chaining)


Amir Kamil and Jack Sampson

Final Review

40

Hash Table Solution

- Draw the structure of a size 7 hash table after insertion of keys with the following hash codes: 0, 95, 21, 6, 64, 74, 3, 54, 34, 75, 10.



Amir Kamil and Jack Sampson


Final Review

41

AVL Tree Problem

- Given the following AVL Tree, performs these consecutive operations and draw out the tree in each step:

- Remove(7)
- Insert (11)
- Insert(12)



Amir Kamil and Jack Sampson

Final Review

42


AVL Trees

- AVL Trees are just Binary Search Trees that can rotate their nodes to try to maintain balance.
 - Two kinds of rotations – single and double
 - Can decide which to do based on structure of tree

Insertions/Removals


- You have 3 nodes of importance, which we will call x, y, and z (z is the parent of y which is the parent of x)
 - If x is the right child of y, and y is the right child of z, you do a single rotation (same goes for left child of left child)
 - If x is the right child of y, and y is the left child of z, you do a double rotation (same goes for left child of right child)

Remove(7)




Remove 7 as in BST

Remove(7)




Single rotate

Remove(7)




Final tree

Insert(11)



Insert as in BST

Insert(12)




Insert as in BST

Amir Kamil and Jack Sampson

Final Review

49

Insert(12)




Double rotate

Amir Kamil and Jack Sampson

Final Review

50

Insert(12)



Final tree

Amir Kamil and Jack Sampson

Final Review

51

Searches (BFS and DFS)

- BFS uses a queue, DFS uses a stack

```
public void BFS/DFS(Node start) {
    Queue/Stack s = new Queue/Stack();
    s.enqueue/push(start);
    while (!s.empty()) {
        Node n = s.dequeue/pop();
        mark(n);
        for (all children that are not yet marked) {
            s.enqueue/push(child);
        }
    }
}
```


Amir Kamil and Jack Sampson

Final Review

52

Searches (BFS and DFS) Problem

- Perform BFS and DFS on the graph, starting at node 1




Amir Kamil and Jack Sampson

Final Review

53

Searches (BFS and DFS) Solution

- Perform BFS and DFS on the graph, starting at node 1




Amir Kamil and Jack Sampson

Final Review

54

Topological Sort Problem

- Perform a topological sort on the graph




Topological Sort

- Perform DFS, computing start/finish times
- Order nodes by decreasing finish times


Topological Sort Solution

- Perform a topological sort on the graph



SCC Problem

- Find the strongly connected components of the graph




SCC Algorithm

- Perform DFS, computing start/finish times
- Invert graph
- Repeatedly run DFS on the remaining node with the highest finishing time
- The nodes marked in each DFS run compose a strongly connected component


SCC Solution

- Find the strongly connected components of the graph



SCC Solution

- Find the strongly connected components of the graph



Invert graph


Amir Kamil and Jack Sampson

Final Review

61

SCC Solution

- Find the strongly connected components of the graph



Run DFS on highest finish times


Amir Kamil and Jack Sampson

Final Review

62

SCC Solution

- Find the strongly connected components of the graph



Run DFS on highest finish times


Amir Kamil and Jack Sampson

Final Review

63

SCC Solution

- Find the strongly connected components of the graph



Run DFS on highest finish times


Amir Kamil and Jack Sampson

Final Review

64

Dijkstra's Algorithm Problem

- Find the shortest distances to each node from node 1



Amir Kamil and Jack Sampson

Final Review

65

Dijkstra's Algorithm

- Set all distances initially to ∞ , except the start node, which should be set to 0
- Construct a min priority queue of the nodes, with their distances as keys
- Repeatedly remove the minimum element, updating each of its adjacent node's distances if they are still in the queue and if the updated distance is less than the current distance


Amir Kamil and Jack Sampson

Final Review

66

Dijkstra's Algorithm Solution

- Find the shortest distances to each node from node 1




Amir Kamil and Jack Sampson

Final Review

67

Dijkstra's Algorithm Solution

- Find the shortest distances to each node from node 1




Amir Kamil and Jack Sampson

Final Review

68

Dijkstra's Algorithm Solution

- Find the shortest distances to each node from node 1




Amir Kamil and Jack Sampson

Final Review

69

Dijkstra's Algorithm Solution

- Find the shortest distances to each node from node 1




Amir Kamil and Jack Sampson

Final Review

70

Dijkstra's Algorithm Solution

- Find the shortest distances to each node from node 1




Amir Kamil and Jack Sampson

Final Review

71

Dijkstra's Algorithm Solution

- Find the shortest distances to each node from node 1




Amir Kamil and Jack Sampson

Final Review

72

Dijkstra's Algorithm Solution

- Find the shortest distances to each node from node 1



P.Q.
x1 (0)
x2 (3)
x3 (9)
x5 (10)
x4 (11)
x7 (14)
6 (15)


Amir Kamal and Jack Sampson

Final Review

73

Dijkstra's Algorithm Solution

- Find the shortest distances to each node from node 1



P.Q.
x1 (0)
x2 (3)
x3 (9)
x5 (10)
x4 (11)
x7 (14)
x6 (15)


Amir Kamal and Jack Sampson

Final Review

74

Kruskal's Algorithm Problem

- Find the MST of the graph, using Kruskal's Algorithm



Amir Kamal and Jack Sampson

Final Review

75

Kruskal's Algorithm

- Put each node into a set by itself
- Sort all the edges in ascending order by their weights
- Pick the least-weight edge, if the edge connects two nodes in different sets, add the edge to the MST and merge the two sets


Amir Kamal and Jack Sampson

Final Review

76

Kruskal's Algorithm Solution

- Find the MST of the graph, using Kruskal's Algorithm



Edges
3-5 (1)
3-4 (2)
1-2 (3)
4-6 (4)
5-7 (5)
2-3 (6)
5-6 (8)
2-4 (10)
5-6 (12)
1-5 (13)
6-7 (16)


Amir Kamal and Jack Sampson

Final Review

77

Kruskal's Algorithm Solution

- Find the MST of the graph, using Kruskal's Algorithm



Edges
x3-5 (1)
3-4 (2)
1-2 (3)
4-6 (4)
5-7 (5)
2-3 (6)
5-6 (8)
2-4 (10)
5-6 (12)
1-5 (13)
6-7 (16)


Amir Kamal and Jack Sampson

Final Review

78

Kruskal's Algorithm Solution

- Find the MST of the graph, using Kruskal's Algorithm




Amir Kamil and Jack Sampson

Final Review

79

Kruskal's Algorithm Solution

- Find the MST of the graph, using Kruskal's Algorithm




Amir Kamil and Jack Sampson

Final Review

80

Kruskal's Algorithm Solution

- Find the MST of the graph, using Kruskal's Algorithm




Amir Kamil and Jack Sampson

Final Review

81

Kruskal's Algorithm Solution

- Find the MST of the graph, using Kruskal's Algorithm




Amir Kamil and Jack Sampson

Final Review

82

Kruskal's Algorithm Solution

- Find the MST of the graph, using Kruskal's Algorithm




Amir Kamil and Jack Sampson

Final Review

83

Kruskal's Algorithm Solution

- Find the MST of the graph, using Kruskal's Algorithm



Amir Kamil and Jack Sampson

Final Review

84

Sorting

- Given the following steps, which sorting algorithms were used in each case?

13 27 89 26 9 37 5 1 38	13 27 89 26 9 37 5 1 38
1 27 89 26 9 37 5 13 38	13 27 26 9 37 5 1 38 89
1 5 89 26 9 37 27 13 38	1 13 27 26 9 37 5 38 89
1 5 9 26 89 37 27 13 38	1 5 13 27 26 9 37 38 89
1 5 9 13 89 37 27 26 38	1 5 13 27 26 9 37 38 89
1 5 9 13 26 37 27 89 38	1 5 9 13 27 26 37 38 89
1 5 9 13 26 27 37 89 38	1 5 9 13 26 27 37 38 89
1 5 9 13 26 27 37 89 38	
1 5 9 13 26 27 37 89 38	

Amir Kamil and Jack Sampson

Final Review

85

Sorting

Selection Sort

13 27 89 26 9 37 5 1 38
1 27 89 26 9 37 5 13 38
1 5 89 26 9 37 27 13 38
1 5 9 26 89 37 27 13 38
1 5 9 13 89 37 27 26 38
1 5 9 13 26 37 27 89 38
1 5 9 13 26 27 37 89 38
1 5 9 13 26 27 37 89 38
1 5 9 13 26 27 37 89 38

Quick Sort

13 27 89 26 9 37 5 1 38
13 27 26 9 37 5 1 38 89
1 13 27 26 9 37 5 38 89
1 5 13 27 26 9 37 38 89
1 5 13 27 26 9 37 38 89
1 5 9 13 27 26 37 38 89
1 5 9 13 26 37 27 89 38
1 5 9 13 26 27 37 89 38
1 5 9 13 26 27 37 89 38
1 5 9 13 26 27 37 89 38

Amir Kamil and Jack Sampson

Final Review

86

Sorting

- Do a radix sort on the following sequence, showing each step

(1087 643 2532 954 8174 65 340 1752)

Amir Kamil and Jack Sampson

Final Review

87

Sorting

- Step 1: sort by ones place

(1087 643 2532 954 8174 65 340 1752)



(340 2532 1752 643 954 8174 65 1087)

Amir Kamil and Jack Sampson

Final Review

88

Sorting

- Step 2: sort by tens place

(340 2532 1752 643 954 8174 65 1087)



(2532 340 643 1752 954 65 8174 1087)

Amir Kamil and Jack Sampson

Final Review

89

Sorting

- Step 3: sort by hundreds place

(2532 340 643 1752 954 65 8174 1087)



(65 1087 8174 340 2532 643 1752 954)

Amir Kamil and Jack Sampson

Final Review

90

Sorting

- Step 4: sort by thousands place

(65 1087 8174 340 2532 643 1752 954)



(65 340 643 954 1087 1752 2532 8174)

Skip List Problem

- Write code for searching a skip list for a key. Assume a skip list node is defined as


```
class Node {
    Comparable key;
    Node left, right, up, down;
}
```

and that the skip list pointer references the top left node.

Skip Lists

- 2D linked lists
- Bottom level contains all keys, and each subsequent level contains probabilistically half the keys of the previous level
- Each level starts at $-\infty$ and ends at $+\infty$
- The keys in each level are in ascending order

Skip List Example



Skip List Searching

- Start at top left node
- If the current key is equal to the search key, return the node
- If the next key is greater than the search key, go down and repeat search
- Otherwise go right and repeat search


Skip List Solution

- Write code for searching a skip list for a key

```
Node search(Node n, Comparable key) {
    if (n.key.equals(key)) {
        return n;
    } else if (n.next.key.compareTo(key) > 0) {
        return search(n.down, key);
    } else {
        return search(n.next, key);
    }
}
```


Skip List Searching

Search for 18



9 is not greater than 18, so move right


Amir Kamil and Jack Sampson

Final Review

97

Skip List Searching

Search for 18



∞ is greater than 18, so move down


Amir Kamil and Jack Sampson

Final Review

98

Skip List Searching

Search for 18



∞ is greater than 18, so move down


Amir Kamil and Jack Sampson

Final Review

99

Skip List Searching

Search for 18



18 is not greater than 18, so move right


Amir Kamil and Jack Sampson

Final Review

100

Skip List Searching

Search for 18



18 is equal to 18, so return node

Amir Kamil and Jack Sampson

Final Review

101

Threading

- Motivations:
 - Modeling of simultaneous actions
 - Counteract I/O Latency
- Mechanism: Multiple threads of control
 - Shared memory space, multiple program counters
- Dangers:
 - Shared access to memory can result in conflicts
 - Multiple threads per processor can result in unequal time sharing (see scheduling)
- Conflict types:
 - WAR (write after read)
 - WAW (write after write)
 - RAW (read after write)
- How to avoid shared data conflicts? Locking
- Dangers of locking? Deadlock

Amir Kamil and Jack Sampson

Final Review

102

Scheduling

- **Throughput** – Average number of tasks completed per unit time
- **CPU Utilization** – Average usage of the processor
- **Wait time** – time spent waiting for processor
- **Turnaround time** – time from task assignment to task completion
- **Response time** – time between assignment of task and first work on task
- **Large values => GOOD:**
 - throughput
 - cpu utilization
- **Large values => BAD (maybe):**
 - wait time
 - turnaround time
 - response time
- **I/O ?**

Amir Kamil and Jack Sampson

Final Review

103

The Min-Max Algorithm

- An algorithm for making the best possible move in a **ZERO-SUM-GAME** (not applicable to other types of games)

```
MinMax( State, maxtype)
  if gameover(State) return [null move, score(State)]
  if (maxtype)
    return pair with max score from
      for each valid move from State MinMax(NewState, !
maxtype)
  else
    return pair with min score from
      for each valid move from State MinMax(NewState, !
maxtype)
```

- **Justification:**

- In a zero-sum-game, the best move for an opponent is to minimize your score, just as your best move is to maximize your score. This will therefore return the best possible move under the assumption that one's opponent plays perfectly.

Amir Kamil and Jack Sampson

Final Review

104

The Min-Max Algorithm

- The following is an implementation of Min-Max in Common Lisp:

```
;; The minimax decision procedure returns the optimal move in the game
;; using exhaustive generation of the entire game tree. Implementation
;; uses the fact that the evaluation and utility functions return a list of
;; values from the point of view of each player, with the "current" player
;; first. Hence, rather than using #min, we always use #max for the
;; current player. A successor value is passed up the tree using
;; right-rotation. This works for any number of players.
;; The notation "a+s" means an (action . state) pair.
```

```
(defun minimax-decision (state game)
  (car (the-biggest
        #(lambda (a+s) (first (right-rotate (minimax-value (cdr a+s) game))))
        (game-successors state game))))
```

```
(defun minimax-value (state game)
  (if (game-over? game state)
      (terminal-values state)
      (right-rotate
       (the-biggest
        #(lambda (values) (first (right-rotate values))))
       (mapcar #(lambda (a+s) (minimax-value (cdr a+s) game))
               (game-successors state game)))))
```

Amir Kamil and Jack Sampson

Final Review

105

Min-Max with cutoff

```
(defun minimax-cutoff-decision (state game eval-fn limit)
  "Return the best action, according to backed-up evaluation down to LIMIT.
  After we search LIMIT levels deep, we use EVAL-FN to provide an estimate
  of the true value of a state; thus the action may not actually be best."
  (car (the-biggest
```

```
    #(lambda (a+s)
      (first (right-rotate
              (minimax-cutoff-value (cdr a+s) game eval-fn (- limit 1))))
      (game-successors state game))))
```

```
(defun minimax-cutoff-value (state game eval-fn limit)
  (cond ((game-over? game state) (terminal-values state))
        ((<= limit 0) (uncall eval-fn state))
        (t (right-rotate
            (the-biggest
             #(lambda (values) (first (right-rotate values))))
            (mapcar #(lambda (a+s)
                      (minimax-cutoff-value (cdr a+s) game eval-fn
                                              (- limit 1)))
                    (game-successors state game))))))
```

Amir Kamil and Jack Sampson

Final Review

106

Min-Max with cutoff

```
(defun game-successors (state game)
  "Return a list of (move . state) pairs that can be reached from this state."
  (mapcar #(lambda (move) (cons move (make-move game state move)))
          (legal-moves game state)))
```

```
(defun terminal-values (state)
  "Return the values of the state for each player."
  (mapcar #(lambda (player) (getf (game-state-scores state) player))
          (game-state-players state)))
```

Amir Kamil and Jack Sampson

Final Review

107

alpha-beta pruning

```
(defun alpha-beta-decision (state game eval-fn &optional (limit 4))
  "Return the estimated best action, searching up to LIMIT and then
  applying the EVAL-FN."
```

```
(car (the-biggest
      #(lambda (a+s)
        (first (right-rotate
                (alpha-value (cdr a+s) game
                             (game-worst game) (game-worst game)
                             eval-fn (- limit 1))))
        (game-successors state game))))
```

```
(defun alpha-value (state game alpha beta eval-fn limit)
  (cond ((game-over? game state) (terminal-values state))
        ((= 0 limit) (uncall eval-fn state))
        (t (dolist (a+s (game-successors state game))
              (list alpha (- alpha)))
            (setq alpha (max alpha
                             (first (right-rotate
                                     (beta-value (cdr a+s) game alpha beta
                                                  eval-fn (- limit 1))))))
              (when (>= alpha (- beta))
                (return (list (- beta) beta))))))
```

Amir Kamil and Jack Sampson

Final Review

108

alpha-beta pruning

```
(defun beta-value (state game alpha beta eval-fn limit)
  (cond ((game-over? game state) (terminal-values state))
        ((= 0 limit) (luncali eval-fn state))
        (t (doalist (a+s (game-successors state game))
                     (list beta (- beta a))
                     (lambda ()
                       (first (right-rotate
                              (alpha-value (cdr a+s) game alpha beta
                                             eval-fn (- limit 1)))))))
        (when (>= beta (- alpha))
          (return (list (- alpha) alpha))))))
```

Cool tree variants

■ The threaded tree:

- Motivations:
 - Inorder traversals are common
 - Naive BST implementation can waste space (~half of all child pointers are null)
- Mechanism:
 - Add boolean flag to pointers (or do fun polymorphism) so as to have leaf nodes point to the next node in an inorder traversal
- Results:
 - For a minimal change in the space requirements and structure of a tree, inorder traversals can now be computed using a straightforward iterative algorithm

Cool tree variants continued

■ The B+ tree:

- Motivations:
 - Range queries are common
 - size of Data >> size of Key, so treat differently
- Mechanism:
 - Start with B-tree
 - Differentiate between Leaf and index nodes. Index nodes hold keys, leaf nodes hold data. Key values for all data are in leaf nodes.
 - Insert and delete as before, except keys are copied up on split, not moved, and keys may remain on delete for data that no longer exists
 - Add next and previous fields to all leaf nodes, forming a doubly linked list
- Results:
 - Range query now straightforward to return result for - tree now optimized for contiguous storage on physical media

Credits

■ Thanks to CS 61b staff of

- Fall 2001
- Spring 2002

■ Thanks to Steve Sinha and Winston Liaw

■ Thanks to

- CMU – MIT
- Cornell – Johns Hopkins U

for slide and example ideas

GOOD LUCK!

(and may you not need it)