

[home](#) [articles](#) [quick answers](#) [discussions](#) [features](#) [community](#) [help](#)

Search for articles, questions, tips



Articles » Languages » C / C++ Language » General

Next ➞

Article

[Browse Code](#)
[Stats](#)
[Revisions](#)
[Alternatives](#)
[Comments & Discussions \(46\)](#)

Calling Conventions Demystified

By **Nemanja Trifunovic**, 22 Sep 2001[Sign Up](#) to vote★★★★★ 4.88 (144 votes) [Like](#) 7[Tweet](#) 4

1

Introduction

During the long, hard, but yet beautiful process of learning C++ programming for Windows, you have probably been curious about the strange specifiers that sometime appear in front of function declarations, like `__cdecl`, `__stdcall`, `__fastcall`, `WINAPI`, etc. After looking through MSDN, or some other reference, you probably found out that these specifiers specify the *calling conventions* for functions. In this article, I will try to explain different calling conventions used by Visual C++ (and probably other Windows C/C++ compilers). I emphasize that above mentioned specifiers are Microsoft-specific, and that you should not use them if you want to write portable code.

So, what are the calling conventions? When a function is called, the arguments are typically passed to it, and the return value is retrieved. A calling convention describes *how* the arguments are passed and values returned by functions. It also specifies how the function names are decorated. Is it really necessary to understand the calling conventions to write good C/C++ programs? Not at all. However, it may be helpful with debugging. Also, it is necessary for linking C/C++ with assembly code.

To understand this article, you will need to have some very basic knowledge of assembly programming.

No matter which calling convention is used, the following things will happen:

1. All arguments are widened to 4 bytes (on Win32, of course), and put into appropriate memory locations. These locations are typically on the stack, but may also be in registers; this is specified by calling conventions.
2. Program execution jumps to the address of the called function.
3. Inside the function, registers ESI, EDI, EBX, and EBP are saved on the stack. The part of code that performs these operations is called *function prolog* and usually is generated by the compiler.
4. The function-specific code is executed, and the return value is placed into the EAX register.
5. Registers ESI, EDI, EBX, and EBP are restored from the stack. The piece of code that does this is called *function epilog*, and as with the function prolog, in most cases the compiler generates it.
6. Arguments are removed from the stack. This operation is called *stack cleanup* and may be performed either inside the called function or by the caller, depending on the calling convention used.

As an example for the calling conventions (except for *this*), we are going to use a simple function:

[Collapse](#) | [Copy Code](#)

```
int sumExample (int a, int b)
{
    return a + b;
}
```

The call to this function will look like this:

[Collapse](#) | [Copy Code](#)

```
int c = sum (2, 3);
```

For `__cdecl`, `__stdcall`, and `__fastcall` calling conventions, I compiled the example code as C (not C++). The function name decorations, mentioned later in the article, apply to the C decoration schema. C++ name decorations are beyond the scope of this article.

C calling convention (__cdecl)

About Article

Visual C++ calling conventions explained

Type **Article**Licence **CPOL**First Posted **22 Sep 2001**Views **248,461**Bookmarked **155 times**

VC6 Win2K

Visual-Studio Dev . . .



Print

Email

Top News

[6 dirty secrets of the IT industry](#)[Get the Insider News free each](#)

This convention is the default for C/C++ programs (compiler option /Gd). If a project is set to use some other calling convention, we can still declare a function to use `__cdecl`:

[Collapse](#) | [Copy Code](#)

```
int __cdecl sumExample (int a, int b);
```

The main characteristics of `__cdecl` calling convention are:

1. Arguments are passed from right to left, and placed on the stack.
2. Stack cleanup is performed by the caller.
3. Function name is decorated by prefixing it with an underscore character '_'.

Now, take a look at an example of a `__cdecl` call:

[Collapse](#) | [Copy Code](#)

```
; // push arguments to the stack, from right to left
push    3
push    2

; // call the function
call    _sumExample

; // cleanup the stack by adding the size of the arguments to ESP register
add     esp,8

; // copy the return value from EAX to a local variable (int c)
mov     dword ptr [c],eax
```

The called function is shown below:

[Collapse](#) | [Copy Code](#)

```
; // function prolog
push    ebp
mov     ebp,esp
sub     esp,0C0h
push    ebx
push    esi
push    edi
lea     edi,[ebp-0C0h]
mov     ecx,30h
mov     eax,0CCCCCCCCh
rep stos dword ptr [edi]

; // return a + b;
mov     eax,dword ptr [a]
add     eax,dword ptr [b]

; // function epilog
pop     edi
pop     esi
pop     ebx
mov     esp,ebp
pop     ebp
ret
```

Standard calling convention (__stdcall)

This convention is usually used to call Win32 API functions. In fact, **WINAPI** is nothing but another name for `__stdcall`:

[Collapse](#) | [Copy Code](#)

```
#define WINAPI __stdcall
```

We can explicitly declare a function to use the `__stdcall` convention:

[Collapse](#) | [Copy Code](#)

```
int __stdcall sumExample (int a, int b);
```


Also, we can use the compiler option /Gz to specify `__stdcall` for all functions not explicitly declared with some other calling convention.

The main characteristics of `__stdcall` calling convention are:

1. Arguments are passed from right to left, and placed on the stack.
2. Stack cleanup is performed by the called function.
3. Function name is decorated by prepending an underscore character and appending a '@' character and the number of bytes of stack space required.

The example follows:

Related Videos



Related Articles

.NET file format - Signatures under the hood, Part 1 of 2

How to invoke C++ member operations from inline-assembler code segments

Using the `_CDECL` calling convention in C# (changing compiler service)

Compilers Demystified: Function Pointers in Visual Basic 6.0

P/Invoke Tutorial: Basics (Part 1)

WPFSpark: 1 of n: SprocketControl

Using Assembly routines in Visual C++

Using C calling convention callback functions in C# and VB - the easy way

Finite State Machine and Multithreading using .NET

Thread synchronization: Wait and Pulse demystified

Calling Conventions for SSI Test Modules

Globalization and localization demystified in ASP.NET 2.0

Some practices to write better C#/.NET code

Static Keyword Demystified

Late binding on native DLLs with C#

Switching threads

Case-Insensitive String Search

Step by Step: Calling C++ DLLs from VC++ and VB - Part 2

Accessing an API through a closed source C++ DLL

Calling DLLs in VB and C++

Related Research



The Essential Guide to Mobile App Testing

[Collapse](#) | [Copy Code](#)

```

; // push arguments to the stack, from right to left
push    3
push    2

; // call the function
call    _sumExample@8

; // copy the return value from EAX to a local variable (int c)
mov     dword ptr [c],eax

```

The function code is shown below:

[Collapse](#) | [Copy Code](#)

```

; // function prolog goes here (the same code as in the __cdecl example)

; //     return a + b;
mov     eax,dword ptr [a]
add     eax,dword ptr [b]

; // function epilog goes here (the same code as in the __cdecl example)

; // cleanup the stack and return
ret     8

```

Because the stack is cleaned by the called function, the `__stdcall` calling convention creates smaller executables than `__cdecl`, in which the code for stack cleanup must be generated for each function call. On the other hand, functions with the variable number of arguments (like `printf()`) must use `__cdecl`, because only the caller knows the number of arguments in each function call; therefore only the caller can perform the stack cleanup.

Fast calling convention (`__fastcall`)

Fast calling convention indicates that the arguments should be placed in registers, rather than on the stack, whenever possible. This reduces the cost of a function call, because operations with registers are faster than with the stack.

We can explicitly declare a function to use the `__fastcall` convention as shown:

[Collapse](#) | [Copy Code](#)

```
int __fastcall sumExample (int a, int b);
```

We can also use the compiler option `/Gr` to specify `__fastcall` for all functions not explicitly declared with some other calling convention.

The main characteristics of `__fastcall` calling convention are:

1. The first two function arguments that require 32 bits or less are placed into registers ECX and EDX. The rest of them are pushed on the stack from right to left.
2. Arguments are popped from the stack by the called function.
3. Function name is decorated by prepending a '@' character and appending a '@' and the number of bytes (decimal) of space required by the arguments.

Note: Microsoft have reserved the right to change the registers for passing the arguments in future compiler versions.

Here goes an example:

[Collapse](#) | [Copy Code](#)

```

; // put the arguments in the registers EDX and ECX
mov     edx,3
mov     ecx,2

; // call the function
call    @fastcallSum@8

; // copy the return value from EAX to a local variable (int c)
mov     dword ptr [c],eax

```

Function code:

[Collapse](#) | [Copy Code](#)

```

; // function prolog

push    ebp
mov     ebp,esp
sub     esp,0D8h
push    ebx
push    esi
push    edi
push    ecx
lea     edi,[ebp-0D8h]
mov     ecx,36h

```

```

mov     eax,0CCCCCCCCh
rep stos dword ptr [edi]
pop     ecx
mov     dword ptr [ebp-14h],edx
mov     dword ptr [ebp-8],ecx
; // return a + b;
mov     eax,dword ptr [a]
add     eax,dword ptr [b]
; // function epilog
pop     edi
pop     esi
pop     ebx
mov     esp,ebp
pop     ebp
ret

```

How fast is this calling convention, comparing to `__cdecl` and `__stdcall`? Find out for yourselves. Set the compiler option `/Gr`, and compare the execution time. I didn't find `__fastcall` to be any faster than other calling conventions, but you may come to different conclusions.

Thiscall

Thiscall is the default calling convention for calling member functions of C++ classes (except for those with a variable number of arguments).

The main characteristics of **thiscall** calling convention are:

1. Arguments are passed from right to left, and placed on the stack. **this** is placed in ECX.
2. Stack cleanup is performed by the called function.

The example for this calling convention had to be a little different. First, the code is compiled as C++, and not C. Second, we have a struct with a member function, instead of a global function.

[Collapse](#) | [Copy Code](#)

```

struct CSum
{
    int sum ( int a, int b) {return a+b;}
};

```

The assembly code for the function call looks like this:

[Collapse](#) | [Copy Code](#)

```

push     3
push     2
lea      ecx,[sumObj]
call     ?sum@CSum@@@QAEHHH@Z      ; CSum::sum
mov     dword ptr [s4],eax

```

The function itself is given below:

[Collapse](#) | [Copy Code](#)

```

push     ebp
mov     ebp,esp
sub     esp,0CCh
push     ebx
push     esi
push     edi
push     ecx
lea     edi,[ebp-0CCh]
mov     ecx,33h
mov     eax,0CCCCCCCCh
rep stos dword ptr [edi]
pop     ecx
mov     dword ptr [ebp-8],ecx
mov     eax,dword ptr [a]
add     eax,dword ptr [b]
pop     edi
pop     esi
pop     ebx
mov     esp,ebp
pop     ebp
ret     8

```

Now, what happens if we have a member function with a variable number of arguments? In that case, `__cdecl` is used, and **this** is pushed onto the stack last.

Conclusion

To cut a long story short, we'll outline the main differences between the calling conventions:

- `__cdecl` is the default calling convention for C and C++ programs. The advantage of this calling convention

is that it allows functions with a variable number of arguments to be used. The disadvantage is that it creates larger executables.

- `__stdcall` is used to call Win32 API functions. It does not allow functions to have a variable number of arguments.
- `__fastcall` attempts to put arguments in registers, rather than on the stack, thus making function calls faster.
- `Thiscall` calling convention is the default calling convention used by C++ member functions that do not use variable arguments.

In most cases, this is all you'll ever need to know about the calling conventions.

License

This article, along with any associated source code and files, is licensed under [The Code Project Open License \(CPOL\)](#)

About the Author



Nemanja Trifunovic

Software Developer (Senior) SAP
United States

Born in Kragujevac, Serbia. Now lives in Boston area with his wife and daughters.

Wrote his first program at the age of 13 on a Sinclair Spectrum, became a professional software developer after he graduated.

Very passionate about programming and software development in general.

[Article Top](#)

Comments and Discussions

You must [Sign In](#) to use this message board.

Search this forum

☒ Profile popups Spacing Noise Layout Per page

First	Prev	Next
Differences in Usage in C/C++	rnjailamba	29-Oct-13 21:26
My vote of 5	DaveyM69	22-May-13 3:32
Re: My vote of 5	Nemanja Trifunovic	22-May-13 4:54
Re: My vote of 5	DaveyM69	22-May-13 21:49
My vote of 5	hbobenicio	22-Jan-13 7:21
link different calling conventions	Member 3020704	29-Nov-12 3:05
My vote of 5	victory2381	20-Sep-12 11:04
My vote of 5	Member 9416287	18-Sep-12 0:02

 Benefit a lot here! 	 Vick Qi	27-Jul-12 7:04
 My vote of 4 	 Member 4417071	18-Jun-12 22:43
Last Visit: 31-Dec-99 18:00 Last Update: 4-Nov-13 10:53 Refresh 1 2 3 4 5 Next »		

 General  News  Suggestion  Question  Bug  Answer  Joke  Rant  Admin

Use Ctrl+Left/Right to switch messages, Ctrl+Up/Down to switch threads, Ctrl+Shift+Left/Right to switch pages.