



sa 发布于 2018-01-20    分类: [未分类 \(https://www.centos.bz/category/undefine/\)](https://www.centos.bz/category/undefine/)    阅读(1923)    评论(0)

[查看MariaDB版本](#)

```
brew info mariadb
```

## 安装MariaDB

```
brew install mariadb
```

## 运行数据库安装程序

分别执行下面的命令来实现安装:

```
unset TMPDIR
cd /usr/local/opt/mariadb/bin/
mysql_install_db
```

## 运行MariaDB

mysql.server (<https://www.centos.bz/tag/server/>) start

或

```
brew services start mariadb
```

## 添加环境变量

```
vi ~/.bash_profile
```

## 添加

```
export (https://www.centos.bz/tag/export/)  
PATH=$PATH:/usr/local/opt/mariadb/bin:/usr/local/sbin/
```

## 运行生效

```
source (https://www.centos.bz/tag/source/) ~/.bash_profile
```

重设root用户的密码、移除匿名用户、移除默认的test数据库等等，具体的执行和设置如下：

```
mysql_secure_installation
```

## 依次

```
Enter current password for root (enter for none):  
Set root password? [Y/n] Y  
Remove anonymous users? [Y/n] Y  
Disallow root login remotely? [Y/n] n  
Remove test database and access to it? [Y/n] Y  
Reload privilege tables now? [Y/n] Y
```

连接MariaDB数据库的命令：

```
mysql -u root -p
```

## 验证MariaDB版本

```
MariaDB [(none)]> select @@version;
```

## MariaDB基础命令



