

# Final Project Milestone2

## Data Cleaning/formatting flat file source

In this phase of the project, we will cleanup the properties dataset. The transactions dataset and properties datasets have an ID that is common between them, so we will merge them by that index.

*Please note the webscraping and API sections have been pushed further down to allow room for documenting this phase of the project.*

## Dataset from file

### Data Source

<https://www.kaggle.com/c/zillow-prize-1> (<https://www.kaggle.com/c/zillow-prize-1>)

### Description

There are two data sets with over 1 million records each and 58 columns. properties\_2016 and properties\_2017 datasets contain data for each year. The data we will use for this project will be a small sample of the master data.

The two datasets are linked by parcleid.

In transactions dataset, the transaction date shows the date the property was sold and logerror is the  $\log_{10}(\text{estimated price} - \text{price sold})$ .

Properties dataset has the physical information about the properties. The columns on the properties dataset will have to be renamed. Subsets of data can be used to group by region, and other features such as number of bedrooms, square footage, etc.

```
In [117]: # Load Libraries
import pandas as pd
import matplotlib.pyplot as plt
import xlrd
import numpy as np
# Load Data
transactions_2016 = "Data/transactions_2016.json"
transactions_2017 = "Data/transactions_2017.json"

properties_2016 = "Data/properties_2016.csv"
properties_2017 = "Data/properties_2017.csv"
data_dictionary = "Data/data_dictionary.xlsx"

transactions_2016 = pd.read_json(transactions_2016)
transactions_2017 = pd.read_json(transactions_2017)
properties_2016 = pd.read_csv(properties_2016)
properties_2017 = pd.read_csv(properties_2017)
data_dictionary = pd.read_excel(data_dictionary)
```

c:\users\safar\documents\github\safariel103\bellevue university\courses\dsc540\env\lib\site-packages\IPython\core\interactiveshell.py:3063: DtypeWarning: Columns (50) have mixed types.Specify dtype option on import or set low\_memory=False.

interactivity=interactivity, compiler=compiler, result=result)  
c:\users\safar\documents\github\safariel103\bellevue university\courses\dsc540\env\lib\site-packages\IPython\core\interactiveshell.py:3063: DtypeWarning: Columns (23,50) have mixed types.Specify dtype option on import or set low\_memory=False.

interactivity=interactivity, compiler=compiler, result=result)

```
In [2]: transactions_2016.head()
```

Out[2]:

	parcelid	logerror	transactiondate
0	11016594	0.0276	2016-01-01
1	14366692	-0.1684	2016-01-01
2	12098116	-0.0040	2016-01-01
3	12643413	0.0218	2016-01-02
4	14432541	-0.0050	2016-01-02

```
In [3]: properties_2016.head()
```

```
Out[3]:
```

	Unnamed: 0	parcelid	airconditioningtypeid	architecturalstyletypeid	basements
0	0	10754147	NaN	NaN	1
1	1	10759547	NaN	NaN	1
2	2	10843547	NaN	NaN	1
3	3	10859147	NaN	NaN	1
4	4	10879947	NaN	NaN	1

5 rows × 59 columns

```
In [4]: print(len(properties_2016.columns))
print(properties_2016.columns)
```

```
59
Index(['Unnamed: 0', 'parcelid', 'airconditioningtypeid',
      'architecturalstyletypeid', 'basementsqft', 'bathroomcnt', 'bedroomcnt',
      'buildingclasstypid', 'buildingqualitytypeid', 'calculatedbathnbr',
      'decktypeid', 'finishedfloorlsquarefeet',
      'calculatedfinishedsquarefeet', 'finishedsquarefeet12',
      'finishedsquarefeet13', 'finishedsquarefeet15', 'finishedsquarefeet50',
      'finishedsquarefeet6', 'fips', 'fireplacecnt', 'fullbathcnt',
      'garagecarcnt', 'garagetotalsqft', 'hashottuborspa',
      'heatingorsystemtypeid', 'latitude', 'longitude', 'lotsizesquarefeet',
      'poolcnt', 'poolsizesum', 'pooltypeid10', 'pooltypeid2', 'pooltypeid7',
      'propertycountylandusecode', 'propertylandusetypeid',
      'propertyzoningdesc', 'rawcensustractandblock', 'regionidcity',
      'regionidcounty', 'regionidneighborhood', 'regionidzip', 'roomcnt',
      'storytypeid', 'threequarterbathnbr', 'typeconstructiontypeid',
      'unitcnt', 'yardbuildingsqft17', 'yardbuildingsqft26', 'yearbuilt',
      'numberofstories', 'fireplaceflag', 'structuretaxvaluedollarcnt',
      'taxvaluedollarcnt', 'assessmentyear', 'landtaxvaluedollarcnt',
      'taxamount', 'taxdelinquencyflag', 'taxdelinquencyyear',
      'censustractandblock'],
      dtype='object')
```

```
In [5]: print(len(properties_2017.columns))
print(properties_2017.columns)
```

```
59
Index(['Unnamed: 0', 'parcelid', 'airconditioningtypeid',
      'architecturalstyletypeid', 'basementsqft', 'bathroomcnt', 'bedroomcnt',
      'buildingclasstypoid', 'buildingqualitytypeid', 'calculatedbathnbr',
      'decktypeid', 'finishedfloorlsquarefeet',
      'calculatedfinishedsquarefeet', 'finishedsquarefeet12',
      'finishedsquarefeet13', 'finishedsquarefeet15', 'finishedsquarefeet50',
      'finishedsquarefeet6', 'fips', 'fireplacecnt', 'fullbathcnt',
      'garagecarcnt', 'garagetotalsqft', 'hashottuborspa',
      'heatingorsystemtypeid', 'latitude', 'longitude', 'lotsizesquarefeet',
      'poolcnt', 'poolsizesum', 'pooltypeid10', 'pooltypeid2', 'pooltypeid7',
      'propertycountylandusecode', 'propertylandusetypeid',
      'propertyzoningdesc', 'rawcensustractandblock', 'regionidcity',
      'regionidcounty', 'regionidneighborhood', 'regionidzip', 'roomcnt',
      'storytypeid', 'threequarterbathnbr', 'typeconstructiontypeid',
      'unitcnt', 'yardbuildingsqft17', 'yardbuildingsqft26', 'yearbuilt',
      'numberofstories', 'fireplaceflag', 'structuretaxvaluedollarcnt',
      'taxvaluedollarcnt', 'assessmentyear', 'landtaxvaluedollarcnt',
      'taxamount', 'taxdelinquencyflag', 'taxdelinquencyyear',
      'censustractandblock'],
      dtype='object')
```

```
In [6]: print(len(transactions_2016.columns))
print(transactions_2016.columns)
```

```
3
Index(['parcelid', 'logerror', 'transactiondate'], dtype='object')
```

```
In [7]: print(len(transactions_2017.columns))
print(transactions_2017.columns)
```

```
3
Index(['parcelid', 'logerror', 'transactiondate'], dtype='object')
```

```
In [8]: data_dictionary.head()
```

Out[8]:

	Feature	Description
0	'airconditioningtypeid'	Type of cooling system present in the home (i...
1	'architecturalstyletypeid'	Architectural style of the home (i.e. ranch, ...
2	'basementsqft'	Finished living area below or partially below...
3	'bathroomcnt'	Number of bathrooms in home including fractio...
4	'bedroomcnt'	Number of bedrooms in home

## Cleaning/formatting flat file sources

We will first combine the properties\_2016 and properties\_2017 and call the result properties. We will also combine the two transactions datasets.

```
In [9]: properties = pd.concat([properties_2016,properties_2017],axis=0)
print(properties_2016.shape)
print(properties_2017.shape)
print(properties.shape)
```

```
(20000, 59)
(20000, 59)
(40000, 59)
```

```
In [10]: transactions = pd.concat([transactions_2016,transactions_2017],axis=0)
print(properties_2016.shape)
print(properties_2017.shape)
print(properties.shape)
```

```
(20000, 59)
(20000, 59)
(40000, 59)
```

```
In [11]: properties.columns
```

```
Out[11]: Index(['Unnamed: 0', 'parcelid', 'airconditioningtypeid',  
               'architecturalstyletypeid', 'basementsqft', 'bathroomcnt', 'bedroomcnt',  
               'buildingclasstypid', 'buildingqualitytypeid', 'calculatedbathnbr',  
               'decktypeid', 'finishedfloorlsquarefeet',  
               'calculatedfinishedsquarefeet', 'finishedsquarefeet12',  
               'finishedsquarefeet13', 'finishedsquarefeet15', 'finishedsquarefeet50',  
               'finishedsquarefeet6', 'fips', 'fireplacecnt', 'fullbathcnt',  
               'garagecarcnt', 'garagetotalsqft', 'hashottuborspa',  
               'heatingorsystemtypeid', 'latitude', 'longitude', 'lotsizesquarefeet',  
               'poolcnt', 'poolsizesum', 'pooltypeid10', 'pooltypeid2', 'pooltypeid7',  
               'propertycountylandusecode', 'propertylandusetypeid',  
               'propertyzoningdesc', 'rawcensustractandblock', 'regionidcity',  
               'regionidcounty', 'regionidneighborhood', 'regionidzip', 'roomcnt',  
               'storytypeid', 'threequarterbathnbr', 'typeconstructiontypeid',  
               'unitcnt', 'yardbuildingsqft17', 'yardbuildingsqft26', 'yearbuilt',  
               'numberofstories', 'fireplaceflag', 'structuretaxvaluedollarcnt',  
               'taxvaluedollarcnt', 'assessmentyear', 'landtaxvaluedollarcnt',  
               'taxamount', 'taxdelinquencyflag', 'taxdelinquencyyear',  
               'censustractandblock'],  
              dtype='object')
```

Get rid of the Unamed column.

```
In [12]: properties = properties.loc[:, ~properties.columns.str.contains('^Unnamed')]
properties.columns
```

```
Out[12]: Index(['parcelid', 'airconditioningtypeid', 'architecturalstyletypeid',
               'basementsqft', 'bathroomcnt', 'bedroomcnt', 'buildingclasstypeid',
               'buildingqualitytypeid', 'calculatedbathnbr', 'decktypeid',
               'finishedfloorlsquarefeet', 'calculatedfinishedsquarefeet',
               'finishedsquarefeet12', 'finishedsquarefeet13', 'finishedsquarefeet15',
               'finishedsquarefeet50', 'finishedsquarefeet6', 'fips', 'fireplacecnt',
               'fullbathcnt', 'garagecarcnt', 'garagetotalsqft', 'hashottuborspa',
               'heatingorsystemtypeid', 'latitude', 'longitude', 'lotsizesquarefeet',
               'poolcnt', 'poolsizesum', 'pooltypeid10', 'pooltypeid2', 'pooltypeid7',
               'propertycountylandusecode', 'propertylandusetypeid',
               'propertyzoningdesc', 'rawcensustractandblock', 'regionidcity',
               'regionidcounty', 'regionidneighborhood', 'regionidzip', 'roomcnt',
               'storytypeid', 'threequarterbathnbr', 'typeconstructiontypeid',
               'unitcnt', 'yardbuildingsqft17', 'yardbuildingsqft26', 'yearbuilt',
               'numberofstories', 'fireplaceflag', 'structuretaxvaluedollarcnt',
               'taxvaluedollarcnt', 'assessmentyear', 'landtaxvaluedollarcnt',
               'taxamount', 'taxdelinquencyflag', 'taxdelinquencyyear',
               'censustractandblock'],
              dtype='object')
```

Rename column names in properties dataset.

```

In [13]: properties = properties.rename(columns=
        {
            'parcelid': 'parcelid',
            'yearbuilt': 'build_year',
            'basementsqft': 'area_basement',
            'yardbuildingsqft17': 'area_patio',
            'yardbuildingsqft26': 'area_shed',
            'poolsum': 'area_pool',
            'lotsizesquarefeet': 'area_lot',
            'garagetotalsqft': 'area_garage',
            'finishedfloor1squarefeet': 'area_firstfloor_finished',
            'calculatedfinishedsquarefeet': 'area_total_calc',
            'finishedsquarefeet6': 'area_base',
            'finishedsquarefeet12': 'area_live_finished',
            'finishedsquarefeet13': 'area_liveperi_finished',
            'finishedsquarefeet15': 'area_total_finished',
            'finishedsquarefeet50': 'area_unknown',
            'unitcnt': 'num_unit',
            'numberofstories': 'num_story',
            'roomcnt': 'num_room',
            'bathroomcnt': 'num_bathroom',
            'bedroomcnt': 'num_bedroom',
            'calculatedbathnbr': 'num_bathroom_calc',
            'fullbathcnt': 'num_bath',
            'threequarterbathnbr': 'num_75_bath',
            'fireplacecnt': 'num_fireplace',
            'poolcnt': 'num_pool',
            'garagecarcnt': 'num_garage',
            'regionidcounty': 'region_county',
            'regionidcity': 'region_city',
            'regionidzip': 'region_zip',
            'regionidneighborhood': 'region_neighbor',
            'taxvaluedollarcnt': 'tax_total',
            'structuretaxvaluedollarcnt': 'tax_building',
            'landtaxvaluedollarcnt': 'tax_land',
            'taxamount': 'tax_property',
            'assessmentyear': 'tax_year',
            'taxdelinquencyflag': 'tax_delinquency',
            'taxdelinquencyyear': 'tax_delinquency_year',
            'propertyzoningdesc': 'zoning_property',
            'propertylandusetypeid': 'zoning_landuse',
            'propertycountylandusecode': 'zoning_landuse_county',
            'fireplaceflag': 'flag_fireplace',
            'hashottuborspa': 'flag_tub',
            'buildingqualitytypeid': 'quality',
            'buildingclasstypeid': 'framing',
            'typeconstructiontypeid': 'material',
            'decktypeid': 'deck',
            'storytypeid': 'story',
            'heatingorsystemtypeid': 'heating',
            'airconditioningtypeid': 'aircon',
            'architecturalstyletypeid': 'architectural_style'
        })

```



```
In [14]: properties.columns
```

```
Out[14]: Index(['parcelid', 'aircon', 'architectural_style', 'area_basement',  
               'num_bathroom', 'num_bedroom', 'framing', 'quality',  
               'num_bathroom_calc', 'deck', 'area_firstfloor_finished',  
               'area_total_calc', 'area_live_finished', 'area_liveperi_finished',  
               'area_total_finished', 'area_unknown', 'area_base', 'fips',  
               'num_fireplace', 'num_bath', 'num_garage', 'area_garage', 'flag_tu  
b',  
               'heating', 'latitude', 'longitude', 'area_lot', 'num_pool', 'area_  
pool',  
               'pooltypeid10', 'pooltypeid2', 'pooltypeid7', 'zoning_landuse_coun  
ty',  
               'zoning_landuse', 'zoning_property', 'rawcensustractandblock',  
               'region_city', 'region_county', 'region_neighbor', 'region_zip',  
               'num_room', 'story', 'num_75_bath', 'material', 'num_unit',  
               'area_patio', 'area_shed', 'build_year', 'num_story', 'flag_firepl  
ace',  
               'tax_building', 'tax_total', 'tax_year', 'tax_land', 'tax_proper  
ty',  
               'tax_delinquency', 'tax_delinquency_year', 'censustractandblock'],  
              dtype='object')
```

```
In [15]: # Check new column names  
properties[['num_bedroom', 'num_bathroom']]
```

```
Out[15]:
```

	num_bedroom	num_bathroom
<b>0</b>	0.0	0.0
<b>1</b>	0.0	0.0
<b>2</b>	0.0	0.0
<b>3</b>	0.0	0.0
<b>4</b>	0.0	0.0
...	...	...
<b>19995</b>	2.0	1.0
<b>19996</b>	5.0	3.0
<b>19997</b>	8.0	5.0
<b>19998</b>	4.0	2.0
<b>19999</b>	2.0	1.0

40000 rows × 2 columns

Rename column names in transactions dataset.

```
In [16]: transactions = transactions.rename(columns={'parcelid': 'parcelid', 'date':  
           'transactiondate'})
```

```
In [17]: transactions.columns
```

```
Out[17]: Index(['parcelid', 'logerror', 'transactiondate'], dtype='object')
```

Check out the new columns

```
In [18]: transactions[['parcelid', 'transactiondate']]
```

```
Out[18]:
```

	parcelid	transactiondate
0	11016594	2016-01-01
1	14366692	2016-01-01
2	12098116	2016-01-01
3	12643413	2016-01-02
4	14432541	2016-01-02
...	...	...
77608	10833991	2017-09-20
77609	11000655	2017-09-20
77610	17239384	2017-09-21
77611	12773139	2017-09-21
77612	12826780	2017-09-25

167888 rows × 2 columns

```
In [31]: propertiesAndTransactions = pd.merge(properties, transactions, on='parcelid')
```

check out the merge

```
In [32]: propertiesAndTransactions[['parcelid', 'num_bedroom', 'transactiondate', 'logerror']].head()
```

```
Out[32]:
```

	parcelid	num_bedroom	transactiondate	logerror
0	17054981	4.0	2017-06-15	-0.013099
1	17054981	4.0	2017-06-15	-0.013099
2	17055743	3.0	2017-07-26	0.073985
3	17055743	3.0	2017-07-26	0.073985
4	17068109	3.0	2017-07-28	0.071886

let's take of missings

```
In [33]: column_names = propertiesAndTransactions.columns  
print('sum\n', propertiesAndTransactions.isnull()[column_names].sum())
```

sum	
parcelid	0
aircon	1485
architectural_style	2234
area_basement	2234
num_bathroom	0
num_bedroom	0
framing	2234
quality	705
num_bathroom_calc	26
deck	2214
area_firstfloor_finished	2000
area_total_calc	9
area_live_finished	102
area_liveperi_finished	2234
area_total_finished	2145
area_unknown	2000
area_base	2230
fips	0
num_fireplace	1982
num_bath	26
num_garage	1593
area_garage	1593
flag_tub	2192
heating	752
latitude	0
longitude	0
area_lot	216
num_pool	1708
area_pool	2206
pooltypeid10	2216
pooltypeid2	2210
pooltypeid7	1732
zoning_landuse_county	0
zoning_landuse	0
zoning_property	678
rawcensustractandblock	0
region_city	42
region_county	0
region_neighbor	1186
region_zip	2
num_room	0
story	2234
num_75_bath	1984
material	2234
num_unit	679
area_patio	2137
area_shed	2234
build_year	11
num_story	1792
flag_fireplace	2234
tax_building	6
tax_total	0
tax_year	0
tax_land	0
tax_property	0
tax_delinquency	2166

tax_delinquency_year	2166
censustractandblock	8
logerror	0
transactiondate	0
dtype: int64	

```
In [22]: print('mean\n', propertiesAndTransactions.isnull()[column_names].mean())
```

mean	
parcelid	0.000000
aircon	0.664727
architectural_style	1.000000
area_basement	1.000000
num_bathroom	0.000000
num_bedroom	0.000000
framing	1.000000
quality	0.315577
num_bathroom_calc	0.011638
deck	0.991047
area_firstfloor_finished	0.895255
area_total_calc	0.004029
area_live_finished	0.045658
area_liveperi_finished	1.000000
area_total_finished	0.960161
area_unknown	0.895255
area_base	0.998209
fips	0.000000
num_fireplace	0.887198
num_bath	0.011638
num_garage	0.713071
area_garage	0.713071
flag_tub	0.981200
heating	0.336616
latitude	0.000000
longitude	0.000000
area_lot	0.096688
num_pool	0.764548
area_pool	0.987466
pooltypeid10	0.991943
pooltypeid2	0.989257
pooltypeid7	0.775291
zoning_landuse_county	0.000000
zoning_landuse	0.000000
zoning_property	0.303491
rawcensustractandblock	0.000000
region_city	0.018800
region_county	0.000000
region_neighbor	0.530886
region_zip	0.000895
num_room	0.000000
story	1.000000
num_75_bath	0.888093
material	1.000000
num_unit	0.303939
area_patio	0.956580
area_shed	1.000000
build_year	0.004924
num_story	0.802149
flag_fireplace	1.000000
tax_building	0.002686
tax_total	0.000000
tax_year	0.000000
tax_land	0.000000
tax_property	0.000000
tax_delinquency	0.969561

tax_delinquency_year	0.969561
censustractandblock	0.003581
logerror	0.000000
transactiondate	0.000000
dtype: float64	

Let's look at columns with more than 80% missing values



```
In [34]: propertiesAndTransactions.isnull()[column_names].sum()  
# this shows columns and the number of NaN's. Note parcelID has no missing  
values.
```

```
Out[34]: parcelid      0
         aircon        1485
         architectural_style 2234
         area_basement  2234
         num_bathroom   0
         num_bedroom    0
         framing        2234
         quality        705
         num_bathroom_calc 26
         deck           2214
         area_firstfloor_finished 2000
         area_total_calc 9
         area_live_finished 102
         area_liveperi_finished 2234
         area_total_finished 2145
         area_unknown   2000
         area_base      2230
         fips           0
         num_fireplace  1982
         num_bath        26
         num_garage      1593
         area_garage     1593
         flag_tub        2192
         heating         752
         latitude        0
         longitude       0
         area_lot        216
         num_pool        1708
         area_pool       2206
         pooltypeid10    2216
         pooltypeid2     2210
         pooltypeid7     1732
         zoning_landuse_county 0
         zoning_landuse  0
         zoning_property  678
         rawcensustractandblock 0
         region_city     42
         region_county   0
         region_neighbor 1186
         region_zip      2
         num_room        0
         story           2234
         num_75_bath     1984
         material        2234
         num_unit        679
         area_patio      2137
         area_shed       2234
         build_year      11
         num_story       1792
         flag_fireplace  2234
         tax_building     6
         tax_total        0
         tax_year        0
         tax_land        0
         tax_property     0
         tax_delinquency 2166
         tax_delinquency_year 2166
```

```

censustractandblock      8
logerror                  0
transactiondate           0
dtype: int64

```

Make a list of columns with more than 80% missing data

```

In [35]: remove_columns = propertiesAndTransactions.columns[propertiesAndTransactions.isnull().mean() > .8]
print(remove_columns)

```

```

Index(['architectural_style', 'area_basement', 'framing', 'deck',
       'area_firstfloor_finished', 'area_liveperiod_finished',
       'area_total_finished', 'area_unknown', 'area_base', 'num_fireplaces',
       'flag_tub', 'area_pool', 'pooltypeid10', 'pooltypeid2', 'story',
       'num_75_bath', 'material', 'area_patio', 'area_shed', 'num_story',
       'flag_fireplace', 'tax_delinquency', 'tax_delinquency_year'],
      dtype='object')

```

Drop the columns

```

In [36]: propertiesAndTransactions = propertiesAndTransactions.drop(columns = remove_columns)

```

Check results

```

In [37]: print(len(propertiesAndTransactions.columns))
print(propertiesAndTransactions.columns)

```

```

37
Index(['parcelid', 'aircon', 'num_bathroom', 'num_bedroom', 'quality',
       'num_bathroom_calc', 'area_total_calc', 'area_live_finished', 'fireplaces',
       'num_bath', 'num_garage', 'area_garage', 'heating', 'latitude',
       'longitude', 'area_lot', 'num_pool', 'pooltypeid7',
       'zoning_landuse_county', 'zoning_landuse', 'zoning_property',
       'rawcensustractandblock', 'region_city', 'region_county',
       'region_neighbor', 'region_zip', 'num_room', 'num_unit', 'build_year',
       'tax_building', 'tax_total', 'tax_year', 'tax_land', 'tax_property',
       'censustractandblock', 'logerror', 'transactiondate'],
      dtype='object')

```

Check results

```
In [27]: print(len(propertiesAndTransactions.columns))  
print(propertiesAndTransactions.columns)
```

```
37  
Index(['parcelid', 'aircon', 'num_bathroom', 'num_bedroom', 'quality',  
      'num_bathroom_calc', 'area_total_calc', 'area_live_finished', 'fips',  
      'num_bath', 'num_garage', 'area_garage', 'heating', 'latitude',  
      'longitude', 'area_lot', 'num_pool', 'pooltypeid7',  
      'zoning_landuse_county', 'zoning_landuse', 'zoning_property',  
      'rawcensustractandblock', 'region_city', 'region_county',  
      'region_neighbor', 'region_zip', 'num_room', 'num_unit', 'build_year',  
      'tax_building', 'tax_total', 'tax_year', 'tax_land', 'tax_property',  
      'censustractandblock', 'logerror', 'transactiondate'],  
      dtype='object')
```

Let's check the missing values mean

```
In [38]: print('mean\n', propertiesAndTransactions.isnull()[propertiesAndTransactions.columns].mean())  
# we see the means to all be below 80%.
```

```
mean  
parcelid                0.000000  
aircon                  0.664727  
num_bathroom            0.000000  
num_bedroom             0.000000  
quality                 0.315577  
num_bathroom_calc       0.011638  
area_total_calc         0.004029  
area_live_finished      0.045658  
fips                    0.000000  
num_bath                0.011638  
num_garage              0.713071  
area_garage             0.713071  
heating                 0.336616  
latitude                0.000000  
longitude               0.000000  
area_lot                0.096688  
num_pool                0.764548  
pooltypeid7             0.775291  
zoning_landuse_county   0.000000  
zoning_landuse          0.000000  
zoning_property         0.303491  
rawcensustractandblock  0.000000  
region_city             0.018800  
region_county           0.000000  
region_neighbor         0.530886  
region_zip              0.000895  
num_room                0.000000  
num_unit                0.303939  
build_year              0.004924  
tax_building            0.002686  
tax_total               0.000000  
tax_year                0.000000  
tax_land                0.000000  
tax_property            0.000000  
censustractandblock     0.003581  
logerror                0.000000  
transactiondate         0.000000  
dtype: float64
```

Are there any duplicate?

```
In [39]: propertiesAndTransactions[propertiesAndTransactions.duplicated(keep=False
)]
# There are no duplocate rows; however, there are duplicate parcelIDs and
corresponding latitude and Longitude.
```

```
Out[39]:
```

	parcelid	aircon	num_bathroom	num_bedroom	quality	num_bathroom_calc	are
0 rows × 37 columns							

```
In [257]: propertiesAndTransactions
```

```
Out[257]:
```

	parcelid	aircon	num_bathroom	num_bedroom	quality	num_bathroom_calc	are
0	17054981	NaN	5.0	4.0	NaN	5.0	
1	17054981	NaN	5.0	4.0	NaN	5.0	
2	17055743	NaN	2.0	3.0	NaN	2.0	
3	17055743	NaN	2.0	3.0	NaN	2.0	
4	17068109	NaN	1.5	3.0	NaN	1.5	
...	...	...	...	...	...	...	...
2229	11769554	NaN	3.0	4.0	4.0	3.0	
2230	11778756	NaN	2.0	7.0	7.0	2.0	
2231	11778756	NaN	2.0	7.0	4.0	2.0	
2232	11779780	1.0	2.0	2.0	10.0	2.0	
2233	11779780	1.0	2.0	2.0	11.0	2.0	
2234 rows × 37 columns							

The two datasets have been merged, columns with more than 80% missing values were removed. The final dataset 'propertiesAndTransactions' will be used in the next milestone.

## Webscaraping Data Source

### Description

Using webscraping techniques, we will use 'latitude', 'longitude' from properties dataset to access properties and get current data for those locations. The property description of homes in given region will be stored into a dataset with as many features as in properties dataset we can grab. This dataset can then be used to do some price comparision between properties in 2016 and 2017. Getting data from years prior(say 10 years), we will be able to create trend charts and see market fluctuations.

```
In [388]: # Build a table consisting of the parcelID, latitude and longitude of the properties.
# This table will be used to get data from www.trulia.com by web scraping

LonLat = pd.DataFrame(propertiesAndTransactions[['parcelid','latitude','longitude']])
LonLat
```

Out[388]:

	parcelid	latitude	longitude
<b>0</b>	17054981	34449407	-119254052
<b>1</b>	17054981	34449407	-119254052
<b>2</b>	17055743	34454169	-119237898
<b>3</b>	17055743	34454169	-119237898
<b>4</b>	17068109	34365693	-119448392
...	...	...	...
<b>2229</b>	11769554	34006415	-118246669
<b>2230</b>	11778756	34050678	-118282732
<b>2231</b>	11778756	34050678	-118282732
<b>2232</b>	11779780	34045100	-118261000
<b>2233</b>	11779780	34045100	-118261000

2234 rows × 3 columns

```
In [389]: # We will remove duplicate parcelIDs here since we are only interested in
comparable values near each parcelID.
LonLat = LonLat.sort_values('parcelid', ascending=False)
LonLat = LonLat.drop_duplicates()
LonLat.reset_index(drop=True)
LonLat
```

Out[389]:

	parcelid	latitude	longitude
<b>1761</b>	17299670	34186100	-118767000
<b>107</b>	17296734	34174051	-118757031
<b>1758</b>	17294231	34153879	-118839561
<b>1756</b>	17293716	34152179	-118851454
<b>1427</b>	17292856	34125457	-118891074
...	...	...	...
<b>112</b>	10726315	34184300	-118657000
<b>110</b>	10725532	34196000	-118658000
<b>1767</b>	10722858	34195746	-118624097
<b>108</b>	10722336	34199100	-118633000
<b>1763</b>	10719731	34206094	-118620655

1096 rows × 3 columns

```
In [390]: print('sum\n', LonLat.isnull()[['parcelid', 'latitude', 'longitude']].sum
())
```

```
sum
parcelid    0
latitude    0
longitude    0
dtype: int64
```



In [391]: *# This dictionary is used to return state code. trulia requires the state code rather than state name*

```
us_state_abbrev = {
    'Alabama': 'AL',
    'Alaska': 'AK',
    'American Samoa': 'AS',
    'Arizona': 'AZ',
    'Arkansas': 'AR',
    'California': 'CA',
    'Colorado': 'CO',
    'Connecticut': 'CT',
    'Delaware': 'DE',
    'District of Columbia': 'DC',
    'Florida': 'FL',
    'Georgia': 'GA',
    'Guam': 'GU',
    'Hawaii': 'HI',
    'Idaho': 'ID',
    'Illinois': 'IL',
    'Indiana': 'IN',
    'Iowa': 'IA',
    'Kansas': 'KS',
    'Kentucky': 'KY',
    'Louisiana': 'LA',
    'Maine': 'ME',
    'Maryland': 'MD',
    'Massachusetts': 'MA',
    'Michigan': 'MI',
    'Minnesota': 'MN',
    'Mississippi': 'MS',
    'Missouri': 'MO',
    'Montana': 'MT',
    'Nebraska': 'NE',
    'Nevada': 'NV',
    'New Hampshire': 'NH',
    'New Jersey': 'NJ',
    'New Mexico': 'NM',
    'New York': 'NY',
    'North Carolina': 'NC',
    'North Dakota': 'ND',
    'Northern Mariana Islands': 'MP',
    'Ohio': 'OH',
    'Oklahoma': 'OK',
    'Oregon': 'OR',
    'Pennsylvania': 'PA',
    'Puerto Rico': 'PR',
    'Rhode Island': 'RI',
    'South Carolina': 'SC',
    'South Dakota': 'SD',
    'Tennessee': 'TN',
    'Texas': 'TX',
    'Utah': 'UT',
    'Vermont': 'VT',
    'Virgin Islands': 'VI',
    'Virginia': 'VA',
    'Washington': 'WA',
```

```

        'West Virginia': 'WV',
        'Wisconsin': 'WI',
        'Wyoming': 'WY'
    }

abbrev_us_state = dict(map(reversed, us_state_abbrev.items()))

```

```

In [392]: import urllib.request
import urllib.parse
import urllib.error
import json
from bs4 import BeautifulSoup
from urllib.request import Request, urlopen
import geopy
from geopy.geocoders import Nominatim

def create_url(city,state,zipcode):
    # Creating trulia URL based on the filter.

    url = "https://www.trulia.com/" + state + "/" + city + "/" + zipcode
    return url

def get_response(url):
    ret = None
    try:
        for i in range(5):
            response = requests.get(url, headers={'User-Agent': 'Mozilla/
5.0'})

            print("status code received:", response.status_code)
            if (response.status_code != 200):
                return None
            else:
                return response
    except:
        print('exception in get_response')
        return None

def GetCityStateZip(lat,lon):
    lat = lat/10**6
    lon = lon/10**6
    geolocator = Nominatim(timeout=5)
    #print(location.raw)
    try:
        location = geolocator.reverse((lat, lon))
        city = location.raw['address']['city']
        state = us_state_abbrev[location.raw['address']['state']]
        zipcode = location.raw['address']['postcode'].split('-')[0]
    except:
        city = ""
        state = ""
        zipcode = ""

    return city,state,zipcode

```

```

In [393]: def GetComp(parcelId,latitude,longitude):
            city,state,zipcode = GetCityStateZip(latitude,longitude)
            #print(parcelId,latitude,longitude)
            #print("city=", city)
            #print("state=", state)
            #print("zipcode=",zipcode)

            emptylistings_json = {}
            emptylistings_json['parcelId'] = {0:parcelId}
            emptylistings_json['price'] = {0:np.nan}
            emptylistings_json['bedrooms'] = {0:np.nan}
            emptylistings_json['bathrooms'] = {0:np.nan}
            emptylistings_json['floorSpace'] = {0:np.nan}
            emptylistings_json['region'] = {0:np.nan}

            if (city == "" or state == "" or state == ""):
                return(pd.DataFrame(emptylistings_json))

            url = create_url(city,state,zipcode)

            #req = Requests(url, headers={'User-Agent': 'Mozilla/5.0'})
            #webpage = urlopen(req).read()
            #soup = BeautifulSoup(webpage, 'html.parser')

            response = get_response(url)
            #print(response.text)
            if not response:
                print("Failed to fetch the page, please check `response.html` to
                see the response received from zillow.com.")
                return(pd.DataFrame(emptylistings_json))

            soup = BeautifulSoup(response.text, 'html.parser')

            html = soup.prettify('utf-8')

            details = {}
            parcels = {}
            listings_json = {}
            index = 0

            for price in soup.findAll('div',attrs={'data-testid': 'property-price'}):
                details.update({index:price.text.strip()})
                parcels.update({index:parcelId})
                index = index + 1

            listings_json['parcelId'] = {}
            listings_json['parcelId'] = parcels
            listings_json['price'] = {}
            listings_json['price'] = details
            #print(listings_json['price'])

            details = {}
            index = 0

```

```

    for bedroom in soup.findAll('div',attrs={'data-testid': 'property-beds'}):
        details.update({index:bedroom.text.strip()})
        index = index + 1

    listings_json['bedrooms'] = {}
    listings_json['bedrooms'] = details
    #print(listings_json)

    details = {}
    index = 0
    for bathroom in soup.findAll('div',attrs={'data-testid': 'property-baths'}):
        details.update({index:bathroom.text.strip()})
        index = index + 1

    listings_json['bathrooms'] = {}
    listings_json['bathrooms'] = details
    #print(listings_json)

    details = {}
    index = 0
    for floorSpace in soup.findAll('div',attrs={'data-testid': 'property-floorSpace'}):
        details.update({index:floorSpace.text.strip()})
        index = index + 1

    listings_json['floorSpace'] = {}
    listings_json['floorSpace'] = details
    #print(listings_json)

    details = {}
    index = 0
    for region in soup.findAll('div',attrs={'data-testid': 'property-region'}):
        details.update({index:region.text.strip()})
        index = index + 1

    listings_json['region'] = {}
    listings_json['region'] = details
    #print(listings_json)

    #listings_table = pd.DataFrame()

    #with open('house_details.json', 'w') as outfile:
    #    json.dump(listings_json, outfile, indent=4)
    #listings_table = pd.read_json("house_details.json")
    return pd.DataFrame(listings_json)

```

In [394]: LonLat[:5]

Out[394]:

	parcelid	latitude	longitude
<b>1761</b>	17299670	34186100	-118767000
<b>107</b>	17296734	34174051	-118757031
<b>1758</b>	17294231	34153879	-118839561
<b>1756</b>	17293716	34152179	-118851454
<b>1427</b>	17292856	34125457	-118891074

**Here we get 20 compare properties for the parcelIDs. Note that a parcelID from propertiesAndTransactions table may have one ore more comps near it's latitude and longitude. This process sometime times out. We have taken care to continue collecting even after such exceptions.**

```
In [395]: comp_listing_table = pd.DataFrame(columns={'parcelid', 'price', 'bedrooms',
'bathrooms', 'floorSpace', 'region'})

dfs = []
for index, row in LonLat[:20].iterrows():
    parcelId = row['parcelid']
    latitude = row['latitude']
    longitude = row['longitude']
    #print(parcelId, latitude, longitude)
    Temp_listing_table = GetComp(parcelId, latitude, longitude)
    #print(Temp_listing_table.shape)
    dfs.append(Temp_listing_table)
    #print(Temp_listing_table)

comp_listing_table = pd.concat(dfs, ignore_index=True)
print(comp_listing_table.shape)
```

```
c:\users\safar\documents\github\safariel103\bellevue university\courses\d
sc540\venv\lib\site-packages\ipykernel_launcher.py:33: DeprecationWarnin
g: Using Nominatim with the default "geopy/1.21.0" `user_agent` is strong
ly discouraged, as it violates Nominatim's ToS https://operations.osmfoun
dation.org/policies/nominatim/ and may possibly cause 403 and 429 HTTP er
rors. Please specify a custom `user_agent` with `Nominatim(user_agent="my
-application")` or by overriding the default `user_agent`: `geopy.geocode
rs.options.default_user_agent = "my-application"`. In geopy 2.0 this will
become an exception.
```

[illegible]

```
In [396]: print(comp_listing_table)
```

	parcelId	price	bedrooms	bathrooms	floorSpace	\
0	17299670	NaN	NaN	NaN	NaN	
1	17296734	NaN	NaN	NaN	NaN	
2	17294231	\$14,999,000	7bd	13ba	14,073	sqft
3	17294231	\$1,450,000	4bd	3ba	2,568	sqft
4	17294231	\$1,225,000	4bd	3ba	2,745	sqft
..	...	...	...	...	...	...
475	17273670	\$897,000	4bd	3ba	3,259	sqft
476	17273670	\$680,000	4bd	3ba	2,096	sqft
477	17273670	\$569,000	3bd	3ba	1,550	sqft
478	17273670	\$830,000	3bd	3ba	2,243	sqft
479	17273670	\$999,900	5bd	4ba	3,780	sqft

	region
0	NaN
1	NaN
2	Newbury Park, Thousand Oaks, CA
3	Westlake Village, CA
4	Westlake Village, CA
..	...
475	Newbury Park, Thousand Oaks, CA
476	Newbury Park, Thousand Oaks, CA
477	Newbury Park, Thousand Oaks, CA
478	Newbury Park, Thousand Oaks, CA
479	Newbury Park, Thousand Oaks, CA

[480 rows x 6 columns]

```
In [397]: comp_listing_table.isnull()[comp_listing_table.columns].sum()
```

```
Out[397]: parcelId      0
price              4
bedrooms          13
bathrooms         13
floorSpace        13
region            4
dtype: int64
```

```
In [398]: comp_listing_table = comp_listing_table.dropna()
```

```
In [399]: comp_listing_table.isnull()[comp_listing_table.columns].sum()
```

```
Out[399]: parcelId      0
price              0
bedrooms          0
bathrooms         0
floorSpace        0
region            0
dtype: int64
```

```
In [400]: comp_listing_table.shape
```

```
Out[400]: (467, 6)
```

```
In [401]: # Write scraped data to a file for safe keeps and also to avoid rescrapin
g during development
comp_listing_table.to_csv("data/comp_listing_table.csv")
```

```
In [431]: # Read
comp_listing_table = pd.read_csv("data/comp_listing_table.csv")
```

```
In [432]: comp_listing_table
```

Out[432]:

	Unnamed: 0	parcelId	price	bedrooms	bathrooms	floorSpace	region
0	2	17294231	\$14,999,000	7bd	13ba	14,073 sqft	Newbury Park Thousand Oaks, CA
1	3	17294231	\$1,450,000	4bd	3ba	2,568 sqft	Westlake Village CA
2	4	17294231	\$1,225,000	4bd	3ba	2,745 sqft	Westlake Village CA
3	5	17294231	\$9,990,000	7bd	10ba	12,656 sqft	Newbury Park Thousand Oaks, CA
4	6	17294231	\$1,150,000	5bd	4ba	2,393 sqft	Westlake Village CA
...	...	...	...	...	...	...	...
462	475	17273670	\$897,000	4bd	3ba	3,259 sqft	Newbury Park Thousand Oaks, CA
463	476	17273670	\$680,000	4bd	3ba	2,096 sqft	Newbury Park Thousand Oaks, CA
464	477	17273670	\$569,000	3bd	3ba	1,550 sqft	Newbury Park Thousand Oaks, CA
465	478	17273670	\$830,000	3bd	3ba	2,243 sqft	Newbury Park Thousand Oaks, CA
466	479	17273670	\$999,900	5bd	4ba	3,780 sqft	Newbury Park Thousand Oaks, CA

467 rows × 7 columns



## prepare the dataset

```
In [433]: comp_listing_table = comp_listing_table.loc[:, ~comp_listing_table.columns.str.contains('^Unnamed')]
```

```
In [434]: comp_listing_table['price'] = comp_listing_table['price'].replace('[\$,]', '', regex=True).astype(float)
comp_listing_table
```

c:\users\safar\documents\github\safariel1103\bellevue university\courses\dsc540\venv\lib\site-packages\ipykernel\_launcher.py:1: SettingWithCopyWarning:

A value is trying to be set on a copy of a slice from a DataFrame.  
Try using .loc[row\_indexer,col\_indexer] = value instead

See the caveats in the documentation: [https://pandas.pydata.org/pandas-docs/stable/user\\_guide/indexing.html#returning-a-view-versus-a-copy](https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy)

"""Entry point for launching an IPython kernel.

Out[434]:

	parcelId	price	bedrooms	bathrooms	floorSpace	region
0	17294231	14999000.0	7bd	13ba	14,073 sqft	Newbury Park, Thousand Oaks, CA
1	17294231	1450000.0	4bd	3ba	2,568 sqft	Westlake Village, CA
2	17294231	1225000.0	4bd	3ba	2,745 sqft	Westlake Village, CA
3	17294231	9990000.0	7bd	10ba	12,656 sqft	Newbury Park, Thousand Oaks, CA
4	17294231	1150000.0	5bd	4ba	2,393 sqft	Westlake Village, CA
...	...	...	...	...	...	...
462	17273670	897000.0	4bd	3ba	3,259 sqft	Newbury Park, Thousand Oaks, CA
463	17273670	680000.0	4bd	3ba	2,096 sqft	Newbury Park, Thousand Oaks, CA
464	17273670	569000.0	3bd	3ba	1,550 sqft	Newbury Park, Thousand Oaks, CA
465	17273670	830000.0	3bd	3ba	2,243 sqft	Newbury Park, Thousand Oaks, CA
466	17273670	999900.0	5bd	4ba	3,780 sqft	Newbury Park, Thousand Oaks, CA

467 rows × 6 columns

```
In [435]: comp_listing_table['bedrooms']= comp_listing_table['bedrooms'].replace('b
d', '', regex=True).astype(int)
comp_listing_table
```

```
c:\users\safar\documents\github\safariel103\bellevue university\courses\d
sc540\venv\lib\site-packages\ipykernel_launcher.py:1: SettingWithCopyWarn
ing:
```

A value is trying to be set on a copy of a slice from a DataFrame.  
Try using `.loc[row_indexer,col_indexer] = value` instead

See the caveats in the documentation: [https://pandas.pydata.org/pandas-docs/stable/user\\_guide/indexing.html#returning-a-view-versus-a-copy](https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy)  
""Entry point for launching an IPython kernel.

Out[435]:

	parcelId	price	bedrooms	bathrooms	floorSpace	region
0	17294231	14999000.0	7	13ba	14,073 sqft	Newbury Park, Thousand Oaks, CA
1	17294231	1450000.0	4	3ba	2,568 sqft	Westlake Village, CA
2	17294231	1225000.0	4	3ba	2,745 sqft	Westlake Village, CA
3	17294231	9990000.0	7	10ba	12,656 sqft	Newbury Park, Thousand Oaks, CA
4	17294231	1150000.0	5	4ba	2,393 sqft	Westlake Village, CA
...	...	...	...	...	...	...
462	17273670	897000.0	4	3ba	3,259 sqft	Newbury Park, Thousand Oaks, CA
463	17273670	680000.0	4	3ba	2,096 sqft	Newbury Park, Thousand Oaks, CA
464	17273670	569000.0	3	3ba	1,550 sqft	Newbury Park, Thousand Oaks, CA
465	17273670	830000.0	3	3ba	2,243 sqft	Newbury Park, Thousand Oaks, CA
466	17273670	999900.0	5	4ba	3,780 sqft	Newbury Park, Thousand Oaks, CA

467 rows × 6 columns

```
In [436]: comp_listing_table['bathrooms']= comp_listing_table['bathrooms'].replace('ba', '', regex=True).astype(float)
comp_listing_table
```

```
c:\users\safar\documents\github\safariel103\bellevue university\courses\dsc540\venv\lib\site-packages\ipykernel_launcher.py:1: SettingWithCopyWarning:
```

A value is trying to be set on a copy of a slice from a DataFrame.  
Try using `.loc[row_indexer,col_indexer] = value` instead

See the caveats in the documentation: [https://pandas.pydata.org/pandas-docs/stable/user\\_guide/indexing.html#returning-a-view-versus-a-copy](https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy)  
""Entry point for launching an IPython kernel.

Out[436]:

	parcelId	price	bedrooms	bathrooms	floorSpace	region
0	17294231	14999000.0	7	13.0	14,073 sqft	Newbury Park, Thousand Oaks, CA
1	17294231	1450000.0	4	3.0	2,568 sqft	Westlake Village, CA
2	17294231	1225000.0	4	3.0	2,745 sqft	Westlake Village, CA
3	17294231	9990000.0	7	10.0	12,656 sqft	Newbury Park, Thousand Oaks, CA
4	17294231	1150000.0	5	4.0	2,393 sqft	Westlake Village, CA
...	...	...	...	...	...	...
462	17273670	897000.0	4	3.0	3,259 sqft	Newbury Park, Thousand Oaks, CA
463	17273670	680000.0	4	3.0	2,096 sqft	Newbury Park, Thousand Oaks, CA
464	17273670	569000.0	3	3.0	1,550 sqft	Newbury Park, Thousand Oaks, CA
465	17273670	830000.0	3	3.0	2,243 sqft	Newbury Park, Thousand Oaks, CA
466	17273670	999900.0	5	4.0	3,780 sqft	Newbury Park, Thousand Oaks, CA

467 rows × 6 columns

```
In [437]: comp_listing_table['floorSpace'] = comp_listing_table['floorSpace'].replace('sqft', '', regex=True).replace(',','', regex=True).astype(np.int64)
comp_listing_table.columns
```

c:\users\safar\documents\github\safariel103\bellevue university\courses\dsc540\venv\lib\site-packages\ipykernel\_launcher.py:1: SettingWithCopyWarning:

A value is trying to be set on a copy of a slice from a DataFrame.  
Try using .loc[row\_indexer,col\_indexer] = value instead

See the caveats in the documentation: [https://pandas.pydata.org/pandas-docs/stable/user\\_guide/indexing.html#returning-a-view-versus-a-copy](https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy)  
""Entry point for launching an IPython kernel.

```
Out[437]: Index(['parcelId', 'price', 'bedrooms', 'bathrooms', 'floorSpace', 'region'], dtype='object')
```

## now that we have our comp table built let's do some comparisons

### We'll grab a property from propertiesAndTransactions and query the comp table.

```
In [438]: # This table has duplicates and NaNs removed so it is a subset of the propertiesAndTransactions table.
LonLat
```

Out[438]:

	parcelid	latitude	longitude
<b>1761</b>	17299670	34186100	-118767000
<b>107</b>	17296734	34174051	-118757031
<b>1758</b>	17294231	34153879	-118839561
<b>1756</b>	17293716	34152179	-118851454
<b>1427</b>	17292856	34125457	-118891074
...	...	...	...
<b>112</b>	10726315	34184300	-118657000
<b>110</b>	10725532	34196000	-118658000
<b>1767</b>	10722858	34195746	-118624097
<b>108</b>	10722336	34199100	-118633000
<b>1763</b>	10719731	34206094	-118620655

1096 rows × 3 columns

In [450]: propertiesAndTransactions

Out[450]:

	parcelid	aircon	num_bathroom	num_bedroom	quality	num_bathroom_cal
<b>0</b>	17054981	NaN	5.0	4.0	NaN	5.0
<b>1</b>	17054981	NaN	5.0	4.0	NaN	5.0
<b>2</b>	17055743	NaN	2.0	3.0	NaN	2.0
<b>3</b>	17055743	NaN	2.0	3.0	NaN	2.0
<b>4</b>	17068109	NaN	1.5	3.0	NaN	1.5
...	...	...	...	...	...	...
<b>2229</b>	11769554	NaN	3.0	4.0	4.0	3.0
<b>2230</b>	11778756	NaN	2.0	7.0	7.0	2.0
<b>2231</b>	11778756	NaN	2.0	7.0	4.0	2.0
<b>2232</b>	11779780	1.0	2.0	2.0	10.0	2.0
<b>2233</b>	11779780	1.0	2.0	2.0	11.0	2.0

2234 rows × 37 columns

```
In [451]: # Notice the duplicates
selected_parcelid = propertiesAndTransactions['parcelid'] == 17294231
propertiesAndTransactions[selected_parcelid]
```

Out[451]:

	parcelid	aircon	num_bathroom	num_bedroom	quality	num_bathroom_cal
<b>1758</b>	17294231	NaN	2.0	3.0	NaN	2.0
<b>1759</b>	17294231	NaN	2.0	3.0	NaN	2.0

2 rows × 37 columns

```
In [452]: selected_parcelid = comp_listing_table['parcelId'] == 17294231
          comp_listing_table[selected_parcelid]
```

Out[452]:

	parcelId	price	bedrooms	bathrooms	floorSpace	region
0	17294231	14999000.0	7	13.0	14073	Newbury Park, Thousand Oaks, CA
1	17294231	1450000.0	4	3.0	2568	Westlake Village, CA
2	17294231	1225000.0	4	3.0	2745	Westlake Village, CA
3	17294231	9990000.0	7	10.0	12656	Newbury Park, Thousand Oaks, CA
4	17294231	1150000.0	5	4.0	2393	Westlake Village, CA
5	17294231	525000.0	2	3.0	1440	Westlake Village, CA
6	17294231	1499000.0	5	5.0	3804	Westlake Village, CA
7	17294231	1099000.0	4	3.0	2300	Westlake Village, CA
8	17294231	919000.0	4	2.0	1838	Westlake Village, CA
9	17294231	3195000.0	3	3.0	2543	Westlake Village, CA
10	17294231	1875000.0	5	5.0	4431	Westlake Village, CA
11	17294231	9900000.0	5	7.0	8095	Lake Sherwood, CA
12	17294231	1250000.0	4	3.0	3012	Westlake Village, CA
13	17294231	1799999.0	4	4.0	2106	Westlake Village, CA
14	17294231	640000.0	2	2.0	1231	Westlake Village, CA
15	17294231	1080000.0	4	2.0	2371	Westlake Village, CA
16	17294231	1289000.0	3	3.0	2222	Lake Sherwood, CA
17	17294231	3450000.0	5	6.0	5954	Thousand Oaks, CA
18	17294231	1049000.0	4	3.0	2538	Westlake Village, CA
19	17294231	5495000.0	7	9.0	9304	Thousand Oaks, CA
20	17294231	2995000.0	5	6.0	5421	Westlake Village, CA
21	17294231	1499000.0	4	3.0	2920	Thousand Oaks, CA
22	17294231	1449000.0	4	4.0	3013	Lake Sherwood, CA
23	17294231	765000.0	2	2.0	1508	Westlake Village, CA
24	17294231	1599000.0	3	3.0	2282	Westlake Village, CA
25	17294231	2399000.0	5	4.0	4724	Westlake Village, CA
26	17294231	2975000.0	4	3.0	4075	Westlake Village, CA
27	17294231	988000.0	4	3.0	2412	Westlake Village, CA
28	17294231	4750000.0	6	6.0	7470	Thousand Oaks, CA
29	17294231	3950000.0	5	5.0	5466	Thousand Oaks, CA

