

Custom Search

COURSES

Login

HIRE WITH US



## CSS Preprocessor | SASS

SASS is the abbreviation of Syntactically Awesome Style Sheets. It is a CSS pre-processor with syntax advancements. The style sheets in the advanced syntax are processed by the program and compiled into regular CSS style sheets, which can be used in the website. It is a CSS extension that allows to use features like variables, nesting, imports, mixins, inheritance, etc, all in a CSS-compatible syntax.

**Note:** The link describes the installation process of SASS. Ref: <https://sass-lang.com/install>

There are two types of syntax available for SASS:

- SCSS(Sassy CSS): The files using this syntax use `.scss` extension.
- Indented syntax (referred to as just “sass”): older syntax, Files using this syntax use `.sass` extension.

**Note:** This example use `.scss` extension.

### Working Steps:

- Write the SCSS code.
- Compile the SCSS code into CSS code using the command `sass input.scss output.css`. The first filename (input.scss) is the scss file that is to be compiled and the second file name (output.css) is the processed CSS file, to be included/attached in the html document.
- Include the compiled CSS file in the html file.

Now see how to make effective use of the important features of SCSS like variables, nesting, mixins and operators.

- The main HTML file is named *index.html*
- SCSS file is *styling.scss* and the CSS file is *style.css*
- Command to compile the SCSS file: *sass styling.scss style.css*

**Example:** File name *index.html*

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="utf-8"/>


    <title>SASS</title>

    <meta name="viewport" content=
      "width=device-width, initial-scale=1">

    <link rel="stylesheet" href="style.css">
  </head>

  <body>
    <div id="d1">Welcome to GeeksforGeeks.
      <ul>
        <li>Algo</li>
        <li>DS</li>
        <li>Languages</li>
        <li>Interviews</li>
        <li>CS subjects</li>
      </ul>
    </div>
  </body>
</html>
```

- **Variables:** Variables can be used to store CSS value that may be reused. To declare a variable in SASS, '\$' character is used. Example: *\$v\_name*



After compiling the CSS code save it file by *style.css*

```

1  #d1 {
2    font-size: 30px;
3    color: #00ff40;
4    padding: 100px 350px; }
5
6  /*# sourceMappingURL=style.css.map */
7
OUTPUT  PROBLEMS  DEBUG CONSOLE  TERMINAL
nayonika@developer:~/Desktop/GFG/i1$ sass styling.scss style.css
nayonika@developer:~/Desktop/GFG/i1$

```

- **Nesting:** SASS allows CSS rules to be nested within each other, which follows the same visual hierarchy of HTML. For Example: CSS property can be used to the <li> tag nested inside the div tag.

```

1  $fs: 30px;
2  $bgcolor: #00ff40;
3  $col2: #ff0066e1;
4  $pd:100px 350px;
5  #d1{
6    font-size: $fs;
7    color: $bgcolor;
8    padding: $pd;
9    li{
10     color:$col2;
11   }
12 }
13


```

After compiling the CSS code save it file by *style.css*


```

1  #d1 {
2    font-size: 30px;
3    color: #00ff40;
4    padding: 100px 350px; }
5    #d1 li {
6      color: #ff0066e1; }
7
8  /*# sourceMappingURL=style.css.map */
9
OUTPUT  PROBLEMS  DEBUG CONSOLE  TERMINAL
nayonika@developer:~/Desktop/GFG/i1$ sass styling.scss style.css
nayonika@developer:~/Desktop/GFG/i1$


```

**Output:**

- **Mixins:** Mixins helps to make a set of CSS properties reusable i.e. it save one code and use it again and again. It can be included in other CSS rules by using *@include* directive.

**Example:**

After compiling the CSS code becomes:




## The output of web page:




**Example:** Mixins can also take variables as arguments. The values are passed while including them in the CSS rules.



## The compiled CSS code:



## Final Output:



## Recommended Posts:

What is the difference between ng-if and data-ng-if directives ?

D3.js | d3.timeSunday Function

D3.js | d3.utcSaturdays() Function

D3.js | d3.timeSaturdays() Function

HTML | DOM animationend Event

p5.js | createColorPicker() Function

D3.js | d3.utcSaturday Function

Web Audio API | AudioNode context property

D3.js | d3.timeSundays() Function

D3.js | d3.timeThursday Function

D3.js | d3.utcDays() Function

D3.js | d3.utcSundays() Function

HTML | DOM onafterprint Event

D3.js | d3.timeSaturday Function

**NAYONIKA**Check out this Author's [contributed articles](#).

If you like GeeksforGeeks and would like to contribute, you can also write an article using [contribute.geeksforgeeks.org](https://contribute.geeksforgeeks.org) or mail your article to [contribute@geeksforgeeks.org](mailto:contribute@geeksforgeeks.org). See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please Improve this article if you find anything incorrect by clicking on the "Improve Article" button below.

**Article Tags :**

CSS

Web Technologies

CSS-Misc



6



To-do



Done

3

Based on 2 vote(s)

Feedback/ Suggest Improvement

Add Notes

Improve Article

Please write to us at [contribute@geeksforgeeks.org](mailto:contribute@geeksforgeeks.org) to report any issue with the above content.

Writing code in comment? Please use [ide.geeksforgeeks.org](https://ide.geeksforgeeks.org), generate link and share the link here.

Load Comments

A computer science portal for geeks

5th Floor, A-118,  
Sector-136, Noida, Uttar Pradesh - 201305  
[feedback@geeksforgeeks.org](mailto:feedback@geeksforgeeks.org)

#### COMPANY

About Us  
Careers  
Privacy Policy  
Contact Us

#### PRACTICE

Courses  
Company-wise  
Topic-wise  
How to begin?

#### LEARN

Algorithms  
Data Structures  
Languages  
CS Subjects  
Video Tutorials

#### CONTRIBUTE

Write an Article  
Write Interview Experience  
Internships  
Videos

@geeksforgeeks, Some rights reserved