

## **Top Fabrication (Scale 1:1)**

## **Layer Stack Legend**



Note: external layer thicknesses are specified after plating



## **Impedance Table**

Transmission Line	Impedance [ohms]	Tolerance [ohms]	Layer	Trace Width [mm]	Gap [mm]	Ref. Layers
USB	90	±10 %	L1	0.17	0.275	L2

All dimensions are in millimeters unless otherwise specified.

FABRICATION NOTES (UNLESS OTHERWISE SPECIFIED)

- 1) FABRICATE PER IPC-6012A CLASS 2.
- 2) OUTLINE DEFINED IN SEPARATE GERBER FILE WITH "Edge\_Cuts.GBR" SUFFIX.

DIMENSIONS OF CIRCUMSIZED RECTANGLE SHOWN ON THIS DRAWING FOR REFERENCE ONLY.


 SEE SEPARATE DRILL FILES WITH ".DRL" SUFFIX FOR HOLE LOCATIONS.

SELECTED HOLE LOCATIONS SHOWN ON THIS DRAWING FOR REFERENCE ONLY.

- 4) SURFACE FINISH: HAL LEAD-FREE
- 5) SOLDERMASK ON BOTH SIDES OF THE BOARD SHALL BE LPI, COLOR BLACK.
- SILK SCREEN LEGEND TO BE APPLIED PER LAYER
  STACKUP USING WHITE NON-CONDUCTIVE EPOXY INK,
- 7) ALL VIAS ARE TENTED ON BOTH SIDES UNLESS SOLDERMASK OPENED IN GERBER.
- VENDOR SHOULD FOLLOW ROHS COMPLIANT PROCESS
  AND Pb FREE FOR MANUFACTURING
- 9) PCB MATERIAL REQUIREMENTS:
  - A. FLAMMABILITY RATING MUST MEET OR EXCEED UL94V-0 REQUIREMENTS.
  - B. Tg 170 C OR EQUIVALENT.
  - C. EQUIVALENT MATERIAL SHALL BE RoHS COMPLIANT, HALOGEN FREE AND APPROVED BY TRENDBIT.
- 10) DESIGN GEOMETRY MINIMUM FEATURE SIZES:

BOARD SIZE 20.100 × 22.007 mm BOARD THICKNESS 1.600 mm TRACE WIDTH 1.000 mm TRACE TO TRACE 0.100 mm MIN. HOLE (PTH) 0.500 mm MIN. HOLE (NPTH) N/A mm ANNULAR RING 0.250 mm COPPER TO HOLE 0.150 mm COPPER TO EDGE 0.300 mm HOLE TO HOLE 0.250 mm

- 11) REFER TO IMPEDANCE TABLE FOR IMPEDANCE CONTROL REQUIREMENTS.
- 12) CONFIRM SPACE WIDTHS AND SPACINGS.



# **Drill Drawing L1 - L2 (Scale 1:1)**

#### **Drill Table**

Symbol	Count	Hole Size	Plated	Hole Shape	Drill Layer Pair	Hole Type
×	23	0.50mm (19.69mils)	PTH	Round	L1 (Sig) - L4 (Sig,)	Via
0	6	0.60mm (23.62mlls)	PTH	Slot	L1 (Slg) - L4 (Slg,)	Pad
+	3	0.80mm (31.50mlls)	PTH	Round	L1 (Slg) - L4 (Slg,)	Pad
	Total 32					



