



Certified Kubernetes Administrator Prep

Kubernetes Services & Network Primitives

Kubernetes Services

- Underlying architecture
- Pod -- Simplest kubernetes object, represents one or more containers running on a single node.
- Ephemeral, disposable & replaceable -- Stateless
- “Cattle vs. Pets”
- Usually Managed via Deployments



Kubernetes Services

- Deployment specifications
 - Image
 - Number of replicas
-
- Services -> Deployments
 - Particular port or IP address



Kubernetes Services

- Running the application pods.
- How you set up a service depends on your networking configuration and how you will handle load balancing and port forwarding.
- If you use the pod network IP address method, then a deployment gets assigned a single IP address -- even if there are multiple replicas of that pod.
- The kubernetes service (using kube-proxy on the node) redirects traffic.



Kubernetes Services

- Imperative

- `kubectl run nginx --image=nginx`

- Declarative

- ```
apiVersion: apps/v1
kind: Deployment
metadata:
 name: nginx
 labels:
 app: nginx
spec:
 replicas: 3
 selector:
 matchLabels:
 app: nginx
 ...
```



# Kubernetes Services

## Points to remember:

- Containers are run in Pods, the simplest Kubernetes object representing an application.
- Pods are (usually) managed by deployments.
- Services expose deployments.
- Third parties handle load balancing or port forwarding to those services, though Ingress objects (along with an appropriate ingress controller) are needed to do that work.

