Specifications

Frequency	902-928 MHz
Spreading Method	Frequency Hopping
Forward Error Detection	Hamming BCH Golay Reed-Solomon
Error Detection	32 bits of CRC, ARQ
Encryption	Optional (see –AES option)
Range	40 miles (60 km)
Sensitivity (@10^{-4})	-114 dBm @ 57.6 kbps -112 dBm @ 115.2 kbps -109 dBm @ 172.8 kbps -107 dBm @ 230.4 kbps
Output Power	100mW - 1W (20-30dBm)
Serial Interface	3.3V CMOS RS232/485 (Selectable)
Serial Baud Rate	Up to 230.4 kbps asynchronous
Link Rate	57.6 to 276 kbps
Operating Modes	Mesh, Auto Routing, Store and Forward, Self Healing, Packet Routing Modes
Signals Interface	RxD1, TxD1, RTS, CTS DCD, DSR, DTR, RxD2, TxD2, RSSI LEDs, Tx/Rx LEDs, Reset, Config, Wake-up, RSmode, 4 Digital Inputs/Outputs, 1 Analog Input, 1 Analog Output
Blocking	+/- 1 MHz > 55 dBc +/- 2.5 MHz > 60 dBc +/- 5 MHz > 65 dBc > 930 MHz > 70 dBc < 890 MHz > 70 dBc
Remote Diagnostics	Battery Voltage, Temperature, RSSI, Packet Statistics
Core Voltage	OEM: 3.3VDC Nominal (+/- 0.3V) Enclosed: 9-30 VDC SWP: 7-30 VDC

Power Consumption (3.3V +/- 0.3V @1W)	Sleep < 1mA Idle 3.5mA Rx: 45mA to 98mA Tx : 1000mA to 1400mA
Connectors:	
OEM	
Antenna	UFL
Data	80 Pin SMT
Enclosed	
Antenna	RP-SMA Female Bulkhead
Data	DB-9F
SWP	
Antenna	MMCX
Power, Data	10-Pin (GHR-10V-S)
Environmental	-55°C to +85°C
Weight	
OEM	~ 5 grams
Enclosed	~ 120 grams
SWP	~ 37 grams
Dimensions	
OEM	~ 26.5 x 33 x 3.5 mm
Enclosed	~ 46 x 66 x 25 mm
SWP	~ 36 x 48 x 15 mm
Approvals	FCC Part 15.247 IC RSS210 Anatel RoHS Compliant

Order Options

-AES	128-bit AES Encryption (requires permit for export outside of Canada and USA.)
-AES256	256-bit AES Encryption (requires permit for export outside of Canada and USA.)
-ENC	Enclosed Model
-SWP	SWP Series