


FIG. 1 — FRONT VIEW OASIS CORE™

# OASIS™ CORE

Portable 48 V / 100 Ah LiFePO4 battery power system with ~3,000 VA continuous, 5,000 W momentary surge* AC output, DC and USB outlets, and a connected touchscreen.


- **4800 Wh of LiFePO4 chemistry battery power**
- **~3,000 VA continuous, 5,000 W momentary surge*** across 4× NEMA 120 V outlets, plus 12 V DC and USB-A / USB-C
- **Stay connected** with a touchscreen display: Bluetooth, Wi-Fi, optional 5G*
- Built-in battery charger with power cord
- Cloud port - monitor your battery or fleet of batteries remotely
- Durable wheels & handle - easy to move and reposition
- Internal fusing and breakers - multiple layers of protection

| 48 | 100 | 4800 | ~3000 | 4× | 200 |
|---|---|---|---|---|---|
| V | Ah | Wh | VA | NEMA | W |
| SYSTEM VOLTAGE | CAPACITY | STORED ENERGY | AC CONTINUOUS | 120V AC OUTLETS | DC OUTPUT |


## APPLICATIONS

| Application | Details |
|---|---|
| **Job-site & field power** | Runs 120 V AC equipment from four NEMA outlets |
| **Backup power** | Stored 4800 Wh for outages; recharges from a 120 V power cable included |
| **Mobile & off-grid** | 12 V DC aux charger plus USB-A and USB-C for accessories and devices |

## IMAGES




SIDE VIEW (DIMENSIONS IN INCHES)




TOP VIEW (DIMENSIONS IN INCHES)

* In progress

## BATTERY & ELECTRICAL

| | | | |
|---|---|---|---|
| **Nominal voltage** | **48 V** | **Cell type** | **LiFePO4** |
| **Capacity** | **100 Ah** | **Energy** | **4800 Wh** |
| **Charge voltage** | **54.75 V** | **Float voltage** | **52.0 V** |
| **Operating voltage range** | **42.0 - 54.75 V** | **Low-voltage cut-off** | **42.0 V** |

## THERMAL & ENVIRONMENTAL

| | | | |
|---|---|---|---|
| **Operating temperature** | **14–104 °F** -10–40 °C | **Charge temperature range** | **32–104 °F*** 0–40 °C · Cold-weather battery heater* |
| **Internal heater** | **Cold-weather battery heater*** | **Ingress protection** | **IP66*** Testing in progress |

## MECHANICAL

| | | | |
|---|---|---|---|
| **Enclosure material** | **5052-H32 aluminum** | **Dimensions (L × W × H)** | **18.1in x 22.0in x 32.6in** |
| **Weight** | **~180 lbs.** | **Finish** | **Powdercoat** |

## BMS, DISPLAY & CONNECTIVITY

| | | | |
|---|---|---|---|
| **Display** | **Touchscreen** | **Cellular** | **5G*** Planned optional integration |
| **Bluetooth** | **Supported** | **Wi-Fi** | **Supported** |
| **Remote monitoring app** | **iOS & Android** | **Expansion / series connection** | **See Trifecta Engineering** |

## SHIPPING & CERTIFICATIONS

| Standard / Area | Scope |
|---|---|
| **UN 38.3*** | Lithium battery transport test |
| **UL 1973*** | Battery assembly |
| **UL 1741*** | Inverter assembly |

* In progress