

Package ‘polyBreedR’

September 17, 2022

Title Genomics-assisted breeding for polyploids (and diploids)

Version 0.27

Author Jeffrey B. Endelman

Maintainer Jeffrey Endelman <endelman@wisc.edu>

Description Genomics-assisted breeding for polyploids (and diploids)

Depends R (>= 4.0)

License GPL-3

LazyData true

RoxygenNote 7.1.1

Encoding UTF-8

Imports AGHmatrix, ggplot2, ggrepel, pedigree, grDevices, utils, tidyr, Matrix, methods, rlang, updog

Suggests knitr, rmarkdown, asreml

VignetteBuilder knitr

R topics documented:

A_mat	2
check_ploidy	2
check_trio	3
dart2PO	4
dart_tag	4
geno_call	6
get_pedigree	7
GvsA	7
G_mat	8
impute	9
merge_impute	9
readXY	10
update_alias	10
Index	12

A_mat	<i>Additive relationship matrix from pedigree</i>
-------	---

Description

Additive relationship matrix from pedigree

Usage

```
A_mat(ped, ploidy, order.ped = TRUE)
```

Arguments

ped	Pedigree in three column format: id, mother, father
ploidy	2 or 4
order.ped	TRUE/FALSE does the pedigree need to be ordered so that progeny follow parents

Details

This is a wrapper that prepares the pedigree in the format required for R package AGHmatrix by Amadeu et al. (2016) (cite them if you use this function). A random bivalents model for tetraploid meiosis is assumed.

Value

Additive relationship matrix (dim: indiv x indiv)

References

Amadeu et al. (2016) Plant Genome 9, doi:10.3835/plantgenome2016.01.0009

check_ploidy	<i>Check ploidy</i>
--------------	---------------------

Description

Fraction of simplex or triplex markers

Usage

```
check_ploidy(geno, map)
```

Arguments

geno	Genotype matrix (markers x indiv)
map	Data frame with marker map (Marker, Chrom, Position)

Details

For every indiv in the genotype matrix, the fraction of markers per chromosome called as simplex or triplex is calculated, which should be low for diploids. A small amount of missing genotype data can be tolerated.

Value

- List containing
- mat** Matrix (indiv x chrom) of results
- plot** ggplot2 barplot

check_trio	<i>Check markers for parent-offspring trio</i>
------------	--

Description

Check markers for parent-offspring trio

Usage

check_trio(parentage, geno, ploidy)

Arguments

- parentage Data frame with three columns: id, mother, father
- geno Matrix of allele dosages: markers x indiv
- ploidy 2 or 4

Details

Computes the percentage of markers at which the two parents and offspring have incompatible allele dosages (for tetraploids, the random bivalents model is used). For dihaploid offspring of a single tetraploid parent, use ploidy = 4 and "haploid" for the father in parentage, as well as a diploid (0,1,2) genotype for the offspring. A small amount of missing genotype data can be tolerated.

Value

Data frame with the percentage of incompatible markers for each trio

dart2P0	<i>Convert DArTag data to PolyOrigin format</i>
---------	---

Description

Convert DArTag data to PolyOrigin format

Usage

```
dart2P0(
  infile,
  outfile,
  first.data.row = 9,
  first.data.col = 6,
  array.file = NULL
)
```

Arguments

infile	input filename
outfile	output filename
first.data.row	first data row
first.data.col	first data column
array.file	optional

Details

Designed for standard two-row format from DArT. Column 1 contains the AlleleID in format MarkerName|Haplotype. Haplotypes are named Ref,RefMatch,Alt,AltMatch,Other. Counts are combined for Ref + RefMatch, as well as Alt + AltMatch. Other haplotypes are discarded. Genotype calls can use the updog package (Gerard et al. 2018). If a sample has no reads at a marker, the genotype is NA and posterior probability equals 0.

Value

List of two data frames with statistics for markers and samples

dart_tag	<i>Process DArTag data</i>
----------	----------------------------

Description

Process DArTag data

Usage

```
dart_tag(
  filename,
  first.data.row = 9,
  first.data.col = 6,
  ploidy,
  geno.call = TRUE,
  n.core = 1,
  AB.file = NULL
)
```

Arguments

filename	DArTag CSV filename
first.data.row	first data row
first.data.col	first data column
ploidy	ploidy
geno.call	TRUE/FALSE
n.core	number of cores
AB.file	CSV file to convert to array dosage (allele B)

Details

Designed for standard two-row format from DArT. Column 1 contains the AlleleID in format MarkerName/Haplotype. Haplotypes are named Ref,RefMatch,Alt,AltMatch,Other. Counts are combined for Ref + RefMatch, as well as Alt + AltMatch. Other haplotypes are discarded. Genotype calls are made using the updog package (Gerard et al. 2018). If a sample has no reads at a marker, the genotype is NA and posterior probability equals 0.

Standard output for genotype calls is dosage of Alt allele. Optionally, specify AB.file to output dosage of B allele from SNP array. The file must have columns named "marker" and "REF", where REF is either A or B. Only markers present in AB.file will be in the output.

Value

Data frame with marker statistics and 5 matrices with dimensions markers x indiv

stats data frame with 10th percentile of depth and posterior prob for each marker

depth (Alt+Ref) read count

ratio Alt/(Alt+Ref)

geno.mode Posterior mode for allele dosage

prob Maximum posterior probability

geno.mean Posterior mean for allele dosage

geno_call	<i>Genotype calls</i>
-----------	-----------------------

Description

Genotype calls based on a normal mixture model

Usage

```
geno_call(
  data,
  filename,
  model.ploidy = 4L,
  sample.ploidy = 4L,
  min.posterior = 0,
  transform = TRUE
)
```

Arguments

data	matrix (markers x id) of input values for the normal mixture model
filename	CSV filename with the model parameters
model.ploidy	2 or 4 (default)
sample.ploidy	2 or 4 (default)
min.posterior	minimum posterior probability (default 0) for genotype call
transform	TRUE (default) or FALSE whether to apply arcsin square root transformation

Details

The first column of the CSV input file should be the SNP ID, followed by columns for the normal distribution means, standard deviations, and mixture probabilities. Genotype calls are based on the maximum a posteriori (MAP) method. If the posterior probability of the MAP genotype is less than `min.posterior`, then NA is returned for that sample. By default, an arcsin square root transformation is applied to the input values to match the approach used by R package `fitPoly`. To use a tetraploid mixture model for diploid samples, set `sample.ploidy = 2` and `model.ploidy = 4`.

Value

matrix of allele dosages (0,1,2,..ploidy) with dimensions markers x individuals

get_pedigree	<i>Generate pedigree</i>
--------------	--------------------------

Description

Generate pedigree for a set of individuals

Usage

```
get_pedigree(id, pedfile, delim = ",", na.string = "NA", trim = TRUE)
```

Arguments

id	Vector of names of individuals
pedfile	Name of pedigree file
delim	Delimiter for the pedigree file (default is "," for CSV)
na.string	String used for NA in the pedigree file (default is "NA")
trim	TRUE/FALSE whether to trim pedigree (see Details)

Details

Finds ancestors of individuals in a three-column pedigree file (id,mother,father). The id column can be the identifier for an individual or cross. String matches must be exact or based on the naming convention crossID-progenyID. The returned pedigree is ordered using R package pedigree so that offspring follow parents. When trim is TRUE (default), the pedigree is trimmed to remove ancestors with only one offspring (which are not needed to compute the pedigree relationship matrix).

Value

Data frame with columns id, mother, father

GvsA	<i>Plot G vs. A</i>
------	---------------------

Description

Plot marker-based vs. pedigree-based additive relationship coefficients

Usage

```
GvsA(
  parentage,
  G,
  A,
  filename = NULL,
  thresh.G = Inf,
  thresh.A = 0.5,
  Gmax = NULL,
  Amax = NULL
)
```

Arguments

parentage	Data frame of individuals to plot, with 3 columns: id,mother,father
G	Genomic relationship matrix
A	Pedigree relationship matrix
filename	Name of PDF file to save the results (optional for one individual)
thresh.G	Threshold above which names are displayed (default Inf)
thresh.A	Threshold above which names are displayed (default 0.5)
Gmax	Upper limit for y-axis for plotting. If NULL, maximum value in G is used.
Amax	Upper limit for x-axis for plotting. If NULL, maximum value in A is used.

Details

Useful for finding and correcting pedigree errors. If the G or A coefficient for an individual exceeds the threshold, its name is displayed in the figure. If parentage contains one individual, by default a ggplot2 variable will be returned, but the result can also be written to file. If multiple individuals are present, a filename is required.

G_mat	<i>Additive genomic relationships</i>
-------	---------------------------------------

Description

Relationship matrix for additive effects with bi-allelic markers

Usage

```
G_mat(geno, ploidy)
```

Arguments

geno	Matrix of allele dosages (markers x indiv)
ploidy	Any even integer (2,4,6,...)

Details

Additive effects are based on the traditional orthogonal decomposition of genetic variance in pan-mictic populations (Fisher 1918; Kempthorne 1957; Endelman et al. 2018). Missing genotype data is replaced with the population mean.

Value

G matrix

References

- Fisher (1918) Trans. Roy. Soc. Edin. 52:399-433.
 Kempthorne (1957) An Introduction to Genetic Statistics.
 Endelman et al. (2018) Genetics 209:77-87.

impute

Impute missing marker data

Description

Impute marker data based on the population mean or mode

Usage

```
impute(geno, method)
```

Arguments

geno	Matrix of allele dosages with dimensions markers x indiv
method	Either "mean" or "mode"

Details

Missing values are imputed with either the population mean or mode (most frequent value) for each marker

Value

Imputed genotype matrix (markers x indiv)

merge_impute

Merge two genotype matrices and impute missing data

Description

Merge two genotype matrices and impute missing data by BLUP

Usage

```
merge_impute(geno1, geno2, ploidy)
```

Arguments

geno1	Genotype matrix (coded 0...ploidy) with dimensions markers x indiv
geno2	Genotype matrix (coded 0...ploidy) with dimensions markers x indiv
ploidy	Either 2 or 4

Details

Designed to impute from low to high density markers. The BLUP method is equivalent to Eq. 4 of Poland et al. (2012), but this function is not iterative. Additional shrinkage toward the mean is applied if needed to keep the imputed values within the range [0,ploidy]. Missing data in the input matrices are imputed with the population mean for each marker. If an individual appears in both input matrices, it is renamed with suffixes ".1" and ".2" and treated as two different individuals. Monomorphic markers are removed.

Value

Imputed genotype matrix (markers x indiv)

References

Poland et al. (2012) Plant Genome 5:103-113.

readXY	<i>Read SNP array intensity data</i>
--------	--------------------------------------

Description

Read SNP array intensity data

Usage

```
readXY(filename, skip, output = "ratio")
```

Arguments

filename	filename
skip	number of lines to skip before the header line with the column names
output	Either "ratio" or "theta"

Details

The first two columns of the tab-delimited input file should be the SNP and Sample ID. Columns labeled "X" and "Y" contain the signal intensities for the two alleles. Use output to specify whether to return the ratio = $Y/(X+Y)$ or theta = $\text{atan}(Y/X)*2/\pi$.

Value

matrix with dimensions markers x individuals

update_alias	<i>Update names based on alias</i>
--------------	------------------------------------

Description

Update names based on data frame with alias and preferred name

Usage

```
update_alias(x, alias, remove.space = TRUE, filename = NULL)
```

Arguments

<code>x</code>	Vector of names to update
<code>alias</code>	Data frame with two columns: first is the preferred name and second is the alias
<code>remove.space</code>	TRUE/FALSE
<code>filename</code>	update names in file (variable "id")

Details

Parameter `remove.space` indicates whether blank spaces should be removed before string matching

Value

Vector with updated names

Index

A_mat, [2](#)

check_ploidy, [2](#)

check_trio, [3](#)

dart2P0, [4](#)

dart_tag, [4](#)

G_mat, [8](#)

geno_call, [6](#)

get_pedigree, [7](#)

GvsA, [7](#)

impute, [9](#)

merge_impute, [9](#)

readXY, [10](#)

update_alias, [10](#)