


## Performance

Values are estimated and may vary. The [performance score is calculated](#) directly from these metrics. [See calculator.](#)

▲ 0–49    ■ 50–89    ● 90–100



### METRICS

[Expand view](#)

▲ First Contentful Paint

5.4 s

▲ Time to Interactive

11.4 s

▲ Speed Index

10.9 s

■ Total Blocking Time

590 ms

▲ Largest Contentful Paint

9.4 s

● Cumulative Layout Shift

0.021

[View Treemap](#)



Show audits relevant to: [All](#) [FCP](#) [TBT](#) [LCP](#) [CLS](#)

### OPPORTUNITIES

Opportunity

Estimated Savings

▲ Reduce unused JavaScript



3 s ^

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. [Learn more.](#) [LCP](#)

| URL                                                                                               | Transfer Size | Potential Savings |
|---------------------------------------------------------------------------------------------------|---------------|-------------------|
| ...js/main.59cd4549.js (d1se6lw3xj7v9k.cloudfront.net)                                            | 328.5 KiB     | 200.0 KiB         |
| ...7f53fa3b-5ecd-40fb-5af7-3fd636c1358c/pendo.js (cdn.pendo.io)                                   | 145.0 KiB     | 123.4 KiB         |
| ...7f53fa3b-5ecd-40fb-5af7-3fd636c1358c/pendo-staging.js (pendo-io-static.storage.googleapis.com) | 144.8 KiB     | 100.5 KiB         |
| /modules.8b83be3....js (script.hotjar.com)                                                        | 64.3 KiB      | 43.1 KiB          |
| /gtag/js?id=G-9274CJ3BBL (www.googletagmanager.com)                                               | 71.9 KiB      | 37.7 KiB          |
| /gtag/js?id=AW-106... (www.googletagmanager.com)                                                  | 59.2 KiB      | 34.0 KiB          |

### ▲ Reduce initial server response time 0.96 s ^

Keep the server response time for the main document short because all other requests depend on it. [Learn more](#). FCP LCP

| URL                                     | Time Spent |
|-----------------------------------------|------------|
| /signin (d1se6lw3xj7v9k.cloudfront.net) | 1,060 ms   |

### ■ Eliminate render-blocking resources 0.55 s ^

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. [Learn more](#). FCP LCP

| URL                                                      | Transfer Size | Potential Savings |
|----------------------------------------------------------|---------------|-------------------|
| ...css/main.316708b6.css (d1se6lw3xj7v9k.cloudfront.net) | 108.8 KiB     | 1,200 ms          |

### ■ Reduce unused CSS 0.3 s ^

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. [Learn more](#). FCP LCP

| URL                                                      | Transfer Size | Potential Savings |
|----------------------------------------------------------|---------------|-------------------|
| ...css/main.316708b6.css (d1se6lw3xj7v9k.cloudfront.net) | 108.8 KiB     | 107.4 KiB         |

These suggestions can help your page load faster. They don't [directly affect](#) the Performance score.

Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. [Learn more.](#)

FCP

LCP

| URL                                                                      | Potential Savings |
|--------------------------------------------------------------------------|-------------------|
| ...media/Poppins-Medium.673ed42....ttf (d1se6lw3xj7v9k.cloudfront.net)   | 1,320 ms          |
| ...media/Poppins-Regular.35d26b7....ttf (d1se6lw3xj7v9k.cloudfront.net)  | 1,330 ms          |
| ...media/Poppins-SemiBold.ac8d04b....ttf (d1se6lw3xj7v9k.cloudfront.net) | 1,390 ms          |

The `unload` event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward Cache. Use `pagehide` or `visibilitychange` events instead. [Learn more](#)

☒ Show 3rd-party resources (1)

| Source                                                                                                     |
|------------------------------------------------------------------------------------------------------------|
| ...js/main.59cd4549.js:2:667739 (d1se6lw3xj7v9k.cloudfront.net)                                            |
| ...7f53fa3b-5ecd-40fb-5af7-3fd636c1358c/pendo-staging.js:14:26514 (pendo-io-static.storage.googleapis.com) |

First Contentful Paint 3G marks the time at which the first text or image is painted while on a 3G network. [Learn more.](#)

A long cache lifetime can speed up repeat visits to your page. [Learn more.](#)

☒ Show 3rd-party resources (5)

| URL                                                                      | Cache TTL | Transfer Size |
|--------------------------------------------------------------------------|-----------|---------------|
| ...js/main.59cd4549.js (d1se6lw3xj7v9k.cloudfront.net)                   | None      | 329 KiB       |
| ...css/main.316708b6.css (d1se6lw3xj7v9k.cloudfront.net)                 | None      | 109 KiB       |
| ...media/Poppins-Regular.35d26b7....ttf (d1se6lw3xj7v9k.cloudfront.net)  | None      | 70 KiB        |
| ...media/Poppins-SemiBold.ac8d04b....ttf (d1se6lw3xj7v9k.cloudfront.net) | None      | 69 KiB        |
| ...media/Poppins-Medium.673ed42....ttf (d1se6lw3xj7v9k.cloudfront.net)   | None      | 69 KiB        |
| ...js/868.5969846f.chunk.js (d1se6lw3xj7v9k.cloudfront.net)              | None      | 29 KiB        |
| ...media/sprite.5eff982....svg (d1se6lw3xj7v9k.cloudfront.net)           | None      | 24 KiB        |

| URL                                                                                | Cache TTL | Transfer Size |
|------------------------------------------------------------------------------------|-----------|---------------|
| ...media/Acclaim-b....8e91699....svg (d1se6lw3xj7v9k.cloudfront.net)               | None      | 4 KiB         |
| ...js/909.b9007d19.chunk.js (d1se6lw3xj7v9k.cloudfront.net)                        | None      | 2 KiB         |
| ...js/682.e099fea3.chunk.js (d1se6lw3xj7v9k.cloudfront.net)                        | None      | 2 KiB         |
| ...css/682.2a12ebb2.chunk.css (d1se6lw3xj7v9k.cloudfront.net)                      | None      | 1 KiB         |
| ...guide.js/7f53fa3b-...?jzb=eJx9jk1LB...&v=2.149.0_prod&ct=166... (data.pendo.io) | None      | 1 KiB         |
| ...ptm.gif/7f53fa3b-...?v=2.149.0_prod&ct=166...&jzb=eJzFkdFPw... (data.pendo.io)  | None      | 0 KiB         |
| /c/hotjar-3008608.js?sv=6 (static.hotjar.com)                                      | 1 m       | 3 KiB         |
| /button/sw9pj839sy39xbsfcbbh.js (widget.ybug.io)                                   | 6 m       | 8 KiB         |
| ...7f53fa3b-5ecd-40fb-5af7-3fd636c1358c/pendo.js (cdn.pendo.io)                    | 7 m 30 s  | 145 KiB       |

■ Minimize main-thread work — 2.9 s



Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn more](#) TBT

| Category                     | Time Spent |
|------------------------------|------------|
| Script Evaluation            | 1,934 ms   |
| Other                        | 476 ms     |
| Script Parsing & Compilation | 187 ms     |
| Style & Layout               | 162 ms     |
| Parse HTML & CSS             | 102 ms     |
| Rendering                    | 54 ms      |
| Garbage Collection           | 24 ms      |

■ Reduce JavaScript execution time — 2.0 s



Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. [Learn more](#) TBT

☒ Show 3rd-party resources (5)

| URL                                                                                               | Total CPU Time | Script Evaluation | Script Parse |
|---------------------------------------------------------------------------------------------------|----------------|-------------------|--------------|
| ...js/main.59cd4549.js (d1se6lw3xj7v9k.cloudfront.net)                                            | 920 ms         | 792 ms            | 66 ms        |
| ...7f53fa3b-5ecd-40fb-5af7-3fd636c1358c/pendo-staging.js (pendo-io-static.storage.googleapis.com) | 519 ms         | 457 ms            | 28 ms        |


| URL                                                             | Total CPU Time | Script Evaluation | Script Parse |
|-----------------------------------------------------------------|----------------|-------------------|--------------|
| /modules.8b83be3....js (script.hotjar.com)                      | 385 ms         | 261 ms            | 17 ms        |
| Unattributable                                                  | 234 ms         | 11 ms             | 1 ms         |
| /signin (d1se6lw3xj7v9k.cloudfront.net)                         | 212 ms         | 11 ms             | 4 ms         |
| /gtag/js?id=AW-106... (www.googletagmanager.com)                | 171 ms         | 153 ms            | 11 ms        |
| ...7f53fa3b-5ecd-40fb-5af7-3fd636c1358c/pendo.js (cdn.pendo.io) | 125 ms         | 85 ms             | 26 ms        |
| ...css/main.316708b6.css (d1se6lw3xj7v9k.cloudfront.net)        | 106 ms         | 0 ms              | 0 ms         |
| /button/sw9pj839sy39xbsfcbbh.js (widget.ybug.io)                | 91 ms          | 50 ms             | 6 ms         |

○ Avoid chaining critical requests — 3 chains found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. [Learn more.](#) FCP LCP

Maximum critical path latency: **5,910 ms**

Initial Navigation



○ Keep request counts low and transfer sizes small — 33 requests • 1,213 KiB


To set budgets for the quantity and size of page resources, add a budget.json file. [Learn more.](#)

| Resource Type | Requests | Transfer Size |
|---------------|----------|---------------|
| Total         | 33       | 1,213.0 KiB   |
| Script        | 12       | 858.5 KiB     |
| Font          | 3        | 207.9 KiB     |
| Stylesheet    | 2        | 110.1 KiB     |
| Image         | 3        | 28.4 KiB      |
| Other         | 11       | 5.2 KiB       |
| Document      | 2        | 2.9 KiB       |
| Media         | 0        | 0.0 KiB       |
| Third-party   | 21       | 504.2 KiB     |

This is the largest contentful element painted within the viewport. [Learn More](#)

LCP



Element



Don't have an account? Sign Up  
`<p class="formRedirectText mt-2">`

These DOM elements contribute most to the CLS of the page. 

CLS

| Element                                                                                                                                                                                                                                                                 | CLS Contribution |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| <div><div></div><div>Email Password Forgot Password? SIGN IN Don't have an account? Sign Up<br/><code>&lt;div class="form-block d-flex justify-content-center"&gt;</code></div></div> | 0.021            |
| <div><div></div><div>Sign Up<br/><code>&lt;a class="formRedirectBtn sign-up-link" href="/signup"&gt;</code></div></div>                                                              | 0                |

Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. [Learn more](#)

TBT

☒ Show 3rd-party resources (7)

| URL                                                                                               | Start Time | Duration |
|---------------------------------------------------------------------------------------------------|------------|----------|
| ...js/main.59cd4549.js (d1se6lw3xj7v9k.cloudfront.net)                                            | 4,830 ms   | 532 ms   |
| ...7f53fa3b-5ecd-40fb-5af7-3fd636c1358c/pendo-staging.js (pendo-io-static.storage.googleapis.com) | 11,205 ms  | 166 ms   |
| ...js/main.59cd4549.js (d1se6lw3xj7v9k.cloudfront.net)                                            | 5,362 ms   | 134 ms   |
| ...7f53fa3b-5ecd-40fb-5af7-3fd636c1358c/pendo.js (cdn.pendo.io)                                   | 8,610 ms   | 125 ms   |
| ...7f53fa3b-5ecd-40fb-5af7-3fd636c1358c/pendo-staging.js (pendo-io-static.storage.googleapis.com) | 10,265 ms  | 119 ms   |
| ...css/main.316708b6.css (d1se6lw3xj7v9k.cloudfront.net)                                          | 2,730 ms   | 106 ms   |
| /modules.8b83be3....js (script.hotjar.com)                                                        | 7,844 ms   | 81 ms    |
| /gtag/js?id=AW-106... (www.googletagmanager.com)                                                  | 3,313 ms   | 79 ms    |

| URL                                                                                               | Start Time | Duration |
|---------------------------------------------------------------------------------------------------|------------|----------|
| ...7f53fa3b-5ecd-40fb-5af7-3fd636c1358c/pendo-staging.js (pendo-io-static.storage.googleapis.com) | 10,398 ms  | 63 ms    |
| /gtag/js?id=AW-106... (www.googletagmanager.com)                                                  | 3,257 ms   | 56 ms    |
| ...js/main.59cd4549.js (d1se6lw3xj7v9k.cloudfront.net)                                            | 5,520 ms   | 53 ms    |

More information about the performance of your application. These numbers don't [directly affect](#) the Performance score.

## PASSED AUDITS (25)

Hide

### Properly size images



Serve images that are appropriately-sized to save cellular data and improve load time. [Learn more](#).

### Defer offscreen images



Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. [Learn more](#).

### Minify CSS



Minifying CSS files can reduce network payload sizes. [Learn more](#). FCP LCP

### Minify JavaScript



Minifying JavaScript files can reduce payload sizes and script parse time. [Learn more](#). FCP LCP

### Efficiently encode images



Optimized images load faster and consume less cellular data. [Learn more](#).

### Serve images in next-gen formats



Image formats like WebP and AVIF often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. [Learn more](#).

### Enable text compression



Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. [Learn more](#). FCP LCP

## ● Preconnect to required origins ^

Consider adding `preconnect` or `dns-prefetch` resource hints to establish early connections to important third-party origins. [Learn more](#). FCP LCP

## ● Avoid multiple page redirects ^

Redirects introduce additional delays before the page can be loaded. [Learn more](#). FCP LCP

## ○ Preload key requests ^

Consider using `` to prioritize fetching resources that are currently requested later in page load. [Learn more](#). FCP LCP

## ● Use video formats for animated content ^

Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. [Learn more](#) LCP

## ● Remove duplicate modules in JavaScript bundles ^

Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity. TBT

## ● Avoid serving legacy JavaScript to modern browsers — Potential savings of 38 KiB ^

Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using module/nomodule feature detection to reduce the amount of code shipped to modern browsers, while retaining support for legacy browsers. [Learn More](#) TBT

☐ Show 3rd-party resources (4)

| URL                                                                 | Potential Savings      |
|---------------------------------------------------------------------|------------------------|
| ...js/main.59cd4549.js (d1se6lw3xj7v9k.cloudfront.net)              | 18.3 KiB               |
| ...<br>js/main.59cd4549.js:2:506504 (d1se6lw3xj7v9k.cloudfront.net) | Array.prototype.fill   |
| ...<br>js/main.59cd4549.js:2:506620 (d1se6lw3xj7v9k.cloudfront.net) | Array.prototype.filter |

| URL                                                                 |                                  | Potential Savings |
|---------------------------------------------------------------------|----------------------------------|-------------------|
| ...<br>js/main.59cd4549.js:2:506902 (d1se6lw3xj7v9k.cloudfront.net) | Array.prototype.findIndex        |                   |
| ...<br>js/main.59cd4549.js:2:507159 (d1se6lw3xj7v9k.cloudfront.net) | Array.prototype.find             |                   |
| ...<br>js/main.59cd4549.js:2:507868 (d1se6lw3xj7v9k.cloudfront.net) | Array.from                       |                   |
| ...<br>js/main.59cd4549.js:2:508044 (d1se6lw3xj7v9k.cloudfront.net) | Array.prototype.includes         |                   |
| ...<br>js/main.59cd4549.js:2:509307 (d1se6lw3xj7v9k.cloudfront.net) | Array.prototype.map              |                   |
| ...<br>js/main.59cd4549.js:2:518148 (d1se6lw3xj7v9k.cloudfront.net) | Number.isInteger                 |                   |
| ...<br>js/main.59cd4549.js:2:518377 (d1se6lw3xj7v9k.cloudfront.net) | Number.isSafeInteger             |                   |
| ...<br>js/main.59cd4549.js:2:519387 (d1se6lw3xj7v9k.cloudfront.net) | Object.defineProperties          |                   |
| ...<br>js/main.59cd4549.js:2:519542 (d1se6lw3xj7v9k.cloudfront.net) | Object.defineProperty            |                   |
| ...<br>js/main.59cd4549.js:2:519926 (d1se6lw3xj7v9k.cloudfront.net) | Object.entries                   |                   |
| ...<br>js/main.59cd4549.js:2:520096 (d1se6lw3xj7v9k.cloudfront.net) | Object.freeze                    |                   |
| ...<br>js/main.59cd4549.js:2:520700 (d1se6lw3xj7v9k.cloudfront.net) | Object.getOwnPropertyDescriptors |                   |
| ...<br>js/main.59cd4549.js:2:521347 (d1se6lw3xj7v9k.cloudfront.net) | Object.getPrototypeOf            |                   |
| ...<br>js/main.59cd4549.js:2:521507 (d1se6lw3xj7v9k.cloudfront.net) | Object.isExtensible              |                   |
| ...<br>js/main.59cd4549.js:2:521684 (d1se6lw3xj7v9k.cloudfront.net) | Object.isFrozen                  |                   |
| ...<br>js/main.59cd4549.js:2:521922 (d1se6lw3xj7v9k.cloudfront.net) | Object.isSealed                  |                   |
| ...<br>js/main.59cd4549.js:2:522120 (d1se6lw3xj7v9k.cloudfront.net) | Object.keys                      |                   |
| ...<br>js/main.59cd4549.js:2:522853 (d1se6lw3xj7v9k.cloudfront.net) | Object.preventExtensions         |                   |
| ...<br>js/main.59cd4549.js:2:523081 (d1se6lw3xj7v9k.cloudfront.net) | Object.seal                      |                   |
| ...<br>js/main.59cd4549.js:2:523222 (d1se6lw3xj7v9k.cloudfront.net) | Object.setPrototypeOf            |                   |
| ...<br>js/main.59cd4549.js:2:523440 (d1se6lw3xj7v9k.cloudfront.net) | Object.values                    |                   |
| ...<br>js/main.59cd4549.js:2:528728 (d1se6lw3xj7v9k.cloudfront.net) | Reflect.apply                    |                   |

| URL                                                                 |                                  | Potential Savings |
|---------------------------------------------------------------------|----------------------------------|-------------------|
| ...<br>js/main.59cd4549.js:2:529169 (d1se6lw3xj7v9k.cloudfront.net) | Reflect.construct                |                   |
| ...<br>js/main.59cd4549.js:2:529684 (d1se6lw3xj7v9k.cloudfront.net) | Reflect.defineProperty           |                   |
| ...<br>js/main.59cd4549.js:2:529970 (d1se6lw3xj7v9k.cloudfront.net) | Reflect.deleteProperty           |                   |
| ...<br>js/main.59cd4549.js:2:530159 (d1se6lw3xj7v9k.cloudfront.net) | Reflect.getOwnPropertyDescriptor |                   |
| ...<br>js/main.59cd4549.js:2:530318 (d1se6lw3xj7v9k.cloudfront.net) | Reflect.getPrototypeOf           |                   |
| ...<br>js/main.59cd4549.js:2:530512 (d1se6lw3xj7v9k.cloudfront.net) | Reflect.get                      |                   |
| ...<br>js/main.59cd4549.js:2:530745 (d1se6lw3xj7v9k.cloudfront.net) | Reflect.has                      |                   |
| ...<br>js/main.59cd4549.js:2:530870 (d1se6lw3xj7v9k.cloudfront.net) | Reflect.isExtensible             |                   |
| ...<br>js/main.59cd4549.js:2:530975 (d1se6lw3xj7v9k.cloudfront.net) | Reflect.ownKeys                  |                   |
| ...<br>js/main.59cd4549.js:2:531083 (d1se6lw3xj7v9k.cloudfront.net) | Reflect.preventExtensions        |                   |
| ...<br>js/main.59cd4549.js:2:531317 (d1se6lw3xj7v9k.cloudfront.net) | Reflect.setPrototypeOf           |                   |
| ...<br>js/main.59cd4549.js:2:535043 (d1se6lw3xj7v9k.cloudfront.net) | String.prototype.codePointAt     |                   |
| ...<br>js/main.59cd4549.js:2:535746 (d1se6lw3xj7v9k.cloudfront.net) | String.fromCodePoint             |                   |
| ...<br>js/main.59cd4549.js:2:537671 (d1se6lw3xj7v9k.cloudfront.net) | String.raw                       |                   |
| ...<br>js/main.59cd4549.js:2:537878 (d1se6lw3xj7v9k.cloudfront.net) | String.prototype.repeat          |                   |
| ...<br>js/main.59cd4549.js:2:979730 (d1se6lw3xj7v9k.cloudfront.net) | @babel/plugin-transform-classes  |                   |

## ● Preload Largest Contentful Paint image ^

Preload the image used by the LCP element in order to improve your LCP time. [Learn more.](#) LCP

## ● Avoids enormous network payloads — Total size was 1,213 KiB ^



Large network payloads cost users real money and are highly correlated with long load times. [Learn more.](#)

LCP

| URL                                                                                               | Transfer Size |
|---------------------------------------------------------------------------------------------------|---------------|
| ...js/main.59cd4549.js (d1se6lw3xj7v9k.cloudfront.net)                                            | 328.5 KiB     |
| ...7f53fa3b-5ecd-40fb-5af7-3fd636c1358c/pendo.js (cdn.pendo.io)                                   | 145.0 KiB     |
| ...7f53fa3b-5ecd-40fb-5af7-3fd636c1358c/pendo-staging.js (pendo-io-static.storage.googleapis.com) | 144.8 KiB     |
| ...css/main.316708b6.css (d1se6lw3xj7v9k.cloudfront.net)                                          | 108.8 KiB     |
| /gtag/js?id=G-9274CJ3BBL (www.googletagmanager.com)                                               | 71.9 KiB      |
| ...media/Poppins-Regular.35d26b7....ttf (d1se6lw3xj7v9k.cloudfront.net)                           | 69.6 KiB      |
| ...media/Poppins-SemiBold.ac8d04b....ttf (d1se6lw3xj7v9k.cloudfront.net)                          | 69.4 KiB      |
| ...media/Poppins-Medium.673ed42....ttf (d1se6lw3xj7v9k.cloudfront.net)                            | 69.0 KiB      |
| /modules.8b83be3....js (script.hotjar.com)                                                        | 64.3 KiB      |
| /gtag/js?id=AW-106... (www.googletagmanager.com)                                                  | 59.2 KiB      |

## ● Avoids an excessive DOM size — 38 elements

A large DOM will increase memory usage, cause longer [style calculations](#), and produce costly [layout reflows](#). [Learn more.](#) TBT

| Statistic              | Element                                                                                                                                                                                                                                                      | Value |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|
| Total DOM Elements     |                                                                                                                                                                                                                                                              | 38    |
| Maximum DOM Depth      | <div></div> <div>div.form-group &gt; div.position-relative &gt; div.position-absolute &gt; div.ic-password-eye<br/><code>&lt;div class="ic-password-eye"&gt;</code></div> | 13    |
| Maximum Child Elements | <div><div></div><div>body<br/><code>&lt;body&gt;</code></div></div>                                                                                                       | 5     |

## ○ User Timing marks and measures

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. [Learn more.](#)

## ● Minimize third-party usage — Third-party code blocked the main thread for 130 ms

Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. [Learn more.](#) TBT

| Third-Party                                                     | Transfer Size | Main-Thread Blocking Time |
|-----------------------------------------------------------------|---------------|---------------------------|
| <a href="#">Hotjar</a>                                          | 69 KiB        | 69 ms                     |
| /modules.8b83be3...js (script.hotjar.com)                       | 64 KiB        | 69 ms                     |
| Other resources                                                 | 4 KiB         | 0 ms                      |
| <a href="#">Pendo</a>                                           | 146 KiB       | 34 ms                     |
| ...7f53fa3b-5ecd-40fb-5af7-3fd636c1358c/pendo.js (cdn.pendo.io) | 145 KiB       | 34 ms                     |
| <a href="#">Google Tag Manager</a>                              | 131 KiB       | 29 ms                     |
| /gtag/js?id=AW-106... (www.googletagmanager.com)                | 59 KiB        | 29 ms                     |
| /gtag/js?id=G-9274CJ3BBL (www.googletagmanager.com)             | 72 KiB        | 0 ms                      |
| <a href="#">Launch Darkly</a>                                   | 5 KiB         | 0 ms                      |

#### ○ Lazy load third-party resources with facades ^

Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are required.

[Learn more.](#) TBT

#### ○ Largest Contentful Paint image was not lazily loaded ^

Above-the-fold images that are lazily loaded render later in the page lifecycle, which can delay the largest contentful paint. [Learn more.](#)

#### ● Uses passive listeners to improve scrolling performance ^

Consider marking your touch and wheel event listeners as `passive` to improve your page's scroll performance. [Learn more.](#)

#### ● Avoids `document.write()` ^

For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds. [Learn more.](#)

#### ○ Avoid non-composited animations ^

Animations which are not composited can be janky and increase CLS. [Learn more](#) CLS

#### ○ Image elements have explicit `width` and `height` ^

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. [Learn more](#) CLS

#### ● Has a `<meta name="viewport">` tag with `width` or `initial-scale` ^

A ``<meta name="viewport">`` not only optimizes your app for mobile screen sizes, but also prevents [a 300 millisecond delay to user input](#). [Learn more](#). TBT



## Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

### ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

#### ☐ The page has a logical tab order



Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more](#).

#### ☐ Interactive controls are keyboard focusable



Custom interactive controls are keyboard focusable and display a focus indicator. [Learn more](#).

#### ☐ Interactive elements indicate their purpose and state



Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn more](#).

#### ☐ The user's focus is directed to new content added to the page



If new content, such as a dialog, is added to the page, the user's focus is directed to it. [Learn more](#).

#### ☐ User focus is not accidentally trapped in a region



A user can tab into and out of any control or region without accidentally trapping their focus. [Learn more](#).

#### ☐ Custom controls have associated labels



Custom interactive controls have associated labels, provided by `aria-label` or `aria-labelledby`. [Learn more](#).

#### ☐ Custom controls have ARIA roles



Custom interactive controls have appropriate ARIA roles. [Learn more.](#)

 Visual order on the page follows DOM order 

DOM order matches the visual order, improving navigation for assistive technology. [Learn more.](#)

 Offscreen content is hidden from assistive technology 

Offscreen content is hidden with `display: none` or `aria-hidden=true`. [Learn more.](#)

 HTML5 landmark elements are used to improve navigation 

Landmark elements (`<main>`, `<nav>`, etc.) are used to improve the keyboard navigation of the page for assistive technology. [Learn more.](#)

These items address areas which an automated testing tool cannot cover. Learn more in our guide on [conducting an accessibility review](#).

PASSED AUDITS (12)

Hide

 `[aria-hidden="true"]` is not present on the document `<body>` 

Assistive technologies, like screen readers, work inconsistently when ``aria-hidden="true"``` is set on the document ``<body>``. [Learn more.](#)

 Buttons have an accessible name 

When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. [Learn more.](#)

 ARIA IDs are unique 

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. [Learn more.](#)

 Form elements have associated labels 

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. [Learn more.](#)

 `[user-scalable="no"]` is not used in the `<meta name="viewport">` element and the `[maximum-scale]` attribute is not less than 5. 

Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. [Learn more](#).

- The page contains a heading, skip link, or landmark region ^

Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more](#).

- Background and foreground colors have a sufficient contrast ratio ^

Low-contrast text is difficult or impossible for many users to read. [Learn more](#).

- Document has a `<title>` element ^

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more](#).

- `<frame>` or `<iframe>` elements have a title ^

Screen reader users rely on frame titles to describe the contents of frames. [Learn more](#).

- `<html>` element has a `[lang]` attribute ^

If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. [Learn more](#).

- `<html>` element has a valid value for its `[lang]` attribute ^

Specifying a valid [BCP 47 language](#) helps screen readers announce text properly. [Learn more](#).

- Links have a discernible name ^

Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. [Learn more](#).

NOT APPLICABLE (32)

Hide

- `[accesskey]` values are unique ^

Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. [Learn more](#).

---

☐ `[aria-*)` attributes match their roles ^

---

Each ARIA `role` supports a specific subset of `aria-*)` attributes. Mismatching these invalidates the `aria-*)` attributes. [Learn more](#).

---

☐ `button`, `link`, and `menuitem` elements have accessible names ^

---

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more](#).

---

☐ `[aria-hidden="true"]` elements do not contain focusable descendents ^

---

Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. [Learn more](#).

---

☐ ARIA input fields have accessible names ^

---

When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more](#).

---

☐ ARIA `meter` elements have accessible names ^

---

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more](#).

---

☐ ARIA `progressbar` elements have accessible names ^

---

When a `progressbar` element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more](#).

---

☐ `[role]`s have all required `[aria-*)` attributes ^

---

Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more](#).

---

☐ Elements with an ARIA `[role]` that require children to contain a specific `[role]` have all required children. ^

---

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more](#).

---

☐ `[role]`s are contained by their required parent element ^

---

Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. [Learn more](#).

---

- ☐ `[role]` values are valid ^

ARIA roles must have valid values in order to perform their intended accessibility functions. [Learn more.](#)

- ☐ ARIA toggle fields have accessible names ^

When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

- ☐ ARIA `tooltip` elements have accessible names ^

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

- ☐ ARIA `treeitem` elements have accessible names ^

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

- ☐ `[aria-*) attributes have valid values ^`

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. [Learn more.](#)

- ☐ `[aria-*) attributes are valid and not misspelled ^`

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. [Learn more.](#)

- ☐ `<dl>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>`, `<template>` or `<div>` elements. ^

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn more.](#)

- ☐ Definition list items are wrapped in `<dl>` elements ^

Definition list items (``<dt>`` and ``<dd>``) must be wrapped in a parent ``<dl>`` element to ensure that screen readers can properly announce them. [Learn more.](#)

- ☐ `[id]` attributes on active, focusable elements are unique ^

All focusable elements must have a unique ``id`` to ensure that they're visible to assistive technologies. [Learn more.](#)

- ☐ No form fields have multiple labels ^

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. [Learn more.](#)

- ☐ Heading elements appear in a sequentially-descending order ^

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. [Learn more](#).

☐ Image elements have `[alt]` attributes ^

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more](#).

☐ `<input type="image">` elements have `[alt]` text ^

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn more](#).

☐ Lists contain only `<li>` elements and script supporting elements (`<script>` and `<template>`). ^

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more](#).

☐ List items (`<li>`) are contained within `<ul>` or `<ol>` parent elements ^

Screen readers require list items (`<li>`) to be contained within a parent `<ul>` or `<ol>` to be announced properly. [Learn more](#).

☐ The document does not use `<meta http-equiv="refresh">` ^

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more](#).

☐ `<object>` elements have alternate text ^

Screen readers cannot translate non-text content. Adding alternate text to `<object>` elements helps screen readers convey meaning to users. [Learn more](#).

☐ No element has a `[tabindex]` value greater than 0 ^

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. [Learn more](#).

☐ Cells in a `<table>` element that use the `[headers]` attribute refer to table cells within the same table. ^

Screen readers have features to make navigating tables easier. Ensuring `<td>` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. [Learn more](#).

☐ `<th>` elements and elements with `[role="columnheader"/"rowheader"]` have data cells they describe. ^

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more](#).

○ `[lang]` attributes have a valid value

Specifying a valid [BCP 47 language](#) on elements helps ensure that text is pronounced correctly by a screen reader. [Learn more](#).

○ `<video>` elements contain a `<track>` element with `[kind="captions"]`

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. [Learn more](#).



## Best Practices

### GENERAL

▲ Browser errors were logged to the console

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. [Learn more](#)

| Source                                                         | Description                                 |
|----------------------------------------------------------------|---------------------------------------------|
| ...62a7835.../eyJhbm9ue...:1:0 (clientstream.launchdarkly.com) | Failed to load resource: net::ERR_TIMED_OUT |
| ...62a7835.../eyJhbm9ue...:1:0 (clientstream.launchdarkly.com) | Failed to load resource: net::ERR_TIMED_OUT |

○ Detected JavaScript libraries

All front-end JavaScript libraries detected on the page. [Learn more](#).

| Name             | Version               |
|------------------|-----------------------|
| core-js          | core-js-global@3.24.1 |
| Create React App |                       |

▲ Missing source maps for large first-party JavaScript

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more](#).

| URL                                                         | Map URL                                                         |
|-------------------------------------------------------------|-----------------------------------------------------------------|
| ...js/main.59cd4549.js (d1se6lw3xj7v9k.cloudfront.net)      | ...js/main.59cd4549.js.map (d1se6lw3xj7v9k.cloudfront.net)      |
| Large JavaScript file is missing a source map               |                                                                 |
| Error: Timed out fetching resource.                         |                                                                 |
| ...js/868.5969846f.chunk.js (d1se6lw3xj7v9k.cloudfront.net) | ...js/868.5969846f.chunk.js.map (d1se6lw3xj7v9k.cloudfront.net) |
| Error: Timed out fetching resource.                         |                                                                 |
| ...js/909.b9007d19.chunk.js (d1se6lw3xj7v9k.cloudfront.net) | ...js/909.b9007d19.chunk.js.map (d1se6lw3xj7v9k.cloudfront.net) |
| ...js/682.e099fea3.chunk.js (d1se6lw3xj7v9k.cloudfront.net) | ...js/682.e099fea3.chunk.js.map (d1se6lw3xj7v9k.cloudfront.net) |

TRUST AND SAFETY

 Ensure CSP is effective against XSS attacks

^

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. [Learn more](#)

| Description                      | Directive | Severity |
|----------------------------------|-----------|----------|
| No CSP found in enforcement mode |           | High     |

PASSED AUDITS (11)

Hide

 Uses HTTPS

^

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding [mixed content](#), where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. [Learn more](#).

 Avoids requesting the geolocation permission on page load

^

Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. [Learn more](#).

● Avoids requesting the notification permission on page load ^

Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. [Learn more.](#)

● Avoids front-end JavaScript libraries with known security vulnerabilities ^

Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. [Learn more.](#)

● Allows users to paste into password fields ^

Preventing password pasting undermines good security policy. [Learn more.](#)

● Displays images with correct aspect ratio ^

Image display dimensions should match natural aspect ratio. [Learn more.](#)

● Serves images with appropriate resolution ^

Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. [Learn more.](#)

● Page has the HTML doctype ^

Specifying a doctype prevents the browser from switching to quirks-mode. [Learn more.](#)

● Properly defines charset ^

A character encoding declaration is required. It can be done with a `` tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. [Learn more.](#)

● Avoids deprecated APIs ^

Deprecated APIs will eventually be removed from the browser. [Learn more.](#)

● No issues in the [Issues](#) panel in Chrome Devtools ^

Issues logged to the `Issues` panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

NOT APPLICABLE (1)

Hide

- Fonts with `font-display: optional` are preloaded ^

Preload `optional` fonts so first-time visitors may use them. [Learn more](#)



## SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on [Core Web Vitals](#). [Learn more](#).

ADDITIONAL ITEMS TO MANUALLY CHECK (1)

Hide

- Structured data is valid ^

Run the [Structured Data Testing Tool](#) and the [Structured Data Linter](#) to validate structured data. [Learn more](#).

Run these additional validators on your site to check additional SEO best practices.

PASSED AUDITS (12)

Hide

- Has a `<meta name="viewport">` tag with `width` or `initial-scale` ^

A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents [a 300 millisecond delay to user input](#). [Learn more](#). TBT

- Document has a `<title>` element ^

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more](#).

- Document has a meta description ^

Meta descriptions may be included in search results to concisely summarize page content. [Learn more.](#)

● Page has successful HTTP status code ^

Pages with unsuccessful HTTP status codes may not be indexed properly. [Learn more.](#)

● Links have descriptive text ^

Descriptive link text helps search engines understand your content. [Learn more.](#)

● Links are crawlable ^

Search engines may use `href` attributes on links to crawl websites. Ensure that the `href` attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. [Learn More](#)

● Page isn't blocked from indexing ^

Search engines are unable to include your pages in search results if they don't have permission to crawl them. [Learn more.](#)

● robots.txt is valid ^

If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. [Learn more.](#)

● Document has a valid hreflang ^

hreflang links tell search engines what version of a page they should list in search results for a given language or region. [Learn more.](#)

● Document uses legible font sizes — 100% legible text ^

Font sizes less than 12px are too small to be legible and require mobile visitors to “pinch to zoom” in order to read. Strive to have >60% of page text ≥12px. [Learn more.](#)

| Source       | Selector | % of Page Text | Font Size |
|--------------|----------|----------------|-----------|
| Legible text |          | 100.00%        | ≥ 12px    |

● Document avoids plugins ^

Search engines can't index plugin content, and many devices restrict plugins or don't support them. [Learn more.](#)

● Tap targets are sized appropriately — 100% appropriately sized tap targets ^

Interactive elements like buttons and links should be large enough (48x48px), and have enough space around them, to be easy enough to tap without overlapping onto other elements. [Learn more.](#)

NOT APPLICABLE (2)

Hide

○ Image elements have `[alt]` attributes ^

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more.](#)

○ Document has a valid `rel=canonical` ^

Canonical links suggest which URL to show in search results. [Learn more.](#)



PWA

These checks validate the aspects of a Progressive Web App. [Learn more.](#)

● INSTALLABLE

● Web app manifest and service worker meet the installability requirements ^

Service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. With proper service worker and manifest implementations, browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. [Learn more.](#)



▲ Does not register a service worker that controls page and `start_url`



The service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. [Learn more](#).

▲ Is not configured for a custom splash screen



**Failures: Manifest does not have a PNG icon of at least 512px.**

A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. [Learn more](#).

● Sets a theme color for the address bar.



The browser address bar can be themed to match your site. [Learn more](#).

● Content is sized correctly for the viewport



If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. [Learn more](#).

● Has a `<meta name="viewport">` tag with `width` or `initial-scale`



A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents [a 300 millisecond delay to user input](#). [Learn more](#). TBT

● Provides a valid `apple-touch-icon`



For ideal appearance on iOS when users add a progressive web app to the home screen, define an `apple-touch-icon`. It must point to a non-transparent 192px (or 180px) square PNG. [Learn More](#).

▲ Manifest doesn't have a maskable icon



A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device. [Learn more](#).

#### ADDITIONAL ITEMS TO MANUALLY CHECK (3)

Hide

○ Site works cross-browser



To reach the most number of users, sites should work across every major browser. [Learn more](#).

○ Page transitions don't feel like they block on the network



Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. [Learn more](#).

## ○ Each page has a URL



Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. [Learn more](#).

These checks are required by the baseline [PWA Checklist](#) but are not automatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually.

📅 Captured at Aug 17, 2022, 11:20 AM  
GMT+5:30

🖥️ Emulated Moto G4 with Lighthouse  
9.6.5

🔗 Single page load

🕒 Initial page load

🔍 Unknown

🚀 Using HeadlessChromium  
102.0.5005.115 with Ir

Generated by **Lighthouse** 9.6.5 | [File an issue](#)