



Support Vector Machines

Outline

- Transform a linear learner into a non-linear learner
- Kernels can make high-dimensional spaces tractable
- Kernels can make non-vectorial data tractable



Non-Linear Problems



Problem:


- some tasks have non-linear structure
- no hyperplane is sufficiently accurate

How can SVMs learn non-linear classification rules?




Extending the Hypothesis Space

Idea: add more features




➔ Learn linear rule in feature space.

Example:




➔ The separating hyperplane in feature space is degree two polynomial in input space.




Transformation

- Instead of x_1, x_2 use

$$f_1 = x_1^2, \quad f_2 = x_2^2, \quad f_3 = \sqrt{2}x_1x_2$$





How do we find these features?

- $F(x) =$


$$f_1 = x_1^2, \quad f_2 = x_2^2, \quad f_3 = \sqrt{2}x_1x_2$$

Reminder

- Linear Separation of the input space

$$f(x) = \langle w, x \rangle + b$$

$$h(x) = \text{sign}(f(x))$$



Reminder


Update rule

(ignoring threshold):

- if $y_i(\langle w_k, x_i \rangle) \leq 0$ then

$$w_{k+1} \leftarrow w_k + \eta y_i x_i$$

$$k \leftarrow k + 1$$



Observation

- Solution is a linear combination of training points

$$w = \sum \alpha_i y_i x_i$$

$$\alpha_i \geq 0$$

- Only used informative points (mistake driven)
- The coefficient of a point in combination reflects its 'difficulty'

Dual Representation

possible to rewrite the algorithm using this alternative representation

The decision function can be re-written as follows:

$$f(x) = \langle w, x \rangle + b = \sum \alpha_i y_i \langle x_i, x \rangle + b$$

$$w = \sum \alpha_i y_i x_i$$

New Update Rule

- The update rule can be written as

$$y_i \left(\sum \alpha_j y_j \langle x_j, x_i \rangle + b \right) \leq 0 \quad \text{then} \quad \alpha_i \leftarrow \alpha_i + \eta$$

- And the hypothesis $h(\mathbf{x})$ is

$$h(\mathbf{x}) = \text{sign} \left(\sum_i \alpha_i y_i (\mathbf{x} \cdot \mathbf{x}_i) \right)$$

- Note: Hypothesis uses only dot products with key examples (“support vectors”)

Max Margin = Minimal Norm

- If we fix the functional margin to 1, the geometric margin equal $1/||w||$
- Hence, maximize the margin by minimizing the norm
 - Minimize $\langle w, w \rangle$
 - Subject to $y_i(\langle w, x_i \rangle + b) \geq 1$

How to find the α 's?

- Maximize:
$$W(\alpha) = \sum_i \alpha_i - \frac{1}{2} \sum_{i,j} \alpha_i \alpha_j y_i y_j \langle x_i, x_j \rangle$$
- Subject to: $\alpha_i \geq 0$
$$\sum_i \alpha_i y_i = 0$$

Using Kernels: Implicit features

- We need to compute $\langle x_i, x_j \rangle$ many times
 - Or $\langle F(x_i), F(x_j) \rangle$ if we use features $F(x)$
- But what if we found a set of features $F(x)$ such that $F(x_i) \cdot F(x_j) = (x_i \cdot x_j)^2$?
 - Then we only need to compute $(x_i \cdot x_j)^2$
 - We don't even need to know what F is (!)

Implicit features: Example

$$x = (x_1, x_2);$$

$$z = (z_1, z_2);$$

$$\langle x, z \rangle^2 = (x_1 z_1 + x_2 z_2)^2 =$$

$$= x_1^2 z_1^2 + x_2^2 z_2^2 + 2 x_1 z_1 x_2 z_2 =$$

$$= \langle (x_1^2, x_2^2, \sqrt{2} x_1 x_2), (z_1^2, z_2^2, \sqrt{2} z_1 z_2) \rangle =$$

$$= \langle \phi(x), \phi(z) \rangle$$

Calculate using a Kernel

- Two vectors
 - $A = (1, 2)$
 - $B = (3, 4)$
- Three Features:
 - $F(X) = \{x_1^2, x_2^2, \sqrt{2} \cdot x_1 \cdot x_2\}$
 - Calculate $F(A) \cdot F(B)$

What is $F(A) \cdot F(B)$?

A=120 B=121 C=144 D=256

Calculate without using a Kernel

- $A = (1,2), B = (3,4)$
- $F(X) = \{x_1^2, x_2^2, \sqrt{2} \cdot x_1 \cdot x_2\}$
 - $A=(1,2) \rightarrow F(A)=\{1^2, 2^2, \sqrt{2} \cdot 1 \cdot 2\} = \{1, 4, 2\sqrt{2}\}$
 - $B=(3,4) \rightarrow F(B)=\{3^2, 4^2, \sqrt{2} \cdot 3 \cdot 4\} = \{9, 16, 12\sqrt{2}\}$
- $F(A) \cdot F(B) = 1 \cdot 9 + 4 \cdot 16 + 2 \cdot 12 \cdot 2 = 121$

Calculate using a Kernel

$$\begin{aligned}\langle x, z \rangle^2 &= (x_1 z_1 + x_2 z_2)^2 = \\ &= x_1^2 z_1^2 + x_2^2 z_2^2 + 2x_1 z_1 x_2 z_2 = \\ &= \langle (x_1^2, x_2^2, \sqrt{2}x_1 x_2), (z_1^2, z_2^2, \sqrt{2}z_1 z_2) \rangle =\end{aligned}$$

- $A = (1, 2), B = (3, 4), F(X) = \{x_1^2, x_2^2, \sqrt{2} \cdot x_1 \cdot x_2\}$
- $F(A) \cdot F(B) = (A \cdot B)^2 = (1 \cdot 3 + 2 \cdot 4)^2 = 11^2 = 121$
- We didn't need to explicitly calculate or even know about the terms in F at all!
 - just that $F(A) \cdot F(B) = (A \cdot B)^2$

SVM with Kernel

Training:


$$\begin{aligned} \text{maximize: } D(\vec{\alpha}) &= \sum_{i=1}^n \alpha_i - \frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n y_i y_j \alpha_i \alpha_j K(\vec{x}_i, \vec{x}_j) \\ \text{subject to: } \sum_{i=1}^n y_i \alpha_i &= 0 \\ \forall_{i=1}^n : 0 &\leq \alpha_i \leq C \end{aligned}$$

$$\begin{aligned} \text{Classification: } h(\vec{x}) &= \text{sign} \left(\left[\sum_{i=1}^n \alpha_i y_i \Phi(\vec{x}_i) \right] \cdot \Phi(\vec{x}) + b \right) \\ &= \text{sign} \left(\sum_{i=1}^n \alpha_i y_i K(\vec{x}_i, \vec{x}) + b \right) \end{aligned}$$

New hypotheses spaces through new Kernels:

- Linear: $K(\vec{a}, \vec{b}) = \vec{a} \cdot \vec{b}$
- Polynomial: $K(\vec{a}, \vec{b}) = [\vec{a} \cdot \vec{b} + 1]^d$
- Radial Basis Function: $K(\vec{a}, \vec{b}) = \exp(-\gamma[\vec{a} - \vec{b}]^2)$
- Sigmoid: $K(\vec{a}, \vec{b}) = \tanh(\vec{a} \cdot \vec{b})$


Solution with Gaussian Kernels



Examples of Kernels


Polynomial Function

$$K(\vec{a}, \vec{b}) = [\vec{a} \cdot \vec{b} + 1]^2$$




Radial Basis

$$K(\vec{a}, \vec{b}) = \exp(-\gamma[\vec{a} - \vec{b}]^2)$$



Kernels for Non-Vectorial Data



Kernels for Non-Vectorial Data


- Applications with Non-Vectorial Input Data
 - classify non-vectorial objects
 - Protein classification (x is string of amino acids)
 - Drug activity prediction (x is molecule structure)
 - Information extraction (x is sentence of words)
 - Etc.
 - Applications with Non-Vectorial Output Data
 - predict non-vectorial objects
 - Natural Language Parsing (y is parse tree)
 - Noun-Phrase Co-reference Resolution (y is clustering)
 - Search engines (y is ranking)
- Kernels can compute inner products efficiently!

Properties of SVMs with Kernels

- Expressiveness
 - Can represent any boolean function (for appropriate choice of kernel)
 - Can represent any sufficiently “smooth” function to arbitrary accuracy (for appropriate choice of kernel)
- Computational
 - Objective function has no local optima (only one global)
 - Independent of dimensionality of feature space
- Design decisions
 - Kernel type and parameters
 - Value of C

Benchmark

- Character recognition
- NIST Database of handwritten digits
 - 60,000 samples
 - 20x20 pixels



Mr. J. H. Zurnock

POLE POSITION, JAN 19 1968 P.M. U.S. NY

2c LLOYD WRIGHT

U.S. NAVY OPERATION DEEPFREEZE

8c AIR MAIL

Miss Anne Zurnock
2810 Kanawha St. N.W.
Washington, D.C. 20015

JAMES C. MORRISON
MARTIN MORRISON
UNAPPORTIONED
YOUR LIFE & LIVING

145

Jan. 1, 2002

NORTH POLE, INC.

\$ 295.⁴⁵/₁₀₀

Value: Hundred Ninety Five and ⁴⁵/₁₀₀ -

Your Bank
WELLS FARGO BANK

Cashier James C. Morrison

⑆000067894⑉ 123456789 ⑈45 ⑆0000029545⑈

00000 27545

Digit Recognition

- 3-nearest neighbor: 2.4% error rate
 - stores all samples
- Single hidden layer NN: 1.6%
 - 400 inputs, 10 output, 300 hidden (using CV)
- Specialized nets (LeNet): 0.9%
 - Use specialized 2D architecture
- Boosted NN: 0.7%
 - Three copies of LeNets

Digit Recognition

- SVM: 1.1%
 - Compare to specialized LeNet 0.9%
- Specialized SVM: 0.56%
- Shape Matching: 0.63%
 - Machine vision techniques
- Humans?
 - A=0.1% B=0.5% C=1% D=2.5% E=5%

Generative models

