t27b: A Fast Baseline AArch64 Compiler for a Specification-First Language

Corpus-Scale Differential Measurement against Zig, GCC and Clang Pipelines

Dmitrii Vasilev
Trinity S3AI

2026-11-07

Abstract

t27b is the native backend of t27, a specification-first language whose source files carry their own tests. It lowers t27's internal intermediate representation to AArch64 machine code, runs a specification's tests in-process through a JIT, and emits relocatable objects and assembly listings. We measure it against the t27c reference pipeline (t27c gen, then Zig 0.16 Debug) and against t27c's C emitter compiled with GCC 12.2 and Clang 21.1, over the 1,819-specification corpus at one pinned revision. t27b passes 1,296 of the 1,311 files the reference passes (98.9%) and agrees with the reference on all 8,344 tests both ran. Its test-compile latency, which ends with code in memory and does not link, is 4.8 ms per specification (geometric mean over 18), 8.8× below GCC -O0 compiling the generated C to an object and 640× below one Zig Debug invocation, which builds and links a test binary; when 20 specifications share one Zig invocation the gap is 8.6×. The compiler is a 3.08 MB executable with one crate dependency and a median peak compile memory of 5.3 MiB. Its generated code is at the level of an unoptimising compiler: on the 20 specifications with the most GCC -O0 instructions among the 567 that every pipeline, t27b included, passes, it executes 0.91× the instructions of GCC -O0 and 3.4× those of GCC -O2, runs 4.1× slower than GCC -O2 under qemu-aarch64 emulation (3.7× slower than Clang -O2 on the 9 specifications Clang did not fold), and is 1.8× larger than GCC -O2 code; on four crypto specifications it executes 10.1× the instructions of Zig ReleaseFast. Agreement is self-consistency behind one shared front end, not independent proof: a random-program fuzzer at a nearby commit found 7 disagreements in 1,000 programs. All run times are emulated. The report and its raw JSON are committed with the repository.

1 Introduction

t27 is a specification-first language: a `.t27` file declares functions and data together with the `test` and `invariant` blocks that state what they must do. Its reference compiler, t27c, checks a specification and emits it as Zig, C, Rust or Verilog source; the reference way to run a specification's tests is `t27c gen` followed by the Zig compiler. t27b is a second, native path: it mounts the same front end and lowers the resulting internal representation directly to AArch64 machine code, without LLVM, an assembler or a linker.

This paper asks what such a small native backend costs and what it buys when measured over a whole corpus rather than on a chosen example. The answer, on the evidence below, is the profile of a fast baseline compiler: low test-compile latency and a small footprint, with generated code at the level of an unoptimising compiler.

Contributions. (1) A corpus-scale, test-by-test differential comparison of t27b with the reference pipeline and with C pipelines over the 1,819-specification corpus at one revision, each pair compared on the files both ran (Section 4). (2) Compile-latency, memory and footprint

measurements against Zig, GCC, Clang and rustc on the same host, including the case where Zig amortises its fixed cost over many specifications (Sections 5 and 7). (3) A code-quality measurement by executed guest instructions on specifications ranked by GCC -O0 instruction count, a rule that uses no t27b measurement (Section 6). (4) An explicit list of threats to validity, including the ways in which the agreement result is not independent (Section 9).

Scope: what t27b is not. t27b is not an optimising compiler and not a replacement for LLVM. It is not a multi-language backend: it does not parse C, Rust, Zig, Go or Python, and no front end for those languages lowers to its internal representation. In this paper "t27 IR" means that in-memory representation; it is not an external interchange format, and t27b reads no serialised IR. At the measured revision t27b did not produce a linked executable on Linux (Section 2).

Artifacts. Every number in this paper outside Section 10 comes from one measurement report committed to the public t27 repository, `docs/reports/t27b-bench-2026-10.md`, and its raw data, `docs/reports/t27b-bench-2026-10.json` (`https://github.com/Trinity-S-AI-DNA/t27`). The measurements were taken at commit `9a0f4c394` (2026-10-10; full hash in Table 1), except two trust results that the report quotes from the t27b lab at other commits; Section 9 names their commits. The harness itself is lab scratch and is not committed; the report spells out every command it ran (Section 9). The repository's acceptance matrix for t27b, the t27 specification `specs/tri/shootout/acceptance_matrix.t27`, records the headline ratios as cells tagged with the same commit; it is a ledger of this report, not a second measurement.

2 System under test

t27c. Version 0.5.2, built at the measured commit. `t27c gen` emits Zig, `gen-c` emits C and `gen-rust` emits Rust. gen-rust lowers function bodies but no tests, so it appears only in compile-time, size and determinism results.

t27b. t27b mounts t27c's front end (`bootstrap/src/compiler.rs`) and adds its own AArch64 code generator. `t27b test` compiles a specification and runs each test in an in-process JIT; with `-check` it also runs each test in t27b's own IR interpreter and compares the two. `-overflow trap`, the default, keeps integer-overflow and bounds checks; `wrap` drops the overflow checks. `t27b build` writes a relocatable object and `t27b asm` an assembly listing; `t27b corpus` walks a directory and, with `-reference t27c`, compares every test with the reference. t27b is written in Rust. 36% of its backend source is generated from `.t27` specifications; counting the front end it mounts, the generated share is 12%. Its only crate dependency is `serde`, used by the shared front end.

Limits at the measured revision. `t27b build` wrote Mach-O objects only, did not link, and refused module-level variables in an object file (2 of the 20 code-quality specifications). On aarch64-linux t27b was therefore a JIT test runner, not a compiler that ships binaries; every t27b run time below is a JIT run. Section 10 reports what changed after the snapshot.

3 Environment and method

Pipelines. t27b runs tests in its JIT under qemu-aarch64. The Zig pipelines (Debug, ReleaseSafe, ReleaseFast) and the C pipelines (GCC and Clang at -O0 and -O2) build static aarch64 test binaries and run each test in its own qemu-aarch64 process, the same one-test-per-process protocol as `t27c test-report`. Safety checks differ: t27b (trap) and Zig Debug/ReleaseSafe

Host	Shared x86_64 cloud container: Intel Xeon 6975P-C, 48 host threads, cgroup quota 24 CPUs, 24 GB memory limit, Linux 6.18.5, Debian 12.15. Host 1-minute load 27–103 during the run, recorded with every sample.
Commit	`9a0f4c394a1474bb75103f141cc0b405d9de51b9`
Zig	0.16.0; its aarch64 output goes through LLVM (LLD 21.1.0)
GCC	aarch64-linux-gnu-gcc 12.2.0, binutils 2.40, glibc 2.36, `-static`
Clang	21.1.0 as bundled in Zig 0.16.0 (`zig cc -target aarch64-linux-musl`, `-static`)
rustc	1.99.0 (LLVM 23.1.1), aarch64-unknown-linux-gnu
qemu	qemu-aarch64 7.2.22, user mode

Table 1: Measurement environment.

check overflow and bounds at run time; Zig ReleaseFast, GCC and Clang do not, and in C signed overflow is undefined behaviour. The like-for-like comparison for t27b's default output is Zig ReleaseSafe.

Corpus and classes. The denominator is every `.t27` file under `specs/`: 1,819 files, none left out for being slow or broken. Each file falls into one class per pipeline: pass (compiled, at least one test, all passed), vacuous pass (t27b only: no runtime assert executed), compiled with no tests, a test fails, timeout, or blocked (did not generate, did not compile, or t27b refused a construct). Where two pipelines both ran a file, verdicts are compared test by test, by name.

Compile latency. The host is x86_64, so t27b was also built for the host. On x86_64 `t27b test` runs the front end and code generation, tests included, then stops with exit code 74 when it tries to map the JIT; the wall time of that process is t27b's test-compile time. It therefore covers code generation into memory, with no loading, assembling or linking, while the Zig figures include building and linking a test binary and the C figures stop at an object; the steps are not the same work. All other compilers also run natively. One sample is the wall time of one process from spawn to exit, one compile at a time, round-robin over specifications and pipelines for 6 rounds; rounds 1–5 are warm and their median is reported. Process start (about 1 ms for t27b and t27c) is included.

Code-quality selection. Tier 1 starts from the 567 files that every pipeline, t27b included, passes, builds each with GCC -O0, counts the guest instructions its tests execute, and takes the 20 with the most. The ranking uses no t27b measurement, but the pool is conditioned on t27b passing, and the rule favours compute-heavy specifications. It selects six benchmark kernels, three FPGA-synthesis simulations, an ISA model and ten other specifications. gen-c output does not compile for the crypto specifications, so they are not in tier 1; four of them are measured against Zig only.

Instructions, time and size. A qemu TCG plugin adds each translated block's instruction count at block entry. For Zig and C it counts between two `getppid()` markers around each test call; for t27b it counts blocks in memory the process made executable, which is the JIT image. The count is deterministic and includes t27b's run-time invariants (under 6% of its test time). Run time is the sum over tests of `CLOCK_MONOTONIC` brackets inside the guest, median of 5 repetitions; these are emulated times. Code size is the bytes of machine code for the specification's functions and tests. Pipeline ratios are geometric means over specifications of t27b divided by the other pipeline.

Pipeline	passes, of the 1,311 files the reference passes
t27b (JIT, trap)	1,296 (98.9%)
Zig Debug, aarch64	1,311 (100.0%)
Zig ReleaseFast, aarch64	1,306 (99.6%)
gen-c + GCC -O0 / -O2	581 (44.3%) / 578 (44.1%)
gen-c + Clang -O0 / -O2	571 (43.6%) / 622 (47.4%)

Table 2: Coverage relative to the reference (t27c gen + Zig Debug, x86_64).

Pair	files both ran	files that differ	tests compared	tests that differ
t27b / reference	1,315	0	8,344	0
t27b / Zig ReleaseFast	1,315	5	8,344	8
Zig Debug / Zig ReleaseFast	1,337	7	8,531	11
GCC -O0 / GCC -O2	644	4	4,906	4
Clang -O0 / Clang -O2	635	39	4,798	107
GCC -O2 / Clang -O2	635	35	4,798	95
t27b / GCC -O2	610	24	3,790	48
t27b / Clang -O2	634	12	3,901	28

Table 3: Test-by-test disagreements.

4 Coverage and agreement

t27b agrees with the reference on every test both ran: 0 of 8,344 (Table 3). The reference itself is unchanged by moving from x86_64 to aarch64 (0 of 8,513 tests differ). Zig ReleaseFast is not the reference: it flips 7 files against Zig Debug; t27b runs 5 of them and agrees with Debug on all 5. The C pipelines disagree with themselves across optimisation levels, because gen-c output contains undefined behaviour; GCC -O2 and Clang -O2 differ from each other on 35 files. So t27b's differences with the optimised C pipelines (24 files against GCC -O2, 12 against Clang -O2) do not by themselves locate a t27b fault. The C rows cover only the files gen-c compiles, about a third of the corpus.

Of the 15 files the reference passes and t27b does not, 14 are blocked (i128 three times, an escaping frame address three times, an empty typed array literal twice, `@cos`, `anytype`, `std.*`, an assignment form, a type mismatch, and a 1 MiB frame-size limit) and 1 passes vacuously. t27b passes 3 files the reference cannot compile. A native arm64 CI run at the same commit printed the same t27b tally as the emulated run.

5 Compile latency

Pipeline (18 tier-1 specifications)	geomean warm median (ms)	× t27b test-compile
t27b test-compile (tests included)	4.75	1.00
t27b build (object, no tests)	5.11	1.08
gen-c + GCC -O0, object	42.0	8.84
gen-c + GCC -O2, object	100	21.0
gen-c + Clang -O0, object	71.1	15.0
gen-c + Clang -O2, object	105	22.1
gen + Zig Debug, test binary	3,050	642
gen + Zig ReleaseFast, test binary	13,808	2,906

Table 4: Compile latency per specification, native x86_64. The 18 specifications are the tier-1 set minus the two `t27b build` refuses; generator time is included where there is a generator.

Most of Zig's time per specification is fixed cost (test runner, standard library machinery and the LLVM link), which a project amortises by compiling many specifications at once. With all 20 tier-1 specifications in one `zig test` invocation, Zig takes 6.21 s in Debug and 32.9 s in ReleaseFast, against 0.72 s for 20 separate t27b test-compile processes: the gap falls from about 640× to 8.6× (Debug) and from about 2,900× to 46× (ReleaseFast). t27b has no multi-file mode. Over the 567 files every pipeline passes, t27b test-compiles 183 files per second (3.10 s in all), against 28 files per second for gen-c + GCC -O0 to objects (6.4× slower). The first Zig build after an empty global cache costs more again (6.2 s in Debug on one kernel); t27b, GCC and rustc have no such step.

6 Generated code

t27b (trap) / pipeline	n	executed instructions	emulated run time	code size
Zig Debug	20	0.54	0.69	0.66
Zig ReleaseSafe	20	3.17	3.41	1.89
Zig ReleaseFast	20	4.47	4.14	2.03
GCC -O0	20	0.91	1.11	1.34
GCC -O2	20	3.43	4.05	1.82
Clang -O0	20	0.41	0.62	0.65
Clang -O2	9	3.50	3.72	1.69

Table 5: Geometric-mean ratios over tier 1. Below 1, t27b is better. Clang -O2 evaluated the test at compile time on 11 of the 20 specifications (it executed under 1% of GCC -O0's instructions); those are left out of its row.

t27b's code is at the level of an unoptimising compiler (Table 5). It executes about as many instructions as GCC -O0 and beats only unoptimised LLVM output (Zig Debug, Clang -O0). On tier 1, every optimising pipeline is 3 to 5 times better by geometric mean (individual specifications vary more): against the like-for-like checked build, Zig ReleaseSafe, t27b executes 3.2× the instructions and takes 3.4× the emulated time; against GCC -O2, 3.4× and 4.1×; against Clang -O2 where it did not fold the test, 3.5× and 3.7×. Its code is larger than every optimising build. The gap is larger outside tier 1: on the four crypto specifications measured against Zig only, t27b executes 7.0× the instructions of Zig ReleaseSafe and 10.1× those of Zig ReleaseFast.

Overflow checks add about 12% to the instructions of t27b's unchecked build (trap/wrap 1.12×) and 24% to its emulated time. One case is pathological: before every test the JIT copies the whole module-variable image so each test starts from fresh state, and a specification with large module arrays (`compiler/core/t27core`, 95 tests) runs 8.3× slower than Zig Debug although t27b executes fewer instructions. Instruction counts are the better measure here: emulation cost varies by instruction mix, and on one kernel Zig ReleaseFast executes 43% fewer instructions than t27b yet takes 25% longer under qemu.

7 Compiler resources

t27b is one executable: 3.08 MB for x86_64 and 2.79 MB for aarch64, unstripped, with Rust's standard library linked statically and no assembler or linker. For comparison, the t27c executable is 11.9 MB, Zig 0.16.0 (which also provides the Clang used here) is 363 MB installed, GCC 12 for aarch64 is about 145 MB, and rustc 1.99 is 790 MB. The comparison is not like for like: those toolchains produce linked executables, which t27b did not at the measured revision.

Compiler step	n	median peak RSS (MiB)	max (MiB)
t27b test-compile	24	5.26	48.4
t27b build	22	5.12	14.1
Zig Debug / ReleaseFast	24	354 / 500	412 / 670
GCC -O0 / -O2, object	20	27.1 / 31.6	59.4 / 173
Clang -O0 / -O2, object	20	68.0 / 75.5	118 / 243
rustc -O0 / -O3, object	18	112 / 120	138 / 134

Table 6: Peak resident memory of each compiler's whole process tree, from `wait4`. n is the number of code-quality specifications (tier 1 plus tier 2, up to 24) that step compiled; failed compiles are left out, so the rows are not over the same set. Compile steps only: running the tests, aarch64 t27b under qemu peaks at a median of 26.1 MiB (max 119 MiB, qemu's own memory included).

8 Determinism

Each tier-1 specification was built by every pipeline three times, twice in one directory and once from a different absolute path, where the pipeline could build it: `t27b build` and `t27b asm` built 18 of the 20 (they refuse the two with module-level variables) and rustc 15. All outputs that were built were bit-identical within one directory. t27b's objects and assembly listings, t27c's generators, GCC (without `-g`) and rustc were also identical across directories; Zig and `zig cc` record the build directory in DWARF and were not.

9 Threats to validity

Self-consistency, not independence. The reference t27b agrees with is produced by the same t27c front end that t27b mounts, and the JIT/interpreter check reads one IR. A diverse-double-compiling receipt over three routes (lab, commit `0e8564505`) ends in backend agreement, not independence, for the same reason [8]. A source-level random-program fuzzer against the reference reaches beyond the corpus and, in the lab run the report quotes (commit `8e2e44b7e`, 1,000 programs, 1,975 tests), found 7 disagreements; the corpus result of Table 3 therefore does not mean t27b agrees with the reference on every program. No check here compares t27b with an independently written t27 front end.

Emulation and a shared host. All run times are qemu-aarch64 on x86_64; they rank pipelines on this host and are not arm64 speed. The host was shared with other jobs (load 27–103 on 48 threads); medians are reported, but millisecond-scale compile samples are noisy (over 5 runs, the median max/min spread was 34% for t27b and 36% for GCC -O0).

Different contracts. t27b re-initialises module variables before each test and runs invariants at run time; the Zig and C runners do neither. Undefined behaviour in gen-c output changes C verdicts with the optimisation level, and an optimiser may exploit it. Clang is Zig's bundled Clang with musl, not a distribution Clang with glibc.

Which Zig backend. Zig 0.15 made its self-hosted x86-64 backend the default for Debug builds, and its release notes describe Debug compilation as five times faster with it [17]. The aarch64 target measured here goes through LLVM (Table 1), so the 640× figure is against Zig Debug through LLVM and does not carry over to Zig's self-hosted backends.

Selection and repetition. Tier 1 excludes everything gen-c cannot compile. Coverage numbers come from one corpus run per pipeline. The 4.8 ms figure is a geometric mean over 18 specifications, not over the corpus.

Reproducibility. The harness (about 1,650 lines of lab scratch) is not committed; the report lists every command it ran and the tool hashes, and the JSON holds every sample with its host load. An earlier single-specification demonstration on an arm64 workstation is not used here, because its specification is not on the main branch and no raw runs were retained.

10 State after the snapshot

The results above refer to commit `9a0f4c394`. The following changes are on the main branch, are reported in the repository's issues, and were not re-measured for this paper. `t27b build -elf` writes ELF64 relocatable objects for aarch64-linux, which supersedes the Mach-O-only limit of Section 2; `t27b run` executes a named entry point; `t27b verilog` emits RTL; scalar exports follow the AAPCS64 C calling convention. The corpus has also grown. Later lab runs at other commits are not used here: the revisions are not interchangeable, and no post-snapshot figure enters this paper.

11 Claims and evidence

Claim	Report section	Status
Coverage 1,296 / 1,311; 0 of 8,344 tests disagree	A	measured; self-consistency
Test-compile 4.8 ms; 8.8× GCC -O0; 640×, batched 8.6×, Zig Debug	B	measured; shared host
0.91× GCC -O0 and 3.4× GCC -O2 instructions; 4.1× / 3.7× emulated time vs GCC / Clang -O2	C	measured; emulated time
5.3 MiB median peak memory; 3.08 MB executable	D	measured
Bit-identical, path-independent t27b outputs	E	measured
Native run time comparable to Clang -O2	–	not claimed; contradicted by C
External IR input; C, Rust, Zig, Go or Python front ends	–	not implemented

Table 7: Claims and their evidence in `docs/reports/t27b-bench-2026-10.md`.

12 Related work

LLVM established the pattern of shared front ends, a common IR and retargetable optimising backends [3]; t27b is the opposite trade, a single-target baseline backend with no optimiser. Cranelift, offered as an alternative code generator for rustc, makes a similar compile-time versus code-quality trade within an existing compiler [4, 5].

Baseline compilers. Fast non-optimising compilers are an established design point. TinyCC reports compiling, assembling and linking C several times faster than GCC [9]; QBE aims at 70% of the performance of industrial optimising compilers in 10% of the code [10]. In WebAssembly engines, V8's Liftoff makes a single pass over a function's bytes [11], and Wasmtime's Winch

names compilation performance as its primary goal, with a single pass and no intermediate representation [12]. Titzer compares six baseline compilers and the tradeoff between compilation speed and code quality [13]. Copy-and-patch compilation reports generating code 4.9–6.5× faster than Liftoff [14]; TPDE, a back-end framework for LLVM IR, reports compiling 8–24× faster than LLVM -O0 with on-par run time on SPECint 2017 [15]; Umbra's Flying Start back end targets low query latency [16]. t27b differs from these in what it compiles and checks: it lowers one specification language's own IR and runs that language's embedded tests in process. None of these systems was measured here, and the ratios in this paper are against the same specifications' C and Zig outputs only.

Testing compilers. Csmith and EMI find compiler bugs by random programs and equivalence modulo inputs [6, 7]; this paper runs neither, and its differential method compares two backends behind one front end. The corpus also contains specifications of number formats described elsewhere [1, 2]; two of them (GF16 and OCP MX) are among the measured specifications.

13 Future work

The measured gaps name the next steps: middle-end optimisation passes to close the 3–5× tier-1 instruction gap (10× on the crypto specifications); a multi-file build mode to keep the latency lead when Zig amortises; per-test state isolation without copying the whole module image; a differential fuzzing gate with zero disagreements; and native arm64 timings in place of emulated ones. Lowering restricted subsets of other languages through a versioned IR contract to t27b is an architectural goal; no such front end exists.

14 Conclusion

Over the full 1,819-specification corpus at one revision, t27b passes 98.9% of what its reference passes and agrees with it on all 8,344 tests both ran. It test-compiles a specification in about 5 ms with about 5 MiB of memory from a 3 MB executable without LLVM, though without linking; its code executes 3–5× the instructions of optimising compilers on tier 1 by geometric mean, and 10× on the crypto specifications. That is the profile of a fast baseline compiler; its agreement with the reference is self-consistency behind a shared front end, not independent verification.

References

[1] D. Vasilev, *GoldenFloat: A Phi-Derived Static-Split Floating-Point Family from GF4 to GF1024 with a Lucas-Exact Integer Identity*, 2026. arXiv:2606.05017.

[2] D. Vasilev, *Golden Ruler: A Numeric Format Catalog with Bit-Exact Conformance Vectors for FP8, BF16, MXFP4, and Microscaling Formats*, 2026. arXiv:2606.09686.

[3] C. Lattner and V. Adve, *LLVM: A Compilation Framework for Lifelong Program Analysis & Transformation*, CGO 2004. DOI 10.1109/CGO.2004.1281665.

[4] Rust Compiler Development Guide, *Backend-agnostic code generation.* `https://rustc-dev-guide.rust-lang.org/backend/backend-agnostic.html`.

[5] *Using rustc_codegen_cranelift*, Inside Rust blog, 2020-11-15. `https://blog.rust-lang.org/inside-rust/2020/11/15/Using-rustc_codegen_cranelift/`.

[6] X. Yang, Y. Chen, E. Eide, and J. Regehr, *Finding and Understanding Bugs in C Compilers*, PLDI 2011. DOI 10.1145/1993498.1993532.

[7] V. Le, M. Afshari, and Z. Su, *Compiler Validation via Equivalence Modulo Inputs*, PLDI 2014. DOI 10.1145/2594291.2594334.

[8] D. A. Wheeler, *Fully Countering Trusting Trust through Diverse Double-Compiling*, PhD dissertation, George Mason University, 2009. arXiv:1004.5534.

[9] F. Bellard, *Tiny C Compiler*. `https://bellard.org/tcc/`.

[10] *QBE: compiler backend*. `https://c9x.me/compile/`.

[11] C. Backes, *Liftoff: a new baseline compiler for WebAssembly in V8*, V8 blog, 2018-08-20. `https://v8.dev/blog/liftoff`.

[12] Bytecode Alliance, *Winch: WebAssembly Intentionally Non-optimizing Compiler and Host*, Wasmtime repository. `https://github.com/bytecodealliance/wasmtime/tree/main/winch`.

[13] B. L. Titzer, *Whose baseline compiler is it anyway?*, 2023. arXiv:2305.13241.

[14] H. Xu and F. Kjolstad, *Copy-and-Patch Compilation: A fast compilation algorithm for high-level languages and bytecode*, 2021. DOI 10.1145/3485513; arXiv:2011.13127.

[15] T. Schwarz, T. Kamm, and A. Engelke, *TPDE: A Fast Adaptable Compiler Back-End Framework*, 2025. arXiv:2505.22610.

[16] T. Kersten, V. Leis, et al., *Tidy Tuples and Flying Start: fast compilation and fast execution of relational queries in Umbra*, The VLDB Journal 30:883–905, 2021. DOI 10.1007/s00778-020-00643-4.

[17] *Zig 0.15.1 Release Notes*, section "x86 Backend". `https://ziglang.org/download/0.15.1/release-notes.html`.