Embedded Operating System for *Raspberry* π with *Yocto*

Kaloyan Krastev*

Friday 17th November, 2023 †

*Triple Helix Consulting

†revision 2893

table of contents

1 introduction **3**

2 metadata **5**

2.1 application 5

2.2 layers 6

3 build **8**

3.1 configuration 8

3.2 image 8

4 connection **9**

5 outlook **10**

1 introduction

This article[7] reports the progress in the configuration and build of a Linux-based operating system for *Raspberry* π[9] with *Yocto*[2]. Please refer [8] for technical details.

The *central processing unit* (CPU) is *ARM Cortex-A*72. It is a high performance CPU with low power consumption. With dimensions of 9 x 7 x 2 cm, the machine has 4 GB of RAM. As there are no fixed storage devices, *images* are installed on *SD* cards.

Embedded devices[11] are compact systems with specific purpose. Embedded operating systems provide a limited number of services defined by this purpose and device *hardware* (HW). There are important reasons why Linux is a preferred *operating system* (OS) kernel for embedded devices. Since such devices usually have limited HW resources, they rely on optimized *software* (SW) implementations. Smaller and faster than their original, such programs have limited, but usually sufficient functionality. For example, *BusyBox* combines tiny versions of many common *unix* utilities into a single executable[1]. Another example is *Dropbear SSH* - an optimized *secure shell* (SSH) server implementation[6]. *Dropbear* is significantly smaller in size compared to *OpenSSH*. Unlike *GNU is not UNIX* (GNU)/Linux desktop distributions[10], embedded Linux has neither a *graphical user interface* (GUI) for system configuration nor a centralized service manager like *systemd*.

Yocto Project[2] provides a popular framework for configuration and build of Linux-based operating systems. First of all, *Yocto* supports HW via a SW layer called *board support package* (BSP). In addition, there are custom distribution configuration and a tool called *Bitbake* to create SW packages and to build OS *images*. These *images* are configurable and operational. There is a bootloader, a

kernel release and the user-space part of the OS, including custom user applications. This approach is indispensable when it comes to embedded devices. *Yocto* images are collections of SW packages. Packages are created via SW recipes. Although a recipe may have all sorts of instructions, a typical one contains the source code location and the SW build configuration. These are architecture independent. However, binaries are cross-compiled in case of different target machine processor architecture. This applies to the entire OS.

2 metadata

As they differ, it could be extremely useful to isolate the SW development from the OS build. This way developers may work and test a SW application on their own. As far as I could fetch the source code, in example, from a *git* repository, in theory, it should not be too complicated to build an OS able to run this application. What is more, I can build it for a computing device of my choice. I just need the corresponding BSP and a *bitbake* recipe to fetch the source code, configure, cross-compile, install binaries and create a package.

A complete list of *github* SW repositories used in this project includes *Yocto*, the BSP, a SW layer with custom recipes, the configuration and the source code of the application and the dependencies. Note that for a relatively simple application I must fetch six SW repositories. Follow links for details.

- *Yocto* reference distribution yoctoproject.org/poky.git
- BSP layer for *Raspberry* π boards agherzan/meta-raspberrypi.git
- *Yocto* configuration TripleHelixConsulting/rpiconf.git
- SW layer kaloyanski/meta-thc.git
- immediate mode GUI kaloyanski/imgui_aarch64_glfw_openGL2_exper
- graphics library framework glfw/glfw.git

2.1 application

Dear ImGui[3] is a bloat-free GUI library for C++. It outputs optimized vertex buffers that you can render anytime in your 3D-pipeline-enabled application. It is fast, portable, renderer agnostic,

and self-contained (no external dependencies). *Dear ImGui* is designed to enable fast iterations and to empower programmers to create content creation tools and visualization/debug tools (as opposed to UI for the average end-user). It favors simplicity and productivity toward this goal and lacks certain features commonly found in more high-level libraries. *Dear ImGui* is particularly suited to integration in game engines (for tooling), real-time 3D applications, full-screen applications, embedded applications, or any applications on console platforms where operating system features are non-standard.

Dear ImGui depends on *GLFW*[4], an open-source, multi-platform library for *OpenGL*, *OpenGL ES* and *Vulkan* development on the desktop. It provides a simple API for creating windows, contexts and surfaces, receiving input and events. *GLFW* is written in *C* and supports *Windows*, *macOS*, *X*11 and *Wayland*.

Dear ImGui is licensed under the *MIT* License. *GLFW* is licensed under the *zlib/libpng* license.

2.2 layers

Here is a list of *Yocto metadata* layers. The project reference distribution is *poky*.

- *meta*
  user-space

- *meta* − *poky*
  Yocto reference distribution

- *meta* − *raspberrypi*
  This[5] is the general HW specific BSP overlay for the *RaspberryPi* device. The core BSP part of *meta* − *raspberrypi* works with different *OpenEmbedded*/ *Yocto* distributions and layer stacks.

In short, the recipes to build the kernel and kernel modules are in this layer. For details see the package *linux-raspberrypi*. In addition, here is the HW specific firmware. The build configuration corresponds the specific HW, in this case *Raspberry* π.

- $meta - thc$
  I have introduced a new *Yocto* SW layer to control the build of *Dear ImGui* and $GLFW$. As long as the source codes have a standard build configuration, the *bitbake* recipes are straightforward. Both instructions inherit *cmake bitbake* class.

3 build

3.1 configuration

Yocto provides a list of image types. I have chosen $core - image - x11$[2] - a very basic X11 image with a terminal. In the main build configuration, apart from *Dear ImGui* and *GLFW*, I have added the following packages;

- $os - release$
  OS identification
- *Dropbear*
  Compact SSH server[6]
- *thcp*
  OS post-configuration scripts

3.2 image

The used space on the `/root` partition of the OS is 220 MB. The free space is configurable. The kernel *ARM*, 64 bit boot executable *image* of 23 MB is a *Raspberry* π configuration of Linux 5.15. This kernel release has a $long - term\ support$ (LTS). The total size of kernel modules is 21 MB.

Yocto provides multiple SW package and OS *image* formats. Further, different ways exist to install *images*. Finally, formats do not matter, as long as the result is a complete OS on an *SD* card. I recommend the classic command-line tool *dd* to copy data. It works fine with different *image* formats like $rpi - sdimg$, *hddimg* and *wic*.

4 connection

Connected embedded systems can communicate to one another and to cloud-based *platform-as-a-service* (PaaS) solutions. In addition, a remote control may be required. An SSH server is a standard solution for both problems.

Wireless connection is established via classic command-line tools like *ip*, *iw*, *udhcpc*, and *wpa_supplicant*. Custom shell scripts are installed in `/usr/bin`, as well as a running GUI example to demonstrate the usage of the *Dear ImGui* library. Once an *internet protocol* (IP) address is assigned, the SSH server by *Dropbear* allows for a secured remote login, remote control and file transfer.

5 outlook

This reports the progress in the development of a custom Linux-based OS for *Raspberry* π[9]. The kernel version of this embedded OS is Linux release 5.15. An example GUI application using the *Dear ImGui* library is built as a part of the OS. In addition, an SSH server provides remote connection, data transfer and device control. As the OS is now functional, performance and real-time tests are ongoing.

acronyms

BSP	*board support package*
CPU	*central processing unit*
GNU	*GNU is not UNIX*
GUI	*graphical user interface*
HW	*hardware*
IP	*internet protocol*
LTS	*long – term support*
OS	*operating system*
PaaS	*platform-as-a-service*
SSH	*secure shell*
SW	*software*

bibliography

[1] Erik Andersen. *BusyBox*. 2023.
URL: https://busybox.net (visited on 2023).

[2] Yocto Project community. *Yocto Project*. 2023.
URL: https://www.yoctoproject.org (visited on 2023).

[3] Omar Cornut. *Dear ImGui*. 2023.
URL: https://github.com/ocornut/imgui (visited on 2023).

[4] Marcus Geelnard and Camilla Löwy. *OpenGL*. 2023.
URL: https://www.glfw.org (visited on 2023).

[5] Andrei Gherzan. *meta-raspberrypi*. 2023.
URL: https://github.com/agherzan/meta-raspberrypi
(visited on 2023).

[6] Matt Johnston. *Dropbear SSH*. 2023.
URL: https://matt.ucc.asn.au/dropbear/dropbear.html
(visited on 2023).

[7] Kaloyan Krastev.
Embedded Operating System for Raspberry π with Yocto.
2023. URL:
https://kaloyanski.github.io/meta-thc/thcport.html
(visited on 2023).

[8] Kaloyan Krastev. *Building Embedded Operating System with IMGUI Demo for Raspberry π with* Yocto. 2023. URL:
https://kaloyanski.github.io/meta-thc/thchowto.html
(visited on 2023).

[9] Raspberry π Ltd. *Raspberi π*. 2023.
URL: https://www.raspberrypi.com (visited on 2023).

[10] Atanas Georgiev Rusev. *Manjaro Linux User Guide*. Packt Publishing Limited, 2023.

[11] Frank Vasquez and Chris Simmonds. *Mastering Embedded Linux Programming*. Packt Publishing Limited, 2021.

this document in *html* format

powered by LaTeX