

Faculty of Computer and Information Sciences, Ain Shams University: Too Wrong to Pass Too Correct to Fail

Pillow, Isaac, Mostafa, Islam

Contents

2021

1 Combinatorics

1.1	Burnside Lemma	...
1.2	Catlan Numbers	...

2 Algebra

2.1	Primitive Roots	...
2.2	Discrete Logarithm	...
2.3	Iteration over submasks	...
2.4	Totient function	...
2.5	CRT and EEGCD	...
2.6	FFT	...
2.7	Fibonacci	...
2.8	Gauss Determinant	...
2.9	GAUSS SLAE	...
2.10	Matrix Inverse	...
2.11	NTT	...
2.12	NTT of KACTL	...

3 Data Structures

3.1	2D BIT	...
3.2	2D Sparse table	...
3.3	hillbert Order	...
3.4	Merge Sort Bit with updates	...
3.5	Mo's	...
3.6	Mo With Updates	...
3.7	Ordered Set	...
3.8	Persistent Seg Tree	...
3.9	Sqrt Decomposition	...
3.10	Treap	...
3.11	Wavelet Tree	...

4 Matching

5 Trees

6 Strings

7 Geometry

8 Number Theory

9 DP

10 Misc.

1 Combinatorics

1.1 Burnside Lemma

```

1 // |Classes|=sum (k ^C(pi)) / |G|
2 // C(pi) the number of cycles in the permutation pi
3 // |G| the number of permutations

```

1.2 Catlan Numbers

```

1 const int MOD = ....
2 const int MAX = ....
3 int catalan[MAX];
4 void init() {
5     catalan[0] = catalan[1] = 1;
6     for (int i=2; i<=n; i++) {
7         catalan[i] = 0;
8         for (int j=0; j < i; j++) {
9             catalan[i] += (catalan[j] * catalan[i-j-1]) % MOD;
10            if (catalan[i] >= MOD) {
11                catalan[i] -= MOD;
12            }
13        }
14    }
15 }
16 // 1- Number of correct bracket sequence consisting of n opening and n closing brackets.
17 // 2- The number of rooted full binary trees with n+1 leaves (vertices are not numbered).
18 // 3- A rooted binary tree is full if every vertex has either two children or no children.
19 // 4- The number of ways to completely parenthesize n+1 factors.
20 // 5- The number of triangulations of a convex polygon with n+2 sides (i.e. the number of partitions of polygon into disjoint triangles by using the diagonals).
21 // 6- The number of ways to connect the 2n points on a circle to form n disjoint chords.
22 // 7- The number of non-isomorphic full binary trees with n internal nodes (i.e. nodes having at least one son).
23 // 8- The number of monotonic lattice paths from point (0,0) to point (n,n) in a square lattice of size nxn, which do not pass above the main diagonal (i.e. connecting (0,0) to (n,n)).
24 // 9- Number of permutations of length n that can be stack sorted (i.e. it can be shown that the rearrangement is stack sorted if and only if there is no such index i<j<k, such that ak<ai<aj).
25 // 10- The number of non-crossing partitions of a set of n elements.
26 // 11- The number of ways to cover the ladder 1..n using n rectangles (The ladder consists of n columns, where ith column has a height i).

```

2 Algebra

2.1 Primitive Roots

```

1 int powmod (int a, int b, int p) {
2     int res = 1;
3     while (b)
4         if (b & 1)
5             res = int (res * 1ll * a % p), --b;
6         else
7             a = int (a * 1ll * a % p), b >>= 1;
8     return res;
9 }
10 int generator (int p) {
11     vector<int> fact;
12

```

```

13 int phi = p - 1, n = phi;
14 for (int i = 2; i * i <= n; ++i)
15     if (n % i == 0) {
16         fact.push_back (i);
17         while (n % i == 0)
18             n /= i;
19     }
20 if (n > 1)
21     fact.push_back (n);
22
23 for (int res = 2; res <= p; ++res) {
24     bool ok = true;
25     for (size_t i = 0; i < fact.size() && ok; ++i)
26         ok &= powmod (res, phi / fact[i], p) != 1;
27     if (ok) return res;
28 }
29 return -1;
30 }

```

2.2 Discrete Logarithm

```

1 // Returns minimum x for which a ^ x % m = b % m, a and m are coprime.
2 int solve(int a, int b, int m) {
3     a %= m, b %= m;
4     int n = sqrt(m) + 1;
5
6     int an = 1;
7     for (int i = 0; i < n; ++i)
8         an = (an * 111 * a) % m;
9
10    unordered_map<int, int> vals;
11    for (int q = 0, cur = b; q <= n; ++q) {
12        vals[cur] = q;
13        cur = (cur * 111 * a) % m;
14    }
15
16    for (int p = 1, cur = 1; p <= n; ++p) {
17        cur = (cur * 111 * an) % m;
18        if (vals.count(cur)) {
19            int ans = n * p - vals[cur];
20            return ans;
21        }
22    }
23    return -1;
24 }
25
26 //When a and m are not coprime
27 // Returns minimum x for which a ^ x % m = b % m.
28 int solve(int a, int b, int m) {
29     a %= m, b %= m;
30     int k = 1, add = 0, g;
31     while ((g = gcd(a, m)) > 1) {
32         if (b == k)
33             return add;
34         if (b % g)
35             return -1;
36         b /= g, m /= g, ++add;
37         k = (k * 111 * a / g) % m;
38     }
39
40     int n = sqrt(m) + 1;
41     int an = 1;
42     for (int i = 0; i < n; ++i)
43         an = (an * 111 * a) % m;
44
45     unordered_map<int, int> vals;
46     for (int q = 0, cur = b; q <= n; ++q) {
47         vals[cur] = q;
48         cur = (cur * 111 * a) % m;
49     }
50
51     for (int p = 1, cur = k; p <= n; ++p) {

```

```

52         cur = (cur * 111 * an) % m;
53         if (vals.count(cur)) {
54             int ans = n * p - vals[cur] + add;
55             return ans;
56         }
57     }
58     return -1;
59 }

```

2.3 Iteration over submasks

```

1 int s = m;
2 while (s > 0) {
3     ... you can use s ...
4     s = (s-1) & m;
5 }

```

2.4 Totient function

```

1 void phi_1_to_n(int n) {
2     vector<int> phi(n + 1);
3     phi[0] = 0;
4     phi[1] = 1;
5     for (int i = 2; i <= n; i++)
6         phi[i] = i;
7
8     for (int i = 2; i <= n; i++) {
9         if (phi[i] == i) {
10             for (int j = i; j <= n; j += i)
11                 phi[j] -= phi[j] / i;
12         }
13     }
14 }

```

2.5 CRT and EEGCD

```

1 ll extended(ll a, ll b, ll &x, ll &y) {
2
3     if(b == 0) {
4         x = 1;
5         y = 0;
6         return a;
7     }
8     ll x0, y0;
9     ll g = extended(b, a % b, x0, y0);
10    x = y0;
11    y = x0 - a / b * y0;
12
13    return g;
14 }
15 ll de(ll a, ll b, ll c, ll &x, ll &y) {
16
17     ll g = extended(abs(a), abs(b), x, y);
18     if(c % g) return -1;
19
20     x *= c / g;
21     y *= c / g;
22
23     if(a < 0) x = -x;
24     if(b < 0) y = -y;
25     return g;
26 }
27 pair<ll, ll> CRT(vector<ll> r, vector<ll> m) {
28
29     ll r1 = r[0], m1 = m[0];
30
31     for(int i = 1; i < r.size(); i++) {
32

```

```

33     ll r2 = r[i], m2 = m[i];
34     ll x0, y0;
35     ll g = de(m1, -m2, r2 - r1, x0, y0);
36
37     if(g == -1) return {-1, -1} ;
38
39     ll nr = x0 * m1 + r1;
40     ll nm = m1 / g * m2;
41
42     r1 = (nr % nm + nm) % nm;
43     m1 = nm;
44 }
45 return {r1, m1};
46 }

```

2.6 FFT

```

1  #include<iostream>
2  #include <bits/stdc++.h>
3  #define ll long long
4  #define ld long double
5  #define rep(i, a, b) for(int i = a; i < (b); ++i)
6  #define all(x) begin(x), end(x)
7  #define sz(x) (int)(x).size()
8  #define IO ios_base::sync_with_stdio(0); cin.tie(0); cout.tie(0);
9  using namespace std;
10 typedef complex<double> C;
11 typedef vector<double> vd;
12 typedef vector<int> vi;
13 typedef pair<int, int> pii;
14 void fft(vector<C>& a) {
15     int n = sz(a), L = 31 - __builtin_clz(n);
16     static vector<complex<long double>> R(2, 1);
17     static vector<C> rt(2, 1); // (^ 10% fas te r i f double)
18     for (static int k = 2; k < n; k *= 2) {
19         R.resize(n);
20         rt.resize(n);
21         auto x = polar(1.0L, acos(-1.0L) / k);
22         rep(i, k, 2 * k) rt[i] = R[i] = i & 1 ? R[i / 2] * x : R[i / 2];
23     }
24     vi rev(n);
25     rep(i, 0, n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
26     rep(i, 0, n) if (i < rev[i]) swap(a[i], a[rev[i]]);
27     for (int k = 1; k < n; k *= 2)
28         for (int i = 0; i < n; i += 2 * k) rep(j, 0, k) {
29             C z = rt[j + k] * a[i + j + k]; //
30             a[i + j + k] = a[i + j] - z;
31             a[i + j] += z;
32         }
33 }
34 vd conv(const vd& a, const vd& b) {
35     if (a.empty() || b.empty()) return {};
36     vd res(sz(a) + sz(b) - 1);
37     int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
38     vector<C> in(n), out(n);
39     copy(all(a), begin(in));
40     rep(i, 0, sz(b)) in[i].imag(b[i]);
41     fft(in);
42     for (C& x : in) x *= x;
43     rep(i, 0, n) out[i] = in[-i & (n - 1)] - conj(in[i]);
44     fft(out);
45     rep(i, 0, sz(res)) res[i] = imag(out[i]) / (4 * n);
46     return res;
47 }
48
49 int main() {
50     IO
51     //Applications
52     //1-All possible sums
53
54     //2-All possible scalar products
55     // We are given two arrays a[] and b[] of length n.

```

```

56     //We have to compute the products of a with every cyclic shift of b.
57     //We generate two new arrays of size 2n: We reverse a and append n zeros to
58     //it.
59     //And we just append b to itself. When we multiply these two arrays as
60     //polynomials,
61     //and look at the coefficients c[n-1], c[n], ..., c[2n-2] of the product c,
62     //we get:
63     //c[k]=sum i+j=k a[i]b[j]
64
65     //3-Two stripes
66     //We are given two Boolean stripes (cyclic arrays of values 0 and 1) a and b
67     .
68     //We want to find all ways to attach the first stripe to the second one,
69     //such that at no position we have a 1 of the first stripe next to a 1 of
70     //the second stripe.
71 }

```

2.7 Fibonacci

```

1
2
3 // F(n-1) * F(n+1) - F(n)^2 = (-1)^n
4
5 // F(n+k) = F(k) * F(n+1) + F(k-1) * F(n)
6
7 // F(2*n) = F(n) * (F(n+1) + F(n-1))
8
9 //GCD ( F(m) , F(n) ) = F(GCD(n,m))

```

2.8 Gauss Determinant

```

1 const double EPS = 1E-9;
2 int n;
3 vector < vector<double> > a (n, vector<double> (n));
4
5 double det = 1;
6 for (int i=0; i<n; ++i) {
7     int k = i;
8     for (int j=i+1; j<n; ++j)
9         if (abs (a[j][i]) > abs (a[k][i]))
10             k = j;
11     if (abs (a[k][i]) < EPS) {
12         det = 0;
13         break;
14     }
15     swap (a[i], a[k]);
16     if (i != k)
17         det = -det;
18     det *= a[i][i];
19     for (int j=i+1; j<n; ++j)
20         a[i][j] /= a[i][i];
21     for (int j=0; j<n; ++j)
22         if (j != i && abs (a[j][i]) > EPS)
23             for (int k=i+1; k<n; ++k)
24                 a[j][k] -= a[i][k] * a[j][i];
25 }
26
27 cout << det;

```

2.9 GAUSS SLAE

```

1 const double EPS = 1e-9;
2 const int INF = 2; // it doesn't actually have to be infinity or a big number
3
4 int gauss (vector < vector<double> > a, vector<double> & ans) {
5     int n = (int) a.size();
6     int m = (int) a[0].size() - 1;
7

```

```

8   vector<int> where (m, -1);
9   for (int col = 0, row = 0; col < m && row < n; ++col) {
10       int sel = row;
11       for (int i = row; i < n; ++i)
12           if (abs (a[i][col]) > abs (a[sel][col]))
13               sel = i;
14       if (abs (a[sel][col]) < EPS)
15           continue;
16       for (int i = col; i <= m; ++i)
17           swap (a[sel][i], a[row][i]);
18       where[col] = row;

19
20       for (int i = 0; i < n; ++i)
21           if (i != row) {
22               double c = a[i][col] / a[row][col];
23               for (int j = col; j <= m; ++j)
24                   a[i][j] -= a[row][j] * c;
25           }
26       ++row;
27   }

28
29   ans.assign (m, 0);
30   for (int i = 0; i < m; ++i)
31       if (where[i] != -1)
32           ans[i] = a[where[i]][m] / a[where[i]][i];
33   for (int i = 0; i < n; ++i) {
34       double sum = 0;
35       for (int j = 0; j < m; ++j)
36           sum += ans[j] * a[i][j];
37       if (abs (sum - a[i][m]) > EPS)
38           return 0;
39   }
40
41   for (int i = 0; i < m; ++i)
42       if (where[i] == -1)
43           return INF;
44   return 1;
45 }

```

2.10 Matrix Inverse

```

1   // Sometimes, the questions are complicated - and the answers are simple. //
2   #pragma GCC optimize ("O3")
3   #pragma GCC optimize ("unroll-loops")
4   #include <bits/stdc++.h>
5   #define ll long long
6   #define ld long double
7   #define IO ios_base::sync_with_stdio(0); cin.tie(0); cout.tie(0);
8   using namespace std;
9   vector < vector<double> > gauss (vector < vector<double> > a) {
10
11       int n = (int) a.size();
12       vector<vector<double> > ans(n, vector<double>(n, 0));
13
14       for(int i = 0; i < n; i++)
15           ans[i][i] = 1;
16       for(int i = 0; i < n; i++) {
17           for(int j = i + 1; j < n; j++)
18               if(a[j][i] > a[i][i]) {
19                   swap(a[j], a[i]);
20                   swap(ans[j], ans[i]);
21               }
22           double val = a[i][i];
23           for(int j = 0; j < n; j++) {
24               a[i][j] /= val;
25               ans[i][j] /= val;
26           }
27           for(int j = 0; j < n; j++) {
28               if(j == i) continue;
29               val = a[j][i];
30               for(int k = 0; k < n; k++) {
31                   a[j][k] -= val * a[i][k];

```

```

32                   ans[j][k] -= val * ans[i][k];
33               }
34           }
35       }
36       return ans;
37   }
38   int main() {
39
40       IO
41       vector<vector<double> > v(3, vector<double>(3));
42       for(int i = 0; i < 3; i++)
43           for(int j = 0; j < 3; j++)
44               cin >> v[i][j];
45
46       for(auto i : gauss(v)) {
47           for(auto j : i)
48               cout << j << " ";
49           cout << "\n";
50       }
51   }

```

2.11 NTT

```

1   struct NTT {
2       int mod ;
3       int root ;
4       int root_1 ;
5       int root_pw ;
6
7       NTT(int _mod, int primitive_root, int NTT_Len) {
8
9           mod = _mod;
10          root_pw = NTT_Len;
11          root = fastpower(primitive_root, (mod - 1) / root_pw);
12          root_1 = fastpower(root, mod - 2);
13      }
14      void fft(vector<int> & a, bool invert) {
15          int n = a.size();
16
17          for (int i = 1, j = 0; i < n; i++) {
18              int bit = n >> 1;
19              for (; j & bit; bit >>= 1)
20                  j ^= bit;
21              j ^= bit;
22
23              if (i < j)
24                  swap(a[i], a[j]);
25          }
26
27          for (int len = 2; len <= n; len <= 1) {
28              int wlen = invert ? root_1 : root;
29              for (int i = len; i < root_pw; i <= 1)
30                  wlen = (int)(1LL * wlen * wlen % mod);
31
32              for (int i = 0; i < n; i += len) {
33                  int w = 1;
34                  for (int j = 0; j < len / 2; j++) {
35                      int u = a[i + j], v = (int)(1LL * a[i + j + len / 2] * w %
36                          mod);
37                      a[i + j] = u + v < mod ? u + v : u + v - mod;
38                      a[i + j + len / 2] = u - v >= 0 ? u - v : u - v + mod;
39                      w = (int)(1LL * w * wlen % mod);
40                  }
41              }
42          }
43
44          if (invert) {
45              int n_1 = fastpower(n, mod - 2);
46              for (int & x : a)
47                  x = (int)(1LL * x * n_1 % mod);
48          }

```

```

49     }
50     vector<int> multiply(vector<int> &a, vector<int> &b) {
51         vector<int> fa(a.begin(), a.end()), fb(b.begin(), b.end());
52         int n = 1;
53         while(n < a.size() + b.size())
54             n <<= 1;
55
56         fa.resize(n);
57         fb.resize(n);
58
59         fft(fa, 0);
60         fft(fb, 0);
61
62         for(int i = 0; i < n; i++)
63             fa[i] = 1LL * fa[i] * fb[i] % mod;
64         fft(fa, 1);
65         return fa;
66     }
67 };

```

2.12 NTT of KACTL

```

1  ///(Note faster than the other NTT)
2  ///If the mod changes don't forget to calculate the primitive root
3  using ll = long long;
4  const ll mod = (119 << 23) + 1, root = 3; // = 998244353
5  // For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 << 21
6  // and 483 << 21 (same root). The last two are > 10^9.
7  typedef vector<ll> vl;
8
9  ll modpow(ll b, ll e) {
10     ll ans = 1;
11     for (; e; b = b * b % mod, e /= 2)
12         if (e & 1) ans = ans * b % mod;
13     return ans;
14 }
15 void ntt(vl &a) {
16     int n = sz(a), L = 31 - __builtin_clz(n);
17     static vl rt(2, 1);
18     for (static int k = 2, s = 2; k < n; k *= 2, s++) {
19         rt.resize(n);
20         ll z[] = {1, modpow(root, mod >> s)};
21         f(i, k, 2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
22     }
23     vector<int> rev(n);
24     f(i, 0, n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
25     f(i, 0, n) if (i < rev[i]) swap(a[i], a[rev[i]]);
26     for (int k = 1; k < n; k *= 2)
27         for (int i = 0; i < n; i += 2 * k) f(j, 0, k) {
28             ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
29             a[i + j + k] = ai - z + (z > ai ? mod : 0);
30             ai += (ai + z >= mod ? z - mod : z);
31         }
32 }
33 vl conv(const vl &a, const vl &b) {
34     if (a.empty() || b.empty()) return {};
35     int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s), n = 1 << B;
36     int inv = modpow(n, mod - 2);
37     vl L(a), R(b), out(n);
38     L.resize(n), R.resize(n);
39     ntt(L), ntt(R);
40     f(i, 0, n) out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv % mod;
41     ntt(out);
42     return {out.begin(), out.begin() + s};
43 }
44 vector<int> v;
45 vector<ll> solve(int s, int e) {
46     if (s == e) {
47         vector<ll> res(2);
48         res[0] = 1;
49         res[1] = v[s];
50         return res;

```

```

51     }
52     int md = (s + e) >> 1;
53     return conv(solve(s, md), solve(md + 1, e));
54 }

```

3 Data Structures

3.1 2D BIT

```

1  void upd(int x, int y, int val) {
2      for(int i = x; i <= n; i += i & -i)
3          for(int j = y; j <= m; j += j & -j)
4              bit[i][j] += val;
5  }
6  int get(int x, int y) {
7      int ans = 0;
8      for(int i = x; i; i -= i & -i)
9          for(int j = y; j; j -= j & -j)
10             ans += bit[i][j];
11 }

```

3.2 2D Sparse table

```

1  /*
2   note this isn't the best cache-wise version
3   query O(1), Build O(NMlgNlgM)
4   be careful when using it and note the he build a dimension above another
5   i.e he builds a sparse table for each row
6   the build sparse table over each row's sparse table
7  */
8  const int N = 505, LG = 10;
9
10 int st[N][N][LG][LG];
11 int a[N][N], lg2[N];
12
13 int yo(int x1, int y1, int x2, int y2) {
14     x2++;
15     y2++;
16     int a = lg2[x2 - x1], b = lg2[y2 - y1];
17     return max(
18         max(st[x1][y1][a][b], st[x2 - (1 << a)][y1][a][b]),
19         max(st[x1][y2 - (1 << b)][a][b], st[x2 - (1 << a)][y2 - (1 << b)][a][b])
20     );
21 }
22
23 void build(int n, int m) { // 0 indexed
24     for (int i = 2; i < N; i++) lg2[i] = lg2[i >> 1] + 1;
25     for (int i = 0; i < n; i++) {
26         for (int j = 0; j < m; j++) {
27             st[i][j][0][0] = a[i][j];
28         }
29     }
30     for (int a = 0; a < LG; a++) {
31         for (int b = 0; b < LG; b++) {
32             if (a + b == 0) continue;
33             for (int i = 0; i + (1 << a) <= n; i++) {
34                 for (int j = 0; j + (1 << b) <= m; j++) {
35                     if (!a) {
36                         st[i][j][a][b] = max(st[i][j][a][b - 1], st[i][j + (1 << (b - 1))][a][b - 1]);
37                     } else {
38                         st[i][j][a][b] = max(st[i][j][a - 1][b], st[i + (1 << (a - 1))][j][a - 1][b]);
39                     }
40                 }
41             }

```

```

42     }
43 }
44 }

```

3.3 hillbert Order

```

1  ///Faster Sorting MO
2
3  const int infinity = (int)1e9 + 42;
4  const int64_t llInfinity = (int64_t)1e18 + 256;
5  const int module = (int)1e9 + 7;
6  const long double eps = 1e-8;
7
8  inline int64_t gilbertOrder(int x, int y, int pow, int rotate) {
9      if (pow == 0) {
10         return 0;
11     }
12     int hpow = 1 << (pow-1);
13     int seg = (x < hpow) ? (
14         (y < hpow) ? 0 : 3
15     ) : (
16         (y < hpow) ? 1 : 2
17     );
18     seg = (seg + rotate) & 3;
19     const int rotateDelta[4] = {3, 0, 0, 1};
20     int nx = x & (x ^ hpow), ny = y & (y ^ hpow);
21     int nrot = (rotate + rotateDelta[seg]) & 3;
22     int64_t subSquareSize = int64_t(1) << (2*pow - 2);
23     int64_t ans = seg * subSquareSize;
24     int64_t add = gilbertOrder(nx, ny, pow-1, nrot);
25     ans += (seg == 1 || seg == 2) ? add : (subSquareSize - add - 1);
26     return ans;
27 }
28
29 struct Query {
30     int l, r, idx;
31     int64_t ord;
32
33     inline void calcOrder() {
34         ord = gilbertOrder(l, r, 21, 0);
35     }
36 };
37
38 inline bool operator<(const Query &a, const Query &b) {
39     return a.ord < b.ord;
40 }
41
42 signed main() {
43     #ifndef USE_FILE_IO
44         ios_base::sync_with_stdio(false);
45     #endif
46
47     mt19937 rnd(42);
48
49     int n, m, k; cin >> n >> m; k = rnd() % 1048576;
50     vector<int> p(n+1);
51     for (int i = 0; i < n; i++) {
52         int val = rnd() % 1048576;
53         p[i+1] = p[i] ^ val;
54     }
55
56     vector<Query> qry(m);
57     for (int i = 0; i < m; i++) {
58         int l = rnd() % n + 1, r = rnd() % n + 1;
59         if (l > r) {
60             swap(l, r);
61         }
62         qry[i].l = l; qry[i].r = r;
63         qry[i].idx = i;
64         qry[i].calcOrder();
65     }
66 }

```

```

67     int64_t ans = 0;
68     vector<int64_t> res(m);
69     vector<int64_t> cnt((int)2e6, 0);
70     sort(qry.begin(), qry.end());
71     int l = 0, r = 1;
72     ans = (p[1] == k);
73     cnt[p[0]]++; cnt[p[1]]++;
74
75     for (Query q: qry) {
76         q.l--;
77         while (l > q.l) {
78             l--;
79             ans += cnt[p[l] ^ k];
80             cnt[p[l]]++;
81         }
82         while (r < q.r) {
83             r++;
84             ans += cnt[p[r] ^ k];
85             cnt[p[r]]++;
86         }
87         while (l < q.l) {
88             cnt[p[l]]--;
89             ans -= cnt[p[l] ^ k];
90             l++;
91         }
92         while (r > q.r) {
93             cnt[p[r]]--;
94             ans -= cnt[p[r] ^ k];
95             r--;
96         }
97         res[q.idx] = ans;
98     }
99
100     uint64_t rhsh = 0;
101     for (int i = 0; i < m; i++) {
102         rhsh += (uint64_t)1e9 + 7;
103         rhsh += (uint64_t)res[i];
104     }
105     cout << rhsh << "\n";
106
107     return 0;
108 }

```

3.4 Merge Sort Bit with updates

```

1  ///O(log ^ 2 N) updates and queries
2
3
4  #include <ext/pb_ds/tree_policy.hpp>
5  #include <ext/pb_ds/assoc_container.hpp>
6  #include <ext/rope>
7
8  using namespace std;
9  using namespace __gnu_pbds;
10 using namespace __gnu_cxx;
11
12 template<class T> using Tree = tree<T, null_type, less<T>, rb_tree_tag,
13     tree_order_statistics_node_update>;
14
15 Tree<int> t[N];
16
17 void add(int idx, int v) {
18     for (int x = ++idx; x < N; x += x & -x) {
19         t[x].insert(v);
20     }
21 }
22
23 void erase(int idx, int v) {
24     for (int x = ++idx; x < N; x += x & -x) {
25         t[x].erase(v);
26     }
27 }
28
29 int get(int idx, int limit) {

```

```

27     int ret = 0;
28     for(int x = ++idx; x; x -= x & -x)
29         ret += (t[x].order_of_key(limit+1));
30     return ret;
31 }

```

3.5 Mo's

```

1  #include <bits/stdc++.h>
2
3  int n, qq, arr[N], sz = 1000; // sz is the size of the bucket
4  int co[N], ans = 0, ansq[N];
5  int cul = 1, cur = 1;
6
7  void add(int x) {
8      co[arr[x]]++;
9      if (co[arr[x]] == 1)
10         ans++;
11     else if (co[arr[x]] == 2)
12         ans--;
13 }
14
15 void remove(int x) {
16     co[arr[x]]--;
17     if (co[arr[x]] == 1)
18         ans--;
19     else if (co[arr[x]] == 0)
20         ans++;
21 }
22
23 void solve(int l, int r, int ind) {
24     r++;
25     while (cul < l) remove(cul++);
26     while (cul > l) add(--cul);
27     while (cur < r) add(cur++);
28     while (cur > r) remove(--cur);
29     ansq[ind] = ans;
30 }
31
32
33 int main() {
34     FIO
35     cin >> qq;
36     // priority_queue<pair<pair<int, int>, pair<int, int>>, vector<pair<pair<int,
37     // int>, pair<int, int>>>, greater<pair<pair<int, int>, pair<int, int>>>> q
38     for (int i = 0; i < qq; i++) {
39         int l, r;
40         cin >> l >> r;
41         q.push({{l / sz, r}, {l, i}});
42     }
43     while (q.size()) {
44         int ind = q.top().second.second, l = q.top().second.first, r = q.top().first.second;
45         solve(l, r, ind);
46         q.pop();
47     }
48     for (int i = 0; i < qq; i++)
49         cout << ansq[i] << endl;
50
51     return 0;
52 }
53 }

```

3.6 Mo With Updates

```

1
2  //O(N^5/3) note that the block size is not a standard size

```

```

3
4  #pragma GCC optimize ("O3")
5  #pragma GCC target ("sse4")
6
7  #include <bits/stdc++.h>
8
9  using namespace std;
10
11  using ll = long long;
12
13  const int N = 1e5 + 5;
14  const int M = 2 * N;
15  const int blk = 2155;
16  const int mod = 1e9 + 7;
17  struct Query{
18     int l, r, t, idx;
19     Query(int a = 0, int b = 0, int c = 0, int d = 0) { l = a, r = b, t = c, idx = d; }
20     bool operator < (Query o) {
21         if (r / blk == o.r / blk && l / blk == o.l / blk) return t < o.t;
22         if (r / blk == o.r / blk) return l < o.l;
23         return r < o.r;
24     }
25 } Q[N];
26
27 int a[N], b[N];
28 int cnt1[M], cnt2[N];
29 int L = 0, R = -1, K = -1;
30 void add(int x) { //add item to range
31     // cout << x << '\n';
32     cnt2[cnt1[x]]--;
33     cnt1[x]++;
34     cnt2[cnt1[x]]++;
35 }
36 void del(int x) { //delete item from range
37     cnt2[cnt1[x]]--;
38     cnt1[x]--;
39     cnt2[cnt1[x]]++;
40 }
41 map<int, int> id;
42 int cnt;
43 int ans[N];
44 int p[N], nxt[N];
45 int prv[N];
46 void upd(int idx) { //update item value
47     if (p[idx] >= L && p[idx] <= R)
48         del(a[p[idx]]), add(nxt[idx]);
49     a[p[idx]] = nxt[idx];
50 }
51 void err(int idx) {
52     if (p[idx] >= L && p[idx] <= R)
53         del(a[p[idx]]), add(prv[idx]);
54     a[p[idx]] = prv[idx];
55 }
56 int main() {
57
58     int n, q, l, r, tp;
59
60     scanf("%d%d", &n, &q);
61
62     for (int i = 0; i < n; i++) {
63         scanf("%d", &a[i]);
64         if (id.count(a[i]) == 0)
65             id[a[i]] = cnt++;
66         a[i] = id[a[i]];
67         b[i] = a[i];
68     }
69     int qIdx = 0;
70     int ord = 0;
71     while (q--) {
72
73         scanf("%d", &tp);
74         if (tp == 1) {
75             // ADD Query
76             scanf("%d%d", &l, &r); --l, --r;
77             Q[qIdx] = Query(l, r, ord - 1, qIdx); qIdx++;

```

```

78     } else{
79         /// ADD Update
80         scanf("%d%d",p + ord, nxt + ord); --p[ord];
81         if(id.count(nxt[ord]) == 0)
82             id[nxt[ord]] = cnt++;
83         nxt[ord] = id[nxt[ord]];
84         prv[ord] = b[p[ord]];
85         b[p[ord]] = nxt[ord];
86         ++ord;
87     }
88 }
89 sort(Q,Q+qIdx);
90 for(int i = 0; i < qIdx; i++){
91     while(L < Q[i].l)del(a[L++]);
92     while(L > Q[i].l)add(a[--L]);
93     while(R < Q[i].r)add(a[++R]);
94     while(R > Q[i].r)del(a[R--]);
95     while(K < Q[i].t)upd(++K);
96     while(K > Q[i].t)err(K--);
97     ///Solve Query I
98 }
99
100 for(int i = 0; i < qIdx; i++)
101     printf("%d\n", ans[i]);
102
103
104 return 0;
105 }

```

3.7 Ordered Set

```

1  #include <ext/pb_ds/assoc_container.hpp>
2  #include <ext/pb_ds/tree_policy.hpp>
3  using namespace __gnu_pbds;
4
5  #define ordered_set tree<int, null_type,less<int>, rb_tree_tag,
6      tree_order_statistics_node_update>
7
8  // order_of_key(k): returns the number of elements in the set strictly less than
9  k
10 // find_by_order(k): returns an iterator to the k-th element (zero-based) in the
11 set

```

3.8 Persistent Seg Tree

```

1
2  int val[ N * 60 ], L[ N * 60 ], R[ N * 60 ], ptr, tree[N]; /// N * lgN
3  int upd(int root, int s, int e, int idx) {
4      int ret = ++ptr;
5      val[ret] = L[ret] = R[ret] = 0;
6      if (s == e) {
7          val[ret] = val[root] + 1;
8          return ret;
9      }
10     int md = (s + e) >> 1;
11     if (idx <= md) {
12         L[ret] = upd(L[root], s, md, idx), R[ret] = R[root];
13     } else {
14         R[ret] = upd(R[root], md + 1, e, idx), L[ret] = L[root];
15     }
16     val[ret] = max(val[L[ret]], val[R[ret]]);
17     return ret;
18 }
19 int qry(int node, int s, int e, int l, int r){
20     if(r < s || e < l || !node)return 0; ///Punishment Value
21     if(l <= s && e <= r){
22         return val[node];
23     }
24     int md = (s+e)>>1;

```

```

25     return max(qry(L[node], s, md, l, r), qry(R[node],md+1,e,l,r));
26 }
27 int merge(int x, int y, int s, int e) {
28     if(!x||!y)return x | y;
29     if(s == e) {
30         val[x] += val[y];
31         return x;
32     }
33     int md = (s + e) >> 1;
34     L[x] = merge(L[x], L[y], s, md);
35     R[x] = merge(R[x], R[y], md+1,e);
36     val[x] = val[L[x]] + val[R[x]];
37     return x;
38 }

```

3.9 Sqrt Decomposition

```

1  // Source: https://cp-algorithms.com/data_structures/sqrt_decomposition.html
2
3  // input data
4  int n;
5  vector<int> a (n);
6
7  // preprocessing
8  int len = (int) sqrt (n + .0) + 1; // size of the block and the number of blocks
9  vector<int> b (len);
10 for (int i=0; i<n; ++i)
11     b[i / len] += a[i];
12
13 // answering the queries
14 for (;;) {
15     int l, r;
16     // read input data for the next query
17     int sum = 0;
18     for (int i=l; i<=r; )
19         if (i % len == 0 && i + len - 1 <= r) {
20             // if the whole block starting at i belongs to [l, r]
21             sum += b[i / len];
22             i += len;
23         }
24         else {
25             sum += a[i];
26             ++i;
27         }
28     }
29
30     // If you're getting TLE and can't optimize more, you could reduce the number of
31     slow division operations using the following code:
32
33     int sum = 0;
34     int c_l = l / len, c_r = r / len;
35     if (c_l == c_r)
36         for (int i=l; i<=r; ++i)
37             sum += a[i];
38     else {
39         for (int i=l, end=(c_l+1)*len-1; i<=end; ++i)
40             sum += a[i];
41         for (int i=c_l+1; i<=c_r-1; ++i)
42             sum += b[i];
43         for (int i=c_r*len; i<=r; ++i)
44             sum += a[i];
45     }

```

3.10 Treap

```

1  typedef struct item * pitem;
2  struct item {
3      int prior, value, cnt;
4      bool rev;

```



```

5     pitem l, r;
6     item(int x, int y, int z){
7         value = x;
8         prior = y;
9         cnt = z;
10        rev = 0;
11        l = r = NULL;
12    }
13 };
14
15 int cnt (pitem it) {
16     return it ? it->cnt : 0;
17 }
18
19 void upd_cnt (pitem it) {
20     if (it)
21         it->cnt = cnt(it->l) + cnt(it->r) + 1;
22 }
23
24 void push (pitem it) {
25     if (it && it->rev) {
26         it->rev = false;
27         swap (it->l, it->r);
28         if (it->l) it->l->rev ^= true;
29         if (it->r) it->r->rev ^= true;
30     }
31 }
32
33 void merge (pitem & t, pitem l, pitem r) {
34     push (l);
35     push (r);
36     if (!l || !r)
37         t = l ? l : r;
38     else if (l->prior > r->prior)
39         merge (l->r, l->r, r), t = l;
40     else
41         merge (r->l, l, r->l), t = r;
42     upd_cnt (t);
43 }
44
45 void split (pitem t, pitem & l, pitem & r, int key, int add = 0) {
46     if (!t)
47         return void( l = r = 0 );
48     push (t);
49     int cur_key = add + cnt(t->l);
50     if (key <= cur_key)
51         split (t->l, l, t->l, key, add), r = t;
52     else
53         split (t->r, t->r, r, key, add + 1 + cnt(t->l)), l = t;
54     upd_cnt (t);
55 }
56
57 void reverse (pitem t, int l, int r) {
58     pitem t1, t2, t3;
59     split (t, t1, t2, l);
60     split (t2, t2, t3, r-1+1);
61     t2->rev ^= true;
62     merge (t, t1, t2);
63     merge (t, t, t3);
64 }
65
66 void output (pitem t) {
67     if (!t) return;
68     push (t);
69     output (t->l);
70     printf ("%c", char(t->value));
71     output (t->r);
72 }
73
74 pitem gettreap(string s){
75     pitem ret=NULL;
76     int i;
77     for(i=0;i<s.size();i++)merge(ret,ret,new item(s[i],(rand()<<15)+rand(),
78         1));
79     return ret;

```

79 }

3.11 Wavelet Tree

```

1 // remember your array and values must be 1-based
2 struct wavelet_tree {
3     int lo, hi;
4     wavelet_tree *l, *r;
5     vector<int> b;
6
7     //nos are in range [x,y]
8     //array indices are [from, to]
9     wavelet_tree(int *from, int *to, int x, int y) {
10         lo = x, hi = y;
11         if (lo == hi or from >= to)
12             return;
13         int mid = (lo + hi) / 2;
14         auto f = [mid](int x) {
15             return x <= mid;
16         };
17         b.reserve(to - from + 1);
18         b.pb(0);
19         for (auto it = from; it != to; it++)
20             b.pb(b.back() + f(*it));
21         //see how lambda function is used here
22         auto pivot = stable_partition(from, to, f);
23         l = new wavelet_tree(from, pivot, lo, mid);
24         r = new wavelet_tree(pivot, to, mid + 1, hi);
25     }
26
27     //kth smallest element in [l, r]
28     int kth(int l, int r, int k) {
29         if (l > r)
30             return 0;
31         if (lo == hi)
32             return lo;
33         int inLeft = b[r] - b[l - 1];
34         int lb = b[l - 1]; //amt of nos in first (l-1) nos that go in left
35         int rb = b[r]; //amt of nos in first (r) nos that go in left
36         if (k <= inLeft)
37             return this->l->kth(lb + 1, rb, k);
38         return this->r->kth(l - lb, r - rb, k - inLeft);
39     }
40
41     //count of nos in [l, r] Less than or equal to k
42     int LTE(int l, int r, int k) {
43         if (l > r or k < lo)
44             return 0;
45         if (hi <= k)
46             return r - l + 1;
47         int lb = b[l - 1], rb = b[r];
48         return this->l->LTE(lb + 1, rb, k) + this->r->LTE(l - lb, r - rb, k);
49     }
50
51     //count of nos in [l, r] equal to k
52     int count(int l, int r, int k) {
53         if (l > r or k < lo or k > hi)
54             return 0;
55         if (lo == hi)
56             return r - l + 1;
57         int lb = b[l - 1], rb = b[r], mid = (lo + hi) / 2;
58         if (k <= mid)
59             return this->l->count(lb + 1, rb, k);
60         return this->r->count(l - lb, r - rb, k);
61     }
62 };

```

- 4 Matching
- 5 Trees
- 6 Strings
- 7 Geometry
- 8 Number Theory
- 9 DP
- 10 Misc.