

## Contents

2021

### 1 Combinatorics

1.1	Burnside Lemma	1
1.2	Catlan Numbers	1

### 2 Algebra

2.1	Gray Code	2
2.2	Primitive Roots	2
2.3	Discrete Logarithm minimum $x$ for which $a^x = b \% m$	2
2.4	Discrete Root finds all numbers $x$ such that $x^k = a \% n$	2
2.5	Factorial modulo in $p \cdot \log(n)$ (Wilson Theroem)	2
2.6	Iteration over submasks	3
2.7	Totient function	3
2.8	CRT and EEGCD	3
2.9	FFT	3
2.10	Fibonacci	3
2.11	Gauss Determinant	3
2.12	GAUSS SLAE	4
2.13	Matrix Inverse	4
2.14	NTT of KACTL	4

### 3 Data Structures

3.1	2D BIT	4
3.2	2D Sparse table	4
3.3	Mo With Updates	4
3.4	Ordered Set	5
3.5	Persistent Seg Tree	5
3.6	Treap	5
3.7	Wavelet Tree	6
3.8	SparseTable	6

### 4 DP

4.1	Dynamic Connectivity with SegTree	4
4.2	CHT Line Container	4

### 5 Geometry

5.1	Convex Hull	5
5.2	Geometry Template	5
5.3	Half Plane Intersection	9
5.4	Segments Intersection	9
5.5	Rectangles Union	9

### 6 Graphs

6.1	2 SAD	10
6.2	Ariculation Point	10
6.3	Bridges Tree and Diameter	10
6.4	Dinic With Scalling	11
6.5	Gomory Hu	11
6.6	HopcraftKarp BPM	12
6.7	Hungarian	12
6.8	Kosaraju	12
6.9	Manhattan MST	13
6.10	Maximum Clique	13
6.11	MCMF	14
6.12	Minimum Arbrosccene in a Graph	14
6.13	Minimum Vertex Cover (Bipartite)	14
6.14	Prufer Code	15
6.15	Push Relabel Max Flow	16
6.16	Tarjan Algo	16
6.17	Bipartite Matching	17

### 7 Math

7.1	Sum Of Floor	17
7.2	Xor With Gauss	17
7.3	Josephus	18
7.4	Rabin Miller Primality check	18
8	Strings	18
8.1	Aho-Corasick Mostafa	18
8.2	KMP Anany	18
8.3	Manacher Kactl	19
8.4	Suffix Array Kactl	19
8.5	Suffix Automaton Mostafa	19
8.6	Zalgo Anany	19
8.7	lexicographically smallest rotation of a string	20

### 9 Trees

9.1	Centroid Decomposition	20
9.2	Dsu On Trees	20
9.3	Heavy Light Decomposition (Along with Euler Tour)	20
9.4	Mo on Trees	21

### 10 Numerical

10.1	Lagrange Polynomial	21
------	---------------------	----

### 11 Guide

11.1	Notes	21
11.2	Assignment Problems	21
11.3	XOR problems	22
11.4	Decompositions	22
11.5	Strings	22
11.6	Trees	22
11.7	Flows	22
11.8	Geometry	22
11.9	Area	22
11.10	Volume	23
11.11	Combinatorics	23
11.12	Graph Theory	23
11.13	Max flow with lower bound	23
11.14	Joseph problem	23

## 1 Combinatorics

### 1.1 Burnside Lemma

```
1 #include<iostream>
2 #include <bits/stdc++.h>
3 #define IO ios_base::sync_with_stdio(0); cin.tie(0); cout.tie(0);
4 using namespace std;
5
6 // |Classes|=sum (k ^C(pi)) / |G|
7 // C(pi) the number of cycles in the permutation pi
8 // |G| the number of permutations
```

### 1.2 Catlan Numbers

```
1 void init() {
2     catalan[0] = catalan[1] = 1;
3     for (int i=2; i<=n; i++) {
4         catalan[i] = 0;
5         for (int j=0; j < i; j++) {
6             catalan[i] += (catalan[j] * catalan[i-j-1]) % MOD;
7             if (catalan[i] >= MOD) {
8                 catalan[i] -= MOD;
9             }
10        }
11    }
12 }
13 // 1- Number of correct bracket sequence consisting of n opening and n
14 //    closing brackets.
15 // 2- The number of rooted full binary trees with n+1 leaves (vertices
16 //    are not numbered).
17 // 3- The number of ways to completely parenthesize n+1 factors.
18 // 4- The number of triangulations of a convex polygon with n+2 sides
19 // 5- The number of ways to connect the 2n points on a circle to form
20 //    n disjoint chords.
21 // 6- The number of non-isomorphic full binary trees with n internal
22 //    nodes (i.e. nodes having at least one son).
```

```

19 // 7- The number of monotonic lattice paths from point (0,0) to point
    (n,n) in a square lattice of size nxn, which do not pass above the
    main diagonal (i.e. connecting (0,0) to (n,n)).
20 // 8- Number of permutations of length n that can be stack sorted (it
    can be shown that the rearrangement is stack sorted if and only if
    there is no such index i<j<k, such that ak<ai<aj).
21 // 9- The number of non-crossing partitions of a set of n elements.
22 // 10- The number of ways to cover the ladder 1..n using n rectangles
    (The ladder consists of n columns, where ith column has a height i
    ).

```

## 2 Algebra

### 2.1 Gray Code

```

1 int g(int n) {
2     return n ^ (n >> 1);
3 }
4 int rev_g(int g) {
5     int n = 0;
6     for (; g; g >>= 1)
7         n ^= g;
8     return n;
9 }
10 int calc(int x, int y) { ///2D Gray Code
11     int a = g(x), b = g(y);
12     int res = 0;
13     f(i, 0, LG) {
14         int k1 = (a & (1 << i));
15         int k2 = (b & (1 << i));
16         res |= k1 << (i + 1);
17         res |= k2 << i;
18     }
19     return res;
20 }

```

### 2.2 Primitive Roots

```

1 int primitive_root(int p) {
2     vector<int> fact;
3     int phi = p - 1, n = phi;
4     for (int i = 2; i * i <= n; ++i)
5         if (n % i == 0) {
6             fact.push_back(i);
7             while (n % i == 0)
8                 n /= i;
9         }
10    if (n > 1)
11        fact.push_back(n);
12    for (int res = 2; res <= p; ++res) {
13        bool ok = true;
14        for (size_t i = 0; i < fact.size() && ok; ++i)
15            ok &= powmod(res, phi / fact[i], p) != 1;
16        if (ok) return res;
17    }
18    return -1;
19 }
20 }

```

### 2.3 Discrete Logarithm minimum x for which $a^x = b \% m$

```

1 // Returns minimum x for which a ^ x % m = b % m, a and m are coprime.
2 int solve(int a, int b, int m) {
3     a %= m, b %= m;
4     int n = sqrt(m) + 1;
5     int an = 1;
6     for (int i = 0; i < n; ++i)
7         an = (an * 1ll * a) % m;
8     unordered_map<int, int> vals;
9     for (int q = 0, cur = b; q <= n; ++q) {
10        vals[cur] = q;
11        cur = (cur * 1ll * a) % m;
12    }
13    for (int p = 1, cur = 1; p <= n; ++p) {
14        cur = (cur * 1ll * an) % m;
15        if (vals.count(cur)) {
16            int ans = n * p - vals[cur];
17            return ans;
18        }
19    }
20 }

```

```

19 }
20 return -1;
21 }
22 //When a and m are not coprime
23 // Returns minimum x for which a ^ x % m = b % m.
24 int solve(int a, int b, int m) {
25     a %= m, b %= m;
26     int k = 1, add = 0, g;
27     while ((g = gcd(a, m)) > 1) {
28         if (b == k)
29             return add;
30         if (b % g)
31             return -1;
32         b /= g, m /= g, ++add;
33         k = (k * 1ll * a / g) % m;
34     }
35     int n = sqrt(m) + 1;
36     int an = 1;
37     for (int i = 0; i < n; ++i)
38         an = (an * 1ll * a) % m;
39     unordered_map<int, int> vals;
40     for (int q = 0, cur = b; q <= n; ++q) {
41         vals[cur] = q;
42         cur = (cur * 1ll * a) % m;
43     }
44     for (int p = 1, cur = k; p <= n; ++p) {
45         cur = (cur * 1ll * an) % m;
46         if (vals.count(cur)) {
47             int ans = n * p - vals[cur] + add;
48             return ans;
49         }
50     }
51     return -1;
52 }

```

### 2.4 Discrete Root finds all numbers x such that $x^k = a \% n$

```

1 // This program finds all numbers x such that x^k = a (mod n)
2 vector<int> discrete_root(int n, int k, int a) {
3     if (a == 0)
4         return {0};
5
6     int g = primitive_root(n);
7     // Baby-step giant-step discrete logarithm algorithm
8     int sq = (int) sqrt(n + .0) + 1;
9     vector<pair<int, int>> dec(sq);
10    for (int i = 1; i <= sq; ++i)
11        dec[i - 1] = {powmod(g, i * sq * k % (n - 1), n), i};
12    sort(dec.begin(), dec.end());
13    int any_ans = -1;
14    for (int i = 0; i < sq; ++i) {
15        int my = powmod(g, i * k % (n - 1), n) * a % n;
16        auto it = lower_bound(dec.begin(), dec.end(), make_pair(my, 0));
17        if (it != dec.end() && it->first == my) {
18            any_ans = it->second * sq - i;
19            break;
20        }
21    }
22    if (any_ans == -1) return {};
23
24    int delta = (n - 1) / __gcd(k, n - 1);
25    vector<int> ans;
26    for (int cur = any_ans % delta; cur < n - 1; cur += delta)
27        ans.push_back(powmod(g, cur, n));
28    sort(ans.begin(), ans.end());
29    return ans;
30 }

```

### 2.5 Factorial modulo in $p * \log(n)$ (Wilson Theroem)

```

1 int factmod(int n, int p) {
2     vector<int> f(p);
3     f[0] = 1;
4     for (int i = 1; i < p; ++i)
5         f[i] = f[i-1] * i % p;
6
7     int res = 1;
8     while (n > 1) {
9         if ((n/p) % 2)
10            res = p - res;

```

```

11     res = res * f[n%p] % p;
12     n /= p;
13 }
14 return res;
15 }

```

## 2.6 Iteration over submasks

```

1 int s = m;
2 while (s > 0) {
3     s = (s-1) & m;
4 }

```

## 2.7 Totient function

```

1 void phi_1_to_n(int n) {
2     for (int i = 0; i <= n; i++)
3         phi[i] = i;
4     for (int i = 2; i <= n; i++) {
5         if (phi[i] == i) {
6             for (int j = i; j <= n; j += i)
7                 phi[j] -= phi[j] / i;
8         }
9     }
10 }

```

## 2.8 CRT and EEGCD

```

1 ll extended(ll a, ll b, ll &x, ll &y) {
2     if(b == 0) {
3         x = 1;
4         y = 0;
5         return a;
6     }
7     ll x0, y0;
8     ll g = extended(b, a % b, x0, y0);
9     x = y0;
10    y = x0 - a / b * y0;
11
12    return g;
13 }
14 ll de(ll a, ll b, ll c, ll &x, ll &y) {
15     ll g = extended(abs(a), abs(b), x, y);
16     if(c % g) return -1;
17     x *= c / g;
18     y *= c / g;
19     if(a < 0) x = -x;
20     if(b < 0) y = -y;
21     return g;
22 }
23 pair<ll, ll> CRT(vector<ll> r, vector<ll> m) {
24     ll r1 = r[0], m1 = m[0];
25     for(int i = 1; i < r.size(); i++) {
26         ll r2 = r[i], m2 = m[i];
27         ll x0, y0;
28         ll g = de(m1, -m2, r2 - r1, x0, y0);
29         if(g == -1) return {-1, -1};
30         x0 %= m2;
31         ll nr = x0 * m1 + r1;
32         ll nm = m1 / g * m2;
33         r1 = (nr % nm + nm) % nm;
34         m1 = nm;
35     }
36     return {r1, m1};
37 }

```

## 2.9 FFT

```

1 typedef complex<double> C;
2 typedef vector<double> vd;
3 typedef vector<int> vi;
4 typedef pair<int, int> pii;
5 void fft(vector<C>& a) {
6     int n = sz(a), L = 31 - __builtin_clz(n);
7     static vector<complex<long double>> R(2, 1);
8     static vector<C> rt(2, 1); // (^ 10% fas te r i f double)
9     for (static int k = 2; k < n; k *= 2) {
10         R.resize(n);
11         rt.resize(n);
12         auto x = polar(1.0L, acos(-1.0L) / k);
13         rep(i, k, 2 * k) rt[i] = R[i] = i & 1 ? R[i / 2] * x : R[i /
14         2];
15     }
16 }

```

```

15 vi rev(n);
16 rep(i, 0, n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
17 rep(i, 0, n) if (i < rev[i]) swap(a[i], a[rev[i]]);
18 for (int k = 1; k < n; k *= 2)
19     for (int i = 0; i < n; i += 2 * k) rep(j, 0, k) {
20         C z = rt[j + k] * a[i + j + k]; //
21         a[i + j + k] = a[i + j] - z;
22         a[i + j] += z;
23     }
24 }
25 vd conv(const vd& a, const vd& b) {
26     if (a.empty() || b.empty()) return {};
27     vd res(sz(a) + sz(b) - 1);
28     int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
29     vector<C> in(n), out(n);
30     copy(all(a), begin(in));
31     rep(i, 0, sz(b)) in[i].imag(b[i]);
32     fft(in);
33     for (C& x : in) x *= x;
34     rep(i, 0, n) out[i] = in[-i & (n - 1)] - conj(in[i]);
35     fft(out);
36     /// rep(i, 0, sz(res)) res[i] = (MOD+(ll)round(imag(out[i]) / (4 * n
37     ))) % MOD; ///in case of mod
38     rep(i, 0, sz(res)) res[i] = imag(out[i]) / (4 * n);
39     return res;
40 }
41 int main() {
42     //Applications
43     //1-All possible sums
44
45     //2-All possible scalar products
46     // We are given two arrays a[] and b[] of length n.
47     //We have to compute the products of a with every cyclic shift of
48     //b.
49     //We generate two new arrays of size 2n: We reverse a and append n
50     //zeros to it.
51     //And we just append b to itself. When we multiply these two
52     //arrays as polynomials,
53     //and look at the coefficients c[n-1], c[n], ..., c[2n-2] of the
54     //product c, we get:
55     //c[k]=sum i+j=k a[i]b[j]
56
57     //3-Two stripes
58     //We are given two Boolean stripes (cyclic arrays of values 0 and
59     //1) a and b.
60     //We want to find all ways to attach the first stripe to the
61     //second one,
62     //such that at no position we have a 1 of the first stripe next to
63     //a 1 of the second stripe.

```

## 2.10 Fibonacci

```

1 // F(n-1) * F(n+1) - F(n)^2 = (-1)^n
2 // F(n+k) = F(k) * F(n+1) + F(k-1) * F(n)
3 // F(2*n) = F(n) * (F(n+1) + F(n-1))
4 // GCD ( F(m) , F(n) ) = F(GCD(n,m))

```

## 2.11 Gauss Determinant

```

1 double det(vector<vector<double>>& a) {
2     int n = sz(a); double res = 1;
3     rep(i, 0, n) {
4         int b = i;
5         rep(j, i+1, n) if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
6         if (i != b) swap(a[i], a[b]), res *= -1;
7         res *= a[i][i];
8         if (res == 0) return 0;
9         rep(j, i+1, n) {
10             double v = a[j][i] / a[i][i];
11             if (v != 0) rep(k, i+1, n) a[j][k] -= v * a[i][k];
12         }
13     }
14     return res;
15 }
16 // for integers
17 const ll mod = 12345;
18 ll det(vector<vector<ll>>& a) {
19     int n = sz(a); ll ans = 1;
20     rep(i, 0, n) {

```

```

21     rep(j,i+1,n) {
22         while (a[j][i] != 0) { // gcd step
23             ll t = a[i][i] / a[j][i];
24             if (t) rep(k,i,n)
25                 a[i][k] = (a[i][k] - a[j][k] * t) % mod;
26             swap(a[i], a[j]);
27             ans *= -1;
28         }
29     }
30     ans = ans * a[i][i] % mod;
31     if (!ans) return 0;
32 }
33 return (ans + mod) % mod;
34 }

```

## 2.12 GAUSS SLAE

```

1  const double EPS = 1e-9;
2  const int INF = 2; // it doesn't actually have to be infinity or a big
   number
3
4  int gauss (vector < vector<double> > a, vector<double> & ans) {
5      int n = (int) a.size();
6      int m = (int) a[0].size() - 1;
7
8      vector<int> where (m, -1);
9      for (int col = 0, row = 0; col < m && row < n; ++col) {
10         int sel = row;
11         for (int i = row; i < n; ++i)
12             if (abs (a[i][col]) > abs (a[sel][col]))
13                 sel = i;
14         if (abs (a[sel][col]) < EPS)
15             continue;
16         for (int i = col; i <= m; ++i)
17             swap (a[sel][i], a[row][i]);
18         where[col] = row;
19         for (int i = 0; i < n; ++i)
20             if (i != row) {
21                 double c = a[i][col] / a[row][col];
22                 for (int j = col; j <= m; ++j)
23                     a[i][j] -= a[row][j] * c;
24             }
25         ++row;
26     }
27
28     ans.assign (m, 0);
29     for (int i = 0; i < m; ++i)
30         if (where[i] != -1)
31             ans[i] = a[where[i]][m] / a[where[i]][i];
32     for (int i = 0; i < n; ++i) {
33         double sum = 0;
34         for (int j = 0; j < m; ++j)
35             sum += ans[j] * a[i][j];
36         if (abs (sum - a[i][m]) > EPS)
37             return 0;
38     }
39
40     for (int i = 0; i < m; ++i)
41         if (where[i] == -1)
42             return INF;
43     return 1;
44 }

```

## 2.13 Matrix Inverse

```

1  #define ld long double
2  vector < vector<ld> > gauss (vector < vector<ld> > a) {
3
4      int n = (int) a.size();
5      vector<vector<ld> > ans(n, vector<ld>(n, 0));
6
7      for(int i = 0; i < n; i++)
8          ans[i][i] = 1;
9      for(int i = 0; i < n; i++) {
10         for(int j = i + 1; j < n; j++)
11             if(a[j][i] > a[i][i]) {
12                 a[j].swap(a[i]);
13                 ans[j].swap(ans[i]);
14             }
15         ld val = a[i][i];
16         for(int j = 0; j < n; j++) {
17             a[i][j] /= val;
18             ans[i][j] /= val;

```

```

19     }
20     for(int j = 0; j < n; j++) {
21         if(j == i) continue;
22         val = a[j][i];
23         for(int k = 0; k < n; k++) {
24             a[j][k] -= val * a[i][k];
25             ans[j][k] -= val * ans[i][k];
26         }
27     }
28     return ans;
29 }
30 }

```

## 2.14 NTT of KACTL

```

1  const ll mod = (119 << 23) + 1, root = 62; // = 998244353
2  // For p < 2^30 there is a lso e . g . 5 << 25, 7 << 26, 479 << 21
3  // and 483 << 21 (same root) . The l as t two are > 10^9.
4  typedef vector<ll> vl;
5  void ntt(vl &a) {
6      int n = sz(a), L = 31 - __builtin_clz(n);
7      static vl rt(2, 1);
8      for (static int k = 2, s = 2; k < n; k *= 2, s++) {
9          rt.resize(n);
10         ll z[] = {1, modpow(root, mod >> s)};
11         rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
12     }
13     vi rev(n);
14     rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
15     rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
16     for (int k = 1; k < n; k *= 2)
17         for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
18             ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
19             a[i + j + k] = ai - z + (z > ai ? mod : 0);
20             ai += (ai + z >= mod ? z - mod : z);
21         }
22 }
23 vl conv(const vl &a, const vl &b) {
24     if (a.empty() || b.empty()) return {};
25     int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s), n = 1 << B;
26     int inv = modpow(n, mod - 2);
27     vl L(a), R(b), out(n);
28     L.resize(n), R.resize(n);
29     ntt(L), ntt(R);
30     rep(i,0,n) out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv % mod;
31     ntt(out);
32     return {out.begin(), out.begin() + s};
33 }

```

## 3 Data Structures

### 3.1 2D BIT

```

1  void upd(int x, int y, int val) {
2      for(int i = x; i <= n; i += i & -i)
3          for(int j = y; j <= m; j += j & -j)
4              bit[i][j] += val;
5  }
6  int get(int x, int y) {
7      int ans = 0;
8      for(int i = x; i; i -= i & -i)
9          for(int j = y; j; j -= j & -j)
10             ans += bit[i][j];
11 }

```

### 3.2 2D Sparse table

```

1  /*
2   note this isn't the best cache-wise version
3   query O(1), Build O(NMlgNm)
4   be careful when using it and note the he build a dimension above
   another
5   i.e he builds a sparse table for each row
6   the build sparse table over each row's sparse table
7  */
8  const int N = 505, LG = 10;
9
10 int st[N][N][LG][LG];
11 int a[N][N], lg2[N];

```

```

12 int yo(int x1, int y1, int x2, int y2) {
13     x2++;
14     y2++;
15     int a = lg2[x2 - x1], b = lg2[y2 - y1];
16     return max(
17         max(st[x1][y1][a][b], st[x2 - (1 << a)][y1][a][b]),
18         max(st[x1][y2 - (1 << b)][a][b], st[x2 - (1 << a)][y2 - (1 <<
19             b)][a][b])
20     );
21 }
22
23 void build(int n, int m) { // 0 indexed
24     for (int i = 2; i < N; i++) lg2[i] = lg2[i >> 1] + 1;
25     for (int i = 0; i < n; i++) {
26         for (int j = 0; j < m; j++) {
27             st[i][j][0][0] = a[i][j];
28         }
29     }
30     for (int a = 0; a < LG; a++) {
31         for (int b = 0; b < LG; b++) {
32             if (a + b == 0) continue;
33             for (int i = 0; i + (1 << a) <= n; i++) {
34                 for (int j = 0; j + (1 << b) <= m; j++) {
35                     if (!a) {
36                         st[i][j][a][b] = max(st[i][j][a][b - 1], st[i][j + (1 << (
37                             b - 1)][a][b - 1]);
38                     } else {
39                         st[i][j][a][b] = max(st[i][j][a - 1][b], st[i + (1 << (a -
40                             1)][j][a - 1][b]);
41                     }
42                 }
43             }
44         }
45     }

```

### 3.3 Mo With Updates

```

1 //O(N^5/3) note that the block size is not a standard size
2 //O(2SQ + N^2 / S + Q * N^2 / S^2) = O(Q * N^(2/3)) if S = n^(2/3)
3 //fact: S = (2 * n * n)^(1/3) give the best complexity
4 const int block_size = 2000;
5 struct Query{
6     int l, r, t, idx;
7     Query(int l, int r, int t, int idx) : l(l), r(r), t(t), idx(idx) {}
8     bool operator < (Query o) const{
9         if(l / block_size != o.l / block_size) return l < o.l;
10        if(r / block_size != o.r / block_size) return r < o.r;
11        return t < o.t;
12    }
13 };
14 int L = 0, R = -1, K = -1;
15 while(L < Q[i].l) del(a[L++]);
16 while(L > Q[i].l) add(a[--L]);
17 while(R < Q[i].r) add(a[++R]);
18 while(R > Q[i].r) del(a[R--]);
19 while(K < Q[i].t) upd(++K);
20 while(K > Q[i].t) err(K--);

```

### 3.4 Ordered Set

```

1 #include <ext/pb_ds/assoc_container.hpp>
2 #include <ext/pb_ds/tree_policy.hpp>
3 using namespace __gnu_pbds;
4
5 #define ordered_set tree<int, null_type, less<int>, rb_tree_tag,
6     tree_order_statistics_node_update>
7
8 //order_of_key(k): returns the number of elements strictly less than k
9 //find_by_order(k): returns an iterator to the k-th element (0-based)

```

### 3.5 Persistent Seg Tree

```

1
2 int val[ N * 60 ], L[ N * 60 ], R[ N * 60 ], ptr, tree[N]; // N * lgN
3 int upd(int root, int s, int e, int idx) {
4     int ret = ++ptr;
5     val[ret] = L[ret] = R[ret] = 0;
6     if (s == e) {
7         val[ret] = val[root] + 1;
8         return ret;

```

```

9     }
10    int md = (s + e) >> 1;
11    if (idx <= md) {
12        L[ret] = upd(L[root], s, md, idx), R[ret] = R[root];
13    } else {
14        R[ret] = upd(R[root], md + 1, e, idx), L[ret] = L[root];
15    }
16    val[ret] = max(val[L[ret]], val[R[ret]]);
17    return ret;
18 }
19 int qry(int node, int s, int e, int l, int r) {
20     if (r < s || e < l || !node) return 0; //Punishment Value
21     if (l <= s && e <= r) {
22         return val[node];
23     }
24     int md = (s+e)>>1;
25     return max(qry(L[node], s, md, l, r), qry(R[node], md+1, e, l, r));
26 }
27 int merge(int x, int y, int s, int e) {
28     if (!x || !y) return x | y;
29     if (s == e) {
30         val[x] += val[y];
31         return x;
32     }
33     int md = (s + e) >> 1;
34     L[x] = merge(L[x], L[y], s, md);
35     R[x] = merge(R[x], R[y], md+1, e);
36     val[x] = val[L[x]] + val[R[x]];
37     return x;
38 }

```

### 3.6 Treap

```

1 mt19937_64 mrand(chrono::steady_clock::now().time_since_epoch().count
2     ());
3 struct Node {
4     int key, pri = mrand(), sz = 1;
5     int lz = 0;
6     int idx;
7     array<Node*, 2> c = {NULL, NULL};
8     Node(int key, int idx) : key(key), idx(idx) {}
9 };
10 int getsz(Node* t) {
11     return t ? t->sz : 0;
12 }
13 Node* calc(Node* t) {
14     t->sz = 1 + getsz(t->c[0]) + getsz(t->c[1]);
15     return t;
16 }
17 void prop(Node* cur) {
18     if (!cur || !cur->lz)
19         return;
20     cur->key += cur->lz;
21     if (cur->c[0])
22         cur->c[0]->lz += cur->lz;
23     if (cur->c[1])
24         cur->c[1]->lz += cur->lz;
25     cur->lz = 0;
26 }
27 array<Node*, 2> split(Node* t, int k) {
28     prop(t);
29     if (!t)
30         return {t, t};
31     if (getsz(t->c[0]) >= k) { //answer is in left node
32         auto ret = split(t->c[0], k);
33         t->c[0] = ret[1];
34         return {ret[0], calc(t)};
35     } else { //k > t->c[0]
36         auto ret = split(t->c[1], k - 1 - getsz(t->c[0]));
37         t->c[1] = ret[0];
38         return {calc(t), ret[1]};
39     }
40 }
41 Node* merge(Node* u, Node* v) {
42     prop(u);
43     prop(v);
44     if (!u || !v)
45         return u ? u : v;
46     if (u->pri > v->pri) {
47         u->c[1] = merge(u->c[1], v);

```

```

48     return calc(u);
49 } else {
50     v->c[0] = merge(u, v->c[0]);
51     return calc(v);
52 }
53 }
54 int cnt(Node* cur, int x) {
55     prop(cur);
56     if(!cur)
57         return 0;
58     if(cur->key <= x)
59         return getsz(cur->c[0]) + 1 + cnt(cur->c[1], x);
60     return cnt(cur->c[0], x);
61 }
62 Node* ins(Node* root, int val, int idx, int pos) {
63     auto splitted = split(root, pos);
64     root = merge(splitted[0], new Node(val, idx));
65     return merge(root, splitted[1]);
66 }

```

## 3.7 Wavelet Tree

```

1  // remember your array and values must be 1-based
2  struct wavelet_tree {
3      int lo, hi;
4      wavelet_tree *l, *r;
5      vector<int> b;
6
7      //nos are in range [x,y]
8      //array indices are [from, to)
9      wavelet_tree(int *from, int *to, int x, int y) {
10         lo = x, hi = y;
11         if (lo == hi or from >= to)
12             return;
13         int mid = (lo + hi) / 2;
14         auto f = [mid](int x) {
15             return x <= mid;
16         };
17         b.reserve(to - from + 1);
18         b.pb(0);
19         for (auto it = from; it != to; it++)
20             b.pb(b.back() + f(*it));
21         //see how lambda function is used here
22         auto pivot = stable_partition(from, to, f);
23         l = new wavelet_tree(from, pivot, lo, mid);
24         r = new wavelet_tree(pivot, to, mid + 1, hi);
25     }
26
27     //kth smallest element in [l, r]
28     int kth(int l, int r, int k) {
29         if (l > r)
30             return 0;
31         if (lo == hi)
32             return lo;
33         int inLeft = b[r] - b[l - 1];
34         int lb = b[l - 1]; //amt of nos in first (l-1) nos that go in
35         //left
36         int rb = b[r]; //amt of nos in first (r) nos that go in left
37         if (k <= inLeft)
38             return this->l->kth(lb + 1, rb, k);
39         return this->r->kth(l - lb, r - rb, k - inLeft);
40     }
41
42     //count of nos in [l, r] Less than or equal to k
43     int LTE(int l, int r, int k) {
44         if (l > r or k < lo)
45             return 0;
46         if (hi <= k)
47             return r - l + 1;
48         int lb = b[l - 1], rb = b[r];
49         return this->l->LTE(lb + 1, rb, k) + this->r->LTE(l - lb, r -
50         rb, k);
51     }
52
53     //count of nos in [l, r] equal to k
54     int count(int l, int r, int k) {
55         if (l > r or k < lo or k > hi)
56             return 0;
57         if (lo == hi)
58             return r - l + 1;
59         int lb = b[l - 1], rb = b[r], mid = (lo + hi) / 2;
60         if (k <= mid)
61             return this->l->count(lb + 1, rb, k);
62     }

```

```

60     return this->r->count(l - lb, r - rb, k);
61 }
62 };

```

## 3.8 SparseTable

```

1  int S[N];
2  for(int i = 2; i < N; i++) S[i] = S[i >> 1] + 1;
3
4  for (int i = 1; i <= K; i++)
5      for (int j = 0; j + (1 << i) <= N; j++)
6          st[i][j] = f(st[i - 1][j], st[i - 1][j + (1 << (i - 1))]);
7
8  int query(int l, int r) {
9      int k = S[r - l + 1];
10     return mrg(st[k][l], st[k][r - (1 << k) + 1]);
11 }
12

```

## 4 DP

### 4.1 Dynamic Connectivity with SegTree

```

1  #define f(i, a, b) for(int i = a; i < b; i++)
2  #define all(a) a.begin(), a.end()
3  #define sz(x) (int)(x).size()
4  typedef long long ll;
5  const int N = 1e5 + 5;
6
7  struct PT {
8      ll x, y;
9      PT() {}
10     PT(ll a, ll b) : x(a), y(b) {}
11     PT operator-(const PT &o) { return PT{x - o.x, y - o.y}; }
12     bool operator<(const PT &o) const { return make_pair(x, y) <
13     make_pair(o.x, o.y); }
14 };
15 ll cross(PT x, PT y) {
16     return x.x * y.y - x.y * y.x;
17 }
18 PT val[300005];
19 bool in[300005];
20 ll qr[300005];
21 bool ask[300005];
22 ll ans[N];
23 vector<PT> t[300005 * 4]; //segment tree holding points to queries
24 void update(int node, int s, int e, int l, int r, PT x) {
25     if (r < s || e < l) return;
26     if (l <= s && e <= r) { //add this point to maximize it with
27         //queries in this range
28         t[node].push_back(x);
29         return;
30     }
31     int md = (s + e) >> 1;
32     update(node << 1, s, md, l, r, x);
33     update(node << 1 | 1, md + 1, e, l, r, x);
34 }
35 vector<PT> stk;
36 inline void addPts(vector<PT> v) {
37     stk.clear(); //reset the data structure you are using
38     sort(all(v));
39     //build upper envelope
40     for (int i = 0; i < v.size(); i++) {
41         while (sz(stk) > 1 && cross(v[i] - stk.back(), stk.back() -
42         stk[stk.size() - 2]) <= 0)
43             stk.pop_back();
44         stk.push_back(v[i]);
45     }
46 }
47 inline ll calc(PT x, ll val) {
48     return x.x * val + x.y;
49 }
50 ll query(ll x) {
51     if (stk.empty())
52         return LLONG_MIN;
53     int lo = 0, hi = stk.size() - 1;
54     while (lo + 10 < hi) {
55         int md = lo + (hi - lo) / 2;
56         if (calc(stk[md + 1], x) > calc(stk[md], x))

```



```

54         lo = md + 1;
55     else
56         hi = md;
57 }
58 ll ans = LLONG_MIN;
59 for (int i = lo; i <= hi; i++)
60     ans = max(ans, calc(stk[i], x));
61 return ans;
62 }
63
64 void solve(int node, int s, int e) {    ///Solve queries
65     addPts(t[node]);    ///note that there is no need to add/delete
66     just build for t[node]
67     f(i, s, e + 1) {
68         if (ask[i]) {
69             ans[i] = max(ans[i], query(qr[i]));
70         }
71     }
72     if (s == e) return;
73     int md = (s + e) >> 1;
74     solve(node << 1, s, md);
75     solve(node << 1 | 1, md + 1, e);
76 }
77 void doWork() {
78     int n;
79     cin >> n;
80     stk.reserve(n);
81     f(i, 1, n + 1) {
82         int tp;
83         cin >> tp;
84         if (tp == 1) {    ///Add Query
85             int x, y;
86             cin >> x >> y;
87             val[i] = PT(x, y);
88             in[i] = 1;
89         } else if (tp == 2) {    ///Delete Query
90             int x;
91             cin >> x;
92             if (in[x]) update(1, 1, n, x, i - 1, val[x]);
93             in[x] = 0;
94         } else {
95             cin >> qr[i];
96             ask[i] = true;
97         }
98     }
99     f(i, 1, n + 1)    ///Finalize Query
100     if (in[i])
101         update(1, 1, n, i, n, val[i]);
102
103     f(i, 1, n + 1) ans[i] = LLONG_MIN;
104     solve(1, 1, n);
105     f(i, 1, n + 1) if (ask[i]) {
106         if (ans[i] == LLONG_MIN)
107             cout << "EMPTY SET\n";
108         else
109             cout << ans[i] << '\n';
110     }
111 }

```

## 4.2 CHT Line Container

```

1  struct Line {
2      mutable ll m, b, p;
3      bool operator<(const Line &o) const { return m < o.m; }
4      bool operator<(ll x) const { return p < x; }
5  };
6  struct LineContainer : multiset<Line, less<>> {
7      /// (for doubles, use inf = 1/.0, div(a,b) = a/b)
8      static const ll inf = LLONG_MAX;
9      ll div(ll db, ll dm) { // floored division
10         return db / dm - ((db ^ dm) < 0 && db % dm);
11     }
12     bool isect(iterator x, iterator y) {
13         if (y == end()) {
14             x->p = inf;
15             return false;
16         }
17         if (x->m == y->m)
18             x->p = x->b > y->b ? inf : -inf;
19         else
20             x->p = div(y->b - x->b, x->m - y->m);
21         return x->p >= y->p;

```

```

22     }
23     void add(ll m, ll b) {
24         auto z = insert((m, b, 0)), y = z++, x = y;
25         while (isect(y, z))
26             z = erase(z);
27         if (x != begin() && isect(--x, y))
28             isect(x, y = erase(y));
29         while ((y = x) != begin() && (--x)->p >= y->p)
30             isect(x, erase(y));
31     }
32     ll query(ll x) {
33         assert(!empty());
34         auto l = *lower_bound(x);
35         return l.m * x + l.b;
36     }
37 };

```

## 5 Geometry

### 5.1 Convex Hull

```

1  struct point {
2      ll x, y;
3      point(ll x, ll y) : x(x), y(y) {}
4      point operator -(point other) {
5          return point(x - other.x, y - other.y);
6      }
7      bool operator <(const point &other) const {
8          return x != other.x ? x < other.x : y < other.y;
9      }
10 };
11 ll cross(point a, point b) {
12     return a.x * b.y - a.y * b.x;
13 }
14 ll dot(point a, point b) {
15     return a.x * b.x + a.y * b.y;
16 }
17 struct sortCCW {
18     point center;
19     sortCCW(point center) : center(center) {}
20
21     bool operator()(point a, point b) {
22         ll res = cross(a - center, b - center);
23         if (res)
24             return res > 0;
25         return dot(a - center, a - center) < dot(b - center, b - center);
26     }
27 };
28 vector<point> hull(vector<point> v) {
29     sort(v.begin(), v.end());
30     sort(v.begin() + 1, v.end(), sortCCW(v[0]));
31     v.push_back(v[0]);
32     vector<point> ans;
33     for (auto i : v) {
34         int sz = ans.size();
35         while (sz > 1 && cross(i - ans[sz - 1], ans[sz - 2] - ans[sz - 1]) <= 0)
36             ans.pop_back(), sz--;
37         ans.push_back(i);
38     }
39     ans.pop_back();
40     return ans;
41 }
42 }

```

### 5.2 Geometry Template

```

1  using ptype = double edit this first ;
2  double EPS = 1e-9;
3  struct point {
4      ptype x, y;
5      point(ptype x, ptype y) : x(x), y(y) {}
6      point operator -(const point & other) const { return point(x - other.x, y - other.y); }
7      point operator +(const point & other) const { return point(x + other.x, y + other.y); }
8      point operator *(ptype c) const { return point(x * c, y * c); }
9      point operator /(ptype c) const { return point(x / c, y / c); }

```

```

10   point prep() { return point(-y, x); }
11   };
12   ptype cross(point a, point b) { return a.x * b.y - a.y * b.x; }
13   ptype dot(point a, point b) { return a.x * b.x + a.y * b.y; }
14   double abs(point a) { return sqrt(dot(a, a)); }
15
16   double angle (point a, point b) { // angle between [0 , pi]
17       return acos(dot(a, b) / abs(a) / abs(b));
18   }
19   // a : point in Line, d : Line direction
20   point LineLineIntersect(point a1, point d1, point a2, point d2) {
21       return a1 + d1 * cross(a2 - a1, d2) / cross(d1, d2);
22   }
23   // Line a---b, point C
24   point ProjectPointLine(point a, point b, point c) {
25       return a + (b - a) * 1.0 * dot(c - a, b - a) / dot(b - a, b - a);
26   }
27   // segment a---b, point C
28   point ProjectPointSegment(point a, point b, point c) {
29       double r = dot(c - a, b - a) / dot(b - a, b - a);
30       if(r < 0)
31           return a;
32       if(r > 1)
33           return b;
34       return a + (b - a) * r;
35   }
36   // Line a---b, point p
37   point reflectAroundLine(point a, point b, point p) {
38       return ProjectPointLine(a, b, p) * 2 - p; // (proj-p) * 2 + p
39   }
40   // Around origin
41   point RotateCCW(point p, double t) {
42       return point(p.x * cos(t) - p.y * sin(t),
43                   p.x * sin(t) + p.y * cos(t));
44   }
45   // Line a---b
46   vector<point> CircleLineIntersect(point a, point b, point center,
47       double r) {
48       a = a - center;
49       b = b - center;
50       point p = ProjectPointLine(a, b, point(0, 0)); // project point
51       // from center to the Line
52       if(dot(p, p) > r * r)
53           return {};
54       double len = sqrt(r * r - dot(p, p));
55       if(len < EPS)
56           return {center + p};
57
58       point d = (a - b) / abs(a - b);
59       return {center + p + d * len, center + p - d * len};
60   }
61   vector<point> CircleCircleIntersect(point c1, ld r1, point c2, ld r2)
62   {
63       if (r1 < r2) {
64           swap(r1, r2);
65           swap(c1, c2);
66       }
67       ld d = abs(c2 - c1); // distance between c1,c2
68       if (d > r1 + r2 || d < r1 - r2 || d < EPS) // zero or infinite
69           // solutions
70           return {};
71       ld angle = acos(min((d * d + r1 * r1 - r2 * r2) / (2 * r1 * d), (
72           ld) 1.0));
73       point p = (c2 - c1) / d * r1;
74       if (angle < EPS)
75           return {c1 + p};
76       return {c1 + RotateCCW(p, angle), c1 + RotateCCW(p, -angle)};
77   }
78   point circumcircle(point p1, point p2, point p3) {
79       return LineLineIntersect((p1 + p2) / 2, (p1 - p2).prep(),
80           (p1 + p3) / 2, (p1 - p3).prep());
81   }
82   //I : number points with integer coordinates lying strictly inside the
83   //    polygon.
84   //B : number of points lying on polygon sides by B.
85   //Area = I + B/2 - 1

```

## 5.3 Half Plane Intersection

```

1   // Redefine epsilon and infinity as necessary. Be mindful of precision
2   // errors.
3   const long double eps = 1e-9, inf = 1e9;
4   // Basic point/vector struct.
5   struct Point {
6       long double x, y;
7       explicit Point(long double x = 0, long double y = 0) : x(x), y(y)
8       {}
9
10      // Addition, subtraction, multiply by constant, cross product.
11
12      friend Point operator + (const Point& p, const Point& q) {
13          return Point(p.x + q.x, p.y + q.y);
14      }
15
16      friend Point operator - (const Point& p, const Point& q) {
17          return Point(p.x - q.x, p.y - q.y);
18      }
19
20      friend Point operator * (const Point& p, const long double& k) {
21          return Point(p.x * k, p.y * k);
22      }
23
24      friend long double cross(const Point& p, const Point& q) {
25          return p.x * q.y - p.y * q.x;
26      }
27  };
28
29  // Basic half-plane struct.
30  struct Halfplane {
31
32      // 'p' is a passing point of the line and 'pq' is the direction
33      // vector of the line.
34      Point p, pq;
35      long double angle;
36
37      Halfplane() {}
38      Halfplane(const Point& a, const Point& b) : p(a), pq(b - a) {
39          angle = atan2l(pq.y, pq.x);
40      }
41
42      // Check if point 'r' is outside this half-plane.
43      // Every half-plane allows the region to the LEFT of its line.
44      bool out(const Point& r) {
45          return cross(pq, r - p) < -eps;
46      }
47
48      // Comparator for sorting.
49      // If the angle of both half-planes is equal, the leftmost one
50      // should go first.
51      bool operator < (const Halfplane& e) const {
52          if (fabsl(angle - e.angle) < eps) return cross(pq, e.p - p) <
53              0;
54          return angle < e.angle;
55      }
56
57      // We use equal comparator for std::unique to easily remove
58      // parallel half-planes.
59      bool operator == (const Halfplane& e) const {
60          return fabsl(angle - e.angle) < eps;
61      }
62
63      // Intersection point of the lines of two half-planes. It is
64      // assumed they're never parallel.
65      friend Point inter(const Halfplane& s, const Halfplane& t) {
66          long double alpha = cross((t.p - s.p), t.pq) / cross(s.pq, t.
67              pq);
68          return s.p + (s.pq * alpha);
69      }
70  };
71
72  // Actual algorithm
73  vector<Point> hp_intersect(vector<Halfplane>& H) {
74
75      Point box[4] = { // Bounding box in CCW order
76          Point(inf, inf),
77          Point(-inf, inf),
78          Point(-inf, -inf),
79          Point(inf, -inf)
80      };

```



```

76 };
77
78 for(int i = 0; i < 4; i++) { // Add bounding box half-planes.
79     Halfplane aux(box[i], box[(i+1) % 4]);
80     H.push_back(aux);
81 }
82
83 // Sort and remove duplicates
84 sort(H.begin(), H.end());
85 H.erase(unique(H.begin(), H.end()), H.end());
86
87 deque<Halfplane> dq;
88 int len = 0;
89 for(int i = 0; i < int(H.size()); i++) {
90     // Remove from the back of the deque while last half-plane is
91     // redundant
92     while (len > 1 && H[i].out(inter(dq[len-1], dq[len-2]))) {
93         dq.pop_back();
94         --len;
95     }
96     // Remove from the front of the deque while first half-plane
97     // is redundant
98     while (len > 1 && H[i].out(inter(dq[0], dq[1]))) {
99         dq.pop_front();
100         --len;
101     }
102     // Add new half-plane
103     dq.push_back(H[i]);
104     ++len;
105 }
106
107 // Final cleanup: Check half-planes at the front against the back
108 // and vice-versa
109 while (len > 2 && dq[0].out(inter(dq[len-1], dq[len-2]))) {
110     dq.pop_back();
111     --len;
112 }
113
114 while (len > 2 && dq[len-1].out(inter(dq[0], dq[1]))) {
115     dq.pop_front();
116     --len;
117 }
118
119 // Report empty intersection if necessary
120 if (len < 3) return vector<Point>();
121
122 // Reconstruct the convex polygon from the remaining half-planes.
123 vector<Point> ret(len);
124 for(int i = 0; i+1 < len; i++) {
125     ret[i] = inter(dq[i], dq[i+1]);
126 }
127 ret.back() = inter(dq[len-1], dq[0]);
128 return ret;
129 }

```

## 5.4 Segments Intersection

```

1  const double EPS = 1E-9;
2
3  struct pt {
4      double x, y;
5  };
6
7  struct seg {
8      pt p, q;
9      int id;
10
11      double get_y(double x) const {
12          if (abs(p.x - q.x) < EPS)
13              return p.y;
14          return p.y + (q.y - p.y) * (x - p.x) / (q.x - p.x);
15      }
16 };
17
18 bool intersectId(double l1, double r1, double l2, double r2) {
19     if (l1 > r1)
20         swap(l1, r1);
21     if (l2 > r2)
22         swap(l2, r2);
23     return max(l1, l2) <= min(r1, r2) + EPS;
24 }

```

```

25 int vec(const pt& a, const pt& b, const pt& c) {
26     double s = (b.x - a.x) * (c.y - a.y) - (b.y - a.y) * (c.x - a.x);
27     return abs(s) < EPS ? 0 : s > 0 ? +1 : -1;
28 }
29
30 bool intersect(const seg& a, const seg& b)
31 {
32     return intersectId(a.p.x, a.q.x, b.p.x, b.q.x) &&
33         intersectId(a.p.y, a.q.y, b.p.y, b.q.y) &&
34         vec(a.p, a.q, b.p) * vec(a.p, a.q, b.q) <= 0 &&
35         vec(b.p, b.q, a.p) * vec(b.p, b.q, a.q) <= 0;
36 }
37
38 bool operator<(const seg& a, const seg& b)
39 {
40     double x = max(min(a.p.x, a.q.x), min(b.p.x, b.q.x));
41     return a.get_y(x) < b.get_y(x) - EPS;
42 }
43
44 struct event {
45     double x;
46     int tp, id;
47
48     event() {}
49     event(double x, int tp, int id) : x(x), tp(tp), id(id) {}
50
51     bool operator<(const event& e) const {
52         if (abs(x - e.x) > EPS)
53             return x < e.x;
54         return tp > e.tp;
55     }
56 };
57
58 set<seg> s;
59 vector<set<seg>::iterator> where;
60
61 set<seg>::iterator prev(set<seg>::iterator it) {
62     return it == s.begin() ? s.end() : --it;
63 }
64
65 set<seg>::iterator next(set<seg>::iterator it) {
66     return ++it;
67 }
68
69 pair<int, int> solve(const vector<seg>& a) {
70     int n = (int)a.size();
71     vector<event> e;
72     for (int i = 0; i < n; ++i) {
73         e.push_back(event(min(a[i].p.x, a[i].q.x), +1, i));
74         e.push_back(event(max(a[i].p.x, a[i].q.x), -1, i));
75     }
76     sort(e.begin(), e.end());
77
78     s.clear();
79     where.resize(a.size());
80     for (size_t i = 0; i < e.size(); ++i) {
81         int id = e[i].id;
82         if (e[i].tp == +1) {
83             set<seg>::iterator nxt = s.lower_bound(a[id]), prv = prev(
84                 nxt);
85             if (nxt != s.end() && intersect(*nxt, a[id]))
86                 return make_pair(nxt->id, id);
87             if (prv != s.end() && intersect(*prv, a[id]))
88                 return make_pair(prv->id, id);
89             where[id] = s.insert(nxt, a[id]);
90         } else {
91             set<seg>::iterator nxt = next(where[id]), prv = prev(where
92                 [id]);
93             if (nxt != s.end() && prv != s.end() && intersect(*nxt, *
94                 prv))
95                 return make_pair(prv->id, nxt->id);
96             s.erase(where[id]);
97         }
98     }
99     return make_pair(-1, -1);
100 }

```

## 5.5 Rectangles Union

```

1  #include<bits/stdc++.h>
2  #define P(x,y) make_pair(x,y)

```

```

3 using namespace std;
4 class Rectangle {
5 public:
6     int x1, y1, x2, y2;
7     static Rectangle empty;
8     Rectangle() {
9         x1 = y1 = x2 = y2 = 0;
10    }
11    Rectangle(int X1, int Y1, int X2, int Y2) {
12        x1 = X1;
13        y1 = Y1;
14        x2 = X2;
15        y2 = Y2;
16    }
17 };
18 struct Event {
19     int x, y1, y2, type;
20     Event() {}
21     Event(int x, int y1, int y2, int type): x(x), y1(y1), y2(y2), type
22         (type) {}
23 };
24 bool operator < (const Event&A, const Event&B) {
25     //if(A.x != B.x)
26     return A.x < B.x;
27     //if(A.y1 != B.y1) return A.y1 < B.y1;
28     //if(A.y2 != B.y2()) A.y2 < B.y2;
29 }
30 const int MX = (1 << 17);
31 struct Node {
32     int prob, sum, ans;
33     Node() {}
34     Node(int prob, int sum, int ans): prob(prob), sum(sum), ans(ans)
35     {}
36 };
37 Node tree[MX * 4];
38 int interval[MX];
39 void build(int x, int a, int b) {
40     tree[x] = Node(0, 0, 0);
41     if(a == b) {
42         tree[x].sum += interval[a];
43         return;
44     }
45     build(x * 2, a, (a + b) / 2);
46     build(x * 2 + 1, (a + b) / 2 + 1, b);
47     tree[x].sum = tree[x * 2].sum + tree[x * 2 + 1].sum;
48 }
49 int ask(int x) {
50     if(tree[x].prob)
51         return tree[x].sum;
52     return tree[x].ans;
53 }
54 int st, en, V;
55 void update(int x, int a, int b) {
56     if(st > b || en < a)
57         return;
58     if(a >= st && b <= en) {
59         tree[x].prob += V;
60         return;
61     }
62     update(x * 2, a, (a + b) / 2);
63     update(x * 2 + 1, (a + b) / 2 + 1, b);
64     tree[x].ans = ask(x * 2) + ask(x * 2 + 1);
65 }
66 Rectangle Rectangle::empty = Rectangle();
67 vector < Rectangle > Rect;
68 vector < int > sorted;
69 vector < Event > sweep;
70 void compressncalc() {
71     sweep.clear();
72     sorted.clear();
73     for(auto R : Rect) {
74         sorted.push_back(R.y1);
75         sorted.push_back(R.y2);
76     }
77     sort(sorted.begin(), sorted.end());
78     sorted.erase(unique(sorted.begin(), sorted.end()), sorted.end());
79     int sz = sorted.size();
80     for(int j = 0; j < sorted.size() - 1; j++)
81         interval[j + 1] = sorted[j + 1] - sorted[j];
82     for(auto R : Rect) {
83         sweep.push_back(Event(R.x1, R.y1, R.y2, 1));
84         sweep.push_back(Event(R.x2, R.y1, R.y2, -1));
85     }
86 }

```

```

83     }
84     sort(sweep.begin(), sweep.end());
85     build(1, 1, sz - 1);
86 }
87 long long ans;
88 void Sweep() {
89     ans = 0;
90     if(sorted.empty() || sweep.empty())
91         return;
92     int last = 0, sz_ = sorted.size();
93     for(int j = 0; j < sweep.size(); j++) {
94         ans += 1ll * (sweep[j].x - last) * ask(1);
95         last = sweep[j].x;
96         V = sweep[j].type;
97         st = lower_bound(sorted.begin(), sorted.end(), sweep[j].y1) -
98             sorted.begin() + 1;
99         en = lower_bound(sorted.begin(), sorted.end(), sweep[j].y2) -
100             sorted.begin();
101         update(1, 1, sz_ - 1);
102     }
103 }
104 int main() {
105     // freopen("in.in", "r", stdin);
106     int n;
107     scanf("%d", &n);
108     for(int j = 1; j <= n; j++) {
109         int a, b, c, d;
110         scanf("%d %d %d %d", &a, &b, &c, &d);
111         Rect.push_back(Rectangle(a, b, c, d));
112     }
113     compressncalc();
114     Sweep();
115     cout << ans << endl;
116 }

```

## 6 Graphs

### 6.1 2 SAT

```

1 /**
2  * Description: Calculates a valid assignment to boolean variables a,
3  * b, c, ... to a 2-SAT problem, so that an expression of the type $(
4  * a\|\b)\&\&(!a\|\c)\&\&(d\|\!b)\&\&...$ becomes true, or
5  * reports that it is unsatisfiable.
6  * Negated variables are represented by bit-inversions (\texttt{\tilde
7  * {x}}).
8  * Usage:
9  * TwoSat ts(number of boolean variables);
10  * ts.either(0, \tilde{3}); // Var 0 is true or var 3 is false
11  * ts.setValue(2); // Var 2 is true
12  * ts.atMostOne({0, \tilde{1}, 2}); // <= 1 of vars 0, \tilde{1} and 2 are
13  * true
14  * ts.solve(); // Returns true iff it is solvable
15  * ts.values[0..N-1] holds the assigned values to the vars
16  * Time: O(N+E), where N is the number of boolean variables, and E is
17  * the number of clauses.
18  */
19 struct TwoSat {
20     int N;
21     vector<vi> gr;
22     vi values; // 0 = false, 1 = true
23     TwoSat(int n = 0) : N(n), gr(2*n) {}
24
25     int addVar() { // (optional)
26         gr.emplace_back();
27         gr.emplace_back();
28         return N++;
29     }
30
31     void either(int f, int j) {
32         f = max(2*f, -1-2*f);
33         j = max(2*j, -1-2*j);
34         gr[f].push_back(j^1);
35         gr[j].push_back(f^1);
36     }
37
38     void setValue(int x) { either(x, x); }
39
40     void atMostOne(const vi& li) { // (optional)
41         if (sz(li) <= 1) return;
42     }
43 }

```

```

36     int cur = ~li[0];
37     rep(i,2,sz(li)) {
38         int next = addVar();
39         either(cur, ~li[i]);
40         either(cur, next);
41         either(~li[i], next);
42         cur = ~next;
43     }
44     either(cur, ~li[1]);
45 }
46
47 vi val, comp, z; int time = 0;
48 int dfs(int i) {
49     int low = val[i] = ++time, x; z.push_back(i);
50     for(int e : gr[i]) if (!comp[e])
51         low = min(low, val[e] ? dfs(e));
52     if (low == val[i]) do {
53         x = z.back(); z.pop_back();
54         comp[x] = low;
55         if (values[x>>1] == -1)
56             values[x>>1] = x&1;
57     } while (x != i);
58     return val[i] = low;
59 }
60
61 bool solve() {
62     values.assign(N, -1);
63     val.assign(2*N, 0); comp = val;
64     rep(i,0,2*N) if (!comp[i]) dfs(i);
65     rep(i,0,N) if (comp[2*i] == comp[2*i+1]) return 0;
66     return 1;
67 }
68 };

```

## 6.2 Articulation Point

```

1  vector<int> adj[N];
2  int dfsn[N], low[N], instack[N], ar_point[N], timer;
3  stack<int> st;
4
5  void dfs(int node, int par){
6      dfsn[node] = low[node] = ++timer;
7      int kam = 0;
8      for(auto i: adj[node]){
9          if(i == par) continue;
10         if(dfsn[i] == 0){
11             kam++;
12             dfs(i, node);
13             low[node] = min(low[node], low[i]);
14             if(dfsn[node] <= low[i] && par != 0) ar_point[node] = 1;
15         }
16         else low[node] = min(low[node], dfsn[i]);
17     }
18     if(par == 0 && kam > 1) ar_point[node] = 1;
19 }
20
21 int main(){
22     // Input
23     for(int i = 1; i <= n; i++){
24         if(dfsn[i] == 0) dfs(i, 0);
25     }
26     int c = 0;
27     for(int i = 1; i <= n; i++){
28         if(ar_point[i]) c++;
29     }
30     cout << c << '\n';
}

```

## 6.3 Bridges Tree and Diameter

```

1  #include <bits/stdc++.h>
2  #define ll long long
3  using namespace std;
4  const int N = 3e5 + 5, mod = 1e9 + 7;
5
6  vector<int> adj[N], bridge_tree[N];
7  int dfsn[N], low[N], cost[N], timer, cnt, comp_id[N], kam[N], ans;
8  stack<int> st;
9
10 void dfs(int node, int par){
11     dfsn[node] = low[node] = ++timer;
12     st.push(node);
13     for(auto i: adj[node]){

```

```

15         if(i == par) continue;
16         if(dfsn[i] == 0){
17             dfs(i, node);
18             low[node] = min(low[node], low[i]);
19         }
20         else low[node] = min(low[node], dfsn[i]);
21     }
22     if(dfsn[node] == low[node]){
23         cnt++;
24         while(1){
25             int cur = st.top();
26             st.pop();
27             comp_id[cur] = cnt;
28             if(cur == node) break;
29         }
30     }
31 }
32
33 void dfs2(int node, int par){
34     kam[node] = 0;
35     int mx = 0, second_mx = 0;
36     for(auto i: bridge_tree[node]){
37         if(i == par) continue;
38         dfs2(i, node);
39         kam[node] = max(kam[node], 1 + kam[i]);
40         if(kam[i] > mx){
41             second_mx = mx;
42             mx = kam[i];
43         }
44         else second_mx = max(second_mx, kam[i]);
45     }
46     ans = max(ans, kam[node]);
47     if(second_mx) ans = max(ans, 2 + mx + second_mx);
48 }
49
50 int main(){
51     ios_base::sync_with_stdio(0); cin.tie(0); cout.tie(0);
52     int n, m;
53     cin >> n >> m;
54     while(m--){
55         int u, v;
56         cin >> u >> v;
57         adj[u].push_back(v);
58         adj[v].push_back(u);
59     }
60     dfs(1, 0);
61     for(int i = 1; i <= n; i++){
62         for(auto j: adj[i]){
63             if(comp_id[i] != comp_id[j]){
64                 bridge_tree[comp_id[i]].push_back(comp_id[j]);
65             }
66         }
67     }
68     dfs2(1, 0);
69     cout << ans;
70
71     return 0;
72 }

```

## 6.4 Dinic With Scalling

```

1  ///O(ElgFlow) on Bipratite Graphs and O(EVlgFlow) on other graphs (I
2  think)
3  struct Dinic {
4      #define vi vector<int>
5      #define rep(i,a,b) f(i,a,b)
6      struct Edge {
7          int to, rev;
8          ll c, oc;
9          int id;
10         ll flow() { return max(oc - c, 0LL); } // if you need flows
11     };
12     vi lvl, ptr, q;
13     vector<vector<Edge>> adj;
14     Dinic(int n) : lvl(n), ptr(n), q(n), adj(n) {}
15     void addEdge(int a, int b, ll c, int id, ll rcap = 0) {
16         adj[a].push_back({b, sz(adj[b]), c, c, id});
17         adj[b].push_back({a, sz(adj[a]) - 1, rcap, rcap, id});
18     }
19     ll dfs(int v, int t, ll f) {

```

```

20     for (int& i = ptr[v]; i < sz(adj[v]); i++) {
21         Edge& e = adj[v][i];
22         if (lvl[e.to] == lvl[v] + 1)
23             if (ll p = dfs(e.to, t, min(f, e.c))) {
24                 e.c -= p, adj[e.to][e.rev].c += p;
25                 return p;
26             }
27     }
28     return 0;
29 }
30 ll calc(int s, int t) {
31     ll flow = 0; q[0] = s;
32     rep(L, 0, 31) do { // 'int L=30' maybe faster for random data
33         lvl = ptr = vi(sz(q));
34         int qi = 0, qe = lvl[s] = 1;
35         while (qi < qe && !lvl[t]) {
36             int v = q[qi++];
37             for (Edge e : adj[v])
38                 if (!lvl[e.to] && e.c >> (30 - L))
39                     q[qi++] = e.to, lvl[e.to] = lvl[v] + 1;
40         }
41         while (ll p = dfs(s, t, LLONG_MAX)) flow += p;
42     } while (lvl[t]);
43     return flow;
44 }
45 bool leftOfMinCut(int a) { return lvl[a] != 0; }
46 };

```

## 6.5 Gomory Hu

```

1  /**
2   * Author: chilli, Takanori MAEHARA
3   * Date: 2020-04-03
4   * License: CC0
5   * Source: https://github.com/spaghetti-source/algorithm/blob/master/
6   * graph/gomory_hu_tree.cc#L102
7   * Description: Given a list of edges representing an undirected flow
8   * graph,
9   * returns edges of the Gomory-Hu tree. The max flow between any pair
10  * of
11  * vertices is given by minimum edge weight along the Gomory-Hu tree
12  * path.
13  * Time:  $\mathcal{O}(V)$  Flow Computations
14  * Status: Tested on CERC 2015 J, stress-tested
15  *
16  * Details: The implementation used here is not actually the original
17  * Gomory-Hu, but Gusfield's simplified version: "Very simple methods
18  * for all
19  * pairs network flow analysis". PushRelabel is used here, but any
20  * flow
21  * implementation that supports 'leftOfMinCut' also works.
22  */
23 #pragma once
24
25 #include "PushRelabel.h"
26
27 typedef array<ll, 3> Edge;
28 vector<Edge> gomoryHu(int N, vector<Edge> ed) {
29     vector<Edge> tree;
30     vi par(N);
31     rep(i, 1, N) {
32         PushRelabel D(N); // Dinic also works
33         for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
34         tree.push_back({i, par[i], D.calc(i, par[i])});
35         rep(j, i+1, N)
36             if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
37     }
38     return tree;
39 }

```

## 6.6 HopcraftKarp BPM

```

1  /**
2   * Author: Chen Xing
3   * Date: 2009-10-13
4   * License: CC0
5   * Source: N/A
6   * Description: Fast bipartite matching algorithm. Graph $g$ should be
7   * a list
8   * of neighbors of the left partition, and $btoa$ should be a vector
9   * full of
10  * -1's of the same size as the right partition. Returns the size of

```

```

9  * the matching. $btoa[i]$ will be the match for vertex $i$ on the
10  * right side,
11  * or -1 if it's not matched.
12  * Usage: vi btoa(m, -1); hopcroftKarp(g, btoa);
13  * Time:  $\mathcal{O}(\sqrt{V}E)$ 
14  * Status: stress-tested by MinimumVertexCover, and tested on
15  * oldkattis.adkbipmatch and SPOJ:MATCHING
16  */
17 #pragma once
18
19 bool dfs(int a, int L, vector<vi>& g, vi& btoa, vi& A, vi& B) {
20     if (A[a] != L) return 0;
21     A[a] = -1;
22     for (int b : g[a]) if (B[b] == L + 1) {
23         B[b] = 0;
24         if (btoa[b] == -1 || dfs(btoa[b], L + 1, g, btoa, A, B))
25             return btoa[b] = a, 1;
26     }
27     return 0;
28 }
29
30 int hopcroftKarp(vector<vi>& g, vi& btoa) {
31     int res = 0;
32     vi A(g.size(), -1), B(btoa.size(), -1), cur, next;
33     for (;;) {
34         fill(all(A), 0);
35         fill(all(B), 0);
36         /// Find the starting nodes for BFS (i.e. layer 0).
37         cur.clear();
38         for (int a : btoa) if (a != -1) A[a] = -1;
39         rep(a, 0, sz(g)) if (A[a] == 0) cur.push_back(a);
40         /// Find all layers using bfs.
41         for (int lay = 1; lay++ <= cur.size()) {
42             bool islast = 0;
43             next.clear();
44             for (int a : cur) for (int b : g[a]) {
45                 if (btoa[b] == -1) {
46                     B[b] = lay;
47                     islast = 1;
48                 }
49                 else if (btoa[b] != a && !B[b]) {
50                     B[b] = lay;
51                     next.push_back(btoa[b]);
52                 }
53             }
54             if (islast) break;
55             if (next.empty()) return res;
56             for (int a : next) A[a] = lay;
57             cur.swap(next);
58         }
59         /// Use DFS to scan for augmenting paths.
60         rep(a, 0, sz(g))
61             res += dfs(a, 0, g, btoa, A, B);
62     }
63 }

```

## 6.7 Hungarian

```

1  /**
2   * Notes:
3   * note that n must be <= m
4   * so in case in your problem n >= m, just swap
5   * also note this
6   * void set(int x, int y, ll v) {a[x+1][y+1]=v;}
7   * the algorithm assumes you're using 0-index
8   * but it's using 1-based
9  */
10 struct Hungarian {
11     const ll INF = 1000000000000000000; ///10^18
12     int n, m;
13     vector<vector<ll>> > a;
14     vector<ll> u, v; vector<int> p, way;
15     Hungarian(int n, int m) :
16         n(n), m(m), a(n+1, vector<ll>(m+1, INF-1)), u(n+1), v(m+1), p(m+1), way(m+1) {}
17     void set(int x, int y, ll v) {a[x+1][y+1]=v;}
18     ll assign() {
19         for (int i = 1; i <= n; i++) {
20             int j0 = 0; p[0] = i;
21             vector<ll> minv(m+1, INF);
22             vector<char> used(m+1, false);
23             do {

```

```

24     used[j0]=true;
25     int i0=p[j0],j1;ll delta=INF;
26     for(int j = 1; j <= m; j++){if(!used[j]){
27         ll cur=a[i0][j]-u[i0]-v[j];
28         if(cur<minv[j])minv[j]=cur,way[j]=j0;
29         if(minv[j]<delta)delta=minv[j],j1=j;
30     }
31     for(int j = 0; j <= m; j++){
32         if(used[j])u[p[j]]+=delta,v[j]-=delta;
33         else minv[j]-=delta;
34         j0=j1;
35     } while(p[j0]);
36     do {
37         int j1=way[j0];p[j0]=p[j1];j0=j1;
38     } while(j0);
39 }
40 return -v[0];
41 }
42 vector<int> restoreAnswer() {    ///run it after assign
43     vector<int> ans (n+1);
44     for (int j=1; j<=m; ++j)
45         ans[p[j]] = j;
46     return ans;
47 }
48 };

```

## 6.8 Kosaraju

```

1  /*
2  3  g : Adjacency List of the original graph
4  4  rg : Reversed Adjacency List
5  5  vis : A bitset to mark visited nodes
6  6  adj : Adjacency List of the super graph
7  7  stk : holds dfs ordered elements
8  8  cmp[i] : holds the component of node i
9  9  go[i] : holds the nodes inside the strongly connected component i
10 */
11 #define FOR(i,a,b) for(int i = a; i < b; i++)
12 #define pb push_back
13
14 const int N = 1e5+5;
15
16 vector<vector<int>>g, rg;
17 vector<vector<int>>go;
18 bitset<N>vis;
19 vector<vector<int>>adj;
20 stack<int>stk;
21 int n, m, cmp[N];
22 void add_edge(int u, int v){
23     g[u].push_back(v);
24     rg[v].push_back(u);
25 }
26 void dfs(int u){
27     vis[u]=1;
28     for(auto v : g[u])if(!vis[v])dfs(v);
29     stk.push(u);
30 }
31 void rdfs(int u,int c){
32     vis[u] = 1;
33     cmp[u] = c;
34     go[c].push_back(u);
35     for(auto v : rg[u])if(!vis[v])rdfs(v,c);
36 }
37 int scc(){
38     vis.reset();
39     for(int i = 0; i < n; i++)if(!vis[i])
40         dfs(i);
41     vis.reset();
42     int c = 0;
43     while(stk.size()){
44         auto cur = stk.top();
45         stk.pop();
46         if(!vis[cur])
47             rdfs(cur,c++);
48     }
49 }
50 return c;
51 }

```

## 6.9 Manhattan MST

```

1  #include<bits/stdc++.h>
2  using namespace std;
3
4  const int N = 2e5 + 9;
5
6  int n;
7  vector<pair<int, int>> g[N];
8  struct PT {
9      int x, y, id;
10     bool operator < (const PT &p) const {
11         return x == p.x ? y < p.y : x < p.x;
12     }
13 } p[N];
14 struct node {
15     int val, id;
16 } t[N];
17 struct DSU {
18     int p[N];
19     void init(int n) { for (int i = 1; i <= n; i++) p[i] = i; }
20     int find(int u) { return p[u] == u ? u : p[u] = find(p[u]); }
21     void merge(int u, int v) { p[find(u)] = find(v); }
22 } dsu;
23 struct edge {
24     int u, v, w;
25     bool operator < (const edge &p) const { return w < p.w; }
26 };
27 vector<edge> edges;
28 int query(int x) {
29     int r = 2e9 + 10, id = -1;
30     for (; x <= n; x += (x & -x)) if (t[x].val < r) r = t[x].val, id = t[x].id;
31     return id;
32 }
33 void modify(int x, int w, int id) {
34     for (; x > 0; x -= (x & -x)) if (t[x].val > w) t[x].val = w, t[x].id = id;
35 }
36 int dist(PT &a, PT &b) {
37     return abs(a.x - b.x) + abs(a.y - b.y);
38 }
39 void add(int u, int v, int w) {
40     edges.push_back({u, v, w});
41 }
42 long long Kruskal() {
43     dsu.init(n);
44     sort(edges.begin(), edges.end());
45     long long ans = 0;
46     for (edge e : edges) {
47         int u = e.u, v = e.v, w = e.w;
48         if (dsu.find(u) != dsu.find(v)) {
49             ans += w;
50             g[u].push_back({v, w});
51             //g[v].push_back({u, w});
52             dsu.merge(u, v);
53         }
54     }
55     return ans;
56 }
57 void Manhattan() {
58     for (int i = 1; i <= n; ++i) p[i].id = i;
59     for (int dir = 1; dir <= 4; ++dir) {
60         if (dir == 2 || dir == 4) {
61             for (int i = 1; i <= n; ++i) swap(p[i].x, p[i].y);
62         }
63         else if (dir == 3) {
64             for (int i = 1; i <= n; ++i) p[i].x = -p[i].x;
65         }
66         sort(p + 1, p + 1 + n);
67         vector<int> v;
68         static int a[N];
69         for (int i = 1; i <= n; ++i) a[i] = p[i].y - p[i].x, v.push_back(a[i]);
70         sort(v.begin(), v.end());
71         v.erase(unique(v.begin(), v.end()), v.end());
72         for (int i = 1; i <= n; ++i) a[i] = lower_bound(v.begin(), v.end(), a[i]) - v.begin() + 1;
73         for (int i = 1; i <= n; ++i) t[i].val = 2e9 + 10, t[i].id = -1;
74         for (int i = n; i >= 1; --i) {
75             int pos = query(a[i]);
76             if (pos != -1) add(p[i].id, p[pos].id, dist(p[i], p[pos]));
77             modify(a[i], p[i].x + p[i].y, i);

```

```

78 }
79 }
80 }
81 int32_t main() {
82     ios_base::sync_with_stdio(0);
83     cin.tie(0);
84     cin >> n;
85     for (int i = 1; i <= n; i++) cin >> p[i].x >> p[i].y;
86     Manhattan();
87     cout << Kruskal() << '\n';
88     for (int u = 1; u <= n; u++) {
89         for (auto x: g[u]) cout << u - 1 << ' ' << x.first - 1 << '\n';
90     }
91     return 0;
92 }

```

## 6.10 Maximum Clique

```

1  ///Complexity  $O(3^{N/3})$  i.e works for 50
2  ///you can change it to maximum independent set by flipping the edges
   0->1, 1->0
3  ///if you want to extract the nodes they are 1-bits in R
4  int g[60][60];
5  int res;
6  long long edges[60];
7  void BronKerbosch(int n, long long R, long long P, long long X) {
8      if (P == 0LL && X == 0LL) { //here we will find all possible maximal
          cliques (not maximum) i.e. there is no node which can be
          included in this set
          int t = __builtin_popcountll(R);
          res = max(res, t);
          return;
      }
9      int u = 0;
10     while (!(1LL << u) & (P | X)) u++;
11     for (int v = 0; v < n; v++) {
12         if ((1LL << v) & P) && !((1LL << v) & edges[u]) {
13             BronKerbosch(n, R | (1LL << v), P & edges[v], X & edges[v]);
14             P |= (1LL << v);
15             X |= (1LL << v);
16         }
17     }
18 }
19
20 int max_clique (int n) {
21     res = 0;
22     for (int i = 1; i <= n; i++) {
23         edges[i - 1] = 0;
24         for (int j = 1; j <= n; j++) if (g[i][j]) edges[i - 1] |= (1LL
25             << (j - 1));
26     }
27     BronKerbosch(n, 0, (1LL << n) - 1, 0);
28     return res;
29 }

```

## 6.11 MCMF

```

1  /*
2   Notes:
3   make sure you notice the #define int ll
4   focus on the data types of the max flow everythign inside is
   integer
5   addEdge(u,v,cap,cost)
6   note that for min cost max flow the cost is sum of cost * flow
   over all edges
7  */
8
9  struct Edge {
10     int to;
11     int cost;
12     int cap, flow, backEdge;
13 };
14
15 struct MCMF {
16     const int inf = 1000000010;
17     int n;
18     vector<vector<Edge>> g;
19
20     MCMF(int _n) {
21         n = _n + 1;
22         g.resize(n);
23     }
24 }

```

```

25 void addEdge(int u, int v, int cap, int cost) {
26     Edge e1 = {v, cost, cap, 0, (int) g[v].size()};
27     Edge e2 = {u, -cost, 0, 0, (int) g[u].size()};
28     g[u].push_back(e1);
29     g[v].push_back(e2);
30 }
31
32 pair<int, int> minCostMaxFlow(int s, int t) {
33     int flow = 0;
34     int cost = 0;
35     vector<int> state(n), from(n), from_edge(n);
36     vector<int> d(n);
37     deque<int> q;
38     while (true) {
39         for (int i = 0; i < n; i++)
40             state[i] = 2, d[i] = inf, from[i] = -1;
41         state[s] = 1;
42         q.clear();
43         q.push_back(s);
44         d[s] = 0;
45         while (!q.empty()) {
46             int v = q.front();
47             q.pop_front();
48             state[v] = 0;
49             for (int i = 0; i < (int) g[v].size(); i++) {
50                 Edge e = g[v][i];
51                 if (e.flow >= e.cap || (d[e.to] <= d[v] + e.cost))
52                     continue;
53                 int to = e.to;
54                 d[to] = d[v] + e.cost;
55                 from[to] = v;
56                 from_edge[to] = i;
57                 if (state[to] == 1) continue;
58                 if (!state[to] || (!q.empty() && d[q.front()] > d[
59                     to]))
60                     q.push_front(to);
61                 else q.push_back(to);
62                 state[to] = 1;
63             }
64         }
65         if (d[t] == inf) break;
66         int it = t, addflow = inf;
67         while (it != s) {
68             addflow = min(addflow,
69                 g[from[it]][from_edge[it]].cap
70                 - g[from[it]][from_edge[it]].flow);
71             it = from[it];
72         }
73         it = t;
74         while (it != s) {
75             g[from[it]][from_edge[it]].flow += addflow;
76             g[it][g[from[it]][from_edge[it]].backEdge].flow -=
77                 addflow;
78             cost += g[from[it]][from_edge[it]].cost * addflow;
79             it = from[it];
80         }
81         flow += addflow;
82         return {cost, flow};
83     }
84 }

```

## 6.12 Minimum Arbrosce in a Graph

```

1  const int maxn = 2510, maxm = 7000000;
2  const ll maxint = 0x3f3f3f3f3f3f3f3fLL;
3
4  int n, ec, ID[maxn], pre[maxn], vis[maxn];
5  ll in[maxn];
6
7  struct edge_t {
8     int u, v;
9     ll w;
10 } edge[maxm];
11 void add(int u, int v, ll w) {
12     edge[++ec].u = u, edge[ec].v = v, edge[ec].w = w;
13 }
14
15 ll arborescence(int n, int root) {
16     ll res = 0, index;
17     while (true) {

```



```

18     for (int i = 1; i <= n; ++i) {
19         in[i] = maxint, vis[i] = -1, ID[i] = -1;
20     }
21     for (int i = 1; i <= ec; ++i) {
22         int u = edge[i].u, v = edge[i].v;
23         if (u == v || in[v] <= edge[i].w) continue;
24         in[v] = edge[i].w, pre[v] = u;
25     }
26     pre[root] = root, in[root] = 0;
27     for (int i = 1; i <= n; ++i) {
28         res += in[i];
29         if (in[i] == maxint) return -1;
30     }
31     index = 0;
32     for (int i = 1; i <= n; ++i) {
33         if (vis[i] != -1) continue;
34         int u = i, v;
35         while (vis[u] == -1) {
36             vis[u] = i;
37             u = pre[u];
38         }
39         if (vis[u] != i || u == root) continue;
40         for (v = u, u = pre[u], ++index; u != v; u = pre[u]) ID[u]
            = index;
41         ID[v] = index;
42     }
43     if (index == 0) return res;
44     for (int i = 1; i <= n; ++i) if (ID[i] == -1) ID[i] = ++index;
45     for (int i = 1; i <= ec; ++i) {
46         int u = edge[i].u, v = edge[i].v;
47         edge[i].u = ID[u], edge[i].v = ID[v];
48         edge[i].w -= in[v];
49     }
50     n = index, root = ID[root];
51 }
52 return res;
53 }

```

## 6.13 Minmimum Vertex Cover (Bipartite)

```

1  int myrandom (int i) { return std::rand()%i; }
2
3  struct MinimumVertexCover {
4      int n, id;
5      vector<vector<int>> g;
6      vector<int> color, m, seen;
7      vector<int> comp[2];
8      MinimumVertexCover() {}
9      MinimumVertexCover(int n, vector<vector<int>> g) {
10
11         this->n = n;
12         this->g = g;
13         color = m = vector<int>(n, -1);
14         seen = vector<int>(n, 0);
15         makeBipartite();
16     }
17
18     void dfsBipartite(int node, int col) {
19         if (color[node] != -1) {
20             assert(color[node] == col); /* MSH BIPARTITE YA
21                                     BASHMOHANDS */
22             return;
23         }
24         color[node] = col;
25         comp[col].push_back(node);
26         for (int i = 0; i < int(g[node].size()); i++)
27             dfsBipartite(g[node][i], 1 - col);
28     }
29
30     void makeBipartite() {
31         for (int i = 0; i < n; i++)
32             if (color[i] == -1)
33                 dfsBipartite(i, 0);
34     }
35
36     // match a node
37     bool dfs(int node) {
38         random_shuffle(g[node].begin(), g[node].end());
39         for (int i = 0; i < g[node].size(); i++) {
40             int child = g[node][i];
41             if (m[child] == -1) {

```

```

42                 m[child] = node;
43                 return true;
44             }
45             if (seen[child] == id)
46                 continue;
47             seen[child] = id;
48             int enemy = m[child];
49             m[node] = child;
50             m[child] = node;
51             m[enemy] = -1;
52             if (dfs(enemy))
53                 return true;
54             m[node] = -1;
55             m[child] = enemy;
56             m[enemy] = child;
57         }
58         return false;
59     }
60
61     void makeMatching() {
62         for (int j = 0; j < 5; j++)
63             random_shuffle(comp[0].begin(), comp[0].end(), myrandom);
64         for (int i = 0; i < int(comp[0].size()); i++) {
65             id++;
66             if (m[comp[0][i]] == -1)
67                 dfs(comp[0][i]);
68         }
69     }
70
71     void recurse(int node, int x, vector<int> &minCover, vector<int> &
72         done) {
73         if (m[node] != -1)
74             return;
75         if (done[node]) return;
76         done[node] = 1;
77         for (int i = 0; i < int(g[node].size()); i++) {
78             int child = g[node][i];
79             int newnode = m[child];
80             if (done[child]) continue;
81             if (newnode == -1) {
82                 continue;
83             }
84             done[child] = 2;
85             minCover.push_back(child);
86             m[newnode] = -1;
87             recurse(newnode, x, minCover, done);
88         }
89     }
90
91     vector<int> getAnswer() {
92         vector<int> minCover, maxIndep;
93         vector<int> done(n, 0);
94         makeMatching();
95         for (int x = 0; x < 2; x++)
96             for (int i = 0; i < int(comp[x].size()); i++) {
97                 int node = comp[x][i];
98                 if (m[node] == -1)
99                     recurse(node, x, minCover, done);
100             }
101
102         for (int i = 0; i < int(comp[0].size()); i++)
103             if (!done[comp[0][i]]) {
104                 minCover.push_back(comp[0][i]);
105             }
106         return minCover;
107     }
108 }

```

## 6.14 Prufer Code

```

1  const int N = 3e5 + 9;
2  /*
3  prufer code is a sequence of length n-2 to uniquely determine a
4  labeled tree with n vertices
5  Each time take the leaf with the lowest number and add the node number
6  the leaf is connected to
7  the sequence and remove the leaf. Then break the algo after n-2
8  iterations
9  */
10 //0-indexed
11 int n;
12 vector<int> g[N];

```

```

10 int parent[N], degree[N];
11
12 void dfs (int v) {
13     for (size_t i = 0; i < g[v].size(); ++i) {
14         int to = g[v][i];
15         if (to != parent[v]) {
16             parent[to] = v;
17             dfs (to);
18         }
19     }
20 }
21
22 vector<int> prufer_code() {
23     parent[n - 1] = -1;
24     dfs (n - 1);
25     int ptr = -1;
26     for (int i = 0; i < n; ++i) {
27         degree[i] = (int) g[i].size();
28         if (degree[i] == 1 && ptr == -1) ptr = i;
29     }
30     vector<int> result;
31     int leaf = ptr;
32     for (int iter = 0; iter < n - 2; ++iter) {
33         int next = parent[leaf];
34         result.push_back (next);
35         --degree[next];
36         if (degree[next] == 1 && next < ptr) leaf = next;
37         else {
38             ++ptr;
39             while (ptr < n && degree[ptr] != 1) ++ptr;
40             leaf = ptr;
41         }
42     }
43     return result;
44 }
45 vector < pair<int, int> > prufer_to_tree(const vector<int> &
46     prufer_code) {
47     int n = (int) prufer_code.size() + 2;
48     vector<int> degree (n, 1);
49     for (int i = 0; i < n - 2; ++i) ++degree[prufer_code[i]];
50
51     int ptr = 0;
52     while (ptr < n && degree[ptr] != 1) ++ptr;
53     int leaf = ptr;
54     vector < pair<int, int> > result;
55     for (int i = 0; i < n - 2; ++i) {
56         int v = prufer_code[i];
57         result.push_back (make_pair (leaf, v));
58         --degree[leaf];
59         if (--degree[v] == 1 && v < ptr) leaf = v;
60         else {
61             ++ptr;
62             while (ptr < n && degree[ptr] != 1) ++ptr;
63             leaf = ptr;
64         }
65     }
66     for (int v = 0; v < n - 1; ++v) if (degree[v] == 1) result.push_back
67         (make_pair (v, n - 1));
68     return result;
69 }

```

## 6.15 Push Relabel Max Flow

```

1 struct edge
2 {
3     int from, to, cap, flow, index;
4     edge(int from, int to, int cap, int flow, int index):
5         from(from), to(to), cap(cap), flow(flow), index(index) {}
6 };
7
8 struct PushRelabel
9 {
10     int n;
11     vector<vector<edge> > g;
12     vector<long long> excess;
13     vector<int> height, active, count;
14     queue<int> Q;
15
16     PushRelabel(int n):
17         n(n), g(n), excess(n), height(n), active(n), count(2*n) {}
18
19     void addEdge(int from, int to, int cap)

```

```

20 {
21     g[from].push_back(edge(from, to, cap, 0, g[to].size()));
22     if(from==to)
23         g[from].back().index++;
24     g[to].push_back(edge(to, from, 0, 0, g[from].size()-1));
25 }
26
27 void enqueue(int v)
28 {
29     if(!active[v] && excess[v] > 0)
30     {
31         active[v]=true;
32         Q.push(v);
33     }
34 }
35
36 void push(edge &e)
37 {
38     int amt=(int)min(excess[e.from], (long long)e.cap - e.flow);
39     if(height[e.from]<=height[e.to] || amt==0)
40         return;
41     e.flow += amt;
42     g[e.to][e.index].flow -= amt;
43     excess[e.to] += amt;
44     excess[e.from] -= amt;
45     enqueue(e.to);
46 }
47
48 void relabel(int v)
49 {
50     count[height[v]]--;
51     int d=2*n;
52     for(auto &it:g[v])
53     {
54         if(it.cap-it.flow>0)
55             d=min(d, height[it.to]+1);
56     }
57     height[v]=d;
58     count[height[v]]++;
59     enqueue(v);
60 }
61
62 void gap(int k)
63 {
64     for(int v=0;v<n;v++)
65     {
66         if(height[v]<k)
67             continue;
68         count[height[v]]--;
69         height[v]=max(height[v], n+1);
70         count[height[v]]++;
71         enqueue(v);
72     }
73 }
74
75 void discharge(int v)
76 {
77     for(int i=0; excess[v]>0 && i<g[v].size(); i++)
78         push(g[v][i]);
79     if(excess[v]>0)
80     {
81         if(count[height[v]]==1)
82             gap(height[v]);
83         else
84             relabel(v);
85     }
86 }
87
88 long long max_flow(int source, int dest)
89 {
90     count[0] = n-1;
91     count[n] = 1;
92     height[source] = n;
93     active[source] = active[dest] = 1;
94     for(auto &it:g[source])
95     {
96         excess[source]+=it.cap;
97         push(it);
98     }
99
100     while(!Q.empty())
101     {

```

```

102     int v=Q.front();
103     Q.pop();
104     active[v]=false;
105     discharge(v);
106 }
107
108 long long max_flow=0;
109 for(auto &e:g[source])
110     max_flow+=e.flow;
111
112 return max_flow;
113 }
114 };

```

## 6.16 Tarjan Algo

```

1  vector< vector<int> > scc;
2  vector<int> adj[N];
3  int dfsn[N], low[N], cost[N], timer, in_stack[N];
4  stack<int> st;
5
6  // to detect all the components (cycles) in a directed graph
7  void tarjan(int node){
8      dfsn[node] = low[node] = ++timer;
9      in_stack[node] = 1;
10     st.push(node);
11     for(auto i: adj[node]){
12         if(dfsn[i] == 0){
13             tarjan(i);
14             low[node] = min(low[node], low[i]);
15         }
16         else if(in_stack[i]) low[node] = min(low[node], dfsn[i]);
17     }
18     if(dfsn[node] == low[node]){
19         scc.push_back(vector<int>());
20         while(1){
21             int cur = st.top();
22             st.pop();
23             in_stack[cur] = 0;
24             scc.back().push_back(cur);
25             if(cur == node) break;
26         }
27     }
28 }
29 int main(){
30     int m;
31     cin >> m;
32     while(m--){
33         int u, v;
34         cin >> u >> v;
35         adj[u].push_back(v);
36     }
37     for(int i = 1; i <= n; i++){
38         if(dfsn[i] == 0){
39             tarjan(i);
40         }
41     }
42
43     return 0;
44 }

```

## 6.17 Bipartite Matching

```

1  // vertex are one based
2  struct graph
3  {
4      int L, R;
5      vector<vector<int> > adj;
6      graph(int l, int r) : L(l), R(r), adj(l+1) {}
7      void add_edge(int u, int v)
8      {
9          adj[u].push_back(v+L);
10     }
11     int maximum_matching()
12     {
13         vector<int> mate(L+R+1,-1), level(L+1);
14         function<bool (void)> levelize = [&]() {
15             {
16                 queue<int> q;
17                 for(int i=1; i<=L; i++)
18                     level[i]=-1;
19

```

```

20         if(mate[i]<0)
21             q.push(i), level[i]=0;
22     }
23     while(!q.empty())
24     {
25         int node=q.front();
26         q.pop();
27         for(auto i : adj[node])
28         {
29             int v=mate[i];
30             if(v<0)
31                 return true;
32             if(level[v]<0)
33             {
34                 level[v]=level[node]+1;
35                 q.push(v);
36             }
37         }
38     }
39     return false;
40 };
41 function<bool (int)> augment = [&](int node)
42 {
43     for(auto i : adj[node])
44     {
45         int v=mate[i];
46         if(v<0 || (level[v]>level[node] && augment(v)))
47         {
48             mate[node]=i;
49             mate[i]=node;
50             return true;
51         }
52     }
53     return false;
54 };
55 int match=0;
56 while(levelize())
57     for(int i=1; i<=L; i++)
58         if(mate[i] < 0 && augment(i))
59             match++;
60 return match;
61 }
62 };

```

## 7 Math

### 7.1 Sum Of Floor

```

1  // return sum_{i=0}^{n-1} floor((ai + b) / m) (mod 2^64)
2  #define ull unsigned long long
3  ull floor_sum_unsigned(ull n, ull m, ull a, ull b) {
4      ull ans = 0;
5      while (true) {
6          if (a >= m) {
7              ans += n * (n - 1) / 2 * (a / m);
8              a %= m;
9          }
10         if (b >= m) {
11             ans += n * (b / m);
12             b %= m;
13         }
14         ull y_max = a * n + b;
15         if (y_max < m) break;
16         // y_max < m * (n + 1)
17         // floor(y_max / m) <= n
18         n = (ull)(y_max / m);
19         b = (ull)(y_max % m);
20         std::swap(m, a);
21     }
22     return ans;
23 }

```

### 7.2 Xor With Gauss

```

1  void insertVector(int mask) {
2      for (int i = d - 1; i >= 0; i--) {
3          if ((mask & 1 << i) == 0) continue;
4          if (!basis[i]) {
5              basis[i] = mask;
6              return;

```

```

7         }
8         mask ^= basis[i];
9     }
10 }

```

## 7.3 Josephus

```

1 // n = total person
2 // will kill every kth person, if k = 2, 2,4,6,...
3 // returns the mth killed person
4 ll josephus(ll n, ll k, ll m) {
5     m = n - m;
6     if (k <= 1) return n - m;
7     ll i = m;
8     while (i < n) {
9         ll r = (i - m + k - 2) / (k - 1);
10        if ((i + r) > n) r = n - i;
11        else if (!r) r = 1;
12        i += r;
13        m = (m + (r * k)) % i;
14    } return m + 1;
15 }

```

## 7.4 Rabin Miller Primality check

```

1
2 // n < 4,759,123,141          3 : 2, 7, 61
3 // n < 1,122,004,669,633      4 : 2, 13, 23, 1662803
4 // n < 3,474,749,660,383      6 : pirmes <= 13
5 // n < 3,825,123,056,546,413,051 9 : primes <= 23
6
7 int testPrimes[] = {2,3,5,7,11,13,17,19,23};
8
9 struct MillerRabin{
10     ///change K according to n
11     const int K = 9;
12     ll mult(ll s, ll m, ll mod){
13         if(!m) return 0;
14         ll ret = mult(s, m/2, mod);
15         ret = (ret + ret) % mod;
16         if(m & 1) ret = (ret + s) % mod;
17         return ret;
18     }
19
20     ll power(ll x, ll p, ll mod){
21         ll s = 1, m = x;
22         while(p){
23             if(p&1) s = mult(s, m, mod);
24             p >>= 1;
25             m = mult(m, m, mod);
26         }
27         return s;
28     }
29
30     bool witness(ll a, ll n, ll u, int t){
31         ll x = power(a, u, n), nx;
32         for(int i = 0; i < t; i++){
33             nx = mult(x, x, n);
34             if(nx == 1 and x != 1 and x != n-1) return 1;
35             x = nx;
36         }
37         return x != 1;
38     }
39
40     bool isPrime(ll n){ // return 1 if prime, 0 otherwise
41         if(n < 2) return 0;
42         if(!(n&1)) return n == 2;
43         for(int i = 0; i < K; i++) if(n == testPrimes[i]) return 1;
44         ll u = n-1; int t = 0;
45
46         while(u&1) u >>= 1, t++; // n-1 = u*2^t
47
48         for(int i = 0; i < K; i++) if(witness(testPrimes[i], n, u, t))
49             return 0;
50         return 1;
51 }tester;

```

## 8 Strings

### 8.1 Aho-Corasick Mostafa

```

1 struct AC_FSM {
2     #define ALPHABET_SIZE 26
3
4     struct Node {
5         int child[ALPHABET_SIZE], failure = 0, match_parent = -1;
6         vector<int> match;
7
8         Node() {
9             for (int i = 0; i < ALPHABET_SIZE; ++i) child[i] = -1;
10        }
11    };
12
13    vector<Node> a;
14
15    AC_FSM() {
16        a.push_back(Node());
17    }
18
19    void construct_automaton(vector<string> &words) {
20        for (int w = 0, n = 0; w < words.size(); ++w, n = 0) {
21            for (int i = 0; i < words[w].size(); ++i) {
22                if (a[n].child[words[w][i] - 'a'] == -1) {
23                    a[n].child[words[w][i] - 'a'] = a.size();
24                    a.push_back(Node());
25                }
26                n = a[n].child[words[w][i] - 'a'];
27            }
28            a[n].match.push_back(w);
29        }
30        queue<int> q;
31        for (int k = 0; k < ALPHABET_SIZE; ++k) {
32            if (a[0].child[k] == -1) a[0].child[k] = 0;
33            else if (a[0].child[k] > 0) {
34                a[a[0].child[k]].failure = 0;
35                q.push(a[0].child[k]);
36            }
37        }
38        while (!q.empty()) {
39            int r = q.front();
40            q.pop();
41            for (int k = 0, arck; k < ALPHABET_SIZE; ++k) {
42                if ((arck = a[r].child[k]) != -1) {
43                    q.push(arck);
44                    int v = a[r].failure;
45                    while (a[v].child[k] == -1) v = a[v].failure;
46                    a[arck].failure = a[v].child[k];
47                    a[arck].match_parent = a[v].child[k];
48                    while (a[arck].match_parent != -1 &&
49                        a[a[arck].match_parent].match.empty())
50                        a[arck].match_parent =
51                            a[a[arck].match_parent].match_parent;
52                }
53            }
54        }
55    }
56
57    void aho_corasick(string &sentence, vector<string> &words,
58        vector<vector<int>> &matches) {
59        matches.assign(words.size(), vector<int>());
60        int state = 0, ss = 0;
61        for (int i = 0; i < sentence.length(); ++i, ss = state) {
62            while (a[ss].child[sentence[i] - 'a'] == -1)
63                ss = a[ss].failure;
64            state = a[ss].child[sentence[i] - 'a'];
65            sentence[i] - 'a';
66            for (ss = state; ss != -1; ss = a[ss].match_parent)
67                for (int w: a[ss].match)
68                    matches[w].push_back(i + 1 - words[w].length());
69        }
70    };

```

## 8.2 KMP Anany

```

1 vector<int> fail(string s) {
2     int n = s.size();
3     vector<int> pi(n);
4     for(int i = 1; i < n; i++) {
5         int g = pi[i-1];
6         while(g && s[i] != s[g])
7             g = pi[g-1];
8         g += s[i] == s[g];

```

```

9         pi[i] = g;
10     }
11     return pi;
12 }
13 vector<int> KMP(string s, string t) {
14     vector<int> pi = fail(t);
15     vector<int> ret;
16     for(int i = 0, g = 0; i < s.size(); i++) {
17         while (g && s[i] != t[g])
18             g = pi[g-1];
19         g += s[i] == t[g];
20         if(g == t.size()) { ///occurrence found
21             ret.push_back(i-t.size()+1);
22             g = pi[g-1];
23         }
24     }
25     return ret;
26 }

```

### 8.3 Manacher Kactl

```

1 /// If the size of palindrome centered at i is x, then dl[i] stores (x
2 +1)/2.
3 vector<int> dl(n);
4 for (int i = 0, l = 0, r = -1; i < n; i++) {
5     int k = (i > r) ? 1 : min(dl[l + r - i], r - i + 1);
6     while (0 <= i - k && i + k < n && s[i - k] == s[i + k]) {
7         k++;
8     }
9     dl[i] = k--;
10    if (i + k > r) {
11        l = i - k;
12        r = i + k;
13    }
14 }
15 /// If the size of palindrome centered at i is x, then d2[i] stores x/2
16 vector<int> d2(n);
17 for (int i = 0, l = 0, r = -1; i < n; i++) {
18     int k = (i > r) ? 0 : min(d2[l + r - i + 1], r - i + 1);
19     while (0 <= i - k - 1 && i + k < n && s[i - k - 1] == s[i + k]) {
20         k++;
21     }
22     d2[i] = k--;
23     if (i + k > r) {
24         l = i - k - 1;
25         r = i + k;
26     }
27 }
28 }

```

### 8.4 Suffix Array Kactl

```

1 struct SuffixArray {
2     using vi = vector<int>;
3     #define rep(i,a,b) for(int i = a; i < b; i++)
4     #define all(x) begin(x), end(x)
5     /*
6     Note this code is considers also the empty suffix
7     so hear sa[0] = n and sa[1] is the smallest non empty suffix
8     and sa[n] is the largest non empty suffix
9     also LCP[i] = LCP(sa[i-1], sa[i]), meaning LCP[0] = LCP[1] =
10    0
11    if you want to get LCP(i..j) you need to build a mapping
12    between
13    sa[i] and i, and build a min sparse table to calculate the
14    minimum
15    note that this minimum should consider sa[i+1...j] since you
16    don't want
17    to consider LCP(sa[i], sa[i-1])
18    you should also print the suffix array and lcp at the
19    beginning of the contest
20    to clarify this stuff
21    */
22    vi sa, lcp;
23    SuffixArray(string& s, int lim=256) { /// or basic_string<int>
24        int n = sz(s) + 1, k = 0, a, b;
25        vi x(all(s)+1), y(n), ws(max(n, lim)), rank(n);
26        sa = lcp = y, iota(all(sa), 0);
27        for (int j = 0, p = 0; p < n; j = max(1, j * 2), lim = p) {
28            p = j, iota(all(y), n - j);
29            rep(i,0,n) if (sa[i] >= j) y[p++] = sa[i] - j;

```

```

26        fill(all(ws), 0);
27        rep(i,0,n) ws[x[i]]++;
28        rep(i,1,lim) ws[i] += ws[i - 1];
29        for (int i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
30        swap(x, y), p = 1, x[sa[0]] = 0;
31        rep(i,1,n) a = sa[i - 1], b = sa[i], x[b] =
32            (y[a] == y[b] && y[a + j] == y[b + j]) ? p - 1 : p++;
33    }
34    rep(i,1,n) rank[sa[i]] = i;
35    for (int i = 0, j; i < n - 1; lcp[rank[i++]] = k)
36        for (k && k--, j = sa[rank[i] - 1];
37             s[i + k] == s[j + k]; k++);
38    }
39 }

```

### 8.5 Suffix Automaton Mostafa

```

1 struct SA {
2     struct node {
3         int to[26];
4         int link, len, co = 0;
5     };
6     node() {
7         memset(to, 0, sizeof to);
8         co = 0, link = 0, len = 0;
9     };
10 };
11 int last, sz;
12 vector<node> v;
13 SA() {
14     v = vector<node>(1);
15     last = 0, sz = 1;
16 }
17 void add_letter(int c) {
18     int p = last;
19     last = sz++;
20     v.push_back({});
21     v[last].len = v[p].len + 1;
22     v[last].co = 1;
23     for (; v[p].to[c] == 0; p = v[p].link)
24         v[p].to[c] = last;
25     if (v[p].to[c] == last) {
26         v[last].link = 0;
27         return;
28     }
29     int q = v[p].to[c];
30     if (v[q].len == v[p].len + 1) {
31         v[last].link = q;
32         return;
33     }
34     int cl = sz++;
35     v.push_back(v[q]);
36     v.back().co = 0;
37     v.back().len = v[p].len + 1;
38     v[last].link = v[q].link = cl;
39     for (; v[p].to[c] == q; p = v[p].link)
40         v[p].to[c] = cl;
41 }
42 void build_co() {
43     priority_queue<pair<int, int>> q;
44     for (int i = sz - 1; i > 0; i--)
45         q.push({v[i].len, i});
46     while (q.size()) {
47         int i = q.top().second;
48         q.pop();
49         v[v[i].link].co += v[i].co;
50     }
51 }
52 }
53 };

```

### 8.6 Zalgo Anany

```

1 int z[N], n;
2 void Zalgo(string s) {
3     int L = 0, R = 0;
4     for(int i = 1; i < n; i++) {

```

```

5     if(i<=R&&z[i-L] < R - i + 1) z[i] = z[i-L];
6     else {
7         L = i;
8         R = max(R,i);
9         while(R < n && s[R-L] == s[R]) R++;
10        z[i] = R-L; --R;
11    }
12 }
13 }

```

## 8.7 lexicographically smallest rotation of a string

```

1 int minRotation(string s) {
2     int a=0, N=sz(s); s += s;
3     rep(b,0,N) rep(k,0,N) {
4         if (a+k == b || s[a+k] < s[b+k]) {b += max(0, k-1); break;}
5         if (s[a+k] > s[b+k]) { a = b; break; }
6     }
7     return a;
8 }

```

## 9 Trees

### 9.1 Centroid Decomposition

```

1  /*
2   Properties:
3   1. consider path(a,b) can be decomposed to path(a,lca(a,b))
4      and path(b,lca(a,b))
5   2. Each one of the n^2 paths is the concatenation of two paths
6      in a set of O(n lg(n))
7   3. paths from a node to all its ancestors in the centroid
8      decomposition.
9   3. Ancestor of a node in the original tree is either an
10      ancestor in the CD tree or
11      a descendant
12 */
13 vector<int> adj[N]; //adjacency list of original graph
14 int n;
15 int sz[N];
16 bool used[N];
17 int centPar[N]; //parent in centroid
18 void init(int node, int par) { //initialize size
19     sz[node] = 1;
20     for(auto p : adj[node])
21         if(p != par && !used[p]) {
22             init(p, node);
23             sz[node] += sz[p];
24         }
25 }
26 int centroid(int node, int par, int limit) { //get centroid
27     for(int p : adj[node])
28         if(!used[p] && p != par && sz[p] * 2 > limit)
29             return centroid(p, node, limit);
30     return node;
31 }
32 int decompose(int node) {
33     init(node,node); //calculate size
34     int c = centroid(node, node, sz[node]); //get centroid
35     used[c] = true;
36     for(auto p : adj[c]) if(!used[p.F]) { //initialize parent for
37         others and decompose
38         centPar[decompose(p.F)] = c;
39     }
40     return c;
41 }
42 void update(int node, int distance, int col) {
43     int centroid = node;
44     while(centroid) {
45         //solve
46         centroid = centPar[centroid];
47     }
48 }
49 int query(int node) {
50     int ans = 0;
51     int centroid = node;
52     while(centroid) {

```

```

51         //solve
52         centroid = centPar[centroid];
53     }
54     return ans;
55 }
56 }

```

### 9.2 Dsu On Trees

```

1 const int N = 1e5 + 9;
2 vector<int> adj[N];
3 int bigChild[N], sz[N];
4 void dfs(int node, int par) {
5     for(auto v : adj[node]) if(v != par) {
6         dfs(v, node);
7         sz[node] += sz[v];
8         if(!bigChild[node] || sz[v] > sz[bigChild[node]]) {
9             bigChild[node] = v;
10        }
11    }
12 }
13 void add(int node, int par, int bigChild, int delta) {
14     //modify node to data structure
15     for(auto v : adj[node])
16         if(v != par && v != bigChild)
17             add(v, node, bigChild, delta);
18 }
19 void dfs2(int node, int par, bool keep) {
20     for(auto v : adj[node]) if(v != par && v != bigChild[node]) {
21         dfs2(v, node, 0);
22     }
23     if(bigChild[node]) {
24         dfs2(bigChild[node], node, true);
25     }
26     add(node, par, bigChild[node], 1);
27     //process queries
28     if(!keep) {
29         add(node, par, -1, -1);
30     }
31 }
32 }
33 }
34 }

```

### 9.3 Heavy Light Decomposition (Along with Euler Tour)

```

1  /*
2   Notes:
3   1. 0-based
4   2. solve function iterates over segments and handles them
5      seperately
6   3. if you're gonna use it make sure you know what you're doing
7   4. to update/query segment in[node], out[node]
8   4. to update/query chain in[nxt[node]], in[node]
9   4. nxt[node]: is the head of the chain so to go to the next chain
10      node = par[nxt[node]]
11 */
12 int sz[mxN], nxt[mxN];
13 int in[N], out[N], rin[N];
14 vector<int> g[mxN];
15 int par[mxN];
16 void dfs_sz(int v = 0, int p = -1) {
17     sz[v] = 1;
18     par[v] = p;
19     for (auto &u : g[v]) {
20         if (u == p) continue;
21         dfs_sz(u,v);
22         sz[v] += sz[u];
23         if (sz[u] > sz[g[v][0]])
24             swap(u, g[v][0]);
25     }
26     if(v != 0)
27         g[v].pop_back();
28 }
29 void dfs_hld(int v = 0) {
30     in[v] = t++;
31     rin[in[v]] = v;
32 }
33 }
34 }

```



```

35     for (auto u : g[v]) {
36         nxt[u] = (u == g[v][0] ? nxt[v] : u);
37         dfs_hld(u);
38     }
39     out[v] = t;
40 }
41
42 int n;
43 bool isChild(int p, int u) {
44     return in[p] <= in[u] && out[u] <= out[p];
45 }
46 int solve(int u, int v) {
47     vector<pair<int, int>> segu;
48     vector<pair<int, int>> segv;
49     if (isChild(u, v)) {
50         while (nxt[u] != nxt[v]) {
51             segv.push_back(make_pair(in[nxt[v]], in[v]));
52             v = par[nxt[v]];
53         }
54         segv.push_back({in[u], in[v]});
55     } else if (isChild(v, u)) {
56         while (nxt[u] != nxt[v]) {
57             segu.push_back(make_pair(in[nxt[u]], in[u]));
58             u = par[nxt[u]];
59         }
60         segu.push_back({in[v], in[u]});
61     } else {
62         while (u != v) {
63             if (nxt[u] == nxt[v]) {
64                 if (in[u] < in[v]) segv.push_back({in[u], in[v]}), R.push_back({u+1, v+1});
65                 else segu.push_back({in[v], in[u]}), L.push_back({v+1, u+1});
66                 u = v;
67                 break;
68             } else if (in[u] > in[v]) {
69                 segu.push_back({in[nxt[u]], in[u]}), L.push_back({nxt[u]+1, u+1});
70                 u = par[nxt[u]];
71             } else {
72                 segv.push_back({in[nxt[v]], in[v]}), R.push_back({nxt[v]+1, v+1});
73                 v = par[nxt[v]];
74             }
75         }
76     }
77     reverse(segv.begin(), segv.end());
78     int res = 0, state = 0;
79     for (auto p : segu) {
80         qry(1, 1, 0, n-1, p.first, p.second, state, res);
81     }
82     for (auto p : segv) {
83         qry(0, 1, 0, n-1, p.first, p.second, state, res);
84     }
85     return res;
86 }

```

## 9.4 Mo on Trees

```

1 // Calculate the DFS order, {1, 2, 3, 3, 4, 4, 2, 5, 6, 6, 5, 1}.
2 // Let a query be (u, v), ST(u) <= ST(v), P = LCA(u, v)
3 // Case 1: P = u : the query range would be [ST(u), ST(v)]
4 // Case 2: P != u : range would be [EN(u), ST(v)] + [ST(P), ST(P)].
5 // the path will be the nodes that appears exactly once in that range

```

## 10 Numerical

### 10.1 Lagrange Polynomial

```

1 class LagrangePoly {
2 public:
3     LagrangePoly(std::vector<long long> _a) {
4         //f(i) = _a[i]
5         //interpola o vetor em um polinomio de grau y.size() - 1
6         y = _a;
7         den.resize(y.size());
8         int n = (int) y.size();
9         for (int i = 0; i < n; i++) {
10             y[i] = (y[i] % MOD + MOD) % MOD;
11             den[i] = ifat[n - i - 1] * ifat[i] % MOD;
12             if ((n - i - 1) % 2 == 1) {

```

```

13                 den[i] = (MOD - den[i]) % MOD;
14             }
15         }
16     }
17
18     long long getVal(long long x) {
19         int n = (int) y.size();
20         x = (x % MOD + MOD) % MOD;
21         if (x < n) {
22             //return y[(int) x];
23         }
24         std::vector<long long> l, r;
25         l.resize(n);
26         l[0] = 1;
27         for (int i = 1; i < n; i++) {
28             l[i] = l[i - 1] * (x - (i - 1) + MOD) % MOD;
29         }
30         r.resize(n);
31         r[n - 1] = 1;
32         for (int i = n - 2; i >= 0; i--) {
33             r[i] = r[i + 1] * (x - (i + 1) + MOD) % MOD;
34         }
35         long long ans = 0;
36         for (int i = 0; i < n; i++) {
37             long long coef = l[i] * r[i] % MOD;
38             ans = (ans + coef * y[i] % MOD * den[i]) % MOD;
39         }
40         return ans;
41     }
42
43 private:
44     std::vector<long long> y, den;
45 };

```

## 11 Guide

### 11.1 Notes

- Don't forget to solve the problem in reverse (i.e deleting->adding or adding->deleting, ...etc)
- Max flow is just choosing the maximum number of paths between source and sink
- If you have a problem that tells you choose a[i] or b[i] (or a range) choose one of them initially and play a take or leave on the other
- If the problem tells you to do something cyclic solving it for  $x + x$
- Problems that are close to NP problems sometimes have greedy solutions for large input i.e  $n \leq 20-30$
- in case of merging between sets try bitsets (i.e  $i + j$  or sth)
- If you have a TLE soln using bitset might help
- If everything else fails think Brute force or randomization

### 11.2 Assignment Problems

- If you see a problem that tells you out of N choose K that has some property (think flows or aliens trick)
- If you see a problem that tells for some X choose a Y (think flows)

- If the problem tells you to choose a Y from L-R (think range flow i.e putting edges between the same layer)

### 11.3 XOR problems

- If the problem tells you something about choosing an XOR of a subset (think FWHT or XOR-basis)
- If the problem tells you about getting XOR of a tree path let  $a[i]$  = XOR tree from root to i and solve this as an array
- If the problem tells you range XOR sth it's better to have prefix XOR and make it pairs XOR.

### 11.4 Decompositions

- If a problem is asking you to calculate the answer after K steps you can calculate the answer for K
- If the number of queries is significantly larger than updates or vice versa you can use square root Decompositions to give advantage to one over the other

### 11.5 Strings

- Longest Common Substring is easier with suffix automaton
- Problems that tell you count stuff that appears X times or count appearances (Use suffix links)
- Problems that tell you find the largest substring with some property (Use Suffix links)
- Remember suffix links are the same as aho corasick failure links (you can memoize them with dp)
- Problems that ask you to get the k-th string (can be either suffix automaton or array)
- Longest Common Prefix is mostly a (suffix automaton-array) thing
- try thinking bitsets

### 11.6 Trees

- For problems that ask you to count stuff in a subtree think (Euler Tour with RQ - Small to Large - DSU on Trees - PersistentSegTree)
- Note that the farthest node to any node in the tree is one of the two diameter heads
- In case of asking  $F(\text{node}, x)$  for each node it's probably DP on Trees

### 11.7 Flows

- If you want to make a K-covering instead of considering lit edges consider non-lit edges
- To get mincost while maintaining a flow network (note that flows are batched together according to cost)
- If the problem asks you to choose some stuff that minimizes use Min Cut (If maximizes sum up stuff and subtract min cut)

### 11.8 Geometry

- Manhattan to King distance  $(x,y) \rightarrow (x+y, x-y)$
- Lattice points on line:  $\gcd(dx, dy) + 1$
- Pick's theorem:  $A = I + \frac{B}{2} - 1$
- cosine rule:  $C^2 = A^2 + B^2 - 2AB \times \cos(c)$
- Rotation around axis:  $R = (\cos(a) \times Id + \sin(a) \times \text{cross}U + (1 - \cos(a)) \times \text{outer}U)$
- Triangulation of n-gon = Catalan (n-2)

### 11.9 Area

- triangle =  $\sqrt{(S \times (S - A) \times (S - B) \times (S - C))}$ ,  $S = \text{PERIMETER}/2$
- triangle =  $r \times S$ , r = radius of inscribed circle
- ellipse =  $\pi \times r_1 \times r_2$
- sector =  $\frac{(r^2 \times a)}{2}$
- circular cap =  $\frac{R^2 \times (a - \sin(a))}{2}$
- prism =  $\text{perimeter}(B)L + 2\text{area}(B)$
- sphere =  $4\pi r^2$

### 11.10 Volume

- Right circular cylinder =  $\pi r^2 h$
- Pyramid =  $\frac{Bh}{3}$
- Right circular cone =  $\frac{\pi r^2 h}{3}$
- Sphere =  $\frac{4}{3}\pi r^2 h$
- Sphere sector =  $\frac{2}{3}\pi r^2 h = \frac{2}{3}\pi r^3(1 - \cos(a))$
- Sphere cap =  $\frac{\pi h^2(3r-h)}{3}$

### 11.11 Combinatorics

- Cayley formula: number of forest with k trees where first k nodes belongs to different trees =  $kn^{n-k-1}$ . Multinomial theorem for trees of given degree sequence  $\binom{n}{d_i}$
- Prufer sequence (M5da calls it parent array)
- K-Cyclic permutation =  $\binom{n}{k} \times (k-1)!$
- Stirling numbers  $S(n, k) = k \times S(n-1, k) + S(n, k-1)$  number of way to partition n in k sets.
- Bell number  $B_n = \sum_1^n (n-1, k) B_k$
- # ways to make a graph with k components connected  $n^{k-2} \times \prod_{i=1}^k s_i$
- Arithmetic-geometric-progression  $S_n = \frac{A_1 \times G_1 - A_{n+1} \times G_{n+1}}{1-r} + \frac{dr}{(1-r)^2} \times (G_1 - G_{n+1})$

### 11.12 Graph Theory

- Graph realization problem: sorted decreasing degrees:  $\sum_1^k d_i = k(k-1) + \sum_{i=k+1}^n \min(d_i, k)$  (first k form clique and all other nodes are connected to them).
- Euler formula:  $v + f = e + c + 1$
- # perfect matching in bipartite graph,  $DP[S][j] = DP[S][j-1] + DP[S/v][j-1]$  for all v connected to the j node.

### 11.13 Max flow with lower bound

- feasible flow in a network with both upper and lower capacity constraints, no source or sink: capacities are changed to upper bound - lower bound. Add a new source and a sink. let  $M[v] = (\text{sum of lower bounds of ingoing edges to } v) - (\text{sum of lower bounds of outgoing edges from } v)$ . For all v, if  $M[v] < 0$  then add edge (S,v) with capacity  $M[v]$ , otherwise add (v,T) with capacity  $-M[v]$ . If all outgoing edges from S are full, then a feasible flow exists, it is the flow plus the original lower bounds.
- maximum flow in a network with both upper and lower capacity constraints, with source s and sink t: add edge (t,s) with capacity infinity. Binary search for the lower bound, check whether a feasible exists for a network WITHOUT source or sink (B).

### 11.14 Joseph problem

$$g(n, k) = \begin{cases} 0 & \text{if } n = 1 \\ (g(n-1, k) + k) \bmod n & \text{if } 1 < n < k \\ \left\lfloor \frac{k((g(n', k) - n \bmod k) \bmod n')}{k-1} \right\rfloor \text{ where } n' = n - \left\lfloor \frac{n}{k} \right\rfloor & \text{if } k \leq n \end{cases}$$