

# Faculty of Computer and Information Sciences, Ain Shams University: Too Wrong to Pass Too Correct to Fail

Pillow, Isaac, Mostafa, Islam

## Contents

2021

<b>1</b>	<b>Template</b>	
1.1	template	
<b>2</b>	<b>Combinatorics</b>	
2.1	Burnside Lemma	
2.2	Catlan Numbers	
<b>3</b>	<b>Algebra</b>	
3.1	Gray Code	
3.2	Primitive Roots	
3.3	Discrete Logarithm minimum x for which $a^x = b \pmod m$	
3.4	Discrete Root finds all numbers x such that $x^k = a \pmod n$	
3.5	Factorial modulo in $p \cdot \log(n)$ (Wilson Theroem)	
3.6	Iteration over submasks	
3.7	Totient function	
3.8	CRT and EGCD	
3.9	FFT	
3.10	FFT with mod	
3.11	convolutions of AND-XOR-OR	
3.12	NTT of KACTL	
3.13	Fibonacci	
3.14	Gauss Determinant	
3.15	GAUSS SLAE	
3.16	Matrix Inverse	
<b>4</b>	<b>Data Structures</b>	
4.1	UnionFindRollback	
4.2	2D BIT	
4.3	2D Sparse table	
4.4	Mo With Updates	
4.5	Ordered Set	
4.6	Persistent Seg Tree	
4.7	Treap	
4.8	Wavelet Tree	
4.9	SparseTable	
<b>5</b>	<b>DP</b>	
5.1	CHT Line Container	
<b>6</b>	<b>Geometry</b>	
6.1	Convex Hull	
6.2	Geometry Template	
6.3	Half Plane Intersection	
6.4	Segments Intersection	
6.5	Rectangles Union	
<b>7</b>	<b>Graphs</b>	
7.1	2 SAD	
7.2	Ariculation Point	
7.3	Bridges Tree and Diameter	
7.4	Dinic With Scalling	
7.5	Gomory Hu	
7.6	HopcraftKarp BPM	
7.7	Hungarian	
7.8	Kosaraju	
7.9	Manhattan MST	
7.10	Maximum Clique	
7.11	MCMF	
7.12	Minnimum Vertex Cover (Bipartite)	
7.13	Prufer Code	

7.14	Push Relabel Max Flow	13
7.15	Tarjan Algo	14
7.16	Bipartite Matching	14
<b>8</b>	<b>Math</b>	15
8.1	Sum Of floored division.	15
8.2	ModMulLL	15
8.3	MillerRabin Primality check	15
8.4	Pollard-rho randomized factorization algorithm $O(n^{1/4})$	15
8.5	ModSqrt Finds x s.t $x^2 = a \pmod p$	15
8.6	Xor With Gauss	15
8.7	Josephus	15
<b>9</b>	<b>Strings</b>	15
9.1	Aho-Corasick Mostafa	15
9.2	KMP Anany	16
9.3	Manacher Kactl	16
9.4	Suffix Array Kactl	16
9.5	Suffix Automaton Mostafa	16
9.6	Zalgo Anany	17
9.7	lexicographically smallest rotation of a string	17
<b>10</b>	<b>Trees</b>	17
10.1	Centroid Decomposition	17
10.2	Dsu On Trees	17
10.3	Heavy Light Decomposition (Along with Euler Tour)	18
10.4	Mo on Trees	18
<b>11</b>	<b>Numerical</b>	18
11.1	Lagrange Polynomial	18
11.2	Polynomials	18
<b>12</b>	<b>Guide</b>	19
12.1	Strings	19
12.2	Volume	19
12.3	Graph Theory	19
12.4	Joseph problem	19

## 1 Template

### 1.1 template

```

1 #include <bits/stdc++.h>
2 #define IO ios_base::sync_with_stdio(0); cin.tie(0); cout.tie(0);
3 using namespace std;
4 mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());
5
6 // Kactl defines
7 #define rep(i, a, b) for(int i = a; i < (b); ++i)
8 #define all(x) begin(x), end(x)
9 #define sz(x) (int)(x).size()
10 typedef long long ll;
11 typedef pair<int, int> pii;
12 typedef vector<int> vi;
13 typedef vector<double> vd;

```

## 2 Combinatorics

### 2.1 Burnside Lemma

```

1 // |Classes|=sum (k ^C(pi)) / |G|
2 // C(pi) the number of cycles in the permutation pi
3 // |G| the number of permutations

```

### 2.2 Catlan Numbers

```

1 void init() {
2     catalan[0] = catalan[1] = 1;
3     for (int i=2; i<=n; i++) {
4         catalan[i] = 0;
5         for (int j=0; j < i; j++) {
6             catalan[i] += (catalan[j] * catalan[i-j-1]) % MOD;
7             if (catalan[i] >= MOD) {
8                 catalan[i] -= MOD;
9             }
10        }
11    }

```

```

10     }
11 }
12 }
13 // 1- Number of correct bracket sequence consisting of n opening and n closing
    brackets.
14 // 2- The number of rooted full binary trees with n+1 leaves (vertices are not
    numbered).
15 // 3- The number of ways to completely parenthesize n+1 factors.
16 // 4- The number of triangulations of a convex polygon with n+2 sides
17 // 5- The number of ways to connect the 2n points on a circle to form n disjoint
    chords.
18 // 6- The number of non-isomorphic full binary trees with n internal nodes (i.e.
    nodes having at least one son).
19 // 7- The number of monotonic lattice paths from point (0,0) to point (n,n) in a
    square lattice of size nxn, which do not pass above the main diagonal (i.e
    . connecting (0,0) to (n,n)).
20 // 8- Number of permutations of length n that can be stack sorted (it can be
    shown that the rearrangement is stack sorted if and only if there is no
    such index i<j<k, such that ak<ai<aj).
21 // 9- The number of non-crossing partitions of a set of n elements.
22 // 10- The number of ways to cover the ladder 1..n using n rectangles (The
    ladder consists of n columns, where ith column has a height i).

```

## 3 Algebra

### 3.1 Gray Code

```

1  int g (int n) {
2      return n ^ (n >> 1);
3  }
4  int rev_g (int g) {
5      int n = 0;
6      for (; g; g >>= 1)
7          n ^= g;
8      return n;
9  }
10 int calc(int x, int y) { ///2D Gray Code
11     int a = g(x), b = g(y);
12     int res = 0;
13     f(i,0,LG) {
14         int k1 = (a & (1 << i));
15         int k2 = (b & (1 << i));
16         res |= k1 << (i + 1);
17         res |= k2 << i;
18     }
19     return res;
20 }

```

### 3.2 Primitive Roots

```

1  int primitive_root (int p) {
2      vector<int> fact;
3      int phi = p - 1, n = phi;
4      for (int i = 2; i * i <= n; ++i)
5          if (n % i == 0) {
6              fact.push_back (i);
7              while (n % i == 0)
8                  n /= i;
9          }
10     if (n > 1)
11         fact.push_back (n);
12
13     for (int res = 2; res <= p; ++res) {
14         bool ok = true;
15         for (size_t i = 0; i < fact.size() && ok; ++i)
16             ok &= powmod (res, phi / fact[i], p) != 1;
17         if (ok) return res;
18     }
19     return -1;
20 }

```

### 3.3 Discrete Logarithm minimum x for which $a^x = b \% m$

```

1  // Returns the smallest x > 0 : a^x = b mod m
2  ll modLog(ll a, ll b, ll m) {
3      ll n = (ll) sqrt(m) + 1, e = 1, f = 1, j = 1;
4      unordered_map<ll, ll> A;
5      while (j <= n && (e = f * e * a % m) != b % m)
6          A[e * b % m] = j++;
7      if (e == b % m) return j;
8      if ((__gcd(m, e) == (__gcd(m, b)))
9          rep(i, 2, n + 2) if (A.count(e = e * f % m))
10         return n * i - A[e];
11     return -1;
12 }

```

### 3.4 Discrete Root finds all numbers x such that $x^k = a \% n$

```

1  // This program finds all numbers x such that x^k = a (mod n)
2  vector<int> discrete_root(int n, int k, int a) {
3      if (a == 0)
4          return {0};
5
6      int g = primitive_root(n);
7      // Baby-step giant-step discrete logarithm algorithm
8      int sq = (int) sqrt(n + .0) + 1;
9      vector<pair<int, int>> dec(sq);
10     for (int i = 1; i <= sq; ++i)
11         dec[i - 1] = {powmod(g, i * sq * k % (n - 1), n), i};
12     sort(dec.begin(), dec.end());
13     int any_ans = -1;
14     for (int i = 0; i < sq; ++i) {
15         int my = powmod(g, i * k % (n - 1), n) * a % n;
16         auto it = lower_bound(dec.begin(), dec.end(), make_pair(my, 0));
17         if (it != dec.end() && it->first == my) {
18             any_ans = it->second * sq - i;
19             break;
20         }
21     }
22     if (any_ans == -1) return {};
23
24     int delta = (n - 1) / __gcd(k, n - 1);
25     vector<int> ans;
26     for (int cur = any_ans % delta; cur < n - 1; cur += delta)
27         ans.push_back(powmod(g, cur, n));
28     sort(ans.begin(), ans.end());
29     return ans;
30 }

```

### 3.5 Factorial modulo in $p * \log(n)$ (Wilson Theroem)

```

1  int factmod(int n, int p) {
2      vector<int> f(p);
3      f[0] = 1;
4      for (int i = 1; i < p; i++)
5          f[i] = f[i-1] * i % p;
6
7      int res = 1;
8      while (n > 1) {
9          if ((n/p) % 2)
10             res = p - res;
11             res = res * f[n%p] % p;
12             n /= p;
13     }
14     return res;
15 }

```

### 3.6 Iteration over submasks

```

1  int s = m;
2  while (s > 0) {
3      s = (s-1) & m;
4  }

```

### 3.7 Totient function

```

1  void phi_1_to_n(int n) {
2      for (int i = 0; i <= n; i++)
3          phi[i] = i;
4      for (int i = 2; i <= n; i++) {
5          if (phi[i] == i) {
6              for (int j = i; j <= n; j += i)
7                  phi[j] -= phi[j] / i;
8          }
9      }
10 }

```

### 3.8 CRT and EGCD

```

1  ll extended(ll a, ll b, ll &x, ll &y) {
2      if(b == 0) {
3          x = 1;
4          y = 0;
5          return a;
6      }
7      ll x0, y0;
8      ll g = extended(b, a % b, x0, y0);
9      x = y0;
10     y = x0 - a / b * y0;
11
12     return g ;
13 }
14 ll de(ll a, ll b, ll c, ll &x, ll &y) {
15     ll g = extended(abs(a), abs(b), x, y);
16     if(c % g) return -1;

```

```

17     x *= c / g;
18     y *= c / g;
19     if(a < 0) x = -x;
20     if(b < 0) y = -y;
21     return g;
22 }
23 pair<ll, ll> CRT(vector<ll> r, vector<ll> m) {
24     ll r1 = r[0], m1 = m[0];
25     for(int i = 1; i < r.size(); i++) {
26         ll r2 = r[i], m2 = m[i];
27         ll x0, y0;
28         ll g = de(m1, -m2, r2 - r1, x0, y0);
29         if(g == -1) return {-1, -1};
30         x0 %= m2;
31         ll nr = x0 * m1 + r1;
32         ll nm = m1 / g * m2;
33         r1 = (nr % nm + nm) % nm;
34         m1 = nm;
35     }
36     return {r1, m1};
37 }

```

### 3.9 FFT

```

1  typedef complex<double> C;
2  void fft(vector<C>& a) {
3      int n = sz(a), L = 31 - __builtin_clz(n);
4      static vector<complex<long double>> R(2, 1);
5      static vector<C> rt(2, 1); // (^ 10% fas te r i f double)
6      for (static int k = 2; k < n; k *= 2) {
7          R.resize(n);
8          rt.resize(n);
9          auto x = polar(1.0L, acos(-1.0L) / k);
10         rep(i, k, 2 * k) rt[i] = R[i] = i & 1 ? R[i / 2] * x : R[i / 2];
11     }
12     vi rev(n);
13     rep(i, 0, n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
14     rep(i, 0, n) if (i < rev[i]) swap(a[i], a[rev[i]]);
15     for (int k = 1; k < n; k *= 2)
16         for (int i = 0; i < n; i += 2 * k) rep(j, 0, k) {
17             C z = rt[j + k] * a[i + j + k]; //
18             a[i + j + k] = a[i + j] - z;
19             a[i + j] += z;
20         }
21 }
22 vd conv(const vd& a, const vd& b) {
23     if (a.empty() || b.empty()) return {};
24     vd res(sz(a) + sz(b) - 1);
25     int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
26     vector<C> in(n), out(n);
27     copy(all(a), begin(in));
28     rep(i, 0, sz(b)) in[i].imag(b[i]);
29     fft(in);
30     for (C& x : in) x *= x;
31     rep(i, 0, n) out[i] = in[-i & (n - 1)] - conj(in[i]);
32     fft(out);
33     /// rep(i,0,sz(res)) res[i] = (MOD+(ll)round(imag(out[i]) / (4 * n))) % MOD;
34     ///in case of mod
35     rep(i, 0, sz(res)) res[i] = imag(out[i]) / (4 * n);
36     return res;
37 }
38 //Applications
39 //1-All possible sums
40 //2-All possible scalar products
41 // We are given two arrays a[] and b[] of length n.
42 //We have to compute the products of a with every cyclic shift of b.
43 //We generate two new arrays of size 2n: We reverse a and append n zeros to it.
44 //And we just append b to itself. When we multiply these two arrays as
45 //polynomials,
46 //and look at the coefficients c[n-1], c[n], ..., c[2n-2] of the product c, we
47 //get:
48 //c[k]=sum i+j=k a[i]b[j]
49 //3-Two stripes
50 //We are given two Boolean stripes (cyclic arrays of values 0 and 1) a and b.
51 //We want to find all ways to attach the first stripe to the second one,
52 //such that at no position we have a 1 of the first stripe next to a 1 of the
53 //second stripe.

```

### 3.10 FFT with mod

```

1  "FastFourierTransform.cpp"
2  typedef vector<ll> vl;
3  template<int M> vl convMod(const vl &a, const vl &b) {
4      if (a.empty() || b.empty()) return {};
5      vl res(sz(a) + sz(b) - 1);
6      int B=32-__builtin_clz(sz(res)), n=1<<B, cut=int(sqrt(M));

```

```

7      vector<C> L(n), R(n), outs(n), outl(n);
8      rep(i,0,sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] % cut);
9      rep(i,0,sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] % cut);
10     fft(L), fft(R);
11     rep(i,0,n) {
12         int j = -i & (n - 1);
13         outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
14         outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
15     }
16     fft(outl), fft(outs);
17     rep(i,0,sz(res)) {
18         ll av = ll(real(outl[i])+.5), cv = ll(imag(outs[i])+.5);
19         ll bv = ll(imag(outl[i])+.5) + ll(real(outs[i])+.5);
20         res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
21     }
22     return res;
23 }

```

### 3.11 convolutions of AND-XOR-OR

```

1  // The size of a must be a power of two.
2  void FST(vi& a, bool inv) {
3      for (int n = sz(a), step = 1; step < n; step *= 2) {
4          for (int i = 0; i < n; i += 2 * step) rep(j,i,step) {
5              int &u = a[j], &v = a[j + step]; tie(u, v) =
6                  inv ? pii(v - u, u) : pii(v, u + v); // AND
7                  inv ? pii(v, u - v) : pii(u + v, u); // OR
8                  pii(u + v, u - v); // XOR
9          }
10     }
11     if (inv) for (int& x : a) x /= sz(a); // XOR only
12 }
13 vi conv(vi a, vi b) {
14     FST(a, 0); FST(b, 0);
15     rep(i,0,sz(a)) a[i] *= b[i];
16     FST(a, 1); return a;
17 }

```

### 3.12 NTT of KACTL

```

1  const ll mod = (119 << 23) + 1, root = 62; // = 998244353
2  // For p < 2^30 there is a lso e . g . 5 << 25, 7 << 26, 479 << 21
3  // and 483 << 21 (same root) . The 1 as t two are > 10^9.
4  typedef vector<ll> vl;
5  void ntt(vl &a) {
6      int n = sz(a), L = 31 - __builtin_clz(n);
7      static vl rt(2, 1);
8      for (static int k = 2, s = 2; k < n; k *= 2, s++) {
9          rt.resize(n);
10         ll z[] = {1, modpow(root, mod >> s)};
11         rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
12     }
13     vi rev(n);
14     rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
15     rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
16     for (int k = 1; k < n; k *= 2)
17         for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
18             ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
19             a[i + j + k] = ai - z + (z > ai ? mod : 0);
20             ai += (ai + z >= mod ? z - mod : z);
21         }
22 }
23 vl conv(const vl &a, const vl &b) {
24     if (a.empty() || b.empty()) return {};
25     int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s), n = 1 << B;
26     int inv = modpow(n, mod - 2);
27     vl L(a), R(b), out(n);
28     L.resize(n), R.resize(n);
29     ntt(L), ntt(R);
30     rep(i,0,n) out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv % mod;
31     ntt(out);
32     return {out.begin(), out.begin() + s};
33 }

```

### 3.13 Fibonacci

```

1  // F(n-1) * F(n+1) - F(n)^2 = (-1)^n
2  // F(n+k) = F(k) * F(n+1) + F(k-1) * F(n)
3  // F(2*n) = F(n) * (F(n+1) + F(n-1))
4  // GCD ( F(m) , F(n) ) = F(GCD(n,m))

```

### 3.14 Gauss Determinant

```

1  double det(vector<vector<double>>& a) {
2      int n = sz(a); double res = 1;
3      rep(i,0,n) {
4          int b = i;
5          rep(j,i+1,n) if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
6          if (i != b) swap(a[i], a[b]), res *= -1;

```

```

7     res *= a[i][i];
8     if (res == 0) return 0;
9     rep(j,i+1,n) {
10         double v = a[j][i] / a[i][i];
11         if (v != 0) rep(k,i+1,n) a[j][k] -= v * a[i][k];
12     }
13 }
14 return res;
15 }
16 // for integers
17 const ll mod = 12345;
18 ll det(vector<vector<ll>>& a) {
19     int n = sz(a); ll ans = 1;
20     rep(i,0,n) {
21         rep(j,i+1,n) {
22             while (a[j][i] != 0) { // gcd step
23                 ll t = a[i][i] / a[j][i];
24                 if (t) rep(k,i,n)
25                     a[i][k] = (a[i][k] - a[j][k] * t) % mod;
26                 swap(a[i], a[j]);
27                 ans *= -1;
28             }
29         }
30         ans = ans * a[i][i] % mod;
31         if (!ans) return 0;
32     }
33     return (ans + mod) % mod;
34 }

```

### 3.15 GAUSS SLAE

```

1  const double EPS = 1e-9;
2  const int INF = 2; // it doesn't actually have to be infinity or a big number
3
4  int gauss (vector< vector<double>> > a, vector<double> & ans) {
5      int n = (int) a.size();
6      int m = (int) a[0].size() - 1;
7
8      vector<int> where (m, -1);
9      for (int col = 0, row = 0; col < m && row < n; ++col) {
10         int sel = row;
11         for (int i = row; i < n; ++i)
12             if (abs (a[i][col]) > abs (a[sel][col]))
13                 sel = i;
14         if (abs (a[sel][col]) < EPS)
15             continue;
16         for (int i = col; i <= m; ++i)
17             swap (a[sel][i], a[row][i]);
18         where[col] = row;
19
20         for (int i = 0; i < n; ++i)
21             if (i != row) {
22                 double c = a[i][col] / a[row][col];
23                 for (int j = col; j <= m; ++j)
24                     a[i][j] -= a[row][j] * c;
25             }
26         ++row;
27     }
28
29     ans.assign (m, 0);
30     for (int i = 0; i < m; ++i)
31         if (where[i] != -1)
32             ans[i] = a[where[i]][m] / a[where[i]][i];
33     for (int i = 0; i < n; ++i) {
34         double sum = 0;
35         for (int j = 0; j < m; ++j)
36             sum += ans[j] * a[i][j];
37         if (abs (sum - a[i][m]) > EPS)
38             return 0;
39     }
40
41     for (int i = 0; i < m; ++i)
42         if (where[i] == -1)
43             return INF;
44     return 1;
45 }

```

### 3.16 Matrix Inverse

```

1  #define ld long double
2  vector< vector<ld>> gauss (vector< vector<ld>> > a) {
3
4      int n = (int) a.size();
5      vector<vector<ld>> > ans(n, vector<ld>(n, 0));
6
7      for(int i = 0; i < n; i++)
8          ans[i][i] = 1;
9      for(int i = 0; i < n; i++) {
10         for(int j = i + 1; j < n; j++)
11             if(a[j][i] > a[i][i]) {
12                 a[j].swap(a[i]);

```

```

13         ans[j].swap(ans[i]);
14     }
15     ld val = a[i][i];
16     for(int j = 0; j < n; j++) {
17         a[i][j] /= val;
18         ans[i][j] /= val;
19     }
20     for(int j = 0; j < n; j++) {
21         if(j == i) continue;
22         val = a[j][i];
23         for(int k = 0; k < n; k++) {
24             a[j][k] -= val * a[i][k];
25             ans[j][k] -= val * ans[i][k];
26         }
27     }
28 }
29 return ans;
30 }

```

## 4 Data Structures

### 4.1 UnionFindRollback

```

1  struct RollbackUF {
2      vi e; vector<pii> st;
3      RollbackUF(int n) : e(n, -1) {}
4      int size(int x) { return -e[find(x)]; }
5      int find(int x) { return e[x] < 0 ? x : find(e[x]); }
6      int time() { return sz(st); }
7      void rollback(int t) {
8          for (int i = time(); i --> t;)
9              e[st[i].first] = st[i].second;
10         st.resize(t);
11     }
12     bool join(int a, int b) {
13         a = find(a), b = find(b);
14         if (a == b) return false;
15         if (e[a] > e[b]) swap(a, b);
16         st.push_back({a, e[a]});
17         st.push_back({b, e[b]});
18         e[a] += e[b]; e[b] = a;
19         return true;
20     }
21 };

```

### 4.2 2D BIT

```

1  void upd(int x, int y, int val) {
2      for(int i = x; i <= n; i += i & -i)
3          for(int j = y; j <= m; j += j & -j)
4              bit[i][j] += val;
5  }
6  int get(int x, int y) {
7      int ans = 0;
8      for(int i = x; i; i -= i & -i)
9          for(int j = y; j; j -= j & -j)
10             ans += bit[i][j];
11 }

```

### 4.3 2D Sparse table

```

1  const int N = 505, LG = 10;
2  int st[N][N][LG][LG];
3  int a[N][N], lg2[N];
4  int yo(int x1, int y1, int x2, int y2) {
5      x2++;
6      y2++;
7      int a = lg2[x2 - x1], b = lg2[y2 - y1];
8      return max(
9          max(st[x1][y1][a][b], st[x2 - (1 << a)][y1][a][b]),
10         max(st[x1][y2 - (1 << b)][a][b], st[x2 - (1 << a)][y2 - (1 << b)][a][b])
11     );
12 }
13 void build(int n, int m) { // 0 indexed
14     for (int i = 2; i < N; i++) lg2[i] = lg2[i >> 1] + 1;
15     for (int i = 0; i < n; i++) {
16         for (int j = 0; j < m; j++) {
17             st[i][j][0][0] = a[i][j];
18         }
19     }
20     for (int a = 0; a < LG; a++) {
21         for (int b = 0; b < LG; b++) {
22             if (a + b == 0) continue;
23             for (int i = 0; i + (1 << a) <= n; i++) {
24                 for (int j = 0; j + (1 << b) <= m; j++) {
25                     if (!a) {

```

```

26         st[i][j][a][b] = max(st[i][j][a][b - 1], st[i][j + (1 << (b - 1))][a][b - 1]);
27     } else {
28         st[i][j][a][b] = max(st[i][j][a - 1][b], st[i + (1 << (a - 1))][j][a - 1][b]);
29     }
30 }
31 }
32 }
33 }
34 }

```

## 4.4 Mo With Updates

```

1  ///O(N^5/3) note that the block size is not a standard size
2  /// O(2SQ + N^2 / S + Q * N^2 / S^2) = O(Q * N^(2/3)) if S = n^(2/3)
3  /// fact: S = (2 * n * n)^(1/3) give the best complexity
4  const int block_size = 2000;
5  struct Query{
6      int l, r, t, idx;
7      Query(int l,int r,int t,int idx) : l(l),r(r),t(t),idx(idx) {}
8      bool operator < (Query o) const{
9          if(1 / block_size != o.l / block_size) return l < o.l;
10         if(r / block_size != o.r/block_size) return r < o.r;
11         return t < o.t;
12     }
13 };
14 int L = 0, R = -1, K = -1;
15 while(L < Q[i].l)del(a[L++]);
16 while(L > Q[i].l)add(a[--L]);
17 while(R < Q[i].r)add(a[++R]);
18 while(R > Q[i].r)del(a[R--]);
19 while(K < Q[i].t)upd(++K);
20 while(K > Q[i].t)err(K--);

```

## 4.5 Ordered Set

```

1  #include <ext/pb_ds/assoc_container.hpp>
2  #include <ext/pb_ds/tree_policy.hpp>
3  using namespace __gnu_pbds;
4  #define ordered_set tree<int, null_type,less<int>, rb_tree_tag,
   tree_order_statistics_node_update>
5  //order_of_key(k): returns the number of elements strictly less than k
6  //find_by_order(k): returns an iterator to the k-th element (0-based)

```

## 4.6 Persistent Seg Tree

```

1
2  int val[ N * 60 ], L[ N * 60 ], R[ N * 60 ], ptr, tree[N]; /// N * lgN
3  int upd(int root, int s, int e, int idx) {
4      int ret = ++ptr;
5      val[ret] = L[ret] = R[ret] = 0;
6      if (s == e) {
7          val[ret] = val[root] + 1;
8          return ret;
9      }
10     int md = (s + e) >> 1;
11     if (idx <= md) {
12         L[ret] = upd(L[root], s, md, idx), R[ret] = R[root];
13     } else {
14         R[ret] = upd(R[root], md + 1, e, idx), L[ret] = L[root];
15     }
16     val[ret] = max(val[L[ret]], val[R[ret]]);
17     return ret;
18 }
19 int qry(int node, int s, int e, int l, int r){
20     if(r < s || e < l || !node)return 0; //Punishment Value
21     if(l <= s && e <= r){
22         return val[node];
23     }
24     int md = (s+e)>>1;
25     return max(qry(L[node], s, md, l, r), qry(R[node],md+1,e,l,r));
26 }
27 int merge(int x, int y, int s, int e) {
28     if(!x||!y)return x | y;
29     if(s == e) {
30         val[x] += val[y];
31         return x;
32     }
33     int md = (s + e) >> 1;
34     L[x] = merge(L[x], L[y], s, md);
35     R[x] = merge(R[x], R[y], md+1,e);
36     val[x] = val[L[x]] + val[R[x]];
37     return x;
38 }

```

## 4.7 Treap

```

1  mt19937_64 mrand(chrono::steady_clock::now().time_since_epoch().count());
2  struct Node {
3      int key, pri = mrand(), sz = 1;
4      int lz = 0;
5      int idx;
6      array<Node*, 2> c = {NULL,NULL};
7      Node(int key, int idx) : key(key), idx(idx) {}
8  };
9
10 int getsz(Node* t){
11     return t ? t->sz : 0;
12 }
13
14 Node* calc(Node* t) {
15     t->sz = 1 + getsz(t->c[0]) + getsz(t->c[1]);
16     return t;
17 }
18
19 void prop(Node* cur) {
20     if(!cur || !cur->lz)
21         return;
22     cur->key += cur->lz;
23     if(cur->c[0])
24         cur->c[0]->lz += cur->lz;
25     if(cur->c[1])
26         cur->c[1]->lz += cur->lz;
27     cur->lz = 0;
28 }
29
30 array<Node*, 2> split(Node* t, int k) {
31     prop(t);
32     if(!t)
33         return {t, t};
34     if(getsz(t->c[0]) >= k) { ///answer is in left node
35         auto ret = split(t->c[0], k);
36         t->c[0] = ret[1];
37         return {ret[0], calc(t)};
38     } else { ///k > t->c[0]
39         auto ret = split(t->c[1], k - 1 - getsz(t->c[0]));
40         t->c[1] = ret[0];
41         return {calc(t), ret[1]};
42     }
43 }
44
45 Node* merge(Node* u, Node* v) {
46     prop(u);
47     prop(v);
48     if(!u || !v)
49         return u ? u : v;
50     if(u->pri > v->pri) {
51         u->c[1] = merge(u->c[1], v);
52         return calc(u);
53     } else {
54         v->c[0] = merge(u, v->c[0]);
55         return calc(v);
56     }
57 }
58
59 int cnt(Node* cur, int x) {
60     prop(cur);
61     if(!cur)
62         return 0;
63     if(cur->key <= x)
64         return getsz(cur->c[0]) + 1 + cnt(cur->c[1], x);
65     return cnt(cur->c[0], x);
66 }
67
68 Node* ins(Node* root, int val, int idx, int pos) {
69     auto splitted = split(root, pos);
70     root = merge(splitted[0], new Node(val, idx));
71     return merge(root, splitted[1]);
72 }

```

## 4.8 Wavelet Tree

```

1  // remember your array and values must be 1-based
2  struct wavelet_tree {
3      int lo, hi;
4      wavelet_tree *l, *r;
5      vector<int> b;
6  };
7
8  ///nos are in range [x,y]
9  ///array indices are [from, to]
10 wavelet_tree(int *from, int *to, int x, int y) {
11     lo = x, hi = y;
12     if (lo == hi or from >= to)
13         return;
14     int mid = (lo + hi) / 2;
15     auto f = [mid](int x) {
16         return x <= mid;
17     };
18     b.reserve(to - from + 1);
19     b.pb(0);
20     for (auto it = from; it != to; it++)
21         b.pb(b.back() + f(*it));
22     ///see how lambda function is used here

```

```

22     auto pivot = stable_partition(from, to, f);
23     l = new wavelet_tree(from, pivot, lo, mid);
24     r = new wavelet_tree(pivot, to, mid + 1, hi);
25 }
26
27 //kth smallest element in [l, r]
28 int kth(int l, int r, int k) {
29     if (l > r)
30         return 0;
31     if (lo == hi)
32         return lo;
33     int inLeft = b[r] - b[l - 1];
34     int lb = b[l - 1]; //amt of nos in first (l-1) nos that go in left
35     int rb = b[r]; //amt of nos in first (r) nos that go in left
36     if (k <= inLeft)
37         return this->l->kth(lb + 1, rb, k);
38     return this->r->kth(l - lb, r - rb, k - inLeft);
39 }
40
41 //count of nos in [l, r] Less than or equal to k
42 int LTE(int l, int r, int k) {
43     if (l > r or k < lo)
44         return 0;
45     if (hi <= k)
46         return r - l + 1;
47     int lb = b[l - 1], rb = b[r];
48     return this->l->LTE(lb + 1, rb, k) + this->r->LTE(l - lb, r - rb, k);
49 }
50
51 //count of nos in [l, r] equal to k
52 int count(int l, int r, int k) {
53     if (l > r or k < lo or k > hi)
54         return 0;
55     if (lo == hi)
56         return r - l + 1;
57     int lb = b[l - 1], rb = b[r], mid = (lo + hi) / 2;
58     if (k <= mid)
59         return this->l->count(lb + 1, rb, k);
60     return this->r->count(l - lb, r - rb, k);
61 }
62 };

```

## 4.9 SparseTable

```

1  int S[N];
2  for(int i = 2; i < N; i++) S[i] = S[i >> 1] + 1;
3  for (int i = 1; i <= K; i++)
4      for (int j = 0; j + (1 << i) <= N; j++)
5          st[i][j] = f(st[i - 1][j], st[i - 1][j + (1 << (i - 1))]);
6
7  int query(int l, int r) {
8      int k = S[r - l + 1];
9      return mrg(st[k][l], st[k][r - (1 << k) + 1]);
10 }

```

## 5 DP

### 5.1 CHT Line Container

```

1  struct Line {
2      mutable ll m, b, p;
3      bool operator<(const Line &o) const { return m < o.m; }
4      bool operator<(ll x) const { return p < x; }
5  };
6  struct LineContainer : multiset<Line, less<>> {
7      // (for doubles, use inf = 1/.0, div(a,b) = a/b)
8      static const ll inf = LLONG_MAX;
9      ll div(ll db, ll dm) { // floored division
10         return db / dm - ((db ^ dm) < 0 && db % dm);
11     }
12     bool isect(iterator x, iterator y) {
13         if (y == end()) {
14             x->p = inf;
15             return false;
16         }
17         if (x->m == y->m)
18             x->p = x->b > y->b ? inf : -inf;
19         else
20             x->p = div(y->b - x->b, x->m - y->m);
21         return x->p >= y->p;
22     }
23     void add(ll m, ll b) {
24         auto z = insert({m, b, 0}), y = z++, x = y;
25         while (isect(y, z))
26             z = erase(z);
27         if (x != begin() && isect(--x, y))
28             isect(x, y = erase(y));
29         while ((y = x) != begin() && (--x)->p >= y->p)

```

```

30         isect(x, erase(y));
31     }
32     ll query(ll x) {
33         assert(!empty());
34         auto l = *lower_bound(x);
35         return l.m * x + l.b;
36     }
37 };

```

## 6 Geometry

### 6.1 Convex Hull

```

1  struct point {
2      ll x, y;
3      point(ll x, ll y) : x(x), y(y) {}
4      point operator -(point other) {
5          return point(x - other.x, y - other.y);
6      }
7      bool operator <(const point &other) const {
8          return x != other.x ? x < other.x : y < other.y;
9      }
10 };
11 ll cross(point a, point b) {
12     return a.x * b.y - a.y * b.x;
13 }
14 ll dot(point a, point b) {
15     return a.x * b.x + a.y * b.y;
16 }
17 struct sortCCW {
18     point center;
19
20     sortCCW(point center) : center(center) {}
21
22     bool operator()(point a, point b) {
23         ll res = cross(a - center, b - center);
24         if(res)
25             return res > 0;
26         return dot(a - center, a - center) < dot(b - center, b - center);
27     }
28 };
29 vector<point> hull(vector<point> v) {
30     sort(v.begin(), v.end());
31     sort(v.begin() + 1, v.end(), sortCCW(v[0]));
32     v.push_back(v[0]);
33     vector<point> ans;
34     for(auto i : v) {
35         int sz = ans.size();
36         while(sz > 1 && cross(i - ans[sz - 1], ans[sz - 2] - ans[sz - 1]) <= 0)
37             ans.pop_back(), sz--;
38         ans.push_back(i);
39     }
40     ans.pop_back();
41     return ans;
42 }

```

### 6.2 Geometry Template

```

1  using ptype = double edit this first ;
2  double EPS = 1e-9;
3  struct point {
4      ptype x, y;
5      point(ptype x, ptype y) : x(x), y(y) {}
6      point operator -(const point & other) const { return point(x - other.x, y - other.y); }
7      point operator +(const point & other) const { return point(x + other.x, y + other.y); }
8      point operator *(ptype c) const { return point(x * c, y * c); }
9      point operator /(ptype c) const { return point(x / c, y / c); }
10     point prep() { return point(-y, x); }
11 };
12 ptype cross(point a, point b) { return a.x * b.y - a.y * b.x; }
13 ptype dot(point a, point b) { return a.x * b.x + a.y * b.y; }
14 double abs(point a) { return sqrt(dot(a, a)); }
15
16 double angle (point a, point b) { // angle between [0 , pi]
17     return acos(dot(a, b) / abs(a) / abs(b));
18 }
19 // a : point in Line, d : Line direction
20 point LineLineIntersect(point a1, point d1, point a2, point d2) {
21     return a1 + d1 * cross(a2 - a1, d2) / cross(d1, d2);
22 }
23 // Line a---b, point C
24 point ProjectPointLine(point a, point b, point c) {
25     return a + (b - a) * 1.0 * dot(c - a, b - a) / dot(b - a, b - a);
26 }
27 // segment a---b, point C

```



```

28 point ProjectPointSegment(point a, point b, point c) {
29     double r = dot(c - a, b - a) / dot(b - a, b - a);
30     if(r < 0)
31         return a;
32     if(r > 1)
33         return b;
34     return a + (b - a) * r;
35 }
36 // Line a---b, point p
37 point reflectAroundLine(point a, point b, point p) {
38     return ProjectPointLine(a, b, p) * 2 - p; // (proj-p) * 2 + p
39 }
40 // Around origin
41 point RotateCCW(point p, double t) {
42     return point(p.x * cos(t) - p.y * sin(t),
43                 p.x * sin(t) + p.y * cos(t));
44 }
45 // Line a---b
46 vector<point> CircleLineIntersect(point a, point b, point center, double r) {
47     a = a - center;
48     b = b - center;
49     point p = ProjectPointLine(a, b, point(0, 0)); // project point from center
50     // to the Line
51     if(dot(p, p) > r * r)
52         return {};
53     double len = sqrt(r * r - dot(p, p));
54     if(len < EPS)
55         return {center + p};
56
57     point d = (a - b) / abs(a - b);
58     return {center + p + d * len, center + p - d * len};
59 }
60 vector<point> CircleCircleIntersect(point c1, ld r1, point c2, ld r2) {
61     if (r1 < r2) {
62         swap(r1, r2);
63         swap(c1, c2);
64     }
65     ld d = abs(c2 - c1); // distance between c1,c2
66     if (d > r1 + r2 || d < r1 - r2 || d < EPS) // zero or infinite solutions
67         return {};
68     ld angle = acos(min((d * d + r1 * r1 - r2 * r2) / (2 * r1 * d), (ld) 1.0));
69     point p = (c2 - c1) / d * r1;
70
71     if (angle < EPS)
72         return {c1 + p};
73
74     return {c1 + RotateCCW(p, angle), c1 + RotateCCW(p, -angle)};
75 }
76
77 point circumcircle(point p1, point p2, point p3) {
78     return LineLineIntersect((p1 + p2) / 2, (p1 - p2).prep(),
79                             (p1 + p3) / 2, (p1 - p3).prep());
80 }
81 //I : number points with integer coordinates lying strictly inside the polygon.
82 //B : number of points lying on polygon sides by B.
83 //Area = I + B/2 - 1

```

### 6.3 Half Plane Intersection

```

1 // Redefine epsilon and infinity as necessary. Be mindful of precision errors.
2 #define ld long double
3 const ld eps = 1e-9, inf = 1e9;
4
5 // Basic point/vector struct.
6 struct Point {
7
8     ld x, y;
9     explicit Point(ld x = 0, ld y = 0) : x(x), y(y) {}
10
11     // Addition, subtraction, multiply by constant, cross product.
12     friend Point operator + (const Point& p, const Point& q) {
13         return Point(p.x + q.x, p.y + q.y);
14     }
15     friend Point operator - (const Point& p, const Point& q) {
16         return Point(p.x - q.x, p.y - q.y);
17     }
18     friend Point operator * (const Point& p, const ld& k) {
19         return Point(p.x * k, p.y * k);
20     }
21     friend ld cross(const Point& p, const Point& q) {
22         return p.x * q.y - p.y * q.x;
23     }
24 };
25
26 // Basic half-plane struct.
27 struct Halfplane {
28     // 'p' is a passing point of the line and 'pq' is the direction vector of
29     // the line.
30     Point p, pq;
31     ld angle;

```

```

32 Halfplane() {}
33 Halfplane(const Point& a, const Point& b) : p(a), pq(b - a) {
34     angle = atan2l(pq.y, pq.x);
35 }
36 // Check if point 'r' is outside this half-plane.
37 // Every half-plane allows the region to the LEFT of its line.
38 bool out(const Point& r) {
39     return cross(pq, r - p) < -eps;
40 }
41 // Comparator for sorting.
42 // If the angle of both half-planes is equal, the leftmost one should go
43 // first.
44 bool operator < (const Halfplane& e) const {
45     if (fabsl(angle - e.angle) < eps) return cross(pq, e.p - p) < 0;
46     return angle < e.angle;
47 }
48 // We use equal comparator for std::unique to easily remove parallel half-
49 // planes.
50 bool operator == (const Halfplane& e) const {
51     return fabsl(angle - e.angle) < eps;
52 }
53 // Intersection point of the lines of two half-planes. It is assumed they're
54 // never parallel.
55 friend Point inter(const Halfplane& s, const Halfplane& t) {
56     ld alpha = cross((t.p - s.p), t.pq) / cross(s.pq, t.pq);
57     return s.p + (s.pq * alpha);
58 }
59 // Actual algorithm
60 vector<Point> hp_intersect(vector<Halfplane>& H) {
61     Point box[4] = { // Bounding box in CCW order
62         Point(inf, inf),
63         Point(-inf, inf),
64         Point(-inf, -inf),
65         Point(inf, -inf)
66     };
67     for(int i = 0; i < 4; i++) { // Add bounding box half-planes.
68         Halfplane aux(box[i], box[(i+1) % 4]);
69         H.push_back(aux);
70     }
71     // Sort and remove duplicates
72     sort(H.begin(), H.end());
73     H.erase(unique(H.begin(), H.end()), H.end());
74     deque<Halfplane> dq;
75     int len = 0;
76     for(int i = 0; i < int(H.size()); i++) {
77         // Remove from the back of the deque while last half-plane is redundant
78         while (len > 1 && H[i].out(inter(dq[len-1], dq[len-2]))) {
79             dq.pop_back();
80             --len;
81         }
82         // Remove from the front of the deque while first half-plane is
83         // redundant
84         while (len > 1 && H[i].out(inter(dq[0], dq[1]))) {
85             dq.pop_front();
86             --len;
87         }
88         // Add new half-plane
89         dq.push_back(H[i]);
90         ++len;
91     }
92     // Final cleanup: Check half-planes at the front against the back and vice-
93     // versa
94     while (len > 2 && dq[0].out(inter(dq[len-1], dq[len-2]))) {
95         dq.pop_back();
96         --len;
97     }
98     while (len > 2 && dq[len-1].out(inter(dq[0], dq[1]))) {
99         dq.pop_front();
100         --len;
101     }
102     // Report empty intersection if necessary
103     if (len < 3) return vector<Point>();
104     // Reconstruct the convex polygon from the remaining half-planes.
105     vector<Point> ret(len);
106     for(int i = 0; i+1 < len; i++) {
107         ret[i] = inter(dq[i], dq[i+1]);
108     }
109     ret.back() = inter(dq[len-1], dq[0]);
110     return ret;
111 }

```

### 6.4 Segments Intersection

```

1 const double EPS = 1E-9;

```

```

2   struct pt {
3       double x, y;
4   };
5
6   struct seg {
7       pt p, q;
8       int id;
9
10      double get_y(double x) const {
11          if (abs(p.x - q.x) < EPS)
12              return p.y;
13          return p.y + (q.y - p.y) * (x - p.x) / (q.x - p.x);
14      }
15  };
16
17  bool intersectld(double l1, double r1, double l2, double r2) {
18      if (l1 > r1)
19          swap(l1, r1);
20      if (l2 > r2)
21          swap(l2, r2);
22      return max(l1, l2) <= min(r1, r2) + EPS;
23  }
24
25  int vec(const pt& a, const pt& b, const pt& c) {
26      double s = (b.x - a.x) * (c.y - a.y) - (b.y - a.y) * (c.x - a.x);
27      return abs(s) < EPS ? 0 : s > 0 ? +1 : -1;
28  }
29
30  bool intersect(const seg& a, const seg& b)
31  {
32      return intersectld(a.p.x, a.q.x, b.p.x, b.q.x) &&
33             intersectld(a.p.y, a.q.y, b.p.y, b.q.y) &&
34             vec(a.p, a.q, b.p) * vec(a.p, a.q, b.q) <= 0 &&
35             vec(b.p, b.q, a.p) * vec(b.p, b.q, a.q) <= 0;
36  }
37
38  bool operator<(const seg& a, const seg& b)
39  {
40      double x = max(min(a.p.x, a.q.x), min(b.p.x, b.q.x));
41      return a.get_y(x) < b.get_y(x) - EPS;
42  }
43
44  struct event {
45      double x;
46      int tp, id;
47
48      event() {}
49      event(double x, int tp, int id) : x(x), tp(tp), id(id) {}
50
51      bool operator<(const event& e) const {
52          if (abs(x - e.x) > EPS)
53              return x < e.x;
54          return tp > e.tp;
55      }
56  };
57
58  set<seg> s;
59  vector<set<seg>::iterator> where;
60
61  set<seg>::iterator prev(set<seg>::iterator it) {
62      return it == s.begin() ? s.end() : --it;
63  }
64
65  set<seg>::iterator next(set<seg>::iterator it) {
66      return ++it;
67  }
68
69  pair<int, int> solve(const vector<seg>& a) {
70      int n = (int)a.size();
71      vector<event> e;
72      for (int i = 0; i < n; ++i) {
73          e.push_back(event(min(a[i].p.x, a[i].q.x), +1, i));
74          e.push_back(event(max(a[i].p.x, a[i].q.x), -1, i));
75      }
76      sort(e.begin(), e.end());
77
78      s.clear();
79      where.resize(a.size());
80      for (size_t i = 0; i < e.size(); ++i) {
81          int id = e[i].id;
82          if (e[i].tp == +1) {
83              set<seg>::iterator nxt = s.lower_bound(a[id]), prv = prev(nxt);
84              if (nxt != s.end() && intersect(*nxt, a[id]))
85                  return make_pair(nxt->id, id);
86              if (prv != s.end() && intersect(*prv, a[id]))
87                  return make_pair(prv->id, id);
88              where[id] = s.insert(nxt, a[id]);
89          } else {
90              set<seg>::iterator nxt = next(where[id]), prv = prev(where[id]);
91              if (nxt != s.end() && prv != s.end() && intersect(*nxt, *prv))
92                  return make_pair(prv->id, nxt->id);
93          }
94      }
95  }

```

```

94      s.erase(where[id]);
95  }
96  }
97
98  return make_pair(-1, -1);
99  }

```

## 6.5 Rectangles Union

```

1  #include<bits/stdc++.h>
2  #define P(x,y) make_pair(x,y)
3  using namespace std;
4  class Rectangle {
5  public:
6      int x1, y1, x2, y2;
7      static Rectangle empt;
8      Rectangle() {
9          x1 = y1 = x2 = y2 = 0;
10     }
11     Rectangle(int X1, int Y1, int X2, int Y2) {
12         x1 = X1;
13         y1 = Y1;
14         x2 = X2;
15         y2 = Y2;
16     }
17 };
18 struct Event {
19     int x, y1, y2, type;
20     Event() {}
21     Event(int x, int y1, int y2, int type): x(x), y1(y1), y2(y2), type(type) {}
22 };
23 bool operator < (const Event&A, const Event&B) {
24     //if(A.x != B.x)
25     return A.x < B.x;
26     //if(A.y1 != B.y1) return A.y1 < B.y1;
27     //if(A.y2 != B.y2()) A.y2 < B.y2;
28 }
29 const int MX = (1 << 17);
30 struct Node {
31     int prob, sum, ans;
32     Node() {}
33     Node(int prob, int sum, int ans): prob(prob), sum(sum), ans(ans) {}
34 };
35 Node tree[MX * 4];
36 int interval[MX];
37 void build(int x, int a, int b) {
38     tree[x] = Node(0, 0, 0);
39     if(a == b) {
40         tree[x].sum += interval[a];
41         return;
42     }
43     build(x * 2, a, (a + b) / 2);
44     build(x * 2 + 1, (a + b) / 2 + 1, b);
45     tree[x].sum = tree[x * 2].sum + tree[x * 2 + 1].sum;
46 }
47 int ask(int x) {
48     if(tree[x].prob)
49         return tree[x].sum;
50     return tree[x].ans;
51 }
52 int st, en, V;
53 void update(int x, int a, int b) {
54     if(st > b || en < a)
55         return;
56     if(a >= st && b <= en) {
57         tree[x].prob += V;
58         return;
59     }
60     update(x * 2, a, (a + b) / 2);
61     update(x * 2 + 1, (a + b) / 2 + 1, b);
62     tree[x].ans = ask(x * 2) + ask(x * 2 + 1);
63 }
64 Rectangle Rectangle::empt = Rectangle();
65 vector < Rectangle > Rect;
66 vector < int > sorted;
67 vector < Event > sweep;
68 void compressncalc() {
69     sweep.clear();
70     sorted.clear();
71     for(auto R : Rect) {
72         sorted.push_back(R.y1);
73         sorted.push_back(R.y2);
74     }
75     sort(sorted.begin(), sorted.end());
76     sorted.erase(unique(sorted.begin(), sorted.end()), sorted.end());
77     int sz = sorted.size();
78     for(int j = 0; j < sorted.size() - 1; j++)
79         interval[j + 1] = sorted[j + 1] - sorted[j];
80     for(auto R : Rect) {
81         sweep.push_back(Event(R.x1, R.y1, R.y2, 1));
82     }
83 }

```



```

82     sweep.push_back(Event(R.x2, R.y1, R.y2, -1));
83 }
84 sort(sweep.begin(), sweep.end());
85 build(1, 1, sz - 1);
86 }
87 long long ans;
88 void Sweep() {
89     ans = 0;
90     if(sorted.empty() || sweep.empty())
91         return;
92     int last = 0, sz_ = sorted.size();
93     for(int j = 0; j < sweep.size(); j++) {
94         ans += 1ll * (sweep[j].x - last) * ask(1);
95         last = sweep[j].x;
96         V = sweep[j].type;
97         st = lower_bound(sorted.begin(), sorted.end(), sweep[j].y1) - sorted.
            begin() + 1;
98         en = lower_bound(sorted.begin(), sorted.end(), sweep[j].y2) - sorted.
            begin();
99         update(1, 1, sz_ - 1);
100     }
101 }
102 int main() {
103     // freopen("in.in", "r", stdin);
104     int n;
105     scanf("%d", &n);
106     for(int j = 1; j <= n; j++) {
107         int a, b, c, d;
108         scanf("%d %d %d %d", &a, &b, &c, &d);
109         Rect.push_back(Rectangle(a, b, c, d));
110     }
111     compressncalc();
112     Sweep();
113     cout << ans << endl;
114 }

```

## 7 Graphs

### 7.1 2 SAD

```

1  /**
2   * Description: Calculates a valid assignment to boolean variables a, b, c,...
   to a 2-SAT problem, so that an expression of the type $(a\|\b)\&\&(!a\|\
   c)\&\&(d\|\b)\&\&...$ becomes true, or reports that it is unsatisfiable.
3   * Negated variables are represented by bit-inversions (\texttt{\tilde{x}}).
4   * Usage:
5   * TwoSat ts(number of boolean variables);
6   * ts.either(0, \tilde{3}); // Var 0 is true or var 3 is false
7   * ts.setValue(2); // Var 2 is true
8   * ts.atMostOne(0, \tilde{1}, 2); // <= 1 of vars 0, \tilde{1} and 2 are true
9   * ts.solve(); // Returns true iff it is solvable
10  * ts.values[0..N-1] holds the assigned values to the vars
11  * Time: O(N+E), where N is the number of boolean variables, and E is the number
   of clauses.
12  */
13  struct TwoSat {
14      int N;
15      vector<vi> gr;
16      vi values; // 0 = false, 1 = true
17
18      TwoSat(int n = 0) : N(n), gr(2*n) {}
19
20      int addVar() { // (optional)
21          gr.emplace_back();
22          gr.emplace_back();
23          return N++;
24      }
25
26      void either(int f, int j) {
27          f = max(2*f, -1-2*f);
28          j = max(2*j, -1-2*j);
29          gr[f].push_back(j^1);
30          gr[j].push_back(f^1);
31      }
32      void setValue(int x) { either(x, x); }
33
34      void atMostOne(const vi& li) { // (optional)
35          if (sz(li) <= 1) return;
36          int cur = ~li[0];
37          rep(i, 2, sz(li)) {
38              int next = addVar();
39              either(cur, ~li[i]);
40              either(cur, next);
41              either(~li[i], next);
42              cur = next;
43          }
44          either(cur, ~li[1]);
45      }

```

```

46     vi val, comp, z; int time = 0;
47     int dfs(int i) {
48         int low = val[i] = ++time, x; z.push_back(i);
49         for(int e : gr[i]) if (!comp[e])
50             low = min(low, val[e] ? dfs(e));
51         if (low == val[i]) do {
52             x = z.back(); z.pop_back();
53             comp[x] = low;
54             if (values[x>>1] == -1)
55                 values[x>>1] = x&1;
56         } while (x != i);
57         return val[i] = low;
58     }
59
60     bool solve() {
61         values.assign(N, -1);
62         val.assign(2*N, 0); comp = val;
63         rep(i, 0, 2*N) if (!comp[i]) dfs(i);
64         rep(i, 0, N) if (comp[2*i] == comp[2*i+1]) return 0;
65         return 1;
66     }
67 }
68 };

```

### 7.2 Articulation Point

```

1  vector<int> adj[N];
2  int dfsn[N], low[N], instack[N], ar_point[N], timer;
3  stack<int> st;
4
5  void dfs(int node, int par){
6      dfsn[node] = low[node] = ++timer;
7      int kam = 0;
8      for(auto i: adj[node]){
9          if(i == par) continue;
10         if(dfsn[i] == 0){
11             kam++;
12             dfs(i, node);
13             low[node] = min(low[node], low[i]);
14             if(dfsn[node] <= low[i] && par != 0) ar_point[node] = 1;
15         }
16         else low[node] = min(low[node], dfsn[i]);
17     }
18     if(par == 0 && kam > 1) ar_point[node] = 1;
19 }
20 int main(){
21     // Input
22     for(int i = 1; i <= n; i++){
23         if(dfsn[i] == 0) dfs(i, 0);
24     }
25     int c = 0;
26     for(int i = 1; i <= n; i++){
27         if(ar_point[i]) c++;
28     }
29     cout << c << '\n';
30 }

```

### 7.3 Bridges Tree and Diameter

```

1  #include <bits/stdc++.h>
2  #define ll long long
3  using namespace std;
4  const int N = 3e5 + 5, mod = 1e9 + 7;
5
6  vector<int> adj[N], bridge_tree[N];
7  int dfsn[N], low[N], cost[N], timer, cnt, comp_id[N], kam[N], ans;
8  stack<int> st;
9
10 void dfs(int node, int par){
11     dfsn[node] = low[node] = ++timer;
12     st.push(node);
13     for(auto i: adj[node]){
14         if(i == par) continue;
15         if(dfsn[i] == 0){
16             dfs(i, node);
17             low[node] = min(low[node], low[i]);
18         }
19         else low[node] = min(low[node], dfsn[i]);
20     }
21     if(dfsn[node] == low[node]){
22         cnt++;
23         while(1){
24             int cur = st.top();
25             st.pop();
26             comp_id[cur] = cnt;
27             if(cur == node) break;
28         }
29     }
30 }
31 }

```

```

32 void dfs2(int node, int par){
33     kam[node] = 0;
34     int mx = 0, second_mx = 0;
35     for(auto i: bridge_tree[node]){
36         if(i == par) continue;
37         dfs2(i, node);
38         kam[node] = max(kam[node], 1 + kam[i]);
39         if(kam[i] > mx){
40             second_mx = mx;
41             mx = kam[i];
42         }
43         else second_mx = max(second_mx, kam[i]);
44     }
45     ans = max(ans, kam[node]);
46     if(second_mx) ans = max(ans, 2 + mx + second_mx);
47 }
48
49 int main(){
50     ios_base::sync_with_stdio(0); cin.tie(0); cout.tie(0);
51     int n, m;
52     cin >> n >> m;
53     while(m--){
54         int u, v;
55         cin >> u >> v;
56         adj[u].push_back(v);
57         adj[v].push_back(u);
58     }
59     dfs(1, 0);
60     for(int i = 1; i <= n; i++){
61         for(auto j: adj[i]){
62             if(comp_id[i] != comp_id[j]){
63                 bridge_tree[comp_id[i]].push_back(comp_id[j]);
64             }
65         }
66     }
67     dfs2(1, 0);
68     cout << ans;
69
70     return 0;
71 }
72

```

## 7.4 Dinic With Scalling

```

1  ///O(ElgFlow) on Bipartite Graphs and O(EVlgFlow) on other graphs (I think)
2  struct Dinic {
3      #define vi vector<int>
4      #define rep(i,a,b) f(i,a,b)
5      struct Edge {
6          int to, rev;
7          ll c, oc;
8          int id;
9          ll flow() { return max(oc - c, 0LL); } // if you need flows
10     };
11     vi lvl, ptr, q;
12     vector<vector<Edge>> adj;
13     Dinic(int n) : lvl(n), ptr(n), q(n), adj(n) {}
14     void addEdge(int a, int b, ll c, int id, ll rcap = 0) {
15         adj[a].push_back({b, sz(adj[b]), c, c, id});
16         adj[b].push_back({a, sz(adj[a]) - 1, rcap, rcap, id});
17     }
18     ll dfs(int v, int t, ll f) {
19         if (v == t || !f) return f;
20         for (int& i = ptr[v]; i < sz(adj[v]); i++) {
21             Edge& e = adj[v][i];
22             if (lvl[e.to] == lvl[v] + 1)
23                 if (ll p = dfs(e.to, t, min(f, e.c))) {
24                     e.c -= p, adj[e.to][e.rev].c += p;
25                     return p;
26                 }
27         }
28         return 0;
29     }
30     ll calc(int s, int t) {
31         ll flow = 0; q[0] = s;
32         rep(L, 0, 31) do { // 'int L=30' maybe faster for random data
33             lvl = ptr = vi(sz(q));
34             int qi = 0, qe = lvl[s] + 1;
35             while (qi < qe && !lvl[t]) {
36                 int v = q[qi++];
37                 for (Edge e : adj[v])
38                     if (!lvl[e.to] && e.c >> (30 - L))
39                         q[qe++] = e.to, lvl[e.to] = lvl[v] + 1;
40             }
41             while (ll p = dfs(s, t, LLONG_MAX)) flow += p;
42             while (lvl[t]);
43             return flow;
44         }
45         bool leftOfMinCut(int a) { return lvl[a] != 0; }
46     };

```

## 7.5 Gomory Hu

```

1  /**
2   * Author: chilli, Takanori MAEHARA
3   * Date: 2020-04-03
4   * License: CC0
5   * Source: https://github.com/spaghetti-source/algorithm/blob/master/graph/
6   * gomory_hu_tree.cc#L102
7   * Description: Given a list of edges representing an undirected flow graph,
8   * returns edges of the Gomory-Hu tree. The max flow between any pair of
9   * vertices is given by minimum edge weight along the Gomory-Hu tree path.
10  * Time:  $\mathcal{O}(V)^3$  Flow Computations
11  * Status: Tested on CERC 2015 J, stress-tested
12  * Details: The implementation used here is not actually the original
13  * Gomory-Hu, but Gusfield's simplified version: "Very simple methods for all
14  * pairs network flow analysis". PushRelabel is used here, but any flow
15  * implementation that supports 'leftOfMinCut' also works.
16  */
17 #pragma once
18
19 #include "PushRelabel.h"
20
21 typedef array<ll, 3> Edge;
22 vector<Edge> gomoryHu(int N, vector<Edge> ed) {
23     vector<Edge> tree;
24     vi par(N);
25     rep(i, 1, N) {
26         PushRelabel D(N); // Dinic also works
27         for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
28         tree.push_back({i, par[i], D.calc(i, par[i])});
29         rep(j, i+1, N)
30             if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
31     }
32     return tree;
33 }

```

## 7.6 HopcraftKarp BPM

```

1  /**
2   * Author: Chen Xing
3   * Date: 2009-10-13
4   * License: CC0
5   * Source: N/A
6   * Description: Fast bipartite matching algorithm. Graph $g$ should be a list
7   * of neighbors of the left partition, and $btoa$ should be a vector full of
8   * -1's of the same size as the right partition. Returns the size of
9   * the matching. $btoa[i]$ will be the match for vertex $i$ on the right side,
10  * or $-1$ if it's not matched.
11  * Usage: vi btoa(m, -1); hopcroftKarp(g, btoa);
12  * Time:  $\mathcal{O}(\sqrt{V}E)$ 
13  * Status: stress-tested by MinimumVertexCover, and tested on oldkattis.
14  * adkbipmatch and SPOJ:MATCHING
15  */
16 #pragma once
17
18 bool dfs(int a, int L, vector<vi>& g, vi& btoa, vi& A, vi& B) {
19     if (A[a] != L) return 0;
20     A[a] = -1;
21     for (int b : g[a]) if (B[b] == L + 1) {
22         B[b] = 0;
23         if (btoa[b] == -1 || dfs(btoa[b], L + 1, g, btoa, A, B))
24             return btoa[b] = a, 1;
25     }
26     return 0;
27 }
28
29 int hopcroftKarp(vector<vi>& g, vi& btoa) {
30     int res = 0;
31     vi A(g.size(), 0), B(btoa.size(), 0), cur, next;
32     for (;;) {
33         fill(all(A), 0);
34         fill(all(B), 0);
35         /// Find the starting nodes for BFS (i.e. layer 0).
36         cur.clear();
37         for (int a : btoa) if (a != -1) A[a] = -1;
38         rep(a, 0, sz(g)) if (A[a] == 0) cur.push_back(a);
39         /// Find all layers using bfs.
40         for (int lay = 1; lay++;) {
41             bool islast = 0;
42             next.clear();
43             for (int a : cur) for (int b : g[a]) {
44                 if (btoa[b] == -1) {
45                     B[b] = lay;
46                     islast = 1;
47                 }
48                 else if (btoa[b] != a && !B[b]) {
49                     B[b] = lay;
50                 }
51             }
52             if (!islast) break;
53             swap(cur, next);
54         }
55         res += sz(cur);
56         rep(a, 0, sz(g)) if (A[a] != -1) A[a] = 0;
57     }
58     return res;
59 }

```

```

49         next.push_back(btoa[b]);
50     }
51 }
52 if (islast) break;
53 if (next.empty()) return res;
54 for (int a : next) A[a] = lay;
55 cur.swap(next);
56 }
57 /// Use DFS to scan for augmenting paths.
58 rep(a,0,sz(g))
59     res += dfs(a, 0, g, btoa, A, B);
60 }

```

## 7.7 Hungarian

```

1  /*
2  Notes:
3  note that n must be <= m
4  so in case in your problem n >= m, just swap
5  also note this
6  void set(int x, int y, ll v){a[x+1][y+1]=v;}
7  the algorithm assumes you're using 0-index
8  but it's using 1-based
9  */
10 struct Hungarian {
11     const ll INF = 1000000000000000000; ///10^18
12     int n,m;
13     vector<vector<ll>> > a;
14     vector<ll> u,v;vector<int> p,way;
15     Hungarian(int n, int m):
16         n(n),m(m),a(n+1,vector<ll>(m+1,INF-1)),u(n+1),v(m+1),p(m+1),way(m+1){}
17     void set(int x, int y, ll v){a[x+1][y+1]=v;}
18     ll assign(){
19         for(int i = 1; i <= n; i++){
20             int j0=0;p[0]=i;
21             vector<ll> minv(m+1,INF);
22             vector<char> used(m+1,false);
23             do {
24                 used[j0]=true;
25                 int i0=p[j0],j1,ll delta=INF;
26                 for(int j = 1; j <= m; j++){if(!used[j]){
27                     ll cur=a[i0][j]-u[i0]-v[j];
28                     if(cur<minv[j])minv[j]=cur,way[j]=j0;
29                     if(minv[j]<delta)delta=minv[j],j1=j;
30                 }
31                 for(int j = 0; j <= m; j++){
32                     if(used[j])u[p[j]]+=delta,v[j]-=delta;
33                     else minv[j]-=delta;
34                     j0=j1;
35                 } while(p[j0]);
36                 do {
37                     int j1=way[j0];p[j0]=p[j1];j0=j1;
38                 } while(j0);
39             }
40             return -v[0];
41         }
42         vector<int> restoreAnswer() { ///run it after assign
43             vector<int> ans (n+1);
44             for (int j=1; j<=m; ++j)
45                 ans[p[j]] = j;
46             return ans;
47         }
48     };

```

## 7.8 Kosaraju

```

1  /*
2  g : Adjacency List of the original graph
3  rg : Reversed Adjacency List
4  vis : A bitset to mark visited nodes
5  adj : Adjacency List of the super graph
6  stk : holds dfs ordered elements
7  cmp[i] : holds the component of node i
8  go[i] : holds the nodes inside the strongly connected component i
9  */
10
11 #define FOR(i,a,b) for(int i = a; i < b; i++)
12 #define pb push_back
13
14 const int N = 1e5+5;
15
16 vector<vector<int>>g, rg;
17 vector<vector<int>>go;
18 bitset<N>vis;
19 vector<vector<int>>adj;
20 stack<int>stk;
21 int n, m, cmp[N];
22 void add_edge(int u, int v){
23     g[u].push_back(v);

```

```

24     rg[v].push_back(u);
25 }
26 void dfs(int u){
27     vis[u]=1;
28     for(auto v : g[u])if(!vis[v])dfs(v);
29     stk.push(u);
30 }
31 void rdfs(int u,int c){
32     vis[u] = 1;
33     cmp[u] = c;
34     go[c].push_back(u);
35     for(auto v : rg[u])if(!vis[v])rdfs(v,c);
36 }
37 int scc(){
38     vis.reset();
39     for(int i = 0; i < n; i++)if(!vis[i])
40         dfs(i);
41     vis.reset();
42     int c = 0;
43     while(stk.size()){
44         auto cur = stk.top();
45         stk.pop();
46         if(!vis[cur])
47             rdfs(cur,c++);
48     }
49     return c;
50 }
51 }

```

## 7.9 Manhattan MST

```

1  #include<bits/stdc++.h>
2  using namespace std;
3
4  const int N = 2e5 + 9;
5
6  int n;
7  vector<pair<int, int>> g[N];
8  struct PT {
9      int x, y, id;
10     bool operator < (const PT &p) const {
11         return x == p.x ? y < p.y : x < p.x;
12     }
13 } p[N];
14 struct node {
15     int val, id;
16 } t[N];
17 struct DSU {
18     int p[N];
19     void init(int n) { for (int i = 1; i <= n; i++) p[i] = i; }
20     int find(int u) { return p[u] == u ? u : p[u] = find(p[u]); }
21     void merge(int u, int v) { p[find(u)] = find(v); }
22 } dsu;
23 struct edge {
24     int u, v, w;
25     bool operator < (const edge &p) const { return w < p.w; }
26 };
27 vector<edge> edges;
28 int query(int x) {
29     int r = 2e9 + 10, id = -1;
30     for (; x <= n; x += (x & -x)) if (t[x].val < r) r = t[x].val, id = t[x].id;
31     return id;
32 }
33 void modify(int x, int w, int id) {
34     for (; x > 0; x -= (x & -x)) if (t[x].val > w) t[x].val = w, t[x].id = id;
35 }
36 int dist(PT &a, PT &b) {
37     return abs(a.x - b.x) + abs(a.y - b.y);
38 }
39 void add(int u, int v, int w) {
40     edges.push_back({u, v, w});
41 }
42 long long Kruskal() {
43     dsu.init(n);
44     sort(edges.begin(), edges.end());
45     long long ans = 0;
46     for (edge e : edges) {
47         int u = e.u, v = e.v, w = e.w;
48         if (dsu.find(u) != dsu.find(v)) {
49             ans += w;
50             g[u].push_back({v, w});
51             //g[v].push_back({u, w});
52             dsu.merge(u, v);
53         }
54     }
55     return ans;
56 }
57 void Manhattan() {
58     for (int i = 1; i <= n; ++i) p[i].id = i;
59     for (int dir = 1; dir <= 4; ++dir) {

```

```

60     if (dir == 2 || dir == 4) {
61         for (int i = 1; i <= n; ++i) swap(p[i].x, p[i].y);
62     }
63     else if (dir == 3) {
64         for (int i = 1; i <= n; ++i) p[i].x = -p[i].x;
65     }
66     sort(p + 1, p + 1 + n);
67     vector<int> v;
68     static int a[N];
69     for (int i = 1; i <= n; ++i) a[i] = p[i].y - p[i].x, v.push_back(a[i]);
70     sort(v.begin(), v.end());
71     v.erase(unique(v.begin(), v.end()), v.end());
72     for (int i = 1; i <= n; ++i) a[i] = lower_bound(v.begin(), v.end(), a[i]) -
        v.begin() + 1;
73     for (int i = 1; i <= n; ++i) t[i].val = 2e9 + 10, t[i].id = -1;
74     for (int i = n; i >= 1; --i) {
75         int pos = query(a[i]);
76         if (pos != -1) add(p[i].id, p[pos].id, dist(p[i], p[pos]));
77         modify(a[i], p[i].x + p[i].y, i);
78     }
79 }
80 }
81 int32_t main() {
82     ios_base::sync_with_stdio(0);
83     cin.tie(0);
84     cin >> n;
85     for (int i = 1; i <= n; i++) cin >> p[i].x >> p[i].y;
86     Manhattant();
87     cout << Kruskal() << '\n';
88     for (int u = 1; u <= n; u++) {
89         for (auto x: g[u]) cout << u - 1 << ' ' << x.first - 1 << '\n';
90     }
91     return 0;
92 }

```

## 7.10 Maximum Clique

```

1  ///Complexity O(3 ^ (N/3)) i.e works for 50
2  ///you can change it to maximum independent set by flipping the edges 0->1, 1->0
3  ///if you want to extract the nodes they are 1-bits in R
4  int g[60][60];
5  int res;
6  long long edges[60];
7  void BronKerbosch(int n, long long R, long long P, long long X) {
8      if (P == 0LL && X == 0LL) { //here we will find all possible maximal cliques (
        not maximum) i.e. there is no node which can be included in this set
9          int t = __builtin_popcountll(R);
10         res = max(res, t);
11         return;
12     }
13     int u = 0;
14     while (!(1LL << u) & (P | X)) u++;
15     for (int v = 0; v < n; v++) {
16         if (((1LL << v) & P) && !((1LL << v) & edges[u])) {
17             BronKerbosch(n, R | (1LL << v), P & edges[v], X & edges[v]);
18             P |= (1LL << v);
19             X |= (1LL << v);
20         }
21     }
22 }
23 int max_clique (int n) {
24     res = 0;
25     for (int i = 1; i <= n; i++) {
26         edges[i - 1] = 0;
27         for (int j = 1; j <= n; j++) if (g[i][j]) edges[i - 1] |= (1LL << (j - 1));
28     }
29     BronKerbosch(n, 0, (1LL << n) - 1, 0);
30     return res;
31 }

```

## 7.11 MCMF

```

1  /*
2  Notes:
3  make sure you notice the #define int ll
4  focus on the data types of the max flow everythign inside is integer
5  addEdge(u,v,cap,cost)
6  note that for min cost max flow the cost is sum of cost * flow over all
7  edges
8  */
9  struct Edge {
10     int to;
11     int cost;
12     int cap, flow, backEdge;
13 };
14
15 struct MCMF {

```

```

16     const int inf = 1000000010;
17     int n;
18     vector<vector<Edge>> g;
19
20     MCMF(int _n) {
21         n = _n + 1;
22         g.resize(n);
23     }
24
25     void addEdge(int u, int v, int cap, int cost) {
26         Edge e1 = {v, cost, cap, 0, (int) g[v].size()};
27         Edge e2 = {u, -cost, 0, 0, (int) g[u].size()};
28         g[u].push_back(e1);
29         g[v].push_back(e2);
30     }
31
32     pair<int, int> minCostMaxFlow(int s, int t) {
33         int flow = 0;
34         int cost = 0;
35         vector<int> state(n), from(n), from_edge(n);
36         vector<int> d(n);
37         deque<int> q;
38         while (true) {
39             for (int i = 0; i < n; i++)
40                 state[i] = 2, d[i] = inf, from[i] = -1;
41             state[s] = 1;
42             q.clear();
43             q.push_back(s);
44             d[s] = 0;
45             while (!q.empty()) {
46                 int v = q.front();
47                 q.pop_front();
48                 state[v] = 0;
49                 for (int i = 0; i < (int) g[v].size(); i++) {
50                     Edge e = g[v][i];
51                     if (e.flow >= e.cap || (d[e.to] <= d[v] + e.cost))
52                         continue;
53                     int to = e.to;
54                     d[to] = d[v] + e.cost;
55                     from[to] = v;
56                     from_edge[to] = i;
57                     if (state[to] == 1) continue;
58                     if (!state[to] || (!q.empty() && d[q.front()] > d[to]))
59                         q.push_front(to);
60                     else q.push_back(to);
61                     state[to] = 1;
62                 }
63             }
64             if (d[t] == inf) break;
65             int it = t, addflow = inf;
66             while (it != s) {
67                 addflow = min(addflow,
68                             g[from[it]][from_edge[it]].cap
69                             - g[from[it]][from_edge[it]].flow);
70                 it = from[it];
71             }
72             it = t;
73             while (it != s) {
74                 g[from[it]][from_edge[it]].flow += addflow;
75                 g[it][g[from[it]][from_edge[it]].backEdge].flow -= addflow;
76                 cost += g[from[it]][from_edge[it]].cost * addflow;
77                 it = from[it];
78             }
79             flow += addflow;
80         }
81         return {cost, flow};
82     }
83 };

```

## 7.12 Minmimum Vertex Cover (Bipartite)

```

1  int myrandom (int i) { return std::rand()%i; }
2
3  struct MinimumVertexCover {
4     int n, id;
5     vector<vector<int> > g;
6     vector<int> color, m, seen;
7     vector<int> comp[2];
8     MinimumVertexCover() {}
9     MinimumVertexCover(int n, vector<vector<int> > g) {
10         this->n = n;
11         this->g = g;
12         color = m = vector<int>(n, -1);
13         seen = vector<int>(n, 0);
14         makeBipartite();
15     }
16
17     void dfsBipartite(int node, int col) {
18         if (color[node] != -1) {

```

```

19     assert(color[node] == col); /* MSH BIPARTITE YA BASHMOHANDES */
20     return;
21 }
22 color[node] = col;
23 comp[col].push_back(node);
24 for (int i = 0; i < int(g[node].size()); i++)
25     dfsBipartite(g[node][i], 1 - col);
26 }
27
28 void makeBipartite() {
29     for (int i = 0; i < n; i++)
30         if (color[i] == -1)
31             dfsBipartite(i, 0);
32 }
33
34 // match a node
35 bool dfs(int node) {
36     random_shuffle(g[node].begin(), g[node].end());
37     for (int i = 0; i < g[node].size(); i++) {
38         int child = g[node][i];
39         if (m[child] == -1) {
40             m[node] = child;
41             m[child] = node;
42             return true;
43         }
44         if (seen[child] == id)
45             continue;
46         seen[child] = id;
47         int enemy = m[child];
48         m[node] = child;
49         m[child] = node;
50         m[enemy] = -1;
51         if (dfs(enemy))
52             return true;
53         m[node] = -1;
54         m[child] = enemy;
55         m[enemy] = child;
56     }
57     return false;
58 }
59
60 void makeMatching() {
61     for (int j = 0; j < 5; j++)
62         random_shuffle(comp[0].begin(), comp[0].end(), myrandom);
63     for (int i = 0; i < int(comp[0].size()); i++) {
64         id++;
65         if (m[comp[0][i]] == -1)
66             dfs(comp[0][i]);
67     }
68 }
69
70 void recurse(int node, int x, vector<int> &minCover, vector<int> &done) {
71     if (m[node] != -1)
72         return;
73     if (done[node]) return;
74     done[node] = 1;
75     for (int i = 0; i < int(g[node].size()); i++) {
76         int child = g[node][i];
77         int newnode = m[child];
78         if (done[child]) continue;
79         if (newnode == -1) {
80             continue;
81         }
82         done[child] = 2;
83         minCover.push_back(child);
84         m[newnode] = -1;
85         recurse(newnode, x, minCover, done);
86     }
87 }
88
89 vector<int> getAnswer() {
90     vector<int> minCover, maxIndep;
91     vector<int> done(n, 0);
92     makeMatching();
93     for (int x = 0; x < 2; x++)
94         for (int i = 0; i < int(comp[x].size()); i++) {
95             int node = comp[x][i];
96             if (m[node] == -1)
97                 recurse(node, x, minCover, done);
98         }
99
100     for (int i = 0; i < int(comp[0].size()); i++)
101         if (!done[comp[0][i]]) {
102             minCover.push_back(comp[0][i]);
103         }
104     return minCover;
105 }
106 }
107 }

```

## 7.13 Prufer Code

```

1  const int N = 3e5 + 9;
2  /*
3  prufer code is a sequence of length n-2 to uniquely determine a labeled tree
4  with n vertices
5  Each time take the leaf with the lowest number and add the node number the leaf
6  is connected to
7  the sequence and remove the leaf. Then break the algo after n-2 iterations
8  */
9  //0-indexed
10 int n;
11 vector<int> g[N];
12 int parent[N], degree[N];
13
14 void dfs (int v) {
15     for (size_t i = 0; i < g[v].size(); ++i) {
16         int to = g[v][i];
17         if (to != parent[v]) {
18             parent[to] = v;
19             dfs (to);
20         }
21     }
22 }
23
24 vector<int> prufer_code() {
25     parent[n - 1] = -1;
26     dfs (n - 1);
27     int ptr = -1;
28     for (int i = 0; i < n; ++i) {
29         degree[i] = (int) g[i].size();
30         if (degree[i] == 1 && ptr == -1) ptr = i;
31     }
32     vector<int> result;
33     int leaf = ptr;
34     for (int iter = 0; iter < n - 2; ++iter) {
35         int next = parent[leaf];
36         result.push_back (next);
37         --degree[next];
38         if (degree[next] == 1 && next < ptr) leaf = next;
39         else {
40             ++ptr;
41             while (ptr < n && degree[ptr] != 1) ++ptr;
42             leaf = ptr;
43         }
44     }
45     return result;
46 }
47
48 vector < pair<int, int> > prufer_to_tree(const vector<int> & prufer_code) {
49     int n = (int) prufer_code.size() + 2;
50     vector<int> degree (n, 1);
51     for (int i = 0; i < n - 2; ++i) ++degree[prufer_code[i]];
52
53     int ptr = 0;
54     while (ptr < n && degree[ptr] != 1) ++ptr;
55     int leaf = ptr;
56     vector < pair<int, int> > result;
57     for (int i = 0; i < n - 2; ++i) {
58         int v = prufer_code[i];
59         result.push_back (make_pair (leaf, v));
60         --degree[leaf];
61         if (--degree[v] == 1 && v < ptr) leaf = v;
62         else {
63             ++ptr;
64             while (ptr < n && degree[ptr] != 1) ++ptr;
65             leaf = ptr;
66         }
67     }
68     for (int v = 0; v < n - 1; ++v) if (degree[v] == 1) result.push_back (
69         make_pair (v, n - 1));
70     return result;
71 }

```

## 7.14 Push Relabel Max Flow

```

1  struct edge {
2      int from, to, cap, flow, index;
3      edge(int from, int to, int cap, int flow, int index) :
4          from(from), to(to), cap(cap), flow(flow), index(index) {}
5  };
6
7  struct PushRelabel {
8      int n;
9      vector <vector<edge>> g;
10     vector<long long> excess;
11     vector<int> height, active, count;
12     queue<int> Q;
13
14     PushRelabel(int n) :
15         n(n), g(n), excess(n), height(n), active(n), count(2 * n) {}
16
17     void addEdge(int from, int to, int cap) {

```

```

18     g[from].push_back(edge(from, to, cap, 0, g[to].size()));
19     if (from == to)
20         g[from].back().index++;
21     g[to].push_back(edge(to, from, 0, 0, g[from].size() - 1));
22 }
23
24 void enqueue(int v) {
25     if (!active[v] && excess[v] > 0) {
26         active[v] = true;
27         Q.push(v);
28     }
29 }
30
31 void push(edge &e) {
32     int amt = (int) min(excess[e.from], (long long) e.cap - e.flow);
33     if (height[e.from] <= height[e.to] || amt == 0)
34         return;
35     e.flow += amt;
36     g[e.to][e.index].flow -= amt;
37     excess[e.to] += amt;
38     excess[e.from] -= amt;
39     enqueue(e.to);
40 }
41
42 void relabel(int v) {
43     count[height[v]]--;
44     int d = 2 * n;
45     for (auto &it: g[v]) {
46         if (it.cap - it.flow > 0)
47             d = min(d, height[it.to] + 1);
48     }
49     height[v] = d;
50     count[height[v]]++;
51     enqueue(v);
52 }
53
54 void gap(int k) {
55     for (int v = 0; v < n; v++) {
56         if (height[v] < k)
57             continue;
58         count[height[v]]--;
59         height[v] = max(height[v], n + 1);
60         count[height[v]]++;
61         enqueue(v);
62     }
63 }
64
65 void discharge(int v) {
66     for (int i = 0; excess[v] > 0 && i < g[v].size(); i++)
67         push(g[v][i]);
68     if (excess[v] > 0) {
69         if (count[height[v]] == 1)
70             gap(height[v]);
71         else
72             relabel(v);
73     }
74 }
75
76 long long max_flow(int source, int dest) {
77     count[0] = n - 1;
78     count[n] = 1;
79     height[source] = n;
80     active[source] = active[dest] = 1;
81     for (auto &it: g[source]) {
82         excess[source] += it.cap;
83         push(it);
84     }
85
86     while (!Q.empty()) {
87         int v = Q.front();
88         Q.pop();
89         active[v] = false;
90         discharge(v);
91     }
92
93     long long max_flow = 0;
94     for (auto &e: g[source])
95         max_flow += e.flow;
96
97     return max_flow;
98 }
99 };

```

## 7.15 Tarjan Algo

```

1 vector<vector<int>> scc;
2 vector<int> adj[N];
3 int dfsn[N], low[N], cost[N], timer, in_stack[N];
4 stack<int> st;
5
6 // to detect all the components (cycles) in a directed graph

```

```

7 void tarjan(int node) {
8     dfsn[node] = low[node] = ++timer;
9     in_stack[node] = 1;
10    st.push(node);
11    for(auto i: adj[node]) {
12        if(dfsn[i] == 0) {
13            tarjan(i);
14            low[node] = min(low[node], low[i]);
15        }
16        else if(in_stack[i]) low[node] = min(low[node], dfsn[i]);
17    }
18    if(dfsn[node] == low[node]) {
19        scc.push_back(vector<int>());
20        while(1) {
21            int cur = st.top();
22            st.pop();
23            in_stack[cur] = 0;
24            scc.back().push_back(cur);
25            if(cur == node) break;
26        }
27    }
28 }
29
30 int main() {
31     int m;
32     cin >> m;
33     while(m--) {
34         int u, v;
35         cin >> u >> v;
36         adj[u].push_back(v);
37     }
38     for(int i = 1; i <= n; i++) {
39         if(dfsn[i] == 0) {
40             tarjan(i);
41         }
42     }
43     return 0;
44 }

```

## 7.16 Bipartite Matching

```

1 // vertex are one based
2 struct graph
3 {
4     int L, R;
5     vector<vector<int>> adj;
6     graph(int l, int r) : L(l), R(r), adj(l+1) {}
7     void add_edge(int u, int v)
8     {
9         adj[u].push_back(v+L);
10    }
11    int maximum_matching()
12    {
13        vector<int> mate(L+R+1, -1), level(L+1);
14        function<bool (void)> levelize = [&]() {
15            {
16                queue<int> q;
17                for(int i=1; i<=L; i++)
18                {
19                    level[i]=-1;
20                    if(mate[i]<0)
21                        q.push(i), level[i]=0;
22                }
23                while(!q.empty())
24                {
25                    int node=q.front();
26                    q.pop();
27                    for(auto i: adj[node])
28                    {
29                        int v=mate[i];
30                        if(v<0)
31                            return true;
32                        if(level[v]<0)
33                        {
34                            level[v]=level[node]+1;
35                            q.push(v);
36                        }
37                    }
38                }
39                return false;
40            };
41            function<bool (int)> augment = [&](int node)
42            {
43                for(auto i: adj[node])
44                {
45                    int v=mate[i];
46                    if(v<0 || (level[v]>level[node] && augment(v)))
47                    {
48                        mate[node]=i;
49                        mate[i]=node;

```



```

50         return true;
51     }
52 }
53     return false;
54 };
55 int match=0;
56 while(levelize())
57     for(int i=1; i<=L; i++)
58         if(mate[i] < 0 && augment(i))
59             match++;
60     return match;
61 }
62 };

```

## 8 Math

### 8.1 Sum Of floored division.

```

1  typedef unsigned long long ull;
2  ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }
3
4  // return sum_{i=0}^{to-1} floor((ki + c) / m) (mod 2^64)
5  ull divsum(ull to, ull c, ull k, ull m) {
6      ull res = k / m * sumsq(to) + c / m * to;
7      k %= m; c %= m;
8      if (!k) return res;
9      ull to2 = (to * k + c) / m;
10     return res + (to - 1) * to2 - divsum(to2, m-1 - c, m, k);
11 }
12 // return sum_{i=0}^{to-1} (ki+c) % m
13 ll modsum(ull to, ll c, ll k, ll m) {
14     c = ((c % m) + m) % m;
15     k = ((k % m) + m) % m;
16     return to * c + k * sumsq(to) - m * divsum(to, c, k, m);
17 }

```

### 8.2 ModMulLL

```

1  // Calculate a^b % c and a*b % c
2  ull modmul(ull a, ull b, ull M) {
3      ll ret = a * b - M * ull(1.L / M * a * b);
4      return ret + M * (ret < 0) - M * (ret >= (ll)M);
5  }
6  ull modpow(ull b, ull e, ull mod) {
7      ull ans = 1;
8      for (; e; b = modmul(b, b, mod), e /= 2)
9          if (e & 1) ans = modmul(ans, b, mod);
10     return ans;
11 }

```

### 8.3 MillerRabin Primality check

```

1  "ModMulLL.cpp"
2  typedef unsigned long long ull;
3  ull modmul(ull a, ull b, ull M) {
4      ll ret = a * b - M * ull(1.L / M * a * b);
5      return ret + M * (ret < 0) - M * (ret >= (ll)M);
6  }
7  ull modpow(ull b, ull e, ull mod) {
8      ull ans = 1;
9      for (; e; b = modmul(b, b, mod), e /= 2)
10         if (e & 1) ans = modmul(ans, b, mod);
11     return ans;
12 }
13
14 bool isPrime(ull n) {
15     if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
16     ull A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},
17             s = __builtin_ctzll(n - 1), d = n >> s;
18     for (ull a: A) { // ^ count trailing zeroes
19         ull p = modpow(a % n, d, n), i = s;
20         while (p != 1 && p != n - 1 && a % n && i--)
21             p = modmul(p, p, n);
22         if (p != n - 1 && i != s) return 0;
23     }
24     return 1;
25 }

```

### 8.4 Pollard-rho randomized factorization algorithm $O(n^{1/4})$

```

1  "ModMulLL.cpp", "MillerRabin.cpp"
2  ull pollard(ull n) {
3      auto f = [n](ull x) { return modmul(x, x, n) + 1; };
4      ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;
5      while (t++ % 40 || __gcd(prd, n) == 1) {
6          if (x == y) x = ++i, y = f(x);
7          if ((q = modmul(prd, max(x,y) - min(x,y), n))) prd = q;

```

```

8          x = f(x), y = f(f(y));
9      }
10     return __gcd(prd, n);
11 }
12 vector<ull> factor(ull n) {
13     if (n == 1) return {};
14     if (isPrime(n)) return {n};
15     ull x = pollard(n);
16     auto l = factor(x), r = factor(n / x);
17     l.insert(l.end(), all(r));
18     return l;
19 }
20 }

```

### 8.5 ModSqrt Finds $x$ s.t $x^2 = a \pmod p$

```

1  ll sqrt(ll a, ll p) {
2      a %= p; if (a < 0) a += p;
3      if (a == 0) return 0;
4      assert(modpow(a, (p-1)/2, p) == 1); // else no solution
5      if (p % 4 == 3) return modpow(a, (p+1)/4, p);
6      // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works if p % 8 == 5
7      ll s = p - 1, n = 2;
8      int r = 0, m;
9      while (s % 2 == 0)
10         ++r, s /= 2;
11     while (modpow(n, (p - 1) / 2, p) != p - 1) ++n;
12     ll x = modpow(a, (s + 1) / 2, p);
13     ll b = modpow(a, s, p), g = modpow(n, s, p);
14     for (;;) r = m {
15         ll t = b;
16         for (m = 0; m < r && t != 1; ++m)
17             t = t * t % p;
18         if (m == 0) return x;
19         ll gs = modpow(g, 1LL << (r - m - 1), p);
20         g = gs * gs % p;
21         x = x * gs % p;
22         b = b * g % p;
23     }
24 }

```

### 8.6 Xor With Gauss

```

1  void insertVector(int mask) {
2      for (int i = d - 1; i >= 0; i--) {
3          if ((mask & 1 << i) == 0) continue;
4          if (!basis[i]) {
5              basis[i] = mask;
6              return;
7          }
8          mask ^= basis[i];
9      }
10 }

```

### 8.7 Josephus

```

1  // n = total person
2  // will kill every kth person, if k = 2, 2,4,6,...
3  // returns the mth killed person
4  ll josephus(ll n, ll k, ll m) {
5      m = n - m;
6      if (k <= 1) return n - m;
7      ll i = m;
8      while (i < n) {
9          ll r = (i - m + k - 2) / (k - 1);
10         if ((i + r) > n) r = n - i;
11         else if (!r) r = 1;
12         i += r;
13         m = (m + (r * k)) % i;
14     } return m + 1;
15 }

```

## 9 Strings

### 9.1 Aho-Corasick Mostafa

```

1  struct AC_FSM {
2      #define ALPHABET_SIZE 26
3
4      struct Node {
5          int child[ALPHABET_SIZE], failure = 0, match_parent = -1;
6          vector<int> match;
7      }
8      Node() {
9          for (int i = 0; i < ALPHABET_SIZE; ++i) child[i] = -1;
10     }
11 };

```

```

12 vector<Node> a;
13
14 AC_FSM() {
15     a.push_back(Node());
16 }
17
18 void construct_automaton(vector<string> &words) {
19     for (int w = 0, n = 0; w < words.size(); ++w, n = 0) {
20         for (int i = 0; i < words[w].size(); ++i) {
21             if (a[n].child[words[w][i] - 'a'] == -1) {
22                 a[n].child[words[w][i] - 'a'] = a.size();
23                 a.push_back(Node());
24             }
25             n = a[n].child[words[w][i] - 'a'];
26         }
27         a[n].match.push_back(w);
28     }
29     queue<int> q;
30     for (int k = 0; k < ALPHABET_SIZE; ++k) {
31         if (a[0].child[k] == -1) a[0].child[k] = 0;
32         else if (a[0].child[k] > 0) {
33             a[a[0].child[k]].failure = 0;
34             q.push(a[0].child[k]);
35         }
36     }
37     while (!q.empty()) {
38         int r = q.front();
39         q.pop();
40         for (int k = 0, arck; k < ALPHABET_SIZE; ++k) {
41             if ((arck = a[r].child[k]) != -1) {
42                 q.push(arck);
43                 int v = a[r].failure;
44                 while (a[v].child[k] == -1) v = a[v].failure;
45                 a[arck].failure = a[v].child[k];
46                 a[arck].match_parent = a[v].child[k];
47                 while (a[arck].match_parent != -1 &&
48                     a[a[arck].match_parent].match.empty())
49                     a[a[arck].match_parent].match_parent =
50                         a[a[arck].match_parent].match_parent;
51             }
52         }
53     }
54 }
55
56 void aho_corasick(string &sentence, vector<string> &words,
57     vector<vector<int>> &matches) {
58     matches.assign(words.size(), vector<int>());
59     int state = 0, ss = 0;
60     for (int i = 0; i < sentence.length(); ++i, ss = state) {
61         while (a[ss].child[sentence[i] - 'a'] == -1)
62             ss = a[ss].failure;
63         state = a[ss].child[sentence[i] - 'a'];
64         for (ss = state; ss != -1; ss = a[ss].match_parent)
65             for (int w: a[ss].match)
66                 matches[w].push_back(i + 1 - words[w].length());
67     }
68 }
69
70 };

```

## 9.2 KMP Anany

```

1 vector<int> fail(string s) {
2     int n = s.size();
3     vector<int> pi(n);
4     for (int i = 1; i < n; ++i) {
5         int g = pi[i-1];
6         while (g && s[i] != s[g])
7             g = pi[g-1];
8         g += s[i] == s[g];
9         pi[i] = g;
10    }
11    return pi;
12 }
13 vector<int> KMP(string s, string t) {
14     vector<int> pi = fail(t);
15     vector<int> ret;
16     for (int i = 0, g = 0; i < s.size(); ++i) {
17         while (g && s[i] != t[g])
18             g = pi[g-1];
19         g += s[i] == t[g];
20         if (g == t.size()) { ///occurrence found
21             ret.push_back(i-t.size()+1);
22             g = pi[g-1];
23         }
24     }
25     return ret;
26 }

```

## 9.3 Manacher Kactl

```

1 // If the size of palindrome centered at i is x, then dl[i] stores (x+1)/2.
2
3 vector<int> dl(n);
4 for (int i = 0, l = 0, r = -1; i < n; ++i) {
5     int k = (i > r) ? 1 : min(dl[l + r - i], r - i + 1);
6     while (0 <= i - k && i + k < n && s[i - k] == s[i + k]) {
7         k++;
8     }
9     dl[i] = k--;
10    if (i + k > r) {
11        l = i - k;
12        r = i + k;
13    }
14 }
15
16 // If the size of palindrome centered at i is x, then d2[i] stores x/2
17 vector<int> d2(n);
18 for (int i = 0, l = 0, r = -1; i < n; ++i) {
19     int k = (i > r) ? 0 : min(d2[l + r - i + 1], r - i + 1);
20     while (0 <= i - k - 1 && i + k < n && s[i - k - 1] == s[i + k]) {
21         k++;
22     }
23     d2[i] = k--;
24     if (i + k > r) {
25         l = i - k - 1;
26         r = i + k;
27     }
28 }

```

## 9.4 Suffix Array Kactl

```

1 struct SuffixArray {
2     using vi = vector<int>;
3     #define rep(i,a,b) for(int i = a; i < b; i++)
4     #define all(x) begin(x), end(x)
5     /*
6      * Note this code is considers also the empty suffix
7      * so hear sa[0] = n and sa[1] is the smallest non empty suffix
8      * and sa[n] is the largest non empty suffix
9      * also LCP[i] = LCP(sa[i-1], sa[i]), meaning LCP[0] = LCP[1] = 0
10     * if you want to get LCP(i..j) you need to build a mapping between
11     * sa[i] and i, and build a min sparse table to calculate the minimum
12     * note that this minimum should consider sa[i+1...j] since you don't want
13     * to consider LCP(sa[i], sa[i-1])
14     *
15     * you should also print the suffix array and lcp at the beginning of the
16     * contest
17     * to clarify this stuff
18     */
19     vi sa, lcp;
20     SuffixArray(string& s, int lim=256) { // or basic_string<int>
21         int n = sz(s) + 1, k = 0, a, b;
22         vi x(all(s)+1), y(n), ws(max(n, lim)), rank(n);
23         sa = lcp = y, iota(all(sa), 0);
24         for (int j = 0, p = 0; p < n; j = max(1, j * 2), lim = p) {
25             p = j, iota(all(y), n - j);
26             rep(i,0,n) if (sa[i] >= j) y[p++] = sa[i] - j;
27             fill(all(ws), 0);
28             rep(i,0,n) ws[x[i]]++;
29             rep(i,1,lim) ws[i] += ws[i - 1];
30             for (int i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
31             swap(x, y), p = 1, x[sa[0]] = 0;
32             rep(i,1,n) a = sa[i - 1], b = sa[i], x[b] =
33                 (y[a] == y[b] && y[a + j] == y[b + j]) ? p - 1 : p++;
34         }
35         rep(i,1,n) rank[sa[i]] = i;
36         for (int i = 0, j; i < n - 1; lcp[rank[i++]] = k)
37             for (k && k--, j = sa[rank[i] - 1];
38                 s[i + k] == s[j + k]; k++);
39     };

```

## 9.5 Suffix Automaton Mostafa

```

1 struct SA {
2     struct node {
3         int to[26];
4         int link, len, co = 0;
5     };
6     node() {
7         memset(to, 0, sizeof to);
8         co = 0, link = 0, len = 0;
9     }
10 };
11
12 int last, sz;
13 vector<node> v;
14

```

```

15 SA() {
16     v = vector<node>(1);
17     last = 0, sz = 1;
18 }
19
20 void add_letter(int c) {
21     int p = last;
22     last = sz++;
23     v.push_back({});
24     v[last].len = v[p].len + 1;
25     v[last].co = 1;
26     for (; v[p].to[c] == 0; p = v[p].link)
27         v[p].to[c] = last;
28     if (v[p].to[c] == last) {
29         v[last].link = 0;
30         return;
31     }
32     int q = v[p].to[c];
33     if (v[q].len == v[p].len + 1) {
34         v[last].link = q;
35         return;
36     }
37     int cl = sz++;
38     v.push_back(v[q]);
39     v.back().co = 0;
40     v.back().len = v[p].len + 1;
41     v[last].link = v[q].link = cl;
42
43     for (; v[p].to[c] == q; p = v[p].link)
44         v[p].to[c] = cl;
45 }
46
47 void build_co() {
48     priority_queue<pair<int, int>> q;
49     for (int i = sz - 1; i > 0; i--)
50         q.push({v[i].len, i});
51     while (q.size()) {
52         int i = q.top().second;
53         q.pop();
54         v[v[i].link].co += v[i].co;
55     }
56 }
57 };

```

## 9.6 Zalgo Anany

```

1 int z[N], n;
2 void Zalgo(string s) {
3     int L = 0, R = 0;
4     for (int i = 1; i < n; i++) {
5         if (i <= R && z[i-L] < R - i + 1) z[i] = z[i-L];
6         else {
7             L = i;
8             R = max(R, i);
9             while (R < n && s[R-L] == s[R]) R++;
10            z[i] = R-L; --R;
11        }
12    }
13 }

```

## 9.7 lexicographically smallest rotation of a string

```

1 int minRotation(string s) {
2     int a=0, N=sz(s); s += s;
3     rep(b,0,N) rep(k,0,N) {
4         if (a+k == b || s[a+k] < s[b+k]) {b += max(0, k-1); break;}
5         if (s[a+k] > s[b+k]) {a = b; break;}
6     }
7     return a;
8 }

```

# Trees

## 10.1 Centroid Decomposition

```

1 /*
2  Properties:
3  1. consider path(a,b) can be decomposed to path(a,lca(a,b)) and path(b,
4     lca(a,b))
5     where lca(a,b) is the lca on the centroid tree
6     2. Each one of the n^2 paths is the concatenation of two paths in a set
7        of O(n lg(n))
8     paths from a node to all its ancestors in the centroid decomposition.
9     3. Ancestor of a node in the original tree is either an ancestor in the
10        CD tree or
11        a descendant
12 */

```

```

10 vector<int> adj[N]; ///adjacency list of original graph
11 int n;
12 int sz[N];
13 bool used[N];
14 int centPar[N]; ///parent in centroid
15 void init(int node, int par) { ///initialize size
16     sz[node] = 1;
17     for (auto p : adj[node])
18         if (p != par && !used[p]) {
19             init(p, node);
20             sz[node] += sz[p];
21         }
22 }
23 int centroid(int node, int par, int limit) { ///get centroid
24     for (int p : adj[node])
25         if (!used[p] && p != par && sz[p] * 2 > limit)
26             return centroid(p, node, limit);
27     return node;
28 }
29 int decompose(int node) {
30     init(node, node); ///calculate size
31     int c = centroid(node, node, sz[node]); ///get centroid
32     used[c] = true;
33     for (auto p : adj[c]) if (!used[p.F]) { ///initialize parent for others and
34         decompose
35         centPar[decompose(p.F)] = c;
36     }
37     return c;
38 }
39 void update(int node, int distance, int col) {
40     int centroid = node;
41     while (centroid) {
42         ///solve
43         centroid = centPar[centroid];
44     }
45 }
46 int query(int node) {
47     int ans = 0;
48
49     int centroid = node;
50     while (centroid) {
51         ///solve
52         centroid = centPar[centroid];
53     }
54
55     return ans;
56 }

```

## 10.2 Dsu On Trees

```

1 const int N = 1e5 + 9;
2 vector<int> adj[N];
3 int bigChild[N], sz[N];
4 void dfs(int node, int par) {
5     for (auto v : adj[node]) if (v != par) {
6         dfs(v, node);
7         sz[node] += sz[v];
8         if (!bigChild[node] || sz[v] > sz[bigChild[node]]) {
9             bigChild[node] = v;
10        }
11    }
12 }
13 void add(int node, int par, int bigChild, int delta) {
14     ///modify node to data structure
15
16     for (auto v : adj[node])
17         if (v != par && v != bigChild)
18             add(v, node, bigChild, delta);
19
20 }
21 void dfs2(int node, int par, bool keep) {
22     for (auto v : adj[node]) if (v != par && v != bigChild[node]) {
23         dfs2(v, node, 0);
24     }
25     if (bigChild[node]) {
26         dfs2(bigChild[node], node, true);
27     }
28     add(node, par, bigChild[node], 1);
29     ///process queries
30     if (!keep) {
31         add(node, par, -1, -1);
32     }
33 }
34 }

```

## 10.3 Heavy Light Decomposition (Along with Euler Tour)

```

1  /*
2  Notes:
3  1. 0-based
4  2. solve function iterates over segments and handles them separately
5  if you're gonna use it make sure you know what you're doing
6  3. to update/query segment in[node], out[node]
7  4. to update/query chain in[nxt[node]], in[node]
8  nxt[node]: is the head of the chain so to go to the next chain node =
   par[nxt[node]]
9
10 */
11 int sz[mxN], nxt[mxN];
12 int in[N], out[N], rin[N];
13 vector<int> g[mxN];
14 int par[mxN];
15
16 void dfs_sz(int v = 0, int p = -1) {
17     sz[v] = 1;
18     par[v] = p;
19     for (auto &u : g[v]) {
20         if (u == p) {
21             swap(u, g[v].back());
22         }
23         if (u == p) continue;
24         dfs_sz(u, v);
25         sz[v] += sz[u];
26         if (sz[u] > sz[g[v][0]])
27             swap(u, g[v][0]);
28     }
29     if (v != 0)
30         g[v].pop_back();
31 }
32
33 void dfs_hld(int v = 0) {
34     in[v] = t++;
35     rin[in[v]] = v;
36     for (auto u : g[v]) {
37         nxt[u] = (u == g[v][0] ? nxt[v] : u);
38         dfs_hld(u);
39     }
40     out[v] = t;
41 }
42
43 int n;
44 bool isChild(int p, int u) {
45     return in[p] <= in[u] && out[u] <= out[p];
46 }
47
48 int solve(int u, int v) {
49     vector<pair<int, int>> segv;
50     vector<pair<int, int>> segv;
51     if (isChild(u, v)) {
52         while (nxt[u] != nxt[v]) {
53             segv.push_back(make_pair(in[nxt[v]], in[v]));
54             v = par[nxt[v]];
55         }
56         segv.push_back({in[u], in[v]});
57     } else if (isChild(v, u)) {
58         while (nxt[u] != nxt[v]) {
59             segv.push_back(make_pair(in[nxt[u]], in[u]));
60             u = par[nxt[u]];
61         }
62         segv.push_back({in[v], in[u]});
63     } else {
64         while (u != v) {
65             if (nxt[u] == nxt[v]) {
66                 if (in[u] < in[v]) segv.push_back({in[u], in[v]}), R.push_back({v+1, v
67                     +1});
68                 else segv.push_back({in[v], in[u]}), L.push_back({v+1, u+1});
69                 u = v;
70                 break;
71             } else if (in[u] > in[v]) {
72                 segv.push_back({in[nxt[u]], in[u]}), L.push_back({nxt[u]+1, u+1});
73                 u = par[nxt[u]];
74             } else {
75                 segv.push_back({in[nxt[v]], in[v]}), R.push_back({nxt[v]+1, v+1});
76                 v = par[nxt[v]];
77             }
78         }
79         reverse(segv.begin(), segv.end());
80         int res = 0, state = 0;
81         for (auto p : segv) {
82             qry(1, 1, 0, n-1, p.first, p.second, state, res);
83         }
84         for (auto p : segv) {
85             qry(0, 1, 0, n-1, p.first, p.second, state, res);
86         }
87     }
88     return res;
89 }

```

## 10.4 Mo on Trees

```

1 // Calculate the DFS order, {1, 2, 3, 3, 4, 4, 2, 5, 6, 6, 5, 1}.
2 // Let a query be (u, v), ST(u) <= ST(v), P = LCA(u, v)
3 // Case 1: P = u : the query range would be [ST(u), ST(v)]
4 // Case 2: P != u : range would be [EN(u), ST(v)] + [ST(P), ST(P)].
5 // the path will be the nodes that appears exactly once in that range

```

## 11 Numerical

### 11.1 Lagrange Polynomial

```

1 class LagrangePoly {
2 public:
3     LagrangePoly(std::vector<long long> _a) {
4         //f(i) = _a[i]
5         //interpolates a vector em um polinomio de grau y.size() - 1
6         y = _a;
7         den.resize(y.size());
8         int n = (int) y.size();
9         for (int i = 0; i < n; i++) {
10             y[i] = (y[i] % MOD + MOD) % MOD;
11             den[i] = ifat[n - i - 1] * ifat[i] % MOD;
12             if ((n - i - 1) % 2 == 1) {
13                 den[i] = (MOD - den[i]) % MOD;
14             }
15         }
16     }
17
18     long long getVal(long long x) {
19         int n = (int) y.size();
20         x = (x % MOD + MOD) % MOD;
21         if (x < n) {
22             //return y[(int) x];
23         }
24         std::vector<long long> l, r;
25         l.resize(n);
26         l[0] = 1;
27         for (int i = 1; i < n; i++) {
28             l[i] = l[i - 1] * (x - (i - 1) + MOD) % MOD;
29         }
30         r.resize(n);
31         r[n - 1] = 1;
32         for (int i = n - 2; i >= 0; i--) {
33             r[i] = r[i + 1] * (x - (i + 1) + MOD) % MOD;
34         }
35         long long ans = 0;
36         for (int i = 0; i < n; i++) {
37             long long coef = l[i] * r[i] % MOD;
38             ans = (ans + coef * y[i] % MOD * den[i]) % MOD;
39         }
40         return ans;
41     }
42
43 private:
44     std::vector<long long> y, den;
45 };

```

### 11.2 Polynomials

```

1 struct Poly {
2     vector<double> a;
3     double operator()(double x) const {
4         double val = 0;
5         for (int i = sz(a); i--;) (val *= x) += a[i];
6         return val;
7     }
8     void diff() {
9         rep(1, 1, sz(a)) a[i-1] = i*a[i];
10        a.pop_back();
11    }
12    void divroot(double x0) {
13        double b = a.back(), c; a.back() = 0;
14        for (int i = sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0+b, b=c;
15        a.pop_back();
16    }
17 }
18
19 // Finds the real roots to a polynomial
20 // O(n^2 log(1/e))
21 vector<double> polyRoots(Poly p, double xmin, double xmax) {
22     if (sz(p.a) == 2) { return {-p.a[0] / p.a[1]}; }
23     vector<double> ret;
24     Poly der = p;
25     der.diff();
26     auto dr = polyRoots(der, xmin, xmax);
27     dr.push_back(xmin - 1);
28     dr.push_back(xmax + 1);
29     sort(all(dr));

```

```

30     rep(i, 0, sz(dr) - 1) {
31         double l = dr[i], h = dr[i + 1];
32         bool sign = p(l) > 0;
33         if (sign ^ (p(h) > 0)) {
34             rep(it, 0, 60) { // while (h - l > 1e-8)
35                 double m = (l + h) / 2, f = p(m);
36                 if ((f <= 0) ^ sign) l = m;
37                 else h = m;
38             }
39             ret.push_back((l + h) / 2);
40         }
41     }
42     return ret;
43 }
44
45 // Given n points (x[i], y[i]), computes an n-1-degree polynomial that passes
46 // through them.
47 // For numerical precision pick x[k] = c * cos(k / (n - 1) * pi).
48 // O(n^2)
49 typedef vector<double> vd;
50 vd interpolate(vd x, vd y, int n) {
51     vd res(n), temp(n);
52     rep(k, 0, n - 1) rep(i, k + 1, n)
53         y[i] = (y[i] - y[k]) / (x[i] - x[k]);
54     double last = 0;
55     temp[0] = 1;
56     rep(k, 0, n) rep(i, 0, n) {
57         res[i] += y[k] * temp[i];
58         swap(last, temp[i]);
59         temp[i] -= last * x[k];
60     }
61     return res;
62 }
63
64 // Recovers any n-order linear recurrence relation from the first 2n terms of
65 // the recurrence.
66 // Useful for guessing linear recurrences after bruteforcing the first terms.
67 // Should work on any field, but numerical stability for floats is not
68 // guaranteed.
69 // O(n^2)
70 vector<ll> berlekampMassey(vector<ll> s) {
71     int n = sz(s), L = 0, m = 0;
72     vector<ll> C(n), B(n), T;
73     C[0] = B[0] = 1;
74     ll b = 1;
75     rep(i, 0, n) { ++m;
76         ll d = s[i] % mod;
77         rep(j, 1, L + 1) d = (d + C[j] * s[i - j]) % mod;
78         if (!d) continue;
79         T = C; ll coef = d * modpow(b, mod - 2) % mod;
80         rep(j, m, n) C[j] = (C[j] - coef * B[j - m]) % mod;
81         if (2 * L > i) continue;
82         L = i + 1 - L; B = T; b = d; m = 0;
83     }
84     C.resize(L + 1); C.erase(C.begin());
85     for (ll &x: C) x = (mod - x) % mod;
86     return C;
87 }
88
89 // Generates the kth term of an n-order linear recurrence
90 // S[i] = S[i - j - 1]tr[j], given S[0..n-1] and tr[0..n-1]
91 // Useful together with Berlekamp-Massey.
92 // O(n^2 * log(k))
93
94 typedef vector<ll> Poly;
95 ll linearRec(Poly S, Poly tr, ll k) {
96     int n = sz(tr);
97     auto combine = [&](Poly a, Poly b) {
98         Poly res(n * 2 + 1);
99         rep(i, 0, n + 1) rep(j, 0, n + 1)
100             res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
101         for (int i = 2 * n; i > n; --i) rep(j, 0, n)
102             res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j]) % mod;
103         res.resize(n + 1);
104         return res;
105     };
106     Poly pol(n + 1), e(pol);
107     pol[0] = e[1] = 1;
108     for (++k; k; k /= 2) {
109         if (k % 2) pol = combine(pol, e);
110         e = combine(e, e);
111     }
112     ll res = 0;
113     rep(i, 0, n) res = (res + pol[i + 1] * S[i]) % mod;
114     return res;
115 }

```

## 12 Guide

### 12.1 Strings

- Longest Common Substring is easier with suffix automaton
- Problems that tell you count stuff that appears X times or count appearances (Use suffix links)
- Problems that tell you find the largest substring with some property (Use Suffix links)
- Remember suffix links are the same as aho corasick failure links (you can memoize them with dp)
- Problems that ask you to get the k-th string (can be either suffix automaton or array)
- Longest Common Prefix is mostly a (suffix automaton-array) thing
- try thinking bitsets

### 12.2 Volume




- Right circular cylinder =  $\pi r^2 h$
- Pyramid =  $\frac{Bh}{3}$
- Right circular cone =  $\frac{\pi r^2 h}{3}$
- Sphere =  $\frac{4}{3}\pi r^2 h$
- Sphere sector =  $\frac{2}{3}\pi r^2 h = \frac{2}{3}\pi r^3(1 - \cos(a))$
- Sphere cap =  $\frac{\pi h^2(3r - h)}{3}$

### 12.3 Graph Theory

- Euler formula:  $v + f = e + 2$

### 12.4 Joseph problem

$$g(n, k) = \begin{cases} 0 & \text{if } n = 1 \\ (g(n-1, k) + k) \bmod n & \text{if } 1 < n < k \\ \left\lfloor \frac{k((g(n', k) - n \bmod k) \bmod n')}{k-1} \right\rfloor \text{ where } n' = n - \left\lfloor \frac{n}{k} \right\rfloor & \text{if } k \leq n \end{cases}$$

<div></div> <p>Pythagorean theorem:</p> $C^2 = A^2 + B^2.$ <p>Definitions:</p> $\sin a = A/C, \quad \cos a = B/C,$ $\csc a = C/A, \quad \sec a = C/B,$ $\tan a = \frac{\sin a}{\cos a} = \frac{A}{B}, \quad \cot a = \frac{\cos a}{\sin a} = \frac{B}{A}.$ <p>Area, radius of inscribed circle:</p> $\frac{1}{2}AB, \quad \frac{AB}{A + B + C}.$ <p>Identities:</p> $\sin x = \frac{1}{\csc x}, \quad \cos x = \frac{1}{\sec x},$ $\tan x = \frac{1}{\cot x}, \quad \sin^2 x + \cos^2 x = 1,$ $1 + \tan^2 x = \sec^2 x, \quad 1 + \cot^2 x = \csc^2 x,$ $\sin x = \cos\left(\frac{\pi}{2} - x\right), \quad \sin x = \sin(\pi - x),$ $\cos x = -\cos(\pi - x), \quad \tan x = \cot\left(\frac{\pi}{2} - x\right),$ $\cot x = -\cot(\pi - x), \quad \csc x = \cot \frac{x}{2} - \cot x,$ $\sin(x \pm y) = \sin x \cos y \pm \cos x \sin y,$ $\cos(x \pm y) = \cos x \cos y \mp \sin x \sin y,$ $\tan(x \pm y) = \frac{\tan x \pm \tan y}{1 \mp \tan x \tan y},$ $\cot(x \pm y) = \frac{\cot x \cot y \mp 1}{\cot x \pm \cot y},$ $\sin 2x = 2 \sin x \cos x, \quad \sin 2x = \frac{2 \tan x}{1 + \tan^2 x},$ $\cos 2x = \cos^2 x - \sin^2 x, \quad \cos 2x = 2 \cos^2 x - 1,$ $\cos 2x = 1 - 2 \sin^2 x, \quad \cos 2x = \frac{1 - \tan^2 x}{1 + \tan^2 x},$ $\tan 2x = \frac{2 \tan x}{1 - \tan^2 x}, \quad \cot 2x = \frac{\cot^2 x - 1}{2 \cot x},$ $\sin(x + y) \sin(x - y) = \sin^2 x - \sin^2 y,$ $\cos(x + y) \cos(x - y) = \cos^2 x - \sin^2 y.$ <p>Euler's equation:</p> $e^{ix} = \cos x + i \sin x, \quad e^{i\pi} = -1.$	<p>Multiplication:</p> $C = A \cdot B, \quad c_{i,j} = \sum_{k=1}^n a_{i,k} b_{k,j}.$ <p>Determinants: <math>\det A \neq 0</math> iff <math>A</math> is non-singular.</p> $\det A \cdot B = \det A \cdot \det B,$ $\det A = \sum_{\pi} \prod_{i=1}^n \text{sign}(\pi) a_{i,\pi(i)}.$ <p><math>2 \times 2</math> and <math>3 \times 3</math> determinant:</p> $\begin{vmatrix} a & b \\ c & d \end{vmatrix} = ad - bc,$ $\begin{vmatrix} a & b & c \\ d & e & f \\ g & h & i \end{vmatrix} = g \begin{vmatrix} b & c \\ e & f \end{vmatrix} - h \begin{vmatrix} a & c \\ d & f \end{vmatrix} + i \begin{vmatrix} a & b \\ d & e \end{vmatrix}$ $= aei + bfg + cdh - ceg - fha - ibd.$ <p>Permanents:</p> $\text{perm } A = \sum_{\pi} \prod_{i=1}^n a_{i,\pi(i)}.$	<div></div> <p>Law of cosines:</p> $c^2 = a^2 + b^2 - 2ab \cos C.$ <p>Area:</p> $A = \frac{1}{2}hc,$ $= \frac{1}{2}ab \sin C,$ $= \frac{c^2 \sin A \sin B}{2 \sin C}.$ <p>Heron's formula:</p> $A = \sqrt{s \cdot s_a \cdot s_b \cdot s_c},$ $s = \frac{1}{2}(a + b + c),$ $s_a = s - a,$ $s_b = s - b,$ $s_c = s - c.$ <p>More identities:</p> $\sin \frac{x}{2} = \sqrt{\frac{1 - \cos x}{2}},$ $\cos \frac{x}{2} = \sqrt{\frac{1 + \cos x}{2}},$ $\tan \frac{x}{2} = \sqrt{\frac{1 - \cos x}{1 + \cos x}},$ $= \frac{1 - \cos x}{\sin x},$ $= \frac{\sin x}{1 + \cos x},$ $\cot \frac{x}{2} = \sqrt{\frac{1 + \cos x}{1 - \cos x}},$ $= \frac{1 + \cos x}{\sin x},$ $= \frac{\sin x}{1 - \cos x},$ $\sin x = \frac{e^{ix} - e^{-ix}}{2i},$ $\cos x = \frac{e^{ix} + e^{-ix}}{2},$ $\tan x = -i \frac{e^{ix} - e^{-ix}}{e^{ix} + e^{-ix}},$ $= -i \frac{e^{2ix} - 1}{e^{2ix} + 1},$ $\sin x = \frac{\sinh ix}{i},$ $\cos x = \cosh ix,$ $\tan x = \frac{\tanh ix}{i}.$																								
<p>v2.02 ©1994 by Steve Seiden sseiden@acm.org <a href="http://www.csc.lsu.edu/~seiden">http://www.csc.lsu.edu/~seiden</a></p>		<table><tr><th><math>\theta</math></th><th><math>\sin \theta</math></th><th><math>\cos \theta</math></th><th><math>\tan \theta</math></th></tr><tr><td>0</td><td>0</td><td>1</td><td>0</td></tr><tr><td><math>\frac{\pi}{6}</math></td><td><math>\frac{1}{2}</math></td><td><math>\frac{\sqrt{3}}{2}</math></td><td><math>\frac{\sqrt{3}}{3}</math></td></tr><tr><td><math>\frac{\pi}{4}</math></td><td><math>\frac{\sqrt{2}}{2}</math></td><td><math>\frac{\sqrt{2}}{2}</math></td><td>1</td></tr><tr><td><math>\frac{\pi}{3}</math></td><td><math>\frac{\sqrt{3}}{2}</math></td><td><math>\frac{1}{2}</math></td><td><math>\sqrt{3}</math></td></tr><tr><td><math>\frac{\pi}{2}</math></td><td>1</td><td>0</td><td><math>\infty</math></td></tr></table> <p>... in mathematics you don't understand things, you just get used to them.</p> <p>– J. von Neumann</p>	$\theta$	$\sin \theta$	$\cos \theta$	$\tan \theta$	0	0	1	0	$\frac{\pi}{6}$	$\frac{1}{2}$	$\frac{\sqrt{3}}{2}$	$\frac{\sqrt{3}}{3}$	$\frac{\pi}{4}$	$\frac{\sqrt{2}}{2}$	$\frac{\sqrt{2}}{2}$	1	$\frac{\pi}{3}$	$\frac{\sqrt{3}}{2}$	$\frac{1}{2}$	$\sqrt{3}$	$\frac{\pi}{2}$	1	0	$\infty$
$\theta$	$\sin \theta$	$\cos \theta$	$\tan \theta$																							
0	0	1	0																							
$\frac{\pi}{6}$	$\frac{1}{2}$	$\frac{\sqrt{3}}{2}$	$\frac{\sqrt{3}}{3}$																							
$\frac{\pi}{4}$	$\frac{\sqrt{2}}{2}$	$\frac{\sqrt{2}}{2}$	1																							
$\frac{\pi}{3}$	$\frac{\sqrt{3}}{2}$	$\frac{1}{2}$	$\sqrt{3}$																							
$\frac{\pi}{2}$	1	0	$\infty$																							