

EXPERIMENT 10:

```
exp10 | Arduino IDE 2.3.10
File Edit Sketch Tools Help
Arduino UNO
exp10.ino
1 int Status = 13; // Digital pin D13 (LED)
2 int sensor = 12; // Digital pin D12 (PIR OUT)
3
4 void setup() {
5   Serial.begin(9600);
6   pinMode(sensor, INPUT); // PIR sensor as input
7   pinMode(Status, OUTPUT); // LED as output
8 }
9
10 void loop() {
11   long state = digitalRead(sensor);
12   Serial.println(state);
13
14   if (state == HIGH) {
15     digitalWrite(Status, HIGH);
16     Serial.println("Motion detected!");
17     delay(1000);
18   }
19 }
Output
Using precompiled core: C:\Users\trish\AppData\Local\arduino\cores\arduino_avr_uno_1854fb47367fe1f0bbc92a1cf35fbde7\core.a
Linking everything together...
"C:\Users\trish\AppData\Local\Arduino15\packages\arduino\tools\avr-gcc\7.3.0-stm32\bin\avr-gcc" -w -Os -g -flto -fuse-linker-plugin -
"C:\Users\trish\AppData\Local\Arduino15\packages\arduino\tools\avr-gcc\7.3.0-stm32\bin\avr-objcopy" -O ihex -j .eeprom --set-section-
"C:\Users\trish\AppData\Local\Arduino15\packages\arduino\tools\avr-gcc\7.3.0-stm32\bin\avr-objcopy" -O ihex -R .eeprom "C:\Users\tr
"C:\Users\trish\AppData\Local\Arduino15\packages\arduino\tools\avr-gcc\7.3.0-stm32\bin\avr-gcc" -w -Os -g -flto -fuse-linker-plugin -
Sketch uses 2246 bytes (6%) of program storage space. Maximum is 32256 bytes.
Global variables use 220 bytes (10%) of dynamic memory, leaving 1828 bytes for local variables. Maximum is 2048 bytes.
```



