

Trishla Shah
Batch – CSE55
Enrollment No. - 22162171032

Institute of Computer Technology
B. Tech Computer Science and Engineering

Sub: Algorithm Analysis and Design


Practical 11

AIM:

A government official needs to visit several cities within a state. To minimize travel costs, they want to find the shortest path between their starting city and each destination city.

Task:

Given a graph representing the cities and their connecting roads, determine the minimum cost path from a given starting city to all other cities.



Input:

Enter total number of nodes: 5

Enter the node from where you want to calculate the distance: A

Enter Data (Weight):

	A	B	C	D	E
A	0	20	30	∞	∞
B	∞	0	∞	15	∞
C	∞	∞	0	∞	25
D	∞	∞	∞	0	10
E	∞	∞	∞	∞	0

Output:

	A	B	C	D	E
A	0	20	30	35	45
B	∞	0	∞	15	25

C	∞	∞	0	∞	25
D	∞	∞	∞	0	10
E	∞	∞	∞	∞	0

OR

Source	Destination	Cost
A	A	0
	B	20
	C	30
	D	35
	E	45

Code :-

```
import sys
```

```
def dijkstra(graph,
    start_node): n = len(graph)
    visited = [False] * n
    distance = [sys.maxsize] *
    ndistance[start_node] = 0
```

```
for _ in range(n):
    min_distance =
    sys.maxsize min_index = -1
```

```

for i in range(n):
    if not visited[i] and distance[i] <
        min_distance: min_distance = distance[i]
        min_index = i
visited[min_index] =
True

for j in range(n):
    if graph[min_index][j] != float('inf') and not visited[j]:
        new_dist = distance[min_index] + graph[min_index][j]
        if new_dist < distance[j]:
            distance[j] = new_dist
return distance

```

```

def print_distances(distance, cities):
    print("Source Destination Cost")

```

```

for i in range(len(cities)):
    if distance[i] ==
        sys.maxsize:
            print(f"{cities[i]}K: ∞")
    else:

```

```
print(f"{cities[i]}K: {distance[i]}K")
```

```
cities = ['A', 'B', 'C', 'D', 'E']
```

```
graph = [  
    [0, 20, 30, float('inf'), float('inf')],  
    [float('inf'), 0, float('inf'), 15, float('inf')],  
    [float('inf'), float('inf'), 0, float('inf'), 25],  
    [float('inf'), float('inf'), float('inf'), 0, 10],  
    [float('inf'), float('inf'), float('inf'), float('inf'), 0]  
]
```

```
start_city = 'A'
```

```
start_node = cities.index(start_city)
```

```
distances = dijkstra(graph,  
start_node) print_distances(distances,  
cities)
```

Output :-

```
PS D:\Sem 5\Algorithm Analysis and Design> & C:/Users/princ/AppData/Local/Programs/Python/Python312/python.exe -d:/Sem 5/Algorithm Analysis and Design/PS  
actical-7/Minimum_Travel_Cost.py  
Source Destination Cost  
A: 0  
B: 20  
C: 30  
D: 35  
E: 45  
PS D:\Sem 5\Algorithm Analysis and Design> |
```