

## Homework 2 Question 1

Yanlin Li, Student #: 1003770305

February 18, 2021

(a)

There are 7840 parameters.

(b)

Let:

$$y_{nk} = \frac{\exp(w_k^T x_n)}{\sum_{j=0}^9 \exp(w_j^T x_n)}$$

The likelihood function is:

$$p(T|X, w) = \prod_{n=1}^N \left[ \prod_{k=0}^9 y_{nk}^{t_{nk}} \right]$$

The cross-entropy loss is:

$$E(w) = -\ln(p(T|X, w)) = -\sum_{n=1}^N \left[ \sum_{k=0}^9 t_{nk} \ln y_{nk} \right]$$

Take the gradient, we have:

$$\nabla_{w_k} E(w) = \frac{dE(w)}{dw_k}$$

When  $k = j$ :

$$\frac{d(\ln y_{nk})}{dw_j} = x_n \left( 1 - \frac{\exp(w_j^T x_n)}{\sum_{i=0}^9 \exp(w_i^T x_n)} \right)$$

When  $k \neq j$ :

$$\frac{d(\ln y_{nk})}{dw_j} = -x_n \frac{\exp(w_j^T x_n)}{\sum_{i=0}^9 \exp(w_i^T x_n)}$$

Plug in the above values and the value of  $y_{nk}$ :

$$\nabla_{w_k} E(w) = \sum_{n=1}^N (y_{nk} - t_{nk}) x_n$$

(c)

I used 10000 samples, and the final results are:

1. Training accuracy is: 0.8679
2. Test accuracy is: 0.834

(d)

Here is the figure:




Figure 1: weights

**The codes begin on the next page.**