

D:\Lab_Sistemi-Operativi\Tutorato-Sistemi-Operativi-2025-main\Esame-[2025-09-17]\gemini_equisum_mmap.c

```
1  #include <stdio.h>
2  #include <stdlib.h>
3  #include <stdbool.h>
4  #include <unistd.h>
5  #include <fcntl.h>
6  #include <sys/mman.h>
7  #include <sys/stat.h>
8  #include <pthread.h>
9  #include <string.h>
10
11 #define M 12
12 #define BUFFER_SIZE 10
13 #define NUM_VERIFIERS 3
14
15 #define LOCK_IO()  flockfile(stdout)
16 #define UNLOCK_IO() funlockfile(stdout)
17
18 // ===== STRUTTURA =====
19
20 typedef struct {
21     unsigned char dati[M];
22     int file_id;
23     int vector_idx;
24 } Record;
25
26 typedef struct {
27     // Coda Intermedia
28     Record buffer[BUFFER_SIZE];
29     int in, out, count;
30     bool buffer_closed;
31     pthread_mutex_t mtx_buffer;
32     pthread_cond_t cond_buf_not_empty;
33     pthread_cond_t cond_buf_not_full;
34
35     // Slot Finale
36     Record slot_finale;
37     bool slot_full;
38     bool slot_closed;
39     pthread_mutex_t mtx_slot;
40     pthread_cond_t cond_slot_empty;
41     pthread_cond_t cond_slot_full;
42
43     // Contatori per gestione chiusura automatica
44     int readers_active;
45     int verifiers_active;
46     pthread_mutex_t mtx_counts;
47
48 } SharedData;
49
50 // ===== HELPER =====
51 void print_vec(unsigned char *v) {
```

```

52     for (int i = 0; i < M; i++) {
53         printf("%u", v[i]);
54         if (i < M - 1) printf(", ");
55     }
56 }
57
58 // ===== GESTIONE SHARED =====
59 void init_shared(SharedData *s, int n_readers) {
60     s->in = 0; s->out = 0; s->count = 0; s->buffer_closed = false;
61     pthread_mutex_init(&s->mtx_buffer, NULL);
62     pthread_cond_init(&s->cond_buf_not_empty, NULL);
63     pthread_cond_init(&s->cond_buf_not_full, NULL);
64
65     s->slot_full = false; s->slot_closed = false;
66     pthread_mutex_init(&s->mtx_slot, NULL);
67     pthread_cond_init(&s->cond_slot_empty, NULL);
68     pthread_cond_init(&s->cond_slot_full, NULL);
69
70     s->readers_active = n_readers;
71     s->verifiers_active = NUM_VERIFIERS;
72     pthread_mutex_init(&s->mtx_counts, NULL);
73 }
74
75 // Funzioni Buffer
76 void buffer_put(SharedData *s, Record r) {
77     pthread_mutex_lock(&s->mtx_buffer);
78     while (s->count == BUFFER_SIZE && !s->buffer_closed)
79         pthread_cond_wait(&s->cond_buf_not_full, &s->mtx_buffer);
80     if (!s->buffer_closed) {
81         s->buffer[s->in] = r;
82         s->in = (s->in + 1) % BUFFER_SIZE;
83         s->count++;
84         pthread_cond_signal(&s->cond_buf_not_empty);
85     }
86     pthread_mutex_unlock(&s->mtx_buffer);
87 }
88
89 bool buffer_get(SharedData *s, Record *r) {
90     pthread_mutex_lock(&s->mtx_buffer);
91     while (s->count == 0 && !s->buffer_closed)
92         pthread_cond_wait(&s->cond_buf_not_empty, &s->mtx_buffer);
93     bool res = false;
94     if (s->count > 0) {
95         *r = s->buffer[s->out];
96         s->out = (s->out + 1) % BUFFER_SIZE;
97         s->count--;
98         pthread_cond_signal(&s->cond_buf_not_full);
99         res = true;
100     }
101     pthread_mutex_unlock(&s->mtx_buffer);
102     return res;
103 }
104
105 void buffer_close(SharedData *s) {

```

```

106     pthread_mutex_lock(&s->mtx_buffer);
107     s->buffer_closed = true;
108     pthread_cond_broadcast(&s->cond_buf_not_empty);
109     pthread_cond_broadcast(&s->cond_buf_not_full);
110     pthread_mutex_unlock(&s->mtx_buffer);
111 }
112
113 // Funzioni Slot Finale
114 void slot_put(SharedData *s, Record r) {
115     pthread_mutex_lock(&s->mtx_slot);
116     while (s->slot_full && !s->slot_closed)
117         pthread_cond_wait(&s->cond_slot_empty, &s->mtx_slot);
118     if (!s->slot_closed) {
119         s->slot_finale = r;
120         s->slot_full = true;
121         pthread_cond_signal(&s->cond_slot_full);
122     }
123     pthread_mutex_unlock(&s->mtx_slot);
124 }
125
126 bool slot_get(SharedData *s, Record *r) {
127     pthread_mutex_lock(&s->mtx_slot);
128     while (!s->slot_full && !s->slot_closed)
129         pthread_cond_wait(&s->cond_slot_full, &s->mtx_slot);
130     bool res = false;
131     if (s->slot_full) {
132         *r = s->slot_finale;
133         s->slot_full = false;
134         pthread_cond_signal(&s->cond_slot_empty);
135         res = true;
136     }
137     pthread_mutex_unlock(&s->mtx_slot);
138     return res;
139 }
140
141 void slot_close(SharedData *s) {
142     pthread_mutex_lock(&s->mtx_slot);
143     s->slot_closed = true;
144     pthread_cond_broadcast(&s->cond_slot_full);
145     pthread_cond_broadcast(&s->cond_slot_empty);
146     pthread_mutex_unlock(&s->mtx_slot);
147 }
148
149 // ===== THREADS =====
150
151 typedef struct { SharedData *S; char *filename; int id; } ReaderArgs;
152 typedef struct { SharedData *S; int id; } VerifierArgs;
153
154 void *reader_thread(void *arg) {
155     ReaderArgs *a = (ReaderArgs *)arg;
156
157     LOCK_IO(); printf("[READER-%d] file '%s'\n", a->id, a->filename); UNLOCK_IO();
158
159     int fd = open(a->filename, O_RDONLY);

```

```

160     if (fd == -1) { perror("open"); return NULL; } // Gestione errore base
161     struct stat sb; fstat(fd, &sb);
162     size_t fsize = sb.st_size;
163     unsigned char *map = mmap(NULL, fsize, PROT_READ, MAP_PRIVATE, fd, 0);
164     close(fd);
165
166     int num_vec = fsize / M;
167     for (int i = 0; i < num_vec; i++) {
168         Record r;
169         memcpy(r.dati, map + (i*M), M);
170         r.file_id = a->id; r.vector_idx = i + 1;
171
172         LOCK_IO();
173         printf("[READER-%d] vettore candidato n.%d: ", a->id, i + 1);
174         print_vec(r.dati);
175         printf("\n");
176         UNLOCK_IO();
177
178         buffer_put(a->S, r);
179     }
180     if (map != MAP_FAILED) munmap(map, fsize);
181
182     LOCK_IO(); printf("[READER-%d] terminazione con %d vettori letti\n", a->id, num_vec);
183     UNLOCK_IO();
184
185     // Logica Last Man Standing per i lettori
186     pthread_mutex_lock(&a->S->mtx_counts);
187     a->S->readers_active--;
188     if (a->S->readers_active == 0) buffer_close(a->S);
189     pthread_mutex_unlock(&a->S->mtx_counts);
190
191     return NULL;
192 }
193
194 void *verifier_thread(void *arg) {
195     VerifierArgs *a = (VerifierArgs *)arg;
196     Record r;
197     int count = 0;
198
199     while (buffer_get(a->S, &r)) {
200         count++;
201         int p = 0, d = 0;
202         for (int i=0; i<M; i++) { if(i%2==0) p+=r.dati[i]; else d+=r.dati[i]; }
203
204         LOCK_IO();
205         printf("[VERIF-%d] verifico vettore: ", a->id);
206         print_vec(r.dati);
207         printf("\n");
208         if (p == d) {
209             printf("[VERIF-%d] si tratta di un vettore equisomma con somma %d!\n", a->id,
210 p);
211             UNLOCK_IO(); // Sblocco prima di put per evitare attese con lock output
212             slot_put(a->S, r);
213         } else {

```

```
212         printf("[VERIF-%d] non è un vettore equisomma (somma pari %d vs. dispari\n", a->id, p, d);
213         UNLOCK_IO();
214     }
215 }
216
217 LOCK_IO(); printf("[VERIF-%d] terminazione con %d vettori verificati\n", a->id, count); UNLOCK_IO();
218
219 // Logica Last Man Standing per i verificatori
220 pthread_mutex_lock(&a->S->mtx_counts);
221 a->S->verifiers_active--;
222 if (a->S->verifiers_active == 0) slot_close(a->S);
223 pthread_mutex_unlock(&a->S->mtx_counts);
224
225 free(a);
226 return NULL;
227 }
228
229 int main(int argc, char *argv[]) {
230     if (argc < 2) { printf("Uso: %s <f1> ... \n", argv[0]); return 1; }
231     int n_readers = argc - 1;
232     SharedData S;
233     init_shared(&S, n_readers);
234
235     LOCK_IO();
236     printf("[MAIN] creazione di %d thread lettori e %d thread verificatori\n", n_readers, NUM_VERIFIERS);
237     UNLOCK_IO();
238
239     pthread_t readers[n_readers], verifiers[NUM_VERIFIERS];
240     ReaderArgs r_args[n_readers];
241
242     for (int i=0; i<n_readers; i++) {
243         r_args[i].S = &S; r_args[i].filename = argv[i+1]; r_args[i].id = i+1;
244         pthread_create(&readers[i], NULL, reader_thread, &r_args[i]);
245     }
246     for (int i=0; i<NUM_VERIFIERS; i++) {
247         VerifierArgs *va = malloc(sizeof(VerifierArgs));
248         va->S = &S; va->id = i+1;
249         pthread_create(&verifiers[i], NULL, verifier_thread, va);
250     }
251
252     // Il Main consuma i risultati
253     Record r;
254     int total = 0;
255     while (slot_get(&S, &r)) {
256         total++;
257         LOCK_IO();
258         printf("[MAIN] ricevuto nuovo vettore equisomma: ");
259         print_vec(r.dati);
260         printf("\n");
261         UNLOCK_IO();
262     }
```

```
263  
264     for(int i=0;i<n_readers;i++) pthread_join(readers[i], NULL);  
265     for(int i=0;i<NUM_VERIFIERS;i++) pthread_join(verifiers[i], NULL);  
266  
267     LOCK_IO(); printf("[MAIN] terminazione con %d vettori equisomma trovati\n", total);  
    UNLOCK_IO();  
268     return 0;  
269 }
```