

## 2012 AP<sup>®</sup> COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

3. Consider a software system that models a horse barn. Classes that represent horses implement the following interface.

```
public interface Horse
{
    /** @return the horse's name */
    String getName();

    /** @return the horse's weight */
    int getWeight();

    // There may be methods that are not shown.
}
```

A horse barn consists of  $N$  numbered spaces. Each space can hold at most one horse. The spaces are indexed starting from 0; the index of the last space is  $N - 1$ . No two horses in the barn have the same name.

The declaration of the `HorseBarn` class is shown below. You will write two unrelated methods of the `HorseBarn` class.

```
public class HorseBarn
{
    /** The spaces in the barn. Each array element holds a reference to the horse
     *   that is currently occupying the space. A null value indicates an empty space.
     */
    private Horse[] spaces;

    /** Returns the index of the space that contains the horse with the specified name.
     *   Precondition: No two horses in the barn have the same name.
     *   @param name the name of the horse to find
     *   @return the index of the space containing the horse with the specified name;
     *           -1 if no horse with the specified name is in the barn.
     */
    public int findHorseSpace(String name)
    { /* to be implemented in part (a) */ }

    /** Consolidates the barn by moving horses so that the horses are in adjacent spaces,
     *   starting at index 0, with no empty space between any two horses.
     *   Postcondition: The order of the horses is the same as before the consolidation.
     */
    public void consolidate()
    { /* to be implemented in part (b) */ }

    // There may be instance variables, constructors, and methods that are not shown.
}
```

Part (a) begins on page 14.

## 2012 AP<sup>®</sup> COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

- (a) Write the `HorseBarn` method `findHorseSpace`. This method returns the index of the space in which the horse with the specified name is located. If there is no horse with the specified name in the barn, the method returns `-1`.

For example, assume a `HorseBarn` object called `sweetHome` has horses in the following spaces.

0	1	2	3	4	5	6
"Trigger" 1340	null	"Silver" 1210	"Lady" 1575	null	"Patches" 1350	"Duke" 1410

The following table shows the results of several calls to the `findHorseSpace` method.

Method Call	Value Returned	Reason
<code>sweetHome.findHorseSpace("Trigger")</code>	0	A horse named Trigger is in space 0.
<code>sweetHome.findHorseSpace("Silver")</code>	2	A horse named Silver is in space 2.
<code>sweetHome.findHorseSpace("Coco")</code>	-1	A horse named Coco is not in the barn.

Information repeated from the beginning of the question

```
public interface Horse
```

```
String getName()
```

```
int getWeight()
```

```
public class HorseBarn
```

```
private Horse[] spaces
```

```
public int findHorseSpace(String name)
```

```
public void consolidate()
```

**WRITE YOUR SOLUTION ON THE NEXT PAGE.**

## 2012 AP<sup>®</sup> COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

Complete method `findHorseSpace` below.

```
/** Returns the index of the space that contains the horse with the specified name.
 * Precondition: No two horses in the barn have the same name.
 * @param name the name of the horse to find
 * @return the index of the space containing the horse with the specified name;
 *         -1 if no horse with the specified name is in the barn.
 */
public int findHorseSpace(String name)
```

Part (b) begins on page 16.

## 2012 AP<sup>®</sup> COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

- (b) Write the `HorseBarn` method `consolidate`. This method consolidates the barn by moving horses so that the horses are in adjacent spaces, starting at index 0, with no empty spaces between any two horses. After the barn is consolidated, the horses are in the same order as they were before the consolidation.

For example, assume a barn has horses in the following spaces.

0	1	2	3	4	5	6
"Trigger" 1340	null	"Silver" 1210	null	null	"Patches" 1350	"Duke" 1410

The following table shows the arrangement of the horses after `consolidate` is called.

0	1	2	3	4	5	6
"Trigger" 1340	"Silver" 1210	"Patches" 1350	"Duke" 1410	null	null	null

Information repeated from the beginning of the question

```
public interface Horse
```

```
String getName()
```

```
int getWeight()
```

```
public class HorseBarn
```

```
private Horse[] spaces
```

```
public int findHorseSpace(String name)
```

```
public void consolidate()
```

**WRITE YOUR SOLUTION ON THE NEXT PAGE.**

## 2012 AP<sup>®</sup> COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

Complete method `consolidate` below.

```
/** Consolidates the barn by moving horses so that the horses are in adjacent spaces,  
 * starting at index 0, with no empty space between any two horses.  
 * Postcondition: The order of the horses is the same as before the consolidation.  
 */  
public void consolidate()
```