

```

<!DOCTYPE html>
<html lang="zh-TW">
<head>
  <meta charset="UTF-8">
  <title>211 午餐繳費登記表</title>
  <style>
    body { font-family: sans-serif; padding: 20px; background: #f4f4f9; }
    .card { max-width: 400px; margin: auto; background: white; padding: 20px;
border-radius: 10px; box-shadow: 0 2px 5px rgba(0,0,0,0.1); }
    h1 { text-align: center; color: #333; }
    .input-box { display: flex; flex-direction: column; gap: 10px; margin-bottom: 20px; }
    input { padding: 10px; border: 1px solid #ccc; border-radius: 5px; }
    button { padding: 10px; background: #28a745; color: white; border: none; border-radius:
5px; cursor: pointer; }
    ul { list-style: none; padding: 0; }
    li { padding: 10px; border-bottom: 1px solid #eee; display: flex; justify-content:
space-between; }
  </style>
</head>
<body>

<div class="card">
  <h1>211 午餐繳費</h1>
  <div class="input-box">
    <input type="text" id="name" placeholder="同學姓名">
    <input type="number" id="price" placeholder="餐點金額">
    <button onclick="addItem()">新增登記</button>
  </div>
  <ul id="list"></ul>
  <div style="margin-top:20px; font-weight:bold;">總金額: $<span id="total">0</span></div>
</div>

<script>
  let total = 0;
  function addItem() {
    const name = document.getElementById('name').value;
    const price = parseInt(document.getElementById('price').value) || 0;
    if (!name) return;

    const li = document.createElement('li');
    li.innerHTML = `${name} - ${price} <button onclick="removeItem(this, ${price})">刪除
</button>`;
    document.getElementById('list').appendChild(li);

    total += price;
    document.getElementById('total').innerText = total;
    document.getElementById('name').value = "";
    document.getElementById('price').value = "";
  }

```

```
}

function removeItem(btn, price) {
    total -= price;
    document.getElementById('total').innerText = total;
    btn.parentElement.remove();
}
</script>

</body>
</html>
```