

# THE REC-THY PACKAGE

PETER M. GERDES (GERDES@INVARIANT.ORG)

ABSTRACT. The `rec-thy` package is designed to help mathematicians publishing papers in the area of recursion theory (aka Computability Theory) easily use standard notation. This includes easy commands to denote Turing reductions, Turing functionals, c.e. sets, stagewise computations, forcing and syntactic classes.

## 1. INTRODUCTION

This package aims to provide a useful set of  $\text{\LaTeX}$  macros covering basic computability theory notation. Given the variation in usage in several areas this package had to pick particular notational conventions. The package author would like to encourage uniformity in these conventions but has included a multitude of package options to allow individual authors to choose alternative conventions or exclude that part of the package. Some effort has been made to align the semantic content of documents created with this package with the  $\text{\LaTeX}$  source. The author hopes that eventually this package may be incorporated into some larger package for typesetting papers in mathematical logic.

While computability theory is now the more popular name for the subject also known as recursion theory the author deliberately choose to title this package `rec-thy` to avoid confusion with the proliferation of packages for typesetting computer science related disciplines. While the subject matter of computability theory and theoretical computer science overlap significantly the notational conventions often differ.

Comments, patches, suggestions etc.. are all welcome. This project is hosted on github at <https://github.com/TruePath/Recursion-Theory-Latex-Package>.

## 2. USAGE

Include the package in your document by placing `\usepackage{rec-thy}` into your preamble after placing `rec-thy.sty` somewhere  $\text{\TeX}$  can find it. The commands in this package have been divided into related groups. The commands in a given section can be disabled by passing the appropriate package option. For instance to disable the commands in the general mathematics section and the delimiters section you would include the following in your preamble `\usepackage[nomath,nodelim]{rec-thy}`. The commands in each subsection along with their results are listed below and the options to disable the commands in each grouping or modify their behavior are

listed in that subsection. Aliases and variants of a command are listed below the initial version of a command and aliases are indented.

Significant use is made in this package of optional arguments delimited either by square brackets or parenthesis. Users of the package should take care to wrap arguments that may themselves include brackets or parenthesis in braces. For example `\REset(\REset(X){e}){i}` should be fixed to `\REset({\REset(X){e}}){i}`.

### 3. ALTERNATE SYMBOLS

While the symbols used by default in the package are suggested for adoption to achieve greater consistency users may wish to specify their own symbols and options have been provided to enable this. The following parameters may be specified.

`modulescr` Sets the script used to typeset the `\module` command. Default is `mathcal`.

`reqscr` Sets the script used to typeset requirements. Default is `mathscr`.

`pfcasefont` Sets the script used to typeset Case in the cases helper.

`emptystr` Sets the empty string symbol

`concatsym` Sets the concat symbol.

`cdeltasym` Sets the symbol used to denote computably  $\Delta$  formulas. Default is  ${}^C\Delta$ .

`cpisym` Same for  $\Pi$  formulas. Default is  ${}^C\Pi$ .

`csgmasym` Same for  $\Sigma$  formulas. Default is  ${}^C\Sigma$ .

`recfnlsym` Sets the symbol used for recursive functionals. Default is  $\Phi$ .

`recfsym` Sets the symbol used for recursive functions. Default is  $\phi$ .

`usesym` Sets the symbol used for the use operator. Default is **u** where this is printed using `\symbfrac` if `unicode-math` is loaded and with `\mathfrac` otherwise.

`ballsymb` Sets the symbol used for the ball command. Default is  $\mathcal{B}$ .

`nodoubleangles` Prevents redefinition of `\rrangle` and `\llangle` with versions that use the repeated angle brackets e.g., lets you use the weird XITS versions.

As an example of how to use these commands consider the following code changing the ball symbol to **B**.

```
\def\myballsymb{\mathbf{B}}
```

```
\usepackage[suppPriorityTrees, ballsymb=myballsymb]{rec-thy}
```

## 4. COMMANDS

A few general conventions are usually followed in the commands. Whenever an operator can be used as a binary operator (as in  $X \cup Y$ ) and as an operation on some collection  $\bigcup_{i \in \omega} X_i$  the binary operator will begin with a lowercase letter `\union` and the operation on the collection will begin with a capital letter `\Union`. If the first letter is already capitalized then the second letter is used instead.

Objects that have a natural stagewise approximation generally admit an optional argument in brackets to specify a stage. For instance `\REset[s]{e}` yields  $W_{e,s}$ . An optional argument in parenthesis is used for relativization. For instance `\REset(X){e}` produces  $W_e^X$ . A notable exception to this rule are the formula classes where square brackets are used to indicate an oracle to be placed in the superscript, e.g., `\pizn[X]{2}` yields  $\Pi_2^{0,X}$ , so as not to generate confusion with the alternative notion  $\Pi_2^0(X)$ . Also a lowercase first letter in a formula class indicates the lightface version while a capital first letter indicates the boldface version.

Unless indicated otherwise all macros are to be used inside math mode. Indented commands indicate an alias for the command on the line above.

**4.1. Priority Trees.** Note the commands in this section double as suggestions for standardized notation.

<code>\PriorityTree</code>	$\mathbb{T}$	Priority Tree
<code>\tpath</code>	$\mathbf{f}$	Truepath.
<code>\tpath[s]</code>	$\mathbb{f}_s$	Approximate Truepath.
<code>\xi \leq_{\text{leftof}} \eta</code>	$\xi <_L \eta$	The left of relation for priority tree arguments
<code>\module{R}[X]{i,j}</code>	$\mathcal{R}_{i,j}$	Module in tree construction (superscript optional arg)
<code>\ball[X]{y}{s}</code>	$\mathcal{B}^X(y, s)$	Location of ball $y$ (headed to $X$ ) at $s$
<code>\ball{y}{s}</code>	$\mathcal{B}(y, s)$	Location of ball $y$ at $s$

There are a few additional commands relating to priority trees which are less frequently used and require passing the option `suppPriorityTrees` to the package to use. These commands exist in a kind of limbo and will probably be removed in some future edition of the package absent popular demand and feedback for better notation.

<code>\Astages{\xi}</code>	$\mathcal{A}(\xi)$	Set of stages at which $\xi$ is active.
<code>\Vstages{\xi}</code>	$\mathcal{V}(\xi)$	Stages where $\xi < \mathbb{f}_s$ even if links skip $\xi$ .
<code>\reqof{\xi}</code>	$r(\xi)$	Requirement implemented by a node $\xi$ .

**4.2. Computations.** To disable these commands pass the option `nocomputations`. To specify an alternative symbol for either recursive functionals or recursive functions pass `recfnlsym=macroname` or `recfsym=macroname`. For instance, to use  $\psi$  for recursive functions and  $\Psi$  for recursive functionals pass the options `recfsym=psi`, `recfnlsym=Psi`.

<code>\murec{x}{f(x)&gt;1}</code>	$\mu x (f(x) > 1)$	Least $x$ satisfying condition.
<code>\recf{e}</code>	$\phi_e$	Computable functions
<code>\recf[s]{e}</code>	$\phi_{e,s}$	
<code>\recf{e}(x)</code>	$\phi_e(x)$	
<code>\recf[s]{e}(x)</code>	$\phi_{e,s}(x)$	
<code>\recf(Y){e}</code>	$\phi_e^Y$	
<code>\recf[s](Y){e}</code>	$\phi_{e,s}^Y$	
<code>\recf(Y){e}(x)</code>	$\phi_e^Y(x)$	
<code>\recf[s](Y){e}(x)</code>	$\phi_{e,s}^Y(x)$	
<code>\recfnl{e}{Y}{x}</code>	$\Phi_e(Y; x)$	Computable functionals
<code>\recfnl[s]{e}{Y}{x}</code>	$\Phi_{e,s}(Y; x)$	
<code>\recfnl{e}{Y}{}</code>	$\Phi_e(Y)$	
<code>\recfnl{e}{}{x}</code>	$\Phi_e$	
<code>\recfnl{e}{}{}</code>	$\Phi_e$	
<code>\recfnl{e}{}{} \ \cequiv \ \recfnl{i}{}{}</code>	$\Phi_e \simeq \Phi_i$	Equivalent computations
<code>\recfnl{e}{}{} \ \ncequiv \ \recfnl{i}{}{}</code>	$\Phi_e \not\simeq \Phi_i$	Inequivalent computations
<code>\recfnl{e}{}{x} \ \conv</code>	$\Phi_e \downarrow$	Convergence
<code>\recfnl{e}{}{x} \ \conv[s]</code>	$\Phi_e \downarrow_s$	
<code>\recfnl{e}{}{x} \ \nconv</code>	$\Phi_e \not\downarrow$	Divergence
<code>\recfnl{e}{}{x} \ \nconv[s]</code>	$\Phi_e \not\downarrow_s$	
<code>\use{\recfnl{e}{Y}{x}}</code>	$\mathbf{u} [\Phi_e(Y; x)]$	Use of a computation.
<code>\REset{e}</code>	$W_e$	c.e. sets
<code>\REset[s]{e}</code>	$W_{e,s}$	
<code>\REset(X){e}</code>	$W_e^X$	
<code>\REset[s](X){e}</code>	$W_{e,s}^X$	
<code>\Hop{e}(X)</code>	$H_e(X)$	Hop sets
<code>\Hop[s](X){e}</code>	$H_{e,s}(X)$	

<code>\Hop[s]{e}</code>	$\mathcal{H}_{e,s}(\emptyset)$	
<code>\Hop{e}</code>	$\mathcal{H}_e(\emptyset)$	
<code>\iREAop{e}(\reset)</code> <code>\oneREAop{e}(\reset)</code>	$\hat{\mathcal{J}}_e(\emptyset)$	1-REA operator
<code>\REAop{e}{\alpha}</code> <code>\reaop[f]{\alpha}(\reset)</code>	$\hat{\mathcal{J}}_e^\alpha$	

4.3. **Degrees.** To disable these commands pass the option `nodegrees`.

$\backslash\mathrm{Tdeg}\{d\}$	$\mathbf{d}$	Turing degree
$\backslash\mathrm{Tjump}\{X\}$ $\backslash\mathrm{jump}\{X\}$	$X'$	Turing jump
$\backslash\mathrm{jjump}\{X\}$	$X''$	
$\backslash\mathrm{jumpn}\{X\}\{n\}$	$X^{(n)}$	
$\backslash\mathrm{Tzero}$	$\mathbb{0}$	Computable degree
$\backslash\mathrm{zeroj}$	$\mathbb{0}'$	
$\backslash\mathrm{zerojj}$	$\mathbb{0}''$	
$\backslash\mathrm{zerojjj}$	$\mathbb{0}'''$	
$\backslash\mathrm{zeron}\{n\}$	$\mathbb{0}^{(n)}$	
$X \backslash\mathrm{Tequiv} Y$ $X \backslash\mathrm{Teq} Y$	$X \equiv_{\mathbf{T}} Y$	Turing equivalence
$X \backslash\mathrm{nTequiv} Y$ $X \backslash\mathrm{nTeq} Y$	$X \not\equiv_{\mathbf{T}} Y$	Turing inequivalence
$X \backslash\mathrm{Tlneq} Y$	$X \lessdot_{\mathbf{T}} Y$	
$X \backslash\mathrm{Tleq} Y$	$X \leq_{\mathbf{T}} Y$	
$X \backslash\mathrm{Tgneq} Y$	$X \gtrdot_{\mathbf{T}} Y$	
$X \backslash\mathrm{Tgeq} Y$	$X \geq_{\mathbf{T}} Y$	
$X \backslash\mathrm{Tgtr} Y$	$X >_{\mathbf{T}} Y$	
$X \backslash\mathrm{Tless} Y$	$X <_{\mathbf{T}} Y$	
$X \backslash\mathrm{nTleq} Y$	$X \not\leq_{\mathbf{T}} Y$	
$X \backslash\mathrm{nTgeq} Y$	$X \not\geq_{\mathbf{T}} Y$	
$X \backslash\mathrm{Tincompat} Y$ $X \backslash\mathrm{Tincomp} Y$	$X \mid_{\mathbf{T}} Y$	Turing incompatibility
$X \backslash\mathrm{Tcompat} Y$ $X \backslash\mathrm{nTincomp} Y$		$X \nmid_{\mathbf{T}} Y$

$X \setminus \text{nTincompat } Y$		
$\backslash \text{Tdeg}\{d\} \backslash \text{Tdegjoin} \backslash \text{Tdeg}\{d'\}$	$\mathbf{d} \vee_{\mathbf{T}} \mathbf{d}'$	Join of degrees
$\backslash \text{Tdeg}\{d\} \backslash \text{Tdegmeet} \backslash \text{Tdeg}\{d'\}$ $\backslash \text{Tdeg}\{d\} \backslash \text{Tmeet} \backslash \text{Tdeg}\{d'\}$	$\mathbf{d} \wedge_{\mathbf{T}} \mathbf{d}'$	Meet of degrees (when defined)
$X \setminus \text{Tplus } Y$ $X \setminus \text{Tjoin } Y$ $\backslash \text{Tplus}_{\{i \in \omega\}} X_i$ $\backslash \text{Tjoin}_{\{i \in \omega\}} X_i$	$X \oplus Y$ $\bigoplus_{i \in \omega} X_i$	Effective join of sets
$X \setminus \text{ttlneq } Y$	$X \not\leq_{\text{tt}} Y$	Truth table reproducibilities
$X \setminus \text{ttleq } Y$	$X \leq_{\text{tt}} Y$	
$X \setminus \text{ttgneq } Y$	$X \not\geq_{\text{tt}} Y$	
$X \setminus \text{ttgeq } Y$	$X \geq_{\text{tt}} Y$	
$X \setminus \text{ttgtr } Y$	$X >_{\text{tt}} Y$	
$X \setminus \text{ttless } Y$	$X <_{\text{tt}} Y$	
$X \setminus \text{ttnleq } Y$	$X \not\leq_{\text{tt}} Y$	
$X \setminus \text{ttngeq } Y$	$X \not\geq_{\text{tt}} Y$	

**4.4. Requirement Assistance.** To disable these commands pass the option `noreqhelper`.

To disable the hyperlinked requirements pass `nohyperreqs`

Math mode is not required for  $\backslash \text{req}\{R\}\{e\}$

$\backslash \text{req}\{R\}\{e\}$	$\mathcal{R}_e$	
$\backslash \text{req}\{R\}[\backslash \text{nu}\{e\}]$	$\mathcal{R}_e^\vee$	Requirement
$\backslash \text{req}*\{R\}\{e\}$	$\mathcal{R}_e$	
$\backslash \text{req}*\{R\}[\backslash \text{nu}\{e\}]$	$\mathcal{R}_e^\vee$	Requirement without hyperlinks

We also introduce the following environments for introducing requirements. The requirement environment is used as follows

```

\begin{requirement} {\backslash req\{R^*\}\{r,j\}}
  \recfnl\{r\}\{B\}\{\} = \Rset\{j\} \implies
    \exists [k] \left( \backslash Upsilon^{\{j\}}_{\text{k}}(
      C \setminus \text{Tplus} \backslash \Rset\{j\}) = B \right) \lor \backslash
      \Rset\{j\} \setminus \text{Tleq} \setminus \text{Tzero} \right)
\end{requirement}

```

Giving output



$$\mathcal{R}_{r,j}^*: \quad \Phi_r(B) = W_j \implies [\exists k] \left( \Upsilon_k^j(C \oplus W_j) = B \vee W_j \leq_{\mathbf{T}} \mathbb{0} \right)$$

The require environment merges the `\req[\nu]{R}{e\}` command directly into the environment arguments. It also creates an automatic label which makes use of the 1st and 2nd arguments but assumes the third argument contains only indexes whose names are subject to change. Unless `nohyperreqs` is passed the `\req[\nu]{R}{e\}` automatically links to the defining require environment.

```
\begin{require}{R}{i}
    \recfnl{i}{B}{} = \REset{i} \implies \exists
    [k] \left( \Upsilon^i_k(C \Tplus \REset{i}
    ) = B \right) \lor \REset{j} \Tleq \Tzero \right)
\end{require}
```

Giving output

$$\mathcal{R}_i: \quad \Phi_i(B) = W_i \implies [\exists k] \left( \Upsilon_k^i(C \oplus W_i) = B \vee W_j \leq_{\mathbf{T}} \mathbb{0} \right)$$

To list multiple requirements at once without introducing unnecessary spaces we also introduce the requirements environment which can be used as follows. Note that one may *not* end the final line with a linebreak or an undesired tag will appear.

```
\begin{requirements}
\require{P}[A]{e} A \neq \recfnl{i}{}{} \\\
\require{P}[B]{e} B \neq \recfnl{i}{}{} \\\
\require{R}{i,\hat{i},j,\hat{j}} \recfnl{i}{A}{} = \
\hat{A} \land \recfnl{\hat{i}}{\hat{A}}{} = A \land
\recfnl{j}{B}{} = \hat{B} \land \recfnl{\hat{j}}{\
\hat{B}}{} = B \implies \Gamma(\hat{A} \syndiff \hat{B}
\{B\}) = A \Tplus B
\end{requirements}
```

$$\mathcal{P}_e^A: \quad A \neq \Phi_i$$

$$\mathcal{P}_e^B: \quad B \neq \Phi_i$$

$$\mathcal{R}_{i,\hat{i},j,\hat{j}}: \quad \Phi_i(A) = \hat{A} \wedge \Phi_{\hat{i}}(\hat{A}) = A \wedge \Phi_j(B) = \hat{B} \wedge \Phi_{\hat{j}}(\hat{B}) = B \implies \Gamma(\hat{A} \Delta \hat{B}) = A \oplus B$$

**4.5. General Math Commands.** To disable these commands pass the option `nomath`.

<code>\eqdef</code>	$\stackrel{\text{def}}{=}$	Definitional equals
<code>\iffdef</code>	$\stackrel{\text{def}}{\iff}$	Definitional equivalence
<code>\aut</code>	Aut	Automorphisms of some structure
<code>\Ord</code>	Ord	Set of ordinals
<code>\abs{x}</code>	$ x $	Absolute value
<code>\dom</code>	dom	Domain
<code>\rng</code>	rng	Range
<code>f\restr{X}</code>	$f \upharpoonright_X$	Restriction
<code>\ordpair{x}{y}</code>	$(x, y)$	Ordered Pair
<code>f \compfunc g</code> <code>f \compose g</code>	$f \circ g$	Function composition
<code>f: X \pmapsto Y</code>	$f: X \rightarrowtail Y$	partial function from $X$ to $Y$ .
<code>f: Y \pmapsfrom X</code>	$f: Y \leftarrowtail X$	partial function from $X$ to $Y$ .
<code>f: X \fmapsto Y</code>	$f: X \rightarrowtail_{<\infty} Y$	finite partial function from $X$ to $Y$ .
<code>f: Y \fmapsfrom X</code>	$f: Y \leftarrowtail_{<\infty} X$	finite partial function from $X$ to $Y$ .
<code>\ParFuncs{X}{Y}</code>	$Y^{<X}$	set of partial functions from $X$ to $Y$ .
<code>\FinParFuncs{X}{Y}</code>	$Y^{<_{<\infty} X}$	set of finite partial functions from $X$ to $Y$ .
<code>\( \ensuretext{blah} \)</code> <code>\ensuretext{blah}</code>	blah	Types argument in text mode

**4.6. Operators.** Misc operators used in logic and computability. To disable these commands pass the option `nooperators`.

$x \setminus \text{meet } y$	$x \wedge y$	Meet operation
$\setminus \text{Meet}_{\{i \in \omega\}} x_i$	$\bigwedge_{i \in \omega} x_i$	
$x \setminus \text{join } y$	$x \vee y$	Join operation
$\setminus \text{Join}_{\{i \in \omega\}} x_i$	$\bigvee_{i \in \omega} x_i$	
$x \setminus \text{xor } y$	$x \text{ xor } y$	

**4.7. Set Notation.** To disable these commands pass the option `nosets`.

Note that `\Cross` and `\cross` overwrite the existing commands saving them as `\CrossOrig` and `\crossOrig` respectively as these commands have varying meanings between different font packages. However, the other commands avoid overwriting existing commands with that name

$\set{(x,y)}{x > y}$	$\{(x,y) \mid x > y\}$	Set notation
$\set{(x,y)}$	$\{(x,y)\}$	
$\text{card}\{X\}$	$ X $	Cardinality
$X \setminus \text{union } Y$	$X \cup Y$	Union
$\set{Union}_{\{i \in \omega\}} X_i$	$\bigcup_{i \in \omega} X_i$	
$X \setminus \text{isect } Y$	$X \cap Y$	Intersection
$\set{Isect}_{\{i \in \omega\}} X_i$	$\bigcap_{i \in \omega} X_i$	
$X \setminus \text{cross } Y$	$X \times Y$	Cartesian product (Cross Product)
$\set{Cross}_{\{i \in \omega\}} X_i$	$\prod_{i \in \omega} X_i$	
$\text{powset}\{\omega\}$	$\mathcal{P}(\omega)$	Powerset
$\text{eset}$	$\emptyset$	Emptyset abbreviation
$x \setminus \text{nin } A$	$x \notin A$	not an element
$\set{setcmp}\{X\}$	$\overline{X}$	Set compliment
$X \setminus \text{setdiff } Y$	$X - Y$	Set difference
$X \setminus \text{symdiff } Y$	$X \Delta Y$	Symmetric difference

**4.8. Delimiters.** To disable these commands pass the option `nodelim`.

<code>\gcode{\phi}</code>		
<code>\godelnum{\phi}</code>	$\phi$	Godel Code/Corner Quotes
<code>\cornerquote{\phi}</code>		
<code>\llangle x,y,z \rrangle</code>	$\langle\langle x,y,z \rangle\rangle$	Properly spaced double angle brackets

**4.9. Recursive vs. Computable.** To disable these commands pass the option `nonames`. To use recursive, `r.e.` and recursively enumerable everywhere pass the option `re`. To use computable, `c.e.` and computably enumerable everywhere pass the option `ce`. To force REA and CEA use the options `rea` and `cea`. If none of these options are passed the macros will expand as below. All macros in this section work in both text and math modes.

<code>\re</code>	<code>r.e.</code>
<code>\ce</code>	<code>c.e.</code>
<code>\REA</code>	<code>REA</code>
<code>\CEA</code>	<code>CEA</code>
<code>\recursive</code>	<code>recursive</code>
<code>\computable</code>	<code>computable</code>
<code>\recursivelyEnumerable</code>	<code>recursively enumerable</code>
<code>\computablyEnumerable</code>	<code>computably enumerable</code>
<code>\Recursive</code>	<code>Recursive</code>
<code>\Computable</code>	<code>Computable</code>
<code>\RecursivelyEnumerable</code>	<code>Recursively enumerable</code>
<code>\ComputablyEnumerable</code>	<code>Computably enumerable</code>

**4.10. Quantifiers & Connectives.** To disable these commands pass the option `noquants`. The commands `\exists` and `\forall` are standard but the package extends them.

<code>\exists x &lt; y</code>	$[\exists x < y]$	
<code>\exists x(x &lt; y)</code>	$(\exists x < y)$	
<code>\exists x*</code>	$\exists^\infty$	
<code>\exists x* \inf</code>		
<code>\exists x*[x &lt; y]</code>	$[\exists^\infty x < y]$	
<code>\exists x*(x &lt; y)</code>	$(\exists^\infty x < y)$	
<code>\nexists x &lt; y</code>	$[\nexists x < y]$	
<code>\nexists x(x &lt; y)</code>	$(\nexists x < y)$	
<code>\nexists x*</code>	$\nexists^\infty$	
<code>\nexists x* \inf</code>		
<code>\nexists x*[x &lt; y]</code>	$[\nexists^\infty x < y]$	
<code>\nexists x*(x &lt; y)</code>	$(\nexists^\infty x < y)$	
<code>\forall x &lt; y</code>	$[\forall x < y]$	
<code>\forall x(x &lt; y)</code>	$(\forall x < y)$	
<code>\forall x*</code>	$\forall^*$	For almost all.
<code>\forall x* \inf</code>		
<code>\forall x*[x &lt; y]</code>	$[\forall^* x < y]$	
<code>\forall x*(x &lt; y)</code>	$(\forall^* x < y)$	
<code>\True</code>	$\top$	
<code>\False</code>	$\perp$	
<code>\Land \phi_i</code>	$\bigwedge \phi_i$	Operator form of and
<code>\Lor \phi_i</code>	$\bigvee \phi_i$	Operator form of or
<code>\LLand \phi_i</code>	$\bigwedge \phi_i$	Infinitary conjunction
<code>\LLor \phi_i</code>	$\bigvee \phi_i$	Infinitary disjunction

4.11. **Spaces.** To disable these commands pass the option `nospaces`.

<code>\bstrs</code>	$2^{<\omega}$	Finite binary strings
<code>\wstrs</code>	$\omega^{<\omega}$	Finite sequences of integers
<code>\cantor</code>	$2^\omega$	Cantor space
<code>\baire</code>	$\omega^\omega$	Baire space
<code>\Baire</code>	$\mathcal{N}$	Alternate baire space

**4.12. Strings.** To disable these commands pass the option `nostrings`.

To specify an alternative symbol for the empty string pass `emptystr=macroname`. For instance, to use  $\lambda$  as the empty string pass `emptystr=lambda`. Similarly, to specify an alternate value for the concatenation symbol pass `concatsym=macroname`, e.g., if you specify `\def\plus{+}` and then pass `concatsym=plus` the concatenation symbol would be changed to  $+$ .

<code>\str{1,0,1}</code> <code>\code{5,8,13}</code>	$\langle 1,0,1 \rangle$ $\langle 5,8,13 \rangle$	Strings/Codes for strings
<code>\EmptyStr</code> <code>\estr</code>	$\langle \rangle$ $\langle \rangle$	Empty string
<code>\decode{\sigma}{3}</code>	$(\sigma)_3$	Alternate notation for $\sigma(3)$
<code>\sigma\concat\tau</code> <code>\sigma\concat[0]</code>	$\sigma \hat{\ } \tau$ $\sigma \hat{\ } \langle 0 \rangle$	Concatenation
<code>\strpred{\sigma}</code>	$\sigma^-$	The immediate predecessor of $\sigma$
<code>\lh{\sigma}</code>	$ \sigma $	Length of $\sigma$
<code>\sigma \incompat \tau</code> <code>\sigma \incomp \tau</code>	$\sigma \mid \tau$ $\sigma \mid \tau$	Incompatible strings
<code>\sigma \compat \tau</code>	$\sigma \nmid \tau$	Compatible strings
<code>\pair{x}{y}</code>	$\langle x, y \rangle$	Code for the pair $(x, y)$
<code>\setcol{X}{n}</code>	$X^{[n]}$	$\{y \mid \langle n, y \rangle \in X\}$
<code>\setcol{X}{\leq n}</code>	$X^{[\leq n]}$	$\{\langle x, y \rangle \mid \langle x, y \rangle \in X \wedge x \leq n\}$

**4.13. Subfunctions.** To disable these commands pass the option `nosubfuns`.

$f \setminus \text{subfun } g$	$f < g$	Varieties of the function extension relation
$f \setminus \text{supfun } g$	$f > g$	
$f \setminus \text{subfun } g$	$f \nless g$	
$f \setminus \text{nsupfun } g$	$f \nless g$	
$f \setminus \text{subfuneq } g$	$f \leq g$	
$f \setminus \text{subfunneq } g$	$f \lneq g$	
$f \setminus \text{supfuneq } g$	$f \geq g$	
$f \setminus \text{supfunneq } g$	$f \gneq g$	
$f \setminus \text{subfunneq } g$	$f \nless g$	
$f \setminus \text{nsupfunneq } g$	$f \nless g$	

4.14. **Trees.** To disable these commands pass the option `notrees`.

$\setminus \text{CBderiv}\{T\}$	$T^{(1)}$	Cantor-Bendixson Derivative
$\setminus \text{CBderiv}[\alpha]\{T\}$	$T^{(\alpha)}$	
$\setminus \text{pruneTree}\{T\}$	$T^{(\infty)}$	$\{\sigma \in T \mid (\exists g)(g \in [T] \wedge \sigma \subset g)\}$
$\setminus \text{hgt}\{T\}$	$\ T\ $	

4.15. **Set Relations.** To disable these commands pass the option `nosetrels`. Note that many of these commands are extensions of existing commands.

$X \setminus \text{subset}^* Y$	$X \subset^* Y$	All but finitely much of $X$ is in $Y$
$X \setminus \text{subseteq}^* Y$	$X \subseteq^* Y$	
$X \setminus \text{supset}^* Y$	$X \supset^* Y$	All but finitely much of $Y$ is in $X$
$X \setminus \text{supseteq}^* Y$	$X \supseteq^* Y$	
$X \setminus \text{eq } Y$	$X = Y$	Macro for =
$X \setminus \text{eq}^* Y$ $X \setminus \text{eqae } Y$	$X =^* Y$	Equal mod finite
$X \setminus \text{infsubset } Y$	$X \subset_\infty Y$	$X \subset Y \wedge  Y \setminus X  = \omega$
$X \setminus \text{infsubset}^* Y$	$X \subset_\infty^* Y$	$X \subset^* Y \wedge  Y \setminus X  = \omega$
$X \setminus \text{infsubset}^* Y$	$X \supset_\infty Y$	$Y \subset X \wedge  X \setminus Y  = \omega$
$X \setminus \text{infsubset}^* Y$	$X \supset_\infty^* Y$	$Y \subset^* X \wedge  X \setminus Y  = \omega$
$X \setminus \text{majsubset } Y$	$X \subset_m Y$	$X$ is a major subset of $Y$
$X \setminus \text{majsubset}^* Y$	$X \supset_m Y$	$Y$ is a major subset of $X$

**4.16. Ordinal Notations.** To disable these commands pass the option `noordinalnotations`.

<code>\wck</code>	$\omega_1^{\text{CK}}$	First non-computable ordinal
<code>\ordzero</code>	0	Notation for ordinal 0
<code>\abs{\alpha}</code>	$ \alpha $	Ordinal $\alpha$ denotes
<code>\kleene0</code> <code>\ordNotations</code>	$\mathcal{O}_1$	Set of ordinal notations
<code>\kleene0*</code> <code>\uniqOrdNotations</code> <code>\kleene0uniq</code>	$\mathcal{O}_1$	Unique set of ordinal notations
<code>\kleene0(X)</code>	$\mathcal{O}_1^X$	Relativized ordinal notations
<code>\kleene0[\alpha]</code>	$\mathcal{O}_{1, \alpha }$	Ordinal notations for ordinals $<  \alpha $
<code>\kleene0*(X)[\alpha]</code>	$\mathcal{O}_{1, \alpha }^X$	
<code>\alpha \kleeneless \beta</code>	$\alpha <_{\mathcal{O}_1} \beta$	Ordering on notations
<code>\alpha \kleenel \beta</code>	$\alpha <_{\mathcal{O}_1} \beta$	
<code>\alpha \kleeneleq \beta</code>	$\alpha \leq_{\mathcal{O}_1} \beta$	
<code>\alpha \kleenegtr \beta</code>	$\alpha >_{\mathcal{O}_1} \beta$	
<code>\alpha \kleenegeq \beta</code>	$\alpha \geq_{\mathcal{O}_1} \beta$	
<code>\alpha \kleenePlus \beta</code>	$\alpha +_{\mathcal{O}_1} \beta$	Effective addition of notations
<code>\alpha \kleeneMul \beta</code>	$\alpha \cdot_{\mathcal{O}_1} \beta$	Effective multiplication of notations
<code>\kleenelim{\lambda}{n}</code>	$\lambda_{[n]}$	The $n$ -th element in effective limit defining notation $\lambda$
<code>\kleenepred{\alpha}</code>	$\alpha^-$	Predecessor of $\alpha$ if defined
<code>\kleenehgt{R}</code>	$\ R\ _{\mathcal{O}_1}$	Height of computable relation $R$

**4.17. Forcing.** To disable these commands pass the option `noforcing`.

<code>\sigma \forces \phi</code> <code>\sigma \frc \phi</code>	$\sigma \Vdash \phi$	$\sigma$ forces $\phi$
<code>\sigma \forces(X) \phi</code>	$\sigma \Vdash_T^X \phi$	$\phi$ is formula relative to $X$
<code>\sigma \forces[T] \phi</code>	$\sigma \Vdash_T^X \phi$	Local forcing on $T$
<code>\sigma \forces* \phi</code>	$\sigma \Vdash^* \phi$	Strong forcing



4.18. **Syntax.** To disable these commands pass the option `nosyntax`.

All syntax classes can be relativized with an optional argument in square brackets even when not listed below. Only the  $\Delta$  formula classes are listed below since the syntax is identical for  $\Sigma$  and  $\Pi$ . Capitalizing the first letter gives the boldface version in all cases (except the computable infinitary formulas as this doesn't make sense). Not all formulas/abbreviations are demonstrated below given the huge number but the enough are included to make it clear what command is required to generate the desired formula class, e.g., substituting `pi` for `delta` does what you think it does.

To change the syntax for the computable infinitary formulas you can pass the options `cdeltasym=macroname`, `csigmasym=macroname` and `cpisym=macroname` where `macroname` is the name (without the leading `\`) of the macro giving the desired symbol to use for the relevant class.

<code>\Cdeltan[X]{\alpha}</code>	${}^c\Delta_2^X$	The computable $\delta_\alpha^X$ formulas
<code>\deltan{2}</code>	$\Delta_2$	
<code>\deltan[X]{2}</code>	$\Delta_2^X$	
<code>\deltaZeroN[X]{2}</code> <code>\deltazn[X]{2}</code>	$\Delta_2^{0,X}$	
<code>\deltaZeroOne[X]</code> <code>\deltazi[X]</code>	$\Delta_1^{0,X}$	
<code>\sigmaZeroTwo[X]</code> <code>\sigmazii[X]</code>	$\Delta_2^{0,X}$	
<code>\deltaZeroThree[X]</code> <code>\deltaziii[X]</code>	$\Delta_3^{0,X}$	
<code>\deltaOneN[X]{2}</code> <code>\deltaIn[X]{2}</code>	$\Delta_2^{1,X}$	
<code>\deltaOneOne[X]</code> <code>\deltaIi[X]</code>	$\Delta_1^{1,X}$	
<code>\deltaOneTwo[X]</code> <code>\deltaIii[X]</code>	$\Delta_2^{1,X}$	
<code>\deltaOneThree[X]</code> <code>\deltaIiii[X]</code>	$\Delta_3^{1,X}$	
<code>\pizi</code>	$\Pi_1^0$	
<code>\pizn[X]{n}</code>	$\Pi_n^{0,X}$	
<code>\Deltan{2}</code>	$\mathbb{A}_2$	
<code>\DeltaOneN[X]{n}</code>	$\mathbb{A}_n^{1,X}$	
<code>\logic{\omega_1}{\omega}</code>	$\mathcal{L}_{\omega_1,\omega}$	Indicates the kind of infinitary logic

#### 4.19. Proof Cases.

*Proof.* The `pfcases` environment provides a numbered, referenceable division of a proof segment into cases. Note these features are not available if you are using the package in a beamer document (not likely to be an issue).

CASE 1  $x = y$ : Lorem ipsum dolor sit amet, consectetur adipiscing elit. In et enim eget nisl luctus venenatis. Pellentesque sed erat sodales, tincidunt quam non, eleifend risus. Fusce aliquam dignissim pharetra. Integer id dui ac libero tincidunt consectetur. Sed laoreet nunc nec semper laoreet.

Vestibulum semper eget velit ut lobortis. In vel finibus est. Nullam tellus dolor, pellentesque sed orci sed, ornare pretium diam. Nam vel tincidunt tellus. Nulla at mi nisl.

CASE 2  $x = z \wedge z > q \wedge z < r \wedge x + z = r$ : Quisque consectetur, felis non congue dictum, mauris mi suscipit sem, vel laoreet justo ipsum in tellus. Suspendisse blandit malesuada velit faucibus pulvinar.

CASE 2a:  $x = 2$ . ipsum dolor sit amet, consectetur adipiscing elit. In et enim eget nisl luctus venenatis. Pellentesque sed erat sodales, tincidunt quam non, eleifend risus. Fusce aliquam dignissim pharetra. Integer id dui ac libero tincidunt consectetur. Sed laoreet nunc nec semper laoreet.

CASE 2b:  $x = 3$ . consectetur adipiscing elit. In et enim eget nisl luctus venenatis. Pellentesque sed erat sodales, tincidunt quam non, eleifend

We can now reference the case number 2 and cleveref case 2 as well as case 2a and cleveref case 2b.

To skip numbering and instead reference with the argument to \case use pfcases\*

CASE  $x = y$ : Lorem ipsum dolor sit amet, consectetur adipiscing elit. In et enim eget nisl luctus venenatis. Pellentesque sed erat sodales, tincidunt quam non, eleifend risus. Fusce aliquam dignissim pharetra. Integer id dui ac libero tincidunt consectetur. Sed laoreet nunc nec semper laoreet.

Vestibulum semper eget velit ut lobortis. In vel finibus est. Nullam tellus dolor, pellentesque sed orci sed, ornare pretium diam. Nam vel tincidunt tellus. Nulla at mi nisl.

CASE  $x = z \wedge z > q \wedge z < r \wedge x + z = r$ : Quisque consectetur, felis non congue dictum, mauris mi suscipit sem, vel laoreet justo ipsum in tellus. Suspendisse blandit malesuada velit faucibus pulvinar.

CASE  $x = 2$ : Lorem ipsum dolor sit amet, consectetur adipiscing elit. In et enim eget nisl luctus venenatis. Pellentesque sed erat sodales, tincidunt quam non, eleifend risus. Fusce aliquam dignissim pharetra. Integer id dui ac libero tincidunt consectetur. Sed laoreet nunc nec semper laoreet.

CASE  $x = 3$ : consectetur adipiscing elit. In et enim eget nisl luctus venenatis. Pellentesque sed erat sodales, tincidunt quam non, eleifend

□

Again we can ref case  $x = z \wedge z > q \wedge z < r \wedge x + z = r$  and cleverref that case  $x = z \wedge z > q \wedge z < r \wedge x + z = r$ . Also case  $x = 2$  and cleverref subcase  $x = 3$ .

If the choice of cleverref labels aren't to your taste please let me know and I will consider changing them. Also, note that by passing the options pfcasfont=textit one can change the font used to typeset Case to italics (or whatever other font command you choose).

The above is accomplished with the following code.

```

\begin{proof}
\begin{pfcases}
\case[( x = y )]\label{case:first} ...
\case[( x = z \land z > q \land z < r \land x + z = r )]\label{case:second} ..
\begin{pfcases}
\case[( x=2 )]\label{case:second:sub1} ..
\case[( x = 3 )]\label{case:second:sub2}..
\end{pfcases}
\end{pfcases}
.. \ref{case:second}.. \cref{case:second} .. \ref{case:second:sub1} .. \cref{case:second:sub2}
\begin{pfcases*}
\case[( x = y )]\label{case*:first} ..
\case[( x = z \land z > q \land z < r \land x + z = r )]\label{case*:second} ..
\begin{pfcases*}
\case[( x=2 )]\label{case*:second:sub1} ..
\case[( x = 3 )]\label{case*:second:sub2}
\end{pfcases*}
.. \ref{case*:second} .. \cref{case*:second} .. \ref{case*:second:sub1} ..
\cref{case*:second:sub2}.
\end{proof}

```

4.20. **MRref.** Finally to enable the mrref helper macros pass the option mrref. These macros normalize the formatting of mathscinet references for supported bibliography styles and ensure the MR numbers link to the mathscinet page of the article. Unless you have a good reason (like journal formatting guidelines) there is no reason not to always pass this option. Note this option requires the hyperref package.

## 5. RELEASE NOTES

- 3.6 Fixed `\REA[n]` so that dash is shorter. Added BeamerRequirements to add a block for requirements in beamer and fixed the requirements environment for beamer. Fixed `\req*` error. Improved syntax for `\recfnl` so it can accept a parenthesis delimited argument as the oracle. Improved `\setcol` to allow it to be used in a nested fashion without typesetting bugs. Changed the `\code` and `\pair` commands to use only a single angle bracket.
- 3.5 Added `\Hop` and misc code cleanup.
- 3.4 Eliminated dependence on undertilde which is missing from texlive
- 3.3.1 Fixed typo causing error under pdflatex.
- 3.3 - Fixed/added tweak to overline so it looks correct. Also added real symbols so that `\subfunneq` and `\supfunneq` can be defined appropriately. Added `\floor` and `\ceil`. Note these aren't yet shown off in package doc. Fixed incorrect use of tiny in math mode.

- 3.2 - Removed `\reaop`, `\alphaREAop`, `\aREAop` in favor of using the single form `\REAop`. Removed `\functo`, `\map` and `funcomp`, `\hgt0` as useless synonyms and removed `\Kleene0Below` and `Kleene0Less` as beyond what the package should define. Added package option `compat31` to ensure package compatibility with version 3.1. An optional parentheses delimited argument specifying the base has been added to `\REAop`. Both `\REAop` and the pair `\REA/\CEA` have been updated to ignore order of optional arguments. The square brackets used to delimit the argument to the `use` command are now auto-sized. Added `\pmapsto`, `\pmapsfrom`, `\kleeneZero`, `\kleeneNum`, `\entersat`. Also Misc typesetting fixes.
- 3.1 02/26/2019 - Fixed `\wck` to be  $\omega_1^{\text{CK}}$ , i.e., have capitalized roman CK.
- 3.01 02/17/2019 - Fixed `\RE \CE \Re` and `\Ce` for the various capitalized versions. Fixed weird bug with `\recfn1` no longer working based on let. Removed `\interior` and `verb=\C=` as not really appropriate commands for the package and having bugs. Also fixed package to have correct version.
- 3.0 02/16/2019 - Added requirements environment for multiple requirements. Changed the `\req` and `\require` commands to take their optional argument after the first mandatory arguments as well as before. Added the commands `\module` and `\modof` and `\xor`. Improved the corner quotes. Added `\lefttoeq`, `\rightof`, `\righttoeq`. Added `\RE`, `\CE`, `\Ce`, `\Re` and `\Tincompat`, `\Tincomp`, `\Tcompat`. Changed the way strings are symbolized and coded. Fixed suffix commands to work with unicode-math. Also added `\require*` inside `\requirements`. Added `\nlefttoeq`, `\nrightof`, `\nrighttoeq`, `\nleftof`. The commands `\ancestor`, `\descendant` etc... `\reqof`, `\Astages` and `\Vstagesnow` require the option `suppPriorityTrees` be passed to the class to use and should be viewed as depreciated. Fixed the options system so different symbols can be correctly passed to the class. Changed the way `\recf` works to comply with the usual syntax.
- 2.4.3 11/29/2018 - Rendered compatible with beamer by removing `enumitem` requirement if beamer is loaded.
- 2.4.2 11/29/2018 - Fixed horrible bugs introduced in last version and fixed many symbols to work even in `pdflatex` mode. Also have everything compiling again.
- 2.4.1 2/14/2018 - Moved to using `xparse` to define the case macros and several other macros to allow nested brackets for optional arguments. Added the `recf` command and cleaned up some option processing. Also worked around the `mathtools/unicode-math` font bug described [here](#)
- 2.4 1/17/2018 - Added priority tree helpers. Should be more robust with respect to existing definitions of common commands.

- 2.3 12/31/2017 - Added proof cases helper. Also fixed the issue with `\ncequiv` in  $\text{\LaTeX}$
- 2.2 11/14/2017 - Fixed `\Tdeg` so it works different on symbols and vars and added `\Tdegof` and `\Tvarof`. Added `\subfunneq` and `\supfunneq`.
- 2.1 10/05/2017 - Fixed way packages are required so `rec-thy` can be loaded in a flexible order. Also fixed one or two bugs.
- 2.0 09/26/2017 - Added support for introducing requirements, the subfunction relation and probably other undocumented features
- 1.3 06/20/2012 - Added abbreviations for computable infinitary formulas and made a few minor fixes.
- 1.2 01/01/2011 - Fixed awful option processing bug preventing most options from being recognized and added `mrref` option.
- 1.0 10/15/2010 - Initial public release