

Arkade Wallet

Arkade Wallet is the entry-point to the Arkade ecosystem—a self-custodial Bitcoin wallet delivered as a lightweight Progressive Web App (installable on mobile or desktop in seconds, no app-store gatekeepers). Built around the open-source ARK protocol, it speaks natively to any arkd instance, letting you create, send, and receive Virtual Transaction Outputs (VTXOs) for instant, off-chain pre-confirmations and batched, fee-efficient on-chain settlement.

Screenshots

Environment Variables

Variable	Description	Example Value
VITE_ARK_SERVER	Override the default Arkade server URL	VITE_ARK_SERVER=http://localhost:7070
VITE_APP_VERSION	App version string shown in support diagnostics	VITE_APP_VERSION=1.2.3
VITE_BOLTZ_URL	Override the default Boltz swap provider URL for Lightning	VITE_BOLTZ_URL=https://boltz-provider-url.com
VITE_CHATWOOT_WEBSITE_TOKEN	Chatwoot website token for customer support integration	VITE_CHATWOOT_WEBSITE_TOKEN=your-token
VITE_CHATWOOT_BASE_URL	Chatwoot server base URL for customer support integration	VITE_CHATWOOT_BASE_URL=https://app.chatwoot.com
VITE_DELEGATOR_URL	Delegator service URL for the wallet service worker	VITE_DELEGATOR_URL=https://delegator.example.com
VITE_LENDASAT_IFRAME_URL	Override the default LendaSat URL	VITE_LENDASAT_IFRAME_URL=http://localhost:5173
VITE_SATORA_IFRAME_URL	Override the default Satora URL	VITE_SATORA_IFRAME_URL=http://localhost:5174
VITE_MAX_PERCENTAGE	Override the max fee percentage (default 10)	VITE_MAX_PERCENTAGE=5
VITE_NOSTR_RELAY_URL	Override the default Nostr relay URLs for backup	VITE_NOSTR_RELAY_URL=wss://relay.example.com
VITE_PSA_MESSAGE	Message to show on the wallet index page	VITE_PSA_MESSAGE=@arkade_os on TG for support
VITE_SENTRY_DSN	Enable Sentry error tracking (only in production, not on localhost)	VITE_SENTRY_DSN=your-sentry-dsn
VITE_UTXO_MAX_AMOUNT	Override the server's utxoMaxAmount	VITE_UTXO_MAX_AMOUNT=-1
VITE_UTXO_MIN_AMOUNT	Override the server's utxoMinAmount	VITE_UTXO_MIN_AMOUNT=330
VITE_VERIFIED_ASSETS_URL	Override the verified assets list	VITE_VERIFIED_ASSETS_URL=https://arklabshq.github.io/
VITE_VTXO_MAX_AMOUNT	Override the server's vtxoMaxAmount	VITE_VTXO_MAX_AMOUNT=-1
VITE_VTXO_MIN_AMOUNT	Override the server's vtxoMinAmount	VITE_VTXO_MIN_AMOUNT=330
CI	Set to <code>true</code> for Continuous Integration environments	CI=true
GENERATE_SOURCEMAP	Disable source map generation during build	GENERATE_SOURCEMAP=false

Docker

The wallet is available as a Docker image on GitHub Container Registry.

Pull and run

```
docker pull ghcr.io/arkade-os/wallet:latest
docker run -p 8080:80 ghcr.io/arkade-os/wallet:latest
```

Open <http://localhost:8080> to view the wallet.

Runtime configuration

Environment variables can be passed at runtime to configure the wallet without rebuilding the image:

```
docker run -p 8080:80 \
  -e VITE_ARK_SERVER=https://arkade.computer \
  -e VITE_BOLTZ_URL=https://api.boltz.exchange \
  ghcr.io/arkade-os/wallet:latest
```

See the Environment Variables table for all supported variables.

Build locally

```
docker build -t arkade-wallet .
```

With build-time configuration

```
docker build \
  --build-arg VITE_ARK_SERVER=https://arkade.computer \
  --build-arg VITE_BOLTZ_URL=https://api.boltz.exchange \
  -t arkade-wallet .
```

Getting Started

Prerequisites

- Node.js v24.15.0 (see `.nvmrc`)
- PNPM `>=8`

Installation

Install dependencies

```
pnpm install
```

Development

pnpm run start

Runs the app in the development mode.

Open <http://localhost:3002> to view it in the browser.

The page will reload if you make edits.

You will also see any lint errors in the console.

pnpm run build

Builds the app for production to the `dist` folder.

It correctly bundles React in production mode and optimizes the build for the best performance.

The build is minified and the filenames include the hashes.

Your app is ready to be deployed!

```
pnpm run regtest:start
```

Starts the regtest environment and sets up the arkd instance.

Requires Docker and Node.js v20.19+ or v22.12+. The stack is driven by the in-house `arkade-regtest` Node CLI (`regtest/regtest.mjs`) — no Nigiri required.

Use `pnpm run regtest:stop` to stop it and `pnpm run regtest:clean` to tear it down.

Funding your local wallet

To interact with Ark features, you need Regtest coins. 1. Copy your address from the wallet's **Receive** screen (ensure it starts with `bcr1` for Regtest). 2. Run the faucet command (the `--confirm` flag mines a block so the deposit confirms):

```
node regtest/regtest.mjs faucet <bcr1-address> <btc> --confirm
```

e2e tests

note: e2e tests require a regtest environment to be running. `pnpm run regtest:start` to start and setup the regtest environment.

note: e2e tests use playwright for ui testing, you may need to run `pnpm exec playwright install` once to download new browsers.

Run the tests with:

```
pnpm run test:e2e
```

Run the tests in interactive mode with:

```
pnpm run test:e2e --ui
```

Access the playwright code generator tool with:

```
pnpm run test:codegen
```

Troubleshooting

address already in use (Port 5000) on macOS

macOS AirPlay Receiver uses port 5000 by default, which conflicts with the regtest stack. - **Fix:** Go to `System Settings > General > AirDrop & Handoff` and disable **AirPlay Receiver**.