

SatsPath

A transport-neutral Bitcoin payment discovery and routing protocol.

[!CAUTION] **EXPERIMENTAL SOFTWARE — DO NOT USE WITH REAL FUNDS.** SatsPath v2 is currently undergoing internal conformance testing (Issue #60). It must not be deployed for real economic activity until the v2 conformance suite is finalized and an external cryptographic audit gate is deliberately cleared.

The standalone daemon includes an experimental key-transparency log and Merkle explorer. Quote, pay and preview fail closed unless the profile is included in the exact signed checkpoint and consistent with the local `log_id` pin. It is unaudited; see the architecture and limitations.

Problem

Bitcoin has multiple payment rails — Lightning, on-chain, Ark, LNURL, BOLT12, Silent Payments — each with different trade-offs on speed, cost, and privacy. Users and apps must manually decide which rail to use, and there is no universal way to discover payment methods from a human-readable identifier.

Solution

SatsPath maps human-readable identifiers (e.g. `alice@example.com`) to **signed payment profiles** containing all available payment methods. A routing engine selects the best rail automatically based on amount, on-chain fees, and available methods.

Identity keys generated by SatsPath are used exclusively for signing profiles and proving ownership. **SatsPath does NOT generate wallet private keys, seeds, or custody keys for funds.** SatsPath is a resolution and routing layer — not a wallet, not a custodian.

SatsPath is specified as a transport-neutral protocol. Pear/Holepunch P2P is one optional transport for signed profiles, not the protocol itself. Start with `docs/protocol.md`, `docs/resolvers.md`, `docs/wire_p2p.md`, and `docs/implementations.md`.

The core flow is:

`identifier -> resolver chain -> signed profile -> signature check -> route decision -> QR / wallet handoff`

Resolvers can use local files, HTTPS well-known endpoints, BIP-353 DNS, Nostr/NIP-05, or optional P2P. A receiver publishes the same signed SatsPath profile over any of those transports. A sender only trusts it after SatsPath verifies the profile signature.

Current Functional Surface

- Resolve `alice@example.com` to a signed payment profile through the resolver chain.
- Encode/decode universal payment URIs (`satspath:v1:<base64url_json>`).
- Sign profiles with secp256k1 identity keys.
- Verify profile signatures before routing.
- Resolve LNURL-pay endpoints and fetch BOLT11 invoices securely.
- Select the best payment rail (Lightning → On-chain → Ark preview/intents).
- Return a stable `QuoteResponse` with `ok`, `not_registered`, `no_route`, or `invalid_signature`.
- Produce a public payment payload / QR via CLI preview or `satspathd` wallet handoff.
- Fetch real-time on-chain fee estimates from `mempool.space`.
- Generate safe payment previews and Ark route intents; Ark swaps are not claimed as complete unless explicitly testnet-executed and supported by the bridge.

- Resolve DNSSEC-backed **BIP-353** payment instructions (`user@domain`) for domains the receiver controls — see docs/bip353_dns_resolution.md.
- Resolve SatsPath profiles over **Nostr/NIP-05** without P2P: NIP-05 discovers a Nostr pubkey and relays, then relays are queried for a signed SatsPath profile event.
- Generate invite links for unregistered users (receiver generates their own keys).
- Run a local daemon (`satspathd`) that exposes `/v1/node`, `/v1/quote`, `/v1/pay`, and `/v1/dns/resolve`.
- Full CLI: `init`, `register`, `show`, `encode`, `decode`, `quote`, `pay`, `invite`, `dns resolve`, `demo`.
- **Self-Hosting**: Sovereign server deployment and DNS operator onboarding (`satspath server init/check`). See deploy/README.md for Docker Compose and TLS proxy instructions.

SatsPath can resolve DNSSEC-backed BIP-353 payment instructions for domains the receiver controls. For consumer email addresses like `gmail.com`, SatsPath uses platform verification / the invite flow instead, because the user cannot publish DNS records under `gmail.com`. BIP-353 resolution is **mainnet preview only**: SatsPath resolves and displays instructions but never pays, signs, or broadcasts.

Resolver Chain

The default resolver chain is:

`local registry -> BIP-353 -> HTTPS well-known -> Nostr/NIP-05`

Optional Pear/Holepunch P2P can be used as another transport, but the protocol does not depend on it.

For Nostr, publish:

1. A NIP-05 record at `https://<domain>/.well-known/nostr.json?name=<user>` that maps `user` to a Nostr pubkey and relay list.
2. A Nostr kind 30078 event by that pubkey with tag:

`d = satspath-profile:<user@domain>`

The event `content` is the JSON `SignedPaymentProfile`. Senders then resolve the identifier, verify the SatsPath profile signature, route, and get the QR/payment payload.

Consumer email domains such as `gmail.com` cannot be used for DNS or NIP-05 publication unless the user controls the domain endpoint. For those identifiers, the current behavior is invite flow or a future platform-verification resolver.

Email identifiers vs verified identifiers

SatsPath can use an email-shaped value as the human-readable identifier. That does not automatically verify the inbox.

- A signed profile proves control of the SatsPath protocol identity key.
- DNSSEC/BIP-353 or Nostr/NIP-05 can prove domain-controlled publication.
- A consumer email address such as `user@gmail.com` needs a platform challenge flow before it can be marked as an identifier-verified profile.
- Until that exists, consumer email addresses are treated as identifiers for lookup and invite delivery, not as verified payment identities.

Mainnet Preview

```
satspath preview rodrigo@satspath.dev 1000 --mainnet
satspath preview rodrigo@satspath.dev 1000 --mainnet --json
satspath quote rodrigo@satspath.dev 1000 --mainnet-preview --json
```

Lightning Address / LNURL preview does not fetch a real BOLT11 invoice by default. To fetch one explicitly:

```
satspath preview rodrigo@getalby.com 1000 --mainnet --fetch-lnurl-invoice
```

Fetches invoices are displayed only as data. SatsPath never pays them.

Nostr profile discovery

SatsPath can resolve a signed profile through Nostr without using the P2P SDK. This requires an identifier whose domain can publish NIP-05 metadata.

Receiver side:

1. Publish NIP-05 metadata:

`https://example.com/.well-known/nostr.json?name=alice`

with:

```
{
  "names": {
    "alice": "<64-char nostr pubkey hex>"
  },
  "relays": {
    "<64-char nostr pubkey hex>": ["wss://relay.example.com"]
  }
}
```

2. Publish a Nostr event authored by that pubkey:

```
{
  "kind": 30078,
  "tags": [["d", "satspath-profile:alice@example.com"]],
  "content": "{\n  \"profile\": {...},\n  \"signature\": \"3044...\"}"
}
```

`content` is the exact JSON `SignedPaymentProfile` exported by SatsPath.

Sender side:

```
satspath quote alice@example.com 250 --mainnet-preview --json
```

The resolver chain discovers the Nostr pubkey/relays through NIP-05, fetches the SatsPath profile event, verifies the SatsPath signature, and returns the normal `QuoteResponse` with a QR/payment payload.

For `rodrigodiazgt7@gmail.com`, neither DNS nor NIP-05 can be published by the user under `gmail.com`. That identifier currently resolves through invite flow unless a future platform resolver verifies Gmail ownership and publishes a signed profile through a supported transport.

What this prototype does NOT do yet

- Execute real Lightning, on-chain, or Ark payments. The experimental swap engine is **testnet-only scaffolding that previews swap intent**; it does not complete, direct, claim, or refund swaps, and must never be used on mainnet.
- Enable mainnet Ark execution.
- Verify email or domain ownership during registration.
- Publish profiles to Nostr from the Rust CLI. The resolver can read Nostr events, but publishing still needs a Nostr client or a future CLI command.
- Provide a decentralized global registry. SatsPath uses resolver transports; it does not have a single canonical registry.
- Support key rotation or profile revocation.
- Implement BOLT12 invoice fetching.
- Support Silent Payments or Split Payments.
- Provide a production wallet UI.

Safe Path (Mainnet Preview) vs Experimental Execution

The **Safe Path** (Mainnet Preview) is active by default and allowed:

- Resolving public data only.
- Fetching and resolving LNURL-pay metadata.
- Requesting BOLT11 invoices from LNURL callbacks securely.
- Presenting the invoice as a QR code or payment pointer for the user to pay with their own wallet.
- Profile signature and expiry checks.
- Public ownership proof checks where available.
- BIP21 on-chain URI generation.
- Ark public pointer / intent URI generation.

The **Experimental Path** (Automatic Execution via Swaps/Ark) is isolated and restricted:

- Requires explicit `--experimental-swaps` and `--testnet` flags.
- Mainnet execution is strictly disabled (no `--execute-mainnet` flag exists).
- No automatic payment execution exists on mainnet.
- No transaction signing or broadcasting path is exposed.
- No seed phrases, xprv/tprv, macaroons, certs, API secrets, claim keys, or refund keys are accepted into mainnet preview output.

Architecture

Human-readable identifier

(e.g. rodrigo@satspath.dev)

|
v

Resolver /	<-- local .satspath/registry.json (prototype)
Transport chain	<-- BIP-353 / HTTPS / Nostr / optional P2P

|
v

Signed Payment
Profile
(secp256k1 sig)

|
v

Route Engine

		\
v	v	v

LN BTC Ark

Crate layout

```
satspath/  
  crates/  
    satspath-core/    # Types, crypto, codec, registry
```

```
    satspath-router/    # Route selection engine + fee API
    satspath-cli/       # CLI binary
examples/
    rodrigo_profile.json
    demo_flow.md
docs/
    architecture.md
    implementations.md
    resolvers.md
    threat_model.md
    protocol.md
    wire_p2p.md
```

Installation

```
git clone https://github.com/<your-org>/satspath
cd satspath
cargo build --release
# Binary at: target/release/satspath
```

Or run directly:

```
cargo run -p satspath-cli -- <command>
```

CLI Usage

Initialize

```
satspath init
```

Creates `.satspath/registry.json` and `.satspath/keys.json` locally. These directories are git-ignored.

Register

```
satspath register rodrigo@satspath.dev
```

Generates a fresh secp256k1 identity keypair, builds a demo payment profile with Lightning, on-chain ($\times 2$ for privacy), and Ark methods, signs the profile, and stores it in the local registry.

Show

```
satspath show rodrigo@satspath.dev
```

```
Alias:          rodrigo@satspath.dev
Identity pubkey:02a1b2c3...
Fingerprint:    a1b2c3d4
Signature valid: yes
Updated at:     1735000000
```

Methods:

- Lightning Address [Lightning]
Lightning Address: rodrigo@satspath.dev
- Bitcoin (primary) [On-chain]
Address: bc1q...
- Bitcoin (secondary) [On-chain]

```
Address: bc1q...
- Ark [Ark]
Server: ark.satspath.dev
```

Encode a payment URI

```
satspath encode rodrigo@satspath.dev 21000 --memo "coffee"
satspath:v1:eyJ2ZXJzaW9uIjox...
```

Decode a payment URI

```
satspath decode "satspath:v1:eyJ2ZXJzaW9uIjox..."
```

Decoded payment request:

```
Version:      1
Alias:        rodrigo@satspath.dev
Amount:       21000 sats
Memo:         coffee
Profile hint: (none)
```

Quote (route selection)

```
satspath quote rodrigo@satspath.dev 21000
```

```
Resolving alias...
Verifying signature...
Checking payment rails for 21000 sats...
```

Route Quote:

```
Selected rail:  Lightning
Label:         Lightning Address
Reason:        Amount (21000 sats) is below 100000 sats threshold and Lightning is available.
Estimated fee:  2 sats
Confirmation:   instant
```

Pay (simulated)

```
satspath pay rodrigo@satspath.dev 21000 --experimental-swaps --testnet
```

```
Resolving alias 'rodrigo@satspath.dev'...
Verifying signed profile...
Checking available payment rails...
Selected route: Lightning
Reason:        Amount (21000 sats) is below 100000 sats threshold and Lightning is available.
```

Payment status: simulated_success (or real execution if experimental engine is enabled)

Invite (unregistered user)

```
satspath invite julian@example.com 21000
```

'julian@example.com' is not registered on SatsPath.

Invite link:

```
https://satspath.local/claim?alias_hash=a1b2c3d4...&amount=21000
```

WARNING: The receiver must claim this payment by generating their own keys locally.

Full demo

`satspath demo`

Runs all steps above automatically.

Example demo flow

See `examples/demo_flow.md` for a full annotated walkthrough.

Security model

- **Keys are local.** The only private keys SatsPath generates are **identity keys used to sign public payment profiles** — they are not wallet spending keys, seeds, or custody keys, and they do not control funds. They are stored only on the user's machine in `.satspath/keys.json`, which is git-ignored and never transmitted.
 - **Signatures are mandatory.** Every payment profile is signed with the owner's identity key. Signature verification happens before routing.
 - **Public profiles only.** The registry stores only public data: pubkeys, addresses, and signatures.
 - **Invite, don't proxy.** For unknown users, SatsPath creates an invite. The receiver generates their own keys.
-

Threat model summary

Threat	MVP Mitigation
Fake alias registration	Signature-bound profiles; first-come-first-served
Server tampering	secp256k1 signature verification on every resolve
Key replacement attack	Signature covers identity_pubkey; swap breaks sig
Profile replay	expires_at enforced locally and remotely
Email takeover	Not mitigated at MVP (future: DKIM challenge)
LNURL spoofing	Amount and expiry verification before routing
On-chain privacy leaks	Multiple on-chain addresses per profile
Lost keys	Local backup only (future: BIP-39 seed phrase)
Malicious invite links	Alias hash + amount in invite; receiver verifies
Ark server trust	Mock client only (future: covenant-based Ark)

Full threat model: `docs/threat_model.md`

Future integrations

Integration	Purpose
BIP-353	Replace local registry with DNS TXT record resolution
Nostr	Decentralized identity and profile discovery (NIP-05, NIP-57)
Lightning Address	Auto-discover LNURL-pay endpoint from <code>user@domain</code>
BOLT12	Async invoices and reusable payment offers
Ark	Non-custodial off-chain payments via virtual UTXOs

Integration	Purpose
Silent Payments	Privacy-preserving on-chain payments (BIP-352)
Split Payments	Route a single payment across multiple rails

Running tests

`cargo test`

Test coverage includes:

- Profile serialization
 - Profile signing and verification
 - Invalid signature rejection
 - Tampered profile rejection
 - Encode/decode payment URIs
 - Registry register/resolve
 - Router: Lightning for small amounts
 - Router: On-chain for low fees
 - Router: Ark fallback for high fees
 - Ark route planning and testnet-gated intent safety
 - Router: Error when no methods available
 - Registry persistence across opens
-

Hackathon scope

This prototype was built during a hackathon to demonstrate:

1. A working secp256k1-signed payment profile format with expiration.
2. A universal URI encoding scheme for payment requests.
3. An automatic payment rail selector using real mempool.space fee data.
4. A privacy-aware profile with multiple on-chain addresses.
5. An invite flow that preserves receiver key sovereignty.
6. A fail-closed, encrypted swap storage engine (behind `--experimental-swaps`).

It is **not production-ready**. The registry is local, payments are simulated (unless experimental flags are used), and domain verification is not implemented.

DISCLAIMER

This is hackathon software. Do not use with real funds.