



API Reference

This page documents the HTTP API used to run scraping tasks and (optionally) configure custom proxies.

TOOLS

You can use tools like [Bruno](#) or [Postman](#) to explore and test the APIs.

Authentication

All endpoints require an API token:

- **Header:** `Authorization: Bearer ${token}`

To get your token:

1. Log in to the [Console](#).
2. Click **Get API Token** and then **Generate Token**.
3. Copy the token and use it in the `Authorization` header.

Each token is valid for 365 days. Generating a new token does not invalidate previous ones.

Common Concepts

Scraping Task Lifecycle

A scraping task goes through these phases:

1. **PENDING** → task accepted and queued
2. **RUNNING** → actively being executed
3. **SUCCESS** → completed successfully (**billed**)

4. **BLOCKED / ERROR** → recoverable failure, retried automatically (3 times)
5. **BLOCKED_TOO_MANY_TIMES / ERROR_TOO_MANY_TIMES** → non-recoverable failure (**not billed**)
6. **CANCELLED** → cancelled by client or by timeout (**not billed**)
7. **REPLACED** → rare edge cases where a task is replaced by one or more derived tasks (e.g. a page is split into smaller pages)

Synchronous vs Asynchronous Execution

The **Run** endpoints support two modes:

- `waitForCompletion=true` (default): keep the HTTP connection open until tasks complete and return results directly.
- `waitForCompletion=false`: return immediately. You can later fetch results using **Read Scraping Tasks**.

⚠ LONG-LIVED CONNECTIONS

When `waitForCompletion=true`, if the HTTP connection closes prematurely, **ongoing scraping tasks are cancelled**.

💡 RECOMMENDED FOR PRODUCTION

For production integrations, prefer `waitForCompletion=false` + polling/batching to avoid long-lived connections.

Scraping Tasks

Run Scraping Tasks

Run multiple requests in a single call.

HTTP Method and URL

```
POST https://continuous-scraper.common.chartedapi.com/scraping-tasks/${scraper}/run?autoCancelAfterSec=1200&waitForCompletion=false
```

Path Parameters

- `scraper`: `shopee`, `shopee-android` or `lazada`

Query Parameters

- `waitForCompletion` (default = `true`): wait for completion and return results directly.
- `autoCancelAfterSec` (default = `600`): execution timeout (only used when `waitForCompletion=true`).
- `includeAllFields` (default = `false`): if false, only the most important fields are returned.
- `includeFields` (optional): comma-separated list of fields to return (overrides `includeAllFields`). Example: `includeFields=uuid,url,status`
- `httpStatusOnError` (optional): HTTP status code returned if **at least one** task ends in an error/blocked terminal status.
 - If not set, the API always returns `200 OK`.
 - Example: `httpStatusOnError=500`

Request Headers

- `Authorization: Bearer ${token}`

Request Body Example

```
{
  "requests": [
    {
      "url": "https://shopee.co.id/adidas-Runfalcon-3.0-Men's-Running-Shoes---Core-Black-i.234490784.25462132870?sp_atk=67836f0a-c0c8-40d4-a0a7-bd1998943cc9&xptdk=67836f0a-c0c8-40d4-a0a7-bd1998943cc9"
    },
    {
      "url": "https://shopee.co.id/SEPATU-SNEAKERS-CASUAL-ADIDS-SPEZIAL-HANDBALL-BNIB-i.197850298.20595626884?sp_atk=ff613749-9cf1-4b40-ae8e-f76dd2279ba8&xptdk=ff613749-9cf1-4b40-ae8e-f76dd2279ba8"
    },
  ],
}
```

```
{
  "url": "https://shopee.sg/api/v4/microsite/batch_get_item_card",
  "method": "POST",
  "payload": {
    "shop_item_ids": [
      {
        "item_id": 40505798777,
        "shop_id": 1521408445
      },
      {
        "item_id": 40905798740,
        "shop_id": 1521408445
      },
      {
        "item_id": 42105798857,
        "shop_id": 1521408445
      },
      {
        "item_id": 43005798827,
        "shop_id": 1521408445
      },
      {
        "item_id": 27937932620,
        "shop_id": 1521408445
      }
    ]
  }
},
"cacheMaxAgeInSec": 3600
}
```

Request body fields

- `requests`: array of request objects:
 - `url`: the API or page URL to scrape
 - `method` (optional): `GET` or `POST`
 - `payload` (optional): request body when `method=POST`
- `cacheMaxAgeInSec` (default = `0`): if a successful result exists for the same URL and is fresh enough, it will be returned from cache (**not billed**).

You can also pass **scraper-specific parameters** (see the scrapers section), for example:

```
{
  "requests": [
    {
      "url": "https://shopee.co.id/api/v4/search/search_items?keyword=tshirt"
    }
  ],
  "productSearch_enrichUrlQuery_pageSize": 60,
  "productSearch_crawlNextPages": true,
  "productSearch_crawlNextPages_maxPages": 3,
  "productSearch_crawlProductDetails": true
}
```

Response (when `waitForCompletion=true`)

```
[
  {
    "url": "https://shopee.co.id/SEPATU-SNEAKERS-CASUAL-ADIDS-SPEZIAL-HANDBALL-BNIB-i.197850298.20595626884?sp_atk=ff613749-9cf1-4b40-ae8e-f76dd2279ba8&xptdk=ff613749-9cf1-4b40-ae8e-f76dd2279ba8",
    "status": "SUCCESS",
    "responseBody": "..."
  },
  {
    "url": "https://shopee.co.id/adidas-Runfalcon-3.0-Men's-Running-Shoes---Core-Black-i.234490784.25462132870?sp_atk=67836f0a-c0c8-40d4-a0a7-bd1998943cc9&xptdk=67836f0a-c0c8-40d4-a0a7-bd1998943cc9",
    "status": "ERROR_TOO_MANY_TIMES",
    "responseBody": null,
    "errorMessage": "... explanation ..."
  },
  {
    "url": "https://shopee.sg/api/v4/microsite/batch_get_item_card",
    "method": "POST",
    "payload": {
      "shop_item_ids": [
        {
          "item_id": 40505798777,
          "shop_id": 1521408445
        },
        {

```

```

        "item_id": 40905798740,
        "shop_id": 1521408445
    },
    {
        "item_id": 42105798857,
        "shop_id": 1521408445
    },
    {
        "item_id": 43005798827,
        "shop_id": 1521408445
    },
    {
        "item_id": 27937932620,
        "shop_id": 1521408445
    }
]
},
"status": "BLOCKED_TOO_MANY_TIMES",
"responseBody": "... message from scraped platform, if any ..."
}
]

```

CURL Example

```

curl --header "Content-Type: application/json" \
  --header "Authorization: Bearer ${token}" \
  --request POST \
  --data '{"requests":[{"url": "https://shopee.co.id/adidas-Runfalcon-3.0-Mens-Running-Shoes---Core-Black-i.234490784.25462132870?sp_atk=67836f0a-c0c8-40d4-a0a7-bd1998943cc9&xptdk=67836f0a-c0c8-40d4-a0a7-bd1998943cc9"}, {"url": "https://shopee.co.id/SEPATU-SNEAKERS-CASUAL-ADIDS-SPEZIAL-HANDBALL-BNIB-i.197850298.20595626884?sp_atk=ff613749-9cf1-4b40-ae8e-f76dd2279ba8&xptdk=ff613749-9cf1-4b40-ae8e-f76dd2279ba8"}]}' \
  https://continuous-scraper.common.chartedapi.com/requests/shopee/run?autoCancelAfterSec=1200&includeAllFields=false

```

Run a Single Scraping Task

Convenience endpoint to run a single request.

HTTP Method and URL

```
POST https://continuous-scraper.common.chartedapi.com/scraping-tasks/${scraper}/run-single?autoCancelAfterSec=1200
```

Parameters

Same as [Run Scraping Tasks](#).

Request Body Example

```
{
  "url": "https://shopee.co.id/adidas-Runfalcon-3.0-Men's-Running-Shoes---Core-Black-i.234490784.25462132870?sp_atk=67836f0a-c0c8-40d4-a0a7-bd1998943cc9&xptdk=67836f0a-c0c8-40d4-a0a7-bd1998943cc9"
}
```

Request body fields

Same as [Run Scraping Tasks](#), but fields that are normally located in the `requests` array are directly placed at the root (e.g. `url`, `method`, `payload`).

Response (when `waitForCompletion=true`)

```
{
  "url": "https://shopee.co.id/SEPATU-SNEAKERS-CASUAL-ADIDS-SPEZIAL-HANDBALL-BNIB-i.197850298.20595626884?sp_atk=ff613749-9cf1-4b40-ae8e-f76dd2279ba8&xptdk=ff613749-9cf1-4b40-ae8e-f76dd2279ba8",
  "status": "SUCCESS",
  "responseBody": "...",
}
```

CURL Example

```
curl --header "Content-Type: application/json" \
  --header "Authorization: Bearer ${token}" \
  --request POST \
  --data '{"url": "https://shopee.co.id/adidas-Runfalcon-3.0-Mens-Running-Shoes--Core-Black-i.234490784.25462132870?sp_atk=67836f0a-c0c8-40d4-a0a7-
```

```
bd1998943cc9&xptdk=67836f0a-c0c8-40d4-a0a7-bd1998943cc9"}' \
https://continuous-scraper.common.chartedapi.com/requests/shopee/run-single
```

Read Scraping Tasks

Fetch tasks (and results) by UUID and/or filters.

HTTP Method and URL

```
GET https://continuous-scraper.common.chartedapi.com/scraping-tasks/${scraper}?
limit=20&offset=0&uuids=398a3b4d-241c-4297-9e81-5c4c6ecce340,785ebeaf-ae2c-4453-
908b-c7dac008fbf4
```

Path Parameters

- `scraper`: `shopee`, `shopee-android` or `lazada`

Query Parameters

- `limit` (optional, default = `20`): max number of tasks to return
- `offset` (default = `0`): number of tasks to skip
- `uuids` (optional): comma-separated list of task UUIDs
- `urls` (optional): comma-separated list of task URLs
- `minPendingAt` (optional): ISO 8601 datetime (inclusive)
- `maxPendingAt` (optional): ISO 8601 datetime (exclusive)
- `includeAllFields` (default = `false`)
- `includeFields` (optional): overrides `includeAllFields`

Request Headers

- `Authorization: Bearer ${token}`

Response Body Example

```
[
  {
```



```
"uuid": "398a3b4d-241c-4297-9e81-5c4c6ecce340",
"url": "https://shopee.co.id/SEPATU-SNEAKERS-CASUAL-ADIDS-SPEZIAL-HANDBALL-BNIB-i.197850298.20595626884?sp_atk=ff613749-9cf1-4b40-ae8e-f76dd2279ba8&xptdk=ff613749-9cf1-4b40-ae8e-f76dd2279ba8",
"status": "SUCCESS",
"responseBody": "...",
},
{
  "uuid": "785ebeaf-ae2c-4453-908b-c7dac008fbf4",
  "url": "https://shopee.co.id/adidas-Runfalcon-3.0-Men's-Running-Shoes---Core-Black-i.234490784.25462132870?sp_atk=67836f0a-c0c8-40d4-a0a7-bd1998943cc9&xptdk=67836f0a-c0c8-40d4-a0a7-bd1998943cc9",
  "status": "ERROR",
  "responseBody": null,
  "errorMessage": "... explanation ..."
}
]
```

CURL Example

```
curl --header "Authorization: Bearer ${token}" \
  "https://continuous-scraper.common.chartedapi.com/scraping-tasks/shopee?
  limit=20&offset=0"
```

Count Scraping Tasks

Count tasks by status and country.

HTTP Method and URL

```
GET https://continuous-scraper.common.chartedapi.com/scraping-
tasks/${scraper}/count?statuses=PENDING,RUNNING,BLOCKED,ERROR
```

Path Parameters

- scraper: shopee, shopee-android or lazada

Query Parameters

- `statuses` (optional, default = all): comma-separated list of statuses

Example 1:

- `statuses=PENDING,RUNNING,BLOCKED,ERROR` → pending/running counts

Example 2:

- `statuses=BLOCKED_TOO_MANY_TIMES,ERROR_TOO_MANY_TIMES,REPLACED,CANCELLED,SUCCESS`
→ completed/non-recoverable counts

Request Headers

- `Authorization: Bearer ${token}`

Response Body Example

```
[  
  { "country": "ID", "status": "BLOCKED_TOO_MANY_TIMES", "count": 4846 },  
  { "country": "ID", "status": "SUCCESS", "count": 452746545 },  
  { "country": "MY", "status": "SUCCESS", "count": 3054565 }  
]
```

CURL Example

```
curl --header "Authorization: Bearer $token" \  
  "https://continuous-scraper.common.chartedapi.com/scraping-tasks/shopee/count?  
statuses=PENDING,RUNNING,BLOCKED,ERROR"
```

Cancel Scraping Tasks

Cancel tasks (and sub-tasks) by UUID and/or country.

HTTP Method and URL

```
POST https://continuous-scraper.common.chartedapi.com/scraping-  
tasks/${scraper}/cancel
```

Path Parameters

- `scraper`: `shopee`, `shopee-android` or `lazada`

Request Headers

- `Authorization: Bearer ${token}`

Request Body Example

```
{
  "uuids": [
    "2199a83d-3ebe-442c-aa82-afd3a9903967",
    "1ce16c7b-26f1-4851-a281-e09f79ce2de9",
    "34d3449d-b5b9-46a5-a4e0-d524d2ab3222"
  ],
  "countries": ["ID", "MY", "PH", "SG", "TH", "VN"]
}
```

Request body fields

- `uuids`: array of task UUIDs to cancel
- `countries`: array of countries to cancel

! INFO

Sub-scraping tasks are cancelled as well.

Response Body Example

```
{
  "uuids": [
    "2199a83d-3ebe-442c-aa82-afd3a9903967",
    "1ce16c7b-26f1-4851-a281-e09f79ce2de9",
    "34d3449d-b5b9-46a5-a4e0-d524d2ab3222",
    "37744b6d-35fb-47c0-9c73-e9b7feb9f089",
    "29d6b918-745b-4029-bdba-5f6489c43146"
  ],
}
```

```
"countries": ["ID"]
}
```

CURL Example

```
curl --header "Content-Type: application/json" \
  --header "Authorization: Bearer ${token}" \
  --request POST \
  --data '{"uuids":["2199a83d-3ebe-442c-aa82-afd3a9903967", "1ce16c7b-26f1-4851-a281-e09f79ce2de9"]}' \
  https://continuous-scraper.common.chartedapi.com/requests/shopee/cancel
```

Proxy Configuration

By default, **Charted Sea manages proxies** for you. If you want to use your own proxy pool, you can configure custom proxy URLs.

Why configure your own proxies?

- Expand your pool of IPs for higher throughput or improved success rate
- Use your existing proxy provider deals
- Control proxy routing behavior

If you use your own proxies, **Charted Sea will not charge** for managed proxy usage.

STICKY SESSIONS REQUIRED

Configured proxies **must be sticky**, because web browsers can open multiple TCP connections.

Update Proxy Configuration

Replace the entire proxy configuration with a new set of proxy URLs.

HTTP Method and URL

```
PUT https://continuous-scraper.common.chartedapi.com/proxy-configs
```

Request Headers

- Authorization: Bearer \${token}

Request Body Example

```
[
  {
    "scraper": "SHOPEE",
    "proxySettings": [
      {
        "type": "RESIDENTIAL",
        "urls": [
          "http://uuu__cr.${country(case=LOWER)}:ppp@gw.dataimpulse.com:${rand(range=[10000,19999])}",
          "http://uuu-residential-country_${country(case=UPPER)}-r_10m-s_${rand(len=10,use=[lowerCaseChar,upperCaseChar,digit])}:ppp@gate.nstproxy.io:24125"
        ]
      },
      {
        "country": "TW",
        "type": "RESIDENTIAL",
        "urls": [
          "http://uuu__cr.${country(case=LOWER)}:ppp@gw.dataimpulse.com:${rand(range=[10000,19999])}",
          "http://uuu-residential-country_${country(case=UPPER)}-r_10m-s_${rand(len=10,use=[lowerCaseChar,upperCaseChar,digit])}:ppp@gate.nstproxy.io:24125",
          "http://uuu:ppp_country-${country(case=LOWER)}_session-${rand(len=8,use=[lowerCaseChar,upperCaseChar,digit])}_lifetime-15m@geo.iproyal.com:12321"
        ]
      }
    ]
  },
  {
    "scraper": "SHOPEE_ANDROID",
    "proxySettings": [
      {
        "type": "RESIDENTIAL",
```

```
    "urls": [  
  
    "http://uuu__cr.${country(case=LOWER)}:ppp@gw.dataimpulse.com:${rand(range=  
[10000,19999])})",  
        "http://uuu-residential-country_${country(case=UPPER)}-r_10m-  
s_${rand(len=10,use=  
[lowerCaseChar,upperCaseChar,digit])}:ppp@gate.nstproxy.io:24125"  
    ]  
  },  
  {  
    "country": "TW",  
    "type": "RESIDENTIAL",  
    "urls": [  
  
    "http://uuu__cr.${country(case=LOWER)}:ppp@gw.dataimpulse.com:${rand(range=  
[10000,19999])})",  
        "http://uuu-residential-country_${country(case=UPPER)}-r_10m-  
s_${rand(len=10,use=  
[lowerCaseChar,upperCaseChar,digit])}:ppp@gate.nstproxy.io:24125",  
  
    "http://uuu:ppp_country-${country(case=LOWER)}_session-${rand(len=8,use=  
[lowerCaseChar,upperCaseChar,digit])}_lifetime-15m@geo.iproyal.com:12321"  
    ]  
  }  
]  
},  
{  
  "scraper": "LAZADA",  
  "proxySettings": [  
    {  
      "type": "DATACENTER",  
      "urls": [  
  
      "http://uuu__cr.${country(case=LOWER)}:ppp@gw.dataimpulse.com:${rand(range=  
[10000,19999])})",  
    ],  
    },  
    {  
      "type": "RESIDENTIAL",  
      "urls": [  
  
      "http://uuu__cr.${country(case=LOWER)}:ppp@gw.dataimpulse.com:${rand(range=  
[10000,19999])})",  
    ]  
    }  
  ]  
}
```

```
    }  
  ]  
}  
]
```

Request body fields

- `scraper`: SHOPEE, SHOPEE_ANDROID or LAZADA
- `proxySettings`: array of objects:
 - `type`: DATACENTER or RESIDENTIAL
 - `urls`: array of proxy URLs (placeholders supported)
 - `country` (optional): if set, this setting is dedicated to that country

Response

Same as the request body.

Read Proxy Configuration

HTTP Method and URL

```
GET https://continuous-scraper.common.chartedapi.com/proxy-configs
```

Request Headers

- `Authorization: Bearer ${token}`

Response Body Example

Same as the request body in [Update Proxy Configuration](#).

CURL Example

```
curl --header "Authorization: Bearer ${token}" \  
  "https://continuous-scraper.common.chartedapi.com/proxy-configs"
```

Appendix: Proxy URL Placeholders

Proxy URL placeholders are enclosed in `${...}` and expanded server-side before use. They allow you to dynamically generate proxy URLs (for example, to create sticky sessions or country-specific credentials).

Supported functions

`${rand(...)}`

Generates a random value.

Supported arguments:

- `len` (number)
Length of the generated string (required unless `range` is provided).
- `use` (array)
Character sets to include. Allowed values:
 - `lowerCaseChar` → `abcdefghijklmnopqrstuvwxyz`
 - `upperCaseChar` → `ABCDEFGHIJKLMNOPQRSTUVWXYZ`
 - `digit` → `0123456789`
 - `symbol` → `[ ], $&+ : ; = ? @ # | " ' > < . ^ * ( ) % ! -`
- `subset` (string)
Custom set of allowed characters (alternative to `use`).
The characters `$`, `"` and `\` must be escaped as `\$`, `\"` and `\\`.
- `range` (array `[min, max]`)
Generates a random number within the specified range (inclusive).

Examples:

```
${rand(len=8,use=[lowerCaseChar,digit])}  
${rand(range=[10000,19999])}  
${rand(len=12,subset="abcdef012345")}
```



```
${country(case=UPPER|LOWER)}
```

Expands to the target country code associated with the scraping task.

Arguments:

- `case=UPPER` → `SG`, `ID`, `MY`
- `case=LOWER` → `sg`, `id`, `my`

Example:

```
${country(case=LOWER)}
```

Example Proxy URLs

```
{
  "urls": [
    // Generate 9999 DataImpulse URLs
    "http://uuu__cr.${country(case=LOWER)}:ppp@gw.dataimpulse.com:${rand(range=[100

    // Generate many LunaProxy URLs
    "http://user-uuu-region-${country(case=LOWER)}-
    sessid-${country(case=LOWER)}${rand(len=16,use=[lowerCaseChar,digit])}-sesstime-
    30:ppp@as.e4f4xh3i.lunaproxy.net:12233",

    // Generate many IPRoyal URLs
    "http://uuu:ppp_country-${country(case=LOWER)}_session-${rand(len=8,use=
    [lowerCaseChar,upperCaseChar,digit])}_lifetime-30m@geo.iproyal.com:12321",

    // Generate many BrightData URLs
    "http://brd-customer-hl_uuu-zone-zzz-country-${country(case=LOWER)}-session-${r
    [1,70000000]}:ppp@brd.superproxy.io:22225",

    // Generate many Oxylabs URLs
    "http://customer-uuu-cc-${country(case=UPPER)}-sessid-${rand(len=10,use=
    [lowerCaseChar,digit])}-sesstime-30:ppp@pr.oxylabs.io:7777",

    // Generate many Massive URLs (note how the characters @, ?, & and = are URI en

    "http://john.doe%40example.com%3Fcountry%3D${country(case=UPPER)}%26session%3D${ran
    [lowerCaseChar,upperCaseChar,digit]}:ppp@network.joinmassive.com:65534",
```

```
// Generate many Nstproxy URLs
"http://uuu-residential-country_${country(case=UPPER)}-r_10m-s_${rand(len=10,us
[lowerCaseChar,upperCaseChar,digit]):ppp@gate.nstproxy.io:24125",

// Generate many Mango Proxy URLs
"http://uuu-zone-custom-region-${country(case=LOWER)}-session-${rand(len=9,use=
[lowerCaseChar,digit])}-sessTime-30:ppp@p1.mangoproxy.com:2333",

// Generate many Netnut URLs
"http://uuu-res-${country(case=UPPER)}-sid-${rand(len=9,use=[digit]):ppp@gw.nt

// Generate many Zenrows URLs
"http://uuu:ppp_country-${country(case=LOWER)}_ttl-30m_session-${rand(len=12,us
[lowerCaseChar,upperCaseChar,digit])}@superproxy.zenrows.com:1337",

// Generate many Soax Proxy URLs
"http://package-123456-country-${country(case=LOWER)}-sessionid-${rand(len=10,u
[lowerCaseChar,digit])}-sessionlength-10:ppp@proxy.soax.com:5000",

// Generate many 711Proxy Proxy URLs
"http://uuu-zone-custom-region-${country(case=UPPER)}-session-${rand(len=8,use=
sessTime-10-sessAuto-1:ppp@global.711proxy.com:10000"
]
}
```

Important Notes

- Placeholders are expanded for each scraping execution.
- Sticky sessions must remains stable for at least 15 minutes.
- Don't hesitate to [contact us](#) if you need help.

Next Steps

- Review the scraper-specific documentation ([Shopee](#), [Lazada](#), etc.)
- Review the [Quick Start](#) guide for a minimal integration example
- Monitor usage and wallet balance in the [Console](#)