

TCG Markdown User's Guide

Version 0.7.6
Revision 1
January 24, 2024

Contact: admin@trustedcomputinggroup.org

TCG Draft

DISCLAIMERS, NOTICES, AND LICENSE TERMS

THIS SPECIFICATION IS PROVIDED “AS IS” WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NONINFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY OTHERWISE ARISING OUT OF ANY PROPOSAL, SPECIFICATION OR SAMPLE.

Without limitation, TCG disclaims all liability, including liability for infringement of any proprietary rights, relating to use of information in this specification and to the implementation of this specification, and TCG disclaims all liability for cost of procurement of substitute goods or services, lost profits, loss of use, loss of data or any incidental, consequential, direct, indirect, or special damages, whether under contract, tort, warranty or otherwise, arising in any way out of use or reliance upon this specification or any information herein. This document is copyrighted by Trusted Computing Group (TCG), and no license, express or implied, is granted herein other than as follows: You may not copy or reproduce the document or distribute it to others without written permission from TCG, except that you may freely do so for the purposes of (a) examining or implementing TCG specifications or (b) developing, testing, or promoting information technology standards and best practices, so long as you distribute the document with these disclaimers, notices, and license terms. Contact the Trusted Computing Group at www.trustedcomputinggroup.org for information on specification licensing through membership agreements. Any marks and brands contained herein are the property of their respective owners.

CHANGE HISTORY

Revision	Date	Description
0.1/1	2023/12/17	Initial draft

DRAFT

DOCUMENT STYLE

Key Words

The key words “MUST,” “MUST NOT,” “REQUIRED,” “SHALL,” “SHALL NOT,” “SHOULD,” “SHOULD NOT,” “RECOMMENDED,” “MAY,” and “OPTIONAL” in this document’s normative statements are to be interpreted as described in [RFC 2119: Key words for use in RFCs to Indicate Requirement Levels](#).

Statement Type

Please note an important distinction between different sections of text throughout this document. There are two distinctive kinds of text: *informative comments* and *normative statements*. Because most of the text in this specification will be of the kind *normative statements*, the authors have informally defined it as the default and, as such, have specifically called out text of the kind *informative comment*. They have done this by flagging the beginning and end of each informative comment and highlighting its text in gray. This means that unless text is specifically marked as of the kind *informative comment*, it can be considered a *normative statement*.

EXAMPLE:

Informative comment:

This is the first paragraph of 1–n paragraphs containing text of the kind informative comment ...

This is the second paragraph of text of the kind informative comment ...

This is the nth paragraph of text of the kind informative comment ...

To understand the TCG specification, the user must read the specification. (This use of MUST does not require any action).

Contents

1	Scope and Purpose	9
2	Getting Started	10
2.1	Creating a Repository	10
2.2	GitHub Actions	10
2.3	Local Testing	12
2.4	TCG Document Boilerplate	12
2.4.1	Front Matter Variables	12
2.4.2	Backslash Macros	13
3	Collaboration Model	14
3.1	Sending a Pull Request	14
3.2	Reviewing a Pull Request	15
4	Using Markdown	17
4.1	Basic Formatting	17
4.2	Cross-References	18
4.2.1	Sections	19
4.2.2	Tables	19
4.2.3	Figures	19
4.2.4	Equations	19
4.3	TCG-Specific Blocks	19
4.3.1	Informative Text Blocks	19
4.3.2	Other Informative Blocks	20
5	Figures	22
5.1	Images	22
5.2	Mermaid Charts	22
5.2.1	Sequence Diagrams	22
5.2.2	Flow Charts	23
6	Tables	25
6.1	Markdown Tables	25
6.1.1	Simple Markdown Tables	25
6.1.2	Multiline Markdown Tables	25
6.1.3	Grid Tables	27
6.2	HTML Tables	27
7	Math	29
7.1	Equations	29
7.2	Inline math	29
7.3	Words in equations	29
8	Advanced Features	30
8.1	Git Version Parsing	30
8.1.1	Conventions for Release Naming	30
8.2	Git Status Parsing	30
8.3	Running Pandoc with Releases	30
8.4	Regular Quote Support	33
	Appendices	34

DRAFT

List of Tables

3	Shapes	25
4	Table Types	26
5	Fruits (Pipe)	27
6	Fruits (HTML)	28

DRAFT

List of Figures

1	The “Use this template” button	10
2	GitHub Collaboration Workflow	14
3	GitHub Edit Button	14
4	Propose Changes Dialog	15
5	Plus Button	16
6	Finish Review	16
7	Adding an Image	22
8	Startup Sequence	23
9	Flowchart	24

1 Scope and Purpose

The purpose of this guide is to demonstrate the usage of Markdown-plus-GitHub document-authorship flows for TCG workgroup usage.

This document contains a boilerplate section at the front called [Document Style](#). This section is typically included in TCG Specifications and isn't as relevant for Guidance and Reference documents. It's included here, mainly to demonstrate the usage of Markdown for specifications.

2 Getting Started

2.1 Creating a Repository

You can create a repository from scratch, or you can use [the template repository](#) to get started a little more quickly. There's a little green "Use this template" button in the top right (see Figure 1).




Figure 1: The "Use this template" button

2.2 GitHub Actions

Even if you used the template repository, please double-check this. As the tools are being actively developed, there is probably a newer version of the tools available for you!

`.github/workflows/main.yml` might look a bit like this:

```

# Render the spec to PDF on pull requests, and check in the rendered PDF on commits
# to main.

name: Render

on:
  push:
    branches:
      - main
  pull_request:
  workflow_dispatch:

jobs:
  render:
    runs-on: ubuntu-latest
    # This Docker container contains all the Pandoc dependencies for rendering TCG
    # Markdown docs.
    container:
      # IMPORTANT: Check https://github.com/TrustedComputingGroup/pandoc/releases
      # for the latest!
      image: ghcr.io/trustedcomputinggroup/pandoc:0.6.2
    name: Render PDF
    steps:
      - name: Checkout
        uses: actions/checkout@v3

      - name: Render
        # This GitHub action provides an easy way to use the Docker container above
        # with your document.
        # IMPORTANT: Check https://github.com/TrustedComputingGroup/markdown/releases
        # for the latest!
        uses: trustedcomputinggroup/markdown@v0.4.0
        with:
          input-md: main.md
          output-pdf: spec.pdf
          output-docx: spec.docx

      - name: Upload samples
        # This GitHub action uploads samples into the "Checks" tab (for pull requests),
        # so that reviewers can easily see how a proposed change will look in the
        # finished spec.
        uses: actions/upload-artifact@master
        with:
          name: preview
          path: |
            spec.pdf
            spec.docx

      - name: Check in latest render
        # This GitHub action automatically renders and checks-in the PDF produced in
        # the above step. This makes it easier for people to grab the latest rendered
        # version of the document.
        uses: stefanzweifel/git-auto-commit-action@v4
        with:
          commit_message: Generate latest PDF
          file_pattern: spec.pdf
          if: github.event_name != 'pull_request'

```

2.3 Local Testing

These tools have a number of dependencies on LaTeX and LaTeX plugins. The simplest way to get a consistent build is to use the docker container that gets used for the GitHub actions.

`docker_run` is provided as a convenience script for Linux systems.

Usage:

```
./docker_run --pdf=output.pdf ./input.md
```

You can specify a particular version of the docker container using the `DOCKER_IMAGE` environment variable:

```
DOCKER_IMAGE=ghcr.io/trustedcomputinggroup/pandoc:0.6.5 ./docker_run --pdf=output.pdf  
↪ ./input.md
```

If you're working on a change to these tools, it can be beneficial to build and tag a local version of the container and then run it locally:

```
docker build --tag working .  
  
DOCKER_IMAGE=working:latest ./docker_run --pdf=output.pdf ./input.md
```

2.4 TCG Document Boilerplate

There are several sections that are recommended for use in every TCG Markdown document.

The trickiest section is the YAML front matter at the very top of the Markdown file. It looks like this:

```
---  
title: "TCG Markdown User's Guide"  
version: 0.1  
revision: 1  
date: 12/17/2023  
type: GUIDANCE  
status: Draft  
...
```

This section provides metadata to the tools.

2.4.1 Front Matter Variables

2.4.1.1 title

REQUIRED.

`title` is the title of the document.

2.4.1.2 version

REQUIRED unless you're using `--gitversion`

`version` is the version of the document.

2.4.1.3 revision

OPTIONAL.

`revision` is the revision of the document. If not provided, the revision is not printed.

2.4.1.4 date

REQUIRED unless you're using `--gitversion`.

date is the full date of the document, in YYYY/MM/DD form.

2.4.1.5 type

REQUIRED.

type should be one of: "SPECIFICATION", "GUIDANCE", or "REFERENCE". It appears on the title page on the left-hand side.

2.4.1.6 status

REQUIRED unless you're using `--gitstatus`.

status should be one of: "Draft", "Review", or "Published".

If it is not "Published", then a gray watermark "DRAFT" will appear on all pages after the title page.

2.4.1.7 template

OPTIONAL.

template should be one of: greentop, bluetop. It customizes the title page style. If not provided, greentop is the current default.

Typically, specifications use the greentop template, and guidance or reference documents use the bluetop template.

2.4.2 Backslash Macros

Understanding of LaTeX is not required in order to use TCG Markdown tools. However, a few special macros can be used from Markdown to fully specify a TCG document.

2.4.2.1 Table of Contents

After the boilerplate sections, most TCG documents should set up the tables of contents, and lists of tables and figures.

```
\tableofcontents
```

```
\listoftables
```

```
\listoffigures
```

Almost every document should have a table of contents. Some documents may not need lists of tables or figures.

2.4.2.2 Appendices

At the end of the last "regular" section of the document, use

```
\beginappendices
```

to mark the transition to the "Appendix" portion of the document. Only documents that have appendices are expected to use this macro.

3 Collaboration Model

Users familiar with Git and who prefer to use their own tools may choose to skip this section.




Figure 2: GitHub Collaboration Workflow

As visualized in Figure 2, proposed changes to a GitHub Markdown repository take the form of “Pull Requests” (PRs). A *proposer* of a change proposes a PR that changes some files in the repository. This PR contains an initial *commit*, which is a unit of change to files. *Reviewers* can provide comments and suggestions on the proposed edits. The *proposer* can respond to the feedback by adding additional *commits* into their PR. When all parties are satisfied, the PR is *approved* and *merged* into the main repository.

3.1 Sending a Pull Request

When you navigate to a GitHub repository containing Markdown, you can view the Markdown files by clicking on them.

From this view, there is an “Edit” (pencil) button in the upper right-hand corner, pictured in Figure 3:




Figure 3: GitHub Edit Button

This will take you to a view where you can edit the file. There is a “Preview” button that you can use to see roughly how the changes will look when viewed from GitHub. Most everyday changes to TCG docs can be previewed in high enough fidelity with this tool.

When you’re satisfied with your changes, use the green “Commit changes...” button. This will bring up the dialog box pictured in Figure 4:


A screenshot of a 'Propose changes' dialog box. It has a title bar with a close button (X). The dialog is divided into sections: 'Commit message' with a text input field containing 'Update "Sending a Pull Request"'; 'Extended description' with a larger text area containing 'The "Sending a Pull Request" section contains several typos. This change fixes them, and introduces some helpful diagrams to reinforce the concepts.'; 'Commit Email' with a dropdown menu showing 'cfenn@google.com'; and two radio button options: 'Commit directly to the main branch' (unselected) and 'Create a new branch for this commit and start a pull request' (selected). Below the second option is a link 'Learn more about pull requests'. At the bottom is a text input field for a branch name containing 'fix-sending-pull-request' with a branch icon on the left. At the very bottom are two buttons: 'Cancel' and 'Propose changes'.

Figure 4: Propose Changes Dialog

Include a descriptive commit message, extended description, and new branch name for your change, then click the green “Propose changes” button.

You’re almost done! This will take you to a page called “Open a pull request”. You can provide some additional context to reviewers about why you want to make this change. When you’re satisfied, click “Create pull request.”

3.2 Reviewing a Pull Request

After a PR has been sent by someone else, you can review the changes with the “Add your review” button in the upper right-hand corner of the change description page.

This button takes you to a review flow, where you can provide comments on individual lines of the changes. You can leave a comment on an individual line by mousing over the line and clicking the blue “+” button, which looks like Figure 5:




Figure 5: Plus Button

After you’ve gone through all the changed files and provided your comments, you can click “Review changes” to finish the review. This dialog looks like Figure 6:

Figure 6: Finish Review

Here, you can provide summary comments and mark your review as one of:

- Comment (Just providing feedback)
- Approve (Approving the changes)
- Request changes (Explicitly not approving the changes, with specific actionable feedback)

4 Using Markdown

Markdown is intended to be a lightweight language for authoring documents. Most of the time, it looks exactly the same as plain text.

4.1 Basic Formatting

The structure of the document is guided by lines that begin with #:

```
# Section Titles  
## Subsection Titles  
### Sub-subsection Titles
```

and so on.

When you put `*asterisks*` around a word, it renders as *italics*.

When you put `**double asterisks**` around a word, it renders as **boldface**.

When you put ``backticks`` around a word, it renders as monospace.

To force a new page, use `---`. This will appear as a horizontal line in GitHub and a page break in the PDF.

When you need to write math, use `$` dollar signs `$` for inline math notation, or `$$` double dollar signs `$$` for equations. This is explained in more detail in [Clause 7](#).

Numbered and bulleted lists begin with numbers and asterisks:

```
* Something
* Something else

1. First thing
2. Second thing
```

Becomes:

- Something
 - Something else
1. First thing
 2. Second thing

Hyperlink syntax for the [TCG Website](https://trustedcomputinggroup.org) looks like: `[TCG Website](https://trustedcomputinggroup.org)`.

Hyperlink syntax for the [Using Markdown](#) section looks like: `[Using Markdown](#using-markdown)`. If you provided a stable cross-referencing link like this document for [Cross-References](#), you can use it like: `[Cross-References](#sec:cross-references)`.

You can use triple backticks like so to create blocks of code:

```
```
int i = 42;
```
```

The result looks like this:

```
int i = 42;
```

You can tell Markdown what language the code is in, to get syntax highlighting:

```
```c
// Awesome!
int i = 42;
```
```

The result looks like this:

```
// Awesome!
int i = 42;
```

4.2 Cross-References

In general, sections, tables, figures, and equations can be referenced using the `@` symbol. These cross-references do not show up in the GitHub markdown, but will appear in the final document.

4.2.1 Sections

When you add `{#sec:section-reference}` at the end of a section title, as in:

```
## Cross-References {#sec:cross-references}
```

it creates a cross-reference that you can use with `@sec:section-reference`. For example, `@sec:cross-references Clause 4.2`.

4.2.2 Tables

See [Clause 6](#) for more information about cross-references to tables.

4.2.3 Figures

See [Clause 5](#) for more information about cross-references to figures.

4.2.4 Equations

See [Clause 7](#) for more information about cross-references to equations.

4.3 TCG-Specific Blocks

4.3.1 Informative Text Blocks

TCG uses a special visual style to demarcate informative non-binding remarks within specifications.

To create an informative note, use the following syntax:

```
> This is the only informative text block in this document.
>
> These blocks can contain multiple paragraphs, tied together by lines containing just
> ">".
>
> These blocks can even contain tables! However, be wary of providing tables that are
> too large in an Informative Text block.
>
**Document Type**	**Informative Blocks**
> | SPECIFICATION | Usually |
> | GUIDANCE | Rarely |
> | REFERENCE | Rarely |
```

The above Markdown code becomes:

Informative comment:

This is the only informative text block in this document.

These blocks can contain multiple paragraphs, tied together by lines containing just “>”.

These blocks can even contain tables! However, be wary of providing tables that are too large in an Informative Text block.

| Document Type | Informative Blocks |
|---------------|--------------------|
| SPECIFICATION | Usually |
| GUIDANCE | Rarely |
| REFERENCE | Rarely |

4.3.1.1 Alternative Syntax for Informative Text

```
::: Informative :::  
Pandoc calls this a  
["fenced div"](https://pandoc.org/chunkedhtml-demo/8.18-divs-and-spans.html).  
::::::::::::::::::::
```

Informative comment:

Pandoc calls this a “fenced div”.

In addition to “Informative”, the following other types of notes are supported:

4.3.2 Other Informative Blocks

Warning:

These types of blocks are supported by the toolset, but not yet approved by TCG Marketing WG.

Writers of a document may prefer more compact “informative” blocks with more obvious semantics, like the warning above. In this case, the text is still contained within a “TCG Informative” gray box, but with a more meaningful header and no footer.

- Note
- Example
- Caveat
- Tip
- Warning

Note:

This is a “Note” block.

Example:

This is an “Example” block.

Caveat:

This is a “Caveat” block.

Tip:

This is a “Tip” block.

Warning:

This is a “Warning” block.

The behavior of blocks with labels not specified above may change meaningfully in future versions of this toolkit, so use them at your own risk.

5 Figures

There are two ways to include a figure in a document: as an image file checked into the repository, and as a [Mermaid](#) diagram.

5.1 Images

Upload plain image files into the repository with the “Add file” button.

For compatibility reasons, all image files should be in the root of the repository (main directory). In the future, better support for organizing figures may be added to these tools.

See [Clause 3.1](#) for the flow that needs to be followed for getting your image uploads reviewed. You can add more changes to the branch for the PR that reference the image, or you can do it in a subsequent PR.

Markdown syntax for including an image looks like `![Figure Title](filename)`. For example:

```
![Adding an Image](add_plus_button.jpg){#fig:add-plus-button width=60%}
```

becomes:




Figure 7: Adding an Image

The `{#fig:add-plus-button}` attribute (note there are no spaces between the `)` and the `{!}`) does two things:

1. Includes the figure in the List of Figures (if you used `\listoffigures` as described in [Clause 2.4.2.1](#)).
2. Numbers the figure so you can reference it as [Figure 7](#) by just typing `@fig:add-plus-button`.

Including `width=60%` here specifies that the image should take up 60% of the page's width.

5.2 Mermaid Charts

[Mermaid](#) is a language for text-based diagrams for inclusion in Markdown documents. See the Mermaid website for a more exhaustive list of types of diagrams.

5.2.1 Sequence Diagrams

Mermaid supports swim-lane digrams like [Figure 8](#) with the following notation:

```

```mermaid {caption="Startup Sequence" #fig:startup}
sequenceDiagram
Host->>TPM: TPM2_Startup
loop Measurements
 Host->>TPM: TPM2_PCR_Extend
end
Host->>TPM: TPM2_Quote
TPM->>Host: <quoted PCRs>
```

```




Figure 8: Startup Sequence

Crossreferences to Mermaid diagrams are supported by providing both caption and #fig:xxxxx classes in curly braces.

5.2.2 Flow Charts

Mermaid supports flow-charts like Figure 9 with the following notation:

```

```mermaid {caption="Flowchart" #fig:flowchart}
graph TD;
 A-->B;
 A-->C;
 B-->D;
 C-->D;
```

```




Figure 9: Flowchart

6 Tables

We support several notation styles for tables.

6.1 Markdown Tables

There are several ways to write a table in Markdown.

6.1.1 Simple Markdown Tables

Small, simple tables like Table 3 are easier to read in raw Markdown form in the following style:

Table: Shapes {#tbl:shapes}

| Shape | Number of sides |
|--------------|------------------------|
| Square | 4 |
| Triangle | 3 |
| Möbius strip | 1 |

Table 3: Shapes

| Shape | Number of sides |
|--------------|-----------------|
| Square | 4 |
| Triangle | 3 |
| Möbius strip | 1 |

Note the table caption and cross-reference in curly braces above the table.

6.1.2 Multiline Markdown Tables

Sometimes, you may need to write a lot of Markdown content in the cell of a table, and this content may need multiple lines in your editor.

Table: Table Types {#tbl:table-types}

| **Table Kind** | **Easy?** | **Recommended?** | **References** |
|---------------------------|------------------|--|--|
| Simple Markdown Tables | Yes | When each cell is about one word or so. | @sec:simple-markdown-tables, @tbl:shapes |
| Multiline Markdown Tables | Yes | When you have content that's more than a few words. | @sec:multiline-markdown-tables, @tbl:table-types |
| Grid Markdown Tables | No | When you have row or column spans and need full Markdown support (e.g., crossrefs or equations). | @sec:grid-tables, @tbl:fruits-grid |
| HTML Tables | Yes | When you have row or column spans, and don't need full Markdown or don't mind doing all the styling in HTML. | @sec:html-tables, @tbl:fruits-html |

Table 4: Table Types

| Table Kind | Easy? | Recommended? | References |
|---------------------------|--------------|--|--|
| Simple Markdown Tables | Yes | When each cell is about one word or so. | Clause 6.1.1 , Table 3 |
| Multiline Markdown Tables | Yes | When you have content that's more than a few words. | Clause 6.1.2 , Table 4 |
| Grid Markdown Tables | No | When you have row or column spans and need full Markdown support (e.g., crossrefs or equations). | Clause 6.1.3 , Table 5 |
| HTML Tables | Yes | When you have row or column spans, and don't need full Markdown or don't mind doing all the styling in HTML. | Clause 6.2 , Table 6 |

6.1.3 Grid Tables

You may have some data that needs to be presented in a table that allows you to make cells span rows or columns. Grid tables like Table 5 can be used for this. Note that editing these tables requires a bit more typing. It's recommended to use these only when you need row and column spanning.

Some tools provide assistance for generating tables of this type. If you find a tool that is handy for editing Mark-down grid-style tables, please send a PR to github.com/trustedcomputinggroup/pandoc!

Table: Fruits (Pipe) {#tbl:fruits-grid}

| **Color and Fruit** | | **Mistaken for Vegetable** | |
|---------------------|--------|----------------------------|--|
| Apple | Red | No | |
| | Green | No | |
| Tomato | Red | Yes | |
| Banana | Yellow | No | |

Table 5: Fruits (Pipe)

| Color and Fruit | | Mistaken for Vegetable | |
|-----------------|--------|------------------------|--|
| Apple | Red | No | |
| | Green | No | |
| Tomato | Red | Yes | |
| Banana | Yellow | No | |

6.2 HTML Tables

A rowspan/colspan table like Table 5 can be implemented in HTML like the below. Note that this is a little easier to type, and a little harder to read in plain-text form. We recommend preferring [grid tables](#) to HTML tables, but HTML tables can be fine in certain situations (for example, a gradual migration away from a Word document using Pandoc, which typically converts Word tables into HTML).

```

<table id="tbl:fruits-html">
  <caption>Fruits (HTML)</caption>
  <tr>
    <th colspan="2"><strong>Color and Fruit</strong></th>
    <th><strong>Mistaken for Vegetable</strong></th>
  </tr>
  <tr>
    <td rowspan="2">Apple</td>
    <td>Red</td>
    <td>No</td>
  </tr>
  <tr>
    <td>Green</td>
    <td>No</td>
  </tr>
  <tr>
    <td>Tomato</td>
    <td>Red</td>
    <td>Yes</td>
  </tr>
  <tr>
    <td>Banana</td>
    <td>Yellow</td>
    <td>No</td>
  </tr>
</table>

```

The above HTML table becomes the below:

Table 6: Fruits (HTML)

| Color
and
Fruit | Mistaken for Vegetable | |
|-----------------------|------------------------|-----|
| | | |
| Apple | Red | No |
| | Green | No |
| Tomato | Red | Yes |
| Banana | Yellow | No |

Note the table caption in the <caption> element, and the table cross-reference in the id attribute of the <table> element.

To get an HTML table to word-wrap its contents, use <colgroup> to style the width of the columns.

```

<colgroup>
<col style="width: 25%" />
<col style="width: 75%" />
</colgroup>

```

7 Math

7.1 Equations

Markdown supports inline math notation. For example, Equation 1 can be typeset as:

$$\nexists n \geq 3; a, b, c \in \mathbb{Z} \mid a^n + b^n = c^n \quad \{\#eq:fermat\}$$

Note the `{#eq:fermat}` at the end of the equation. This allows referencing Equation 1 with `@eq:fermat`.

$$\nexists n \geq 3; a, b, c \in \mathbb{Z} \mid a^n + b^n = c^n \quad (1)$$

7.2 Inline math

Sometimes, you just need a little inline math in the middle of a sentence, like with $a^2 + b^2 = c^2$ to get $a^2 + b^2 = c^2$.

7.3 Words in equations

To typeset complex equations with multi-character identifiers (such as the function “HMAC” or the word “OPAD”) in Equation 2, we recommend using the functions `\mathbf{f}` (for functions) and `\mathit{i}` (for identifiers). This avoids strange kerning issues where a string is treated as a product of single-character symbols, like in Equation 3:

$$\mathbf{HMAC}(K, \text{someTEXT}) \coloneq H((\bar{K} \oplus \text{OPAD}) \mathbin{\text{Vert}} H((\bar{K} \oplus \text{IPAD}) \mathbin{\text{Vert}} \text{someTEXT}))$$

$\$ \{ \#eq:hmac-iso \}$

$$\mathbf{HMAC}(K, \text{someTEXT}) := H((\bar{K} \oplus \text{OPAD}) \| H((\bar{K} \oplus \text{IPAD}) \| \text{someTEXT})) \quad (2)$$

$$\begin{aligned} & \text{\$} \text{\$} \text{ HMAC}(K, \text{someTEXT}) \text{\textbackslash coloneq} H((\text{\textbackslash bar}\{K\} \text{\textbackslash oplus} 0\text{PAD}) \text{\textbackslash Vert} H((\text{\textbackslash bar}\{K\} \text{\textbackslash oplus} \text{IPAD}) \\ & \text{\textbackslash Vert someTEXT)) \text{\$} \text{\$} \text{\textbackslash #eq:hmac-iso-bad-kerning} \end{aligned}$$

$$HMAC(K, someTEXT) := H((\bar{K} \oplus OPAD) \| H((\bar{K} \oplus IPAD) \| someTEXT)) \quad (3)$$

8 Advanced Features

In the GitHub action YAML, you can enable some advanced features.

8.1 Git Version Parsing

Use extra-build-options: "--gitversion" to let Git number the document for you.

```
- name: Run the action
  uses: trustedcomputinggroup/markdown@latest
  with:
    extra-build-options: "--gitversion"
```

When you do this, the tool will check for a recent [release](#) in the repository. It will use the major.minor version number from the tag as the document version, and the number of commits since that tag as the revision. This way, you don't have to manually update the version or revision numbers in your document!

8.1.1 Conventions for Release Naming

The tooling expects the following conventions for tagging your releases:

- vX.Y indicates a regular draft of version X.Y.
- rX.Y indicates a review draft of version X.Y.
- pX.Y indicates a published version.

8.2 Git Status Parsing

Use extra-build-options: "--gitstatus" to let Git number AND set the status of the document for you.

```
- name: Run the action
  uses: trustedcomputinggroup/markdown@latest
  with:
    extra-build-options: "--gitstatus"
```

See [Conventions](#). When --gitstatus is enabled, the leading character (which is expected to be one of: v, r, or p) is used to determine the document's status at revision 0. Commits on top of any type of version are always considered to be drafts.

8.3 Running Pandoc with Releases

Clause [2.2](#) shows an example of a GitHub action that automatically runs Pandoc on every pull request and push to the repository.

You may wish to run the workflow on releases, and attach the results to the release page, for example to have it generate a docx file to send to the Technical Committee for review, or when publishing a final version of a document.

Use the example below as a guide for how you can have Pandoc automatically render the doc (maybe basing its [status](#) on the released tag).

DRAFT

```

# Render the spec to PDF and Word on releases.

name: Render (PDF and Word)

on:
  release:
    types: [released]

jobs:
  render-spec-pdf:
    runs-on: ubuntu-latest
    container:
      image: ghcr.io/trustedcomputinggroup/pandoc:0.7.1
    name: Render (pdf)
    steps:
      - name: Checkout
        uses: actions/checkout@v3

      - name: Render
        uses: trustedcomputinggroup/markdown@v0.4.2
        with:
          input-md: spec.md
          extra-build-options: "--gitstatus"
          output-pdf: spec.pdf

      - name: Upload to release
        uses: svenstaro/upload-release-action@v2
        with:
          repo_token: ${ secrets.GITHUB_TOKEN }
          file: spec.pdf
          tag: ${ github.ref }
          overwrite: true
          body: "Part 1 (PDF)"

  render-spec-docx:
    runs-on: ubuntu-latest
    container:
      image: ghcr.io/trustedcomputinggroup/pandoc:0.6.8
    name: Render Part 1 (docx)
    steps:
      - name: Checkout
        uses: actions/checkout@v3

      - name: Render
        uses: trustedcomputinggroup/markdown@v0.4.2
        with:
          input-md: spec.md
          extra-build-options: "--gitstatus"
          output-docx: spec.docx

      - name: Upload to release
        uses: svenstaro/upload-release-action@v2
        with:
          repo_token: ${ secrets.GITHUB_TOKEN }
          file: spec.docx
          tag: ${ github.ref }
          overwrite: true
          body: "Part 1 (Word)"

```


8.4 Regular Quote Support

Use extra-build-options: "--plain_quotes" to disable the automatic conversion of block-quotes into TCG Informative Text blocks (see Clause [4.3.1.1](#)). If you use this feature, block-quotes will look like the below:

I'm a block quote!

Look at me!

Instead of like the below:

Informative comment:

I'm a block quote!

Look at me!

Appendices

DRAFT

A Reporting Issues with the Tools

Please report issues with the tooling at <https://github.com/TrustedComputingGroup/pandoc/issues>.

DRAFT