

Trusted Agentic Commerce: Installation Guide

Installation Guide: Trusted Agentic Commerce for Magento 2

Version 1.3.4 · Magento Open Source & Adobe Commerce 2.4.7 / 2.4.8 · PHP 8.2+

Table of contents

1. [System requirements](#)
 2. [Pre-installation checklist](#)
 3. [Installation via Composer](#)
 4. [Manual installation](#)
 5. [Post-installation setup](#)
 6. [Connecting to Trusted](#)
 7. [Verifying the installation](#)
 8. [Cron configuration](#)
 9. [Upgrade instructions](#)
 10. [Uninstallation](#)
 11. [Troubleshooting](#)
-

1. System requirements

Component	Minimum	Recommended
Magento Open Source	2.4.7	2.4.8
Adobe Commerce	2.4.7	2.4.8
PHP	8.2	8.3
PHP extensions	<code>curl</code> , <code>json</code> , <code>openssl</code> , <code>sodium</code>	same
MySQL / MariaDB	8.0 / 10.6	MySQL 8.0
Composer	2.x	2.7+
Cron	Required	n/a

`ext-sodium` is required. It performs the Ed25519 checks behind agent token verification and enforcement-snapshot verification. Without it both verifications return `indeterminate`. The connector cannot establish agent identity, so it never confirms an agent as verified. The module does **not** ship a pure-PHP fallback: `paragonie/sodium_compat` is not a declared dependency, so the compat branch in the code is never reachable in a normal install. `ext-sodium` is bundled and enabled by default in virtually all PHP 8.2+ builds.

2. Pre-installation checklist

Before installing, confirm:

- ☐ You have a Trusted account at trusted.xyz/dashboard
- ☐ Magento cron is running (`bin/magento cron:run` completes without errors)
- ☐ Your Magento project can authenticate against `repo.magento.com` (public key / private key), or you are installing from the `.zip` manually
- ☐ Magento is in maintenance mode during initial installation on production:

```
bin/magento maintenance:enable
```

- ☐ A full database backup has been made

3. Installation via Composer

3.1 Confirm your Magento repository authentication

This module is **not** distributed through the Magento Marketplace, so it needs no Marketplace credentials of its own. You only need `repo.magento.com` authentication if your Magento project already pulls its own packages from there, which it normally does:

```
composer config http-basic.repo.magento.com <PUBLIC_KEY> <PRIVATE_KEY>
```

3.2 Require the package

This package is **not published on Packagist yet**, so Composer must be pointed at the GitHub repository first. Add the following to the `composer.json` of your Magento project, merging it with any `repositories` entries you already have:

```
{
  "repositories": [
    { "type": "vcs", "url": "https://github.com/Trusteedxyz/agentic-commerce-magento" }
  ]
}
```

Only then will the `require` resolve:

```
composer require trusteeed/agentic-commerce-magento:^1.2
```

3.3 Enable the module

```
bin/magento module:enable Trusteed_AgenticCommerce
```

3.4 Run setup upgrade

```
bin/magento setup:upgrade
```

This creates the `trusteed_webhook_outbox` database table and adds the `trusteed_receipt_uri` / `trusteed_receipt_status` columns to `sales_order`.

3.5 Compile dependency injection

```
bin/magento setup:di:compile
```

3.6 Deploy static content (production only)

```
bin/magento setup:static-content:deploy -f
```

3.7 Clear caches

```
bin/magento cache:flush  
bin/magento cache:clean
```

3.8 Disable maintenance mode

```
bin/magento maintenance:disable
```

4. Manual installation

Use this method if you would rather not add a Composer repository entry. Download the installable `.zip` from the [latest GitHub Release](#). The attached asset is named `trusted-agentic-commerce-magento-<version>.zip`.

4.1 Extract the archive

```
unzip trusted-agentic-commerce-magento-1.3.4.zip -d /tmp/trusted-module
```

4.2 Copy files into Magento

```
mkdir -p <MAGENTO_ROOT>/app/code/Trusted/AgenticCommerce  
cp -r /tmp/trusted-module/* <MAGENTO_ROOT>/app/code/Trusted/AgenticCommerce/
```

4.3 Continue from step 3.3

Follow steps 3.3 through 3.8 above.

5. Post-installation setup

After installation the **Trusted** menu appears in the Magento admin sidebar (below **Stores**).

5.1 Open the Setup Wizard

Navigate to **Trusted** → **Configuración** (Setup Wizard).

The wizard presents four sections:

Section	Purpose
Conecta tu tienda con Trusteed	Connects the store. Start here (see §6)
¿Qué tiendas quieres activar?	Store views exposed to agents (§5.2)
Checkout Enforcement (CEL)	Enforcement credentials and fail-mode (see §6.4)
Internal HMAC Secret	Signs internal heartbeat calls to the Trusteed API (§5.3)

There is nothing to copy by hand to connect the store. The Merchant ID, integration token and webhook secret are filled in by the wizard itself during the connection (§6). If you go looking for those fields in the form you will not find them: they are hidden on purpose.

5.2 Configure store views

Under **¿Qué tiendas quieres activar?** select the store views you want to expose to AI agents. Agents can only browse and purchase in enabled store views.

5.3 Internal HMAC Secret (only if Trusteed gave you one)

The HMAC secret signs internal API calls (`X-Trusteed-Signature` header, together with `X-Trusteed-Connection-Id` and `X-Trusteed-Timestamp`). **It is not self-serve and does not appear anywhere in the dashboard:** Trusteed provisions it and only hands it to the accounts that need it.

If you were not given one, **leave the field empty and carry on**. The install works without it. If you were, paste it into **Internal HMAC Secret** and click **Guardar**.

6. Connecting to Trusteed

Connecting is a popup authorization flow, like "sign in with...". **No credential is pasted by hand.**

6.1 Prerequisite: a Trusteed account

You need an account at trusteed.xyz. Create one before continuing: the popup in the next step will ask you to sign in.

6.2 Click "Conectar con Trusteed →"

In the Setup Wizard (**Trusteed → Configuración**), click **Conectar con Trusteed →**. What happens:

1. A popup opens to `trusteed.xyz/connect/magento`.

2. You sign in and authorize this store.
3. The popup closes and hands the wizard a **single-use token** together with your Merchant ID.
4. The wizard saves the form, and **your Magento server** exchanges that token for the real credentials (Connection ID, webhook secret, embed secret). The token is never stored. It only lives for the duration of that exchange.

If your browser blocks popups, allow them for your back-office domain and click the button again.

6.3 Confirm it worked

After saving you will see "**Trusted configuration saved successfully**". Under **Stores → Configuration → Trusted → Agentic Commerce** the **Connection ID** field will no longer be empty. That is the reliable indicator that the connection completed.

Do not hand-edit the Integration Token or Webhook Secret on that screen after connecting. The backend keeps its own copy of the secrets issued during the exchange; overwriting them locally breaks webhook signatures with no warning. To rotate them, click **Conectar con Trusted →** again.

6.4 Enabling checkout enforcement (a separate step)

Connecting the store **does not enable checkout enforcement**. That module needs two more credentials, provisioned separately by Trusted:

Wizard field	Config path
Enforcement Installation ID	<code>trusted/enforcement/installation_id</code>
Enforcement HMAC Secret	<code>trusted/enforcement/hmac_secret</code>

While the **Installation ID** is empty, `EnforcementClient` lets every checkout through without evaluating a single rule. That is deliberate (a half-configured store must not block sales), but it means **you are not protected yet**. The module keeps an admin notice up until both values are set.

If you want enforcement, ask Trusted for those two credentials, paste them into the wizard and save. If you do not need it, you can leave the notice: the rest of the module works.

7. Verifying the installation

7.1 Check module status

```
bin/magento module:status Trusted_AgenticCommerce
# Expected: Module is enabled
```

7.2 Verify database tables

Magento 2 has no schema-validation command (`doctrine:schema:validate` belongs to Doctrine, not Magento). Check the objects directly:

```
mysql -u <user> -p <dbname> -e "DESCRIBE trusted_webhook_outbox;"
mysql -u <user> -p <dbname> -e "SHOW COLUMNS FROM sales_order LIKE 'trusted_%';"
```

7.3 Verify the MCP manifest endpoint

```
curl -sf https://<YOUR_STORE>/well-known/mcp.json
# Should return a JSON manifest whose top-level keys include schema_version,
# issuer, merchant_id, store_views, capabilities and signature
```

Or let the module check it for you, including the webserver rewrite:

```
bin/magento trusted:check-webserver
```

There is no `/trusted/...` frontend route: the module's frontend `frontName` is `nlweb`, and `/well-known/mcp.json` is served by a dedicated router rather than through a `frontName` at all.

7.4 Check the admin dashboard

Navigate to **Trusted** → **Inicio**. The dashboard should show:

- Green "Your store is connected" banner
- Store ID matching your Trusted account
- Count of active store views

7.5 Verify cron jobs

```
bin/magento cron:run --group=default
# In system log: look for "trusted_webhook_drain" and "trusted_lag_heartbeat"
grep trusted var/log/cron.log
```

8. Cron configuration

The module registers two cron jobs in the `default` group:

Job	Schedule	Purpose
<code>trusted_webhook_drain</code>	Every minute	Delivers pending webhooks from the outbox to the Trusted API with exponential backoff
<code>trusted_lag_heartbeat</code>	Every minute	Emits a lag metric so the Trusted dashboard can alert on delivery delays

Cron is required. Without it, order events (created, shipped, refunded) will accumulate in the `trusted_webhook_outbox` table and never be delivered.

Verify Magento cron is scheduled in your server's crontab:

```
* * * * * php /var/www/html/bin/magento cron:run 2>&1 | grep -v "^$" >> /var/www/html/var/log/magento.cron.log
```

For Magento Cloud (Adobe Commerce Cloud), cron is managed by the platform and requires no additional configuration.

9. Upgrade instructions

From a previous 1.x version

```
composer update trusted/agentic-commerce-magento
bin/magento setup:upgrade
bin/magento setup:di:compile
bin/magento cache:flush
```

Check the changelog in this package for configuration changes between versions.

10. Uninstallation

10.1 Disable the module

```
bin/magento module:disable Trusted_AgenticCommerce
bin/magento setup:upgrade
```

10.2 Remove the package

```
composer remove trusted/agentic-commerce-magento
```

10.3 Remove database objects (optional)

Only do this if you want to permanently remove all data:

```
-- Drop outbox table
DROP TABLE IF EXISTS trusted_webhook_outbox;

-- Remove columns from sales_order
ALTER TABLE sales_order
  DROP COLUMN IF EXISTS trusted_receipt_uri,
  DROP COLUMN IF EXISTS trusted_receipt_status;
```

10.4 Clean up configuration

```
DELETE FROM core_config_data
  WHERE path LIKE 'trusted_general/%' OR path LIKE 'trusted/%';
```

```
bin/magento cache:flush
```

11. Troubleshooting

Module is not visible in the admin menu

```
bin/magento module:status Trusted_AgenticCommerce
bin/magento setup:upgrade
bin/magento cache:flush
```

"Store is not connected" after entering credentials

1. Verify `API Base URL` is `https://api.trusted.xyz` (HTTPS required)
2. Check that your server can reach the Trusted API:

```
curl -sf https://api.trusted.xyz/api/v1/health
```

3. Verify the Integration Token is correct (no trailing spaces)
4. Check `var/log/system.log` for `[trusted]` entries

Webhook outbox accumulating entries

```
# Check outbox depth
mysql -u <user> -p <dbname> -e "SELECT status, COUNT(*) FROM trusted_webhook_outbox GROUP BY status;"

# Confirm cron is running
bin/magento cron:run --group=default
grep trusted_webhook var/log/cron.log
```

`ext-sodium` not available

Install via your package manager:

```
# Ubuntu / Debian
sudo apt-get install php8.2-sodium

# CentOS / RHEL
sudo dnf install php-sodium

# After installing, restart PHP-FPM
sudo systemctl restart php8.2-fpm
```

There is no fallback: `paragonie/sodium_compat` is not a declared dependency of this module, so `ext-sodium` must be present. Until it is, agent token verification and enforcement-snapshot verification both return `indeterminate` and no agent is ever confirmed as verified. Confirm it is loaded with:

```
php -m | grep -i sodium
```

Orders not appearing in the Trusted dashboard

Confirm the `sales_order_save_after` observer is registered:

```
bin/magento dev:di:info Trusted\\AgenticCommerce\\Observer\\SalesOrderSaveAfter
```

And check `var/log/system.log` for `[trusted] outbox enqueue` entries after placing a test order.