C8 Enterprise Wallet

> Docker-compose deployment

Main features

- **Any Token Standard supported** - only need to enable new ones on our backend (let us know which do you use, please);
- **PreApproval** for incoming Token Standard transactions (1-step transfer);
- Automated **UTXO management**;
- **Auto-batching** (in-memory/PostgresSQL);
- **USDC Bridge** support;
- Keycloak/Auth0 API auth supported (but optional);

Self-Custodian

You have to generate mnemonic phrase and set it up during the deployment.

> ⚠️ C8 team won't be able to help you recover accounts/funds if mnemonic phrase is lost

Deployment

1. Generate random BIP39 mnemonic phrase (24 words)

   There are hundreds of ways to produce it. For example, via npm:

   ```
   npm install -g bip39
   bip39 generate --words=24
   ```

   or with bitcoin-cli (via brew, for instance):

```
brew install bitcoin
bitcoin-cli mnemonic new 24
```

2. set your .env file

```
WALLET_MNEMONIC={mnemonic}
CLIENT_ID={client_id}
BACKEND_URL=https://wallet-backend.main.digik.cantor8.tech/api
AUTH_TYPE=noop
AUTO_BATCH_SWITCH=false
AUTO_BATCH_DB_TYPE=in-memory
```

⚠️ `AUTH_TYPE=noop` switches wallet API's auth off, so all its APIs are exposed with no auth.

💡 If you want to use your Keycloak/Auth0 IdP to authenticate all API endpoints - C8 team will let you know how to configure it via envs. Connecting IdP would mean that all C8 Enterprise Wallet APIs will expect a valid JWT token from an IdP.

3. Deploy with Docker Compose

```
AWS_REGION=eu-west-1 \
CLOUDWATCH_LOG_GROUP=enterprise-wallet \
CLOUDWATCH_LOG_STREAM={client_id} \
CLOUDWATCH_ENDPOINT=https://logs.eu-west-1.amazonaws.com \
AWS_ACCESS_KEY_ID={access_key_id} \
AWS_SECRET_ACCESS_KEY={secret_access_key} \
docker compose -f docker-compose-client.yml up --force-rec
reate
```

Once deployed, you can visit `http://<host>:8080/docs` for Swagger UI and experiment right there. Similar docs are placed on `https://cantor8.github.io/wallet-api/`