

The linux distribution should be generated as an iso.

If your custom Linux distribution (for your “database OS” / TruthDB appliance) should be delivered as an **ISO image**, then the solution is straightforward — but the *right* approach depends heavily on how much you want to automate, and how minimal/custom the system must be.

Below is a clean, precise breakdown of the *correct modern ways* to generate a bootable ISO for a custom Linux-based distribution.

---

## ✓ Three Correct Paths to Generate a Linux ISO

You have **three viable approaches**, depending on how much control you want.

---

### 1. Build an ISO using NixOS (recommended for a tiny custom DB OS)

This is by far the most robust way to produce consistent, reproducible ISO images.

#### Why NixOS?

- You describe the whole OS in one file ( `configuration.nix` )
- You get *deterministic builds*
- Output is directly an **ISO**
- No surprises with package versions
- Perfect for “database OS”, appliances, etc.

#### Example

```
bash
```

[✎ Copy code](#)

```
nix-build '<nixpkgs/nixos>' \  
  -A config.system.build.isoImage \  
  --arg configuration ./my-config.nix
```

This produces something like:

[✎ Copy code](#)

```
bash
```

```
result/iso/nixos-mydbos-x86_64-linux.iso
```

### You can:

- Remove everything you don't want (systemd remains)
- Add your services (e.g. your database service)
- Add your kernel parameters
- Add your own init scripts
- Include your WAL daemon, networking config, and files.

This is the cleanest and the most future-proof.

---

## 2. Use Debian/Ubuntu live-build (good if you want a Debian-like system)

Debian has an official tool called `live-build` that builds a full ISO from a config directory.

### Steps

```
bash
```

 Copy code

```
apt install live-build
lb config
lb build
```

### Output:

```
arduino
```

 Copy code

```
live-image-amd64.hybrid.iso
```

### You control:

- packages included
- kernel
- services
- custom systemd units
- your database + WAL setup
- persistent storage

This is closest to how "real" distros generate ISOs.

---

## 3. Manually produce an ISO using `xorriso` (good for full control)

Here you build a root filesystem in a directory, chroot into it, install everything manually, then make an ISO.

### Steps Overview

#### 1. Make a rootfs

bash

 Copy code

```
debootstrap stable ./rootfs \  
    http://deb.debian.org/debian
```

#### 2. Chroot and customize

- install your kernel
- install systemd
- install your DB
- install your services
- add your WAL
- add your initramfs

#### 3. Generate the ISO

bash

 Copy code

```
xorriso -as mkisofs \  
    -o output.iso \  
    -isohybrid-mbr /usr/lib/ISOLINUX/isohdpx.bin \  
    -c isolinux/boot.cat \  
    -b isolinux/isolinux.bin \  
    -no-emul-boot \  
    -boot-load-size 4 \  
    -boot-info-table \  
    rootfs/
```

This gives *100% control* but is the most work.

---

## ✓ Given your project and preferences

You want:

- systemd-based
- minimal
- deterministic
- easy to rebuild
- easy to add your DB daemon and WAL
- ISO output

→ NixOS ISO builds are your best tool.

Your OS becomes nothing more than a declarative file:

mydbos.nix :

nix

 Copy code

```
{
  imports = [ <nixpkgs/nixos/modules/installer/cd-dvd/installation-cd-mini>

  boot.loader.systemd-boot.enable = true;

  services.my_db_service = {
    enable = true;
    package = pkgs.callPackage ./mydb {};
  };

  # Kernel, filesystems, ssh, networking etc...
}
```

Then:

bash

 Copy code

```
nix-build '<nixpkgs/nixos>' -A config.system.build.isoImage --arg configur
```

Done.

## ✓ Summary: Best Option for Your "TruthDB OS"

| Method               | Complexity | Reproducibility | Suitability for Custom DB OS |
|----------------------|------------|-----------------|------------------------------|
| NixOS ISO generation | Low        | ★★★★★           | ★★★★★                        |
| Debian live-build    | Medium     | ★★★★☆☆          | ★★★★☆☆                       |
| Manual xorriso build | High       | ★★☆☆☆☆          | ★★★★☆☆                       |

You want **repeatable ISO builds and a tiny distro** → **choose NixOS**.

If you want, I can produce for you:

- A **complete working NixOS config** for your DB OS
- Your DB service packaged as a Nix derivation
- A reproducible build script
- A CI workflow that outputs a new ISO for every commit

Just say **“generate the full NixOS config”** or **“show me the db service derivation”** and I’ll write it.



It should be automated. Maybe the main truthdb repo's releases will be the iso?

Thought for 23s >

Yeah, that’s a totally sensible way to do it: **tag = version, release = ISO**. Let’s nail down what that actually looks like in practice.

I’ll assume:

- You use **Nix** to build the OS ISO (still the cleanest option).
- You use **GitHub + self-hosted Linux runners** (which you already have).

### 1. Repo layout: where does the ISO live?

You’ve basically got two sane patterns:

## Option A – ISO from the main TruthDB repo (what you suggested)

Single repo, e.g.:

text

 Copy code

```
truthdb/  
  crates/  
    truthdb-core/  
    truthdb-wal/  
    ...  
  os/  
    flake.nix  
    nixos/  
      configuration.nix  
      hardware-iso.nix  
      truthdb-service.nix
```

Pros:

- Everything versioned together (code + OS).
- Tag `v0.3.0` clearly means "TruthDB server v0.3.0 + OS config as of that commit".

Cons:

- Repo gets "heavier" (contains OS stuff, maybe big Nix cache config etc).

## Option B – Separate `truthdb-os` repo

text

 Copy code

```
truthdb/  
truthdb-os/
```

Where `truthdb-os` depends on a specific TruthDB version (e.g. pulls a tarball or git rev of the server).

Pros:

- Cleaner boundaries (app vs appliance).
- Possible to have multiple OS flavours for the same TruthDB version.

Cons:

- You now have to sync **two** repos / tags.

Given what you wrote ("main truthdb repo's releases will be the iso"), **Option A is completely fine** and keeps your life simpler to start with.

---

## 2. How the automation works (end-to-end)

Let's pick a very concrete flow:

**Push a git tag → CI builds ISO → CI publishes a GitHub Release with .iso attached**

### 2.1 NixOS config for ISO

In `os/flake.nix`:

nix

 Copy code

```
{
  description = "TruthDB OS ISO";

  inputs = {
    nixpkgs.url = "github:NixOS/nixpkgs/nixos-unstable";
  };

  outputs = { self, nixpkgs, ... }:
    let
      system = "x86_64-linux";
      pkgs = import nixpkgs { inherit system; };
    in {
      nixosConfigurations.truthdb = nixpkgs.lib.nixosSystem {
        inherit system;
        modules = [
          # Minimal installer ISO base
          ({ config, pkgs, ... }: {
            imports = [
              "${nixpkgs}/nixos/modules/installer/cd-dvd/installation-cd-min
            ];

            # Your TruthDB server packaged as a systemd service, for example
            systemd.services.truthdb = {
              description = "TruthDB server";
              wantedBy = [ "multi-user.target" ];
              after = [ "network.target" ];
              serviceConfig = {
                ExecStart = "${pkgs.truthdb}/bin/truthdb-server --config /et
```

```

        Restart = "always";
    };
};

    # Add whatever else you need here...
})
];
};
};
}

```

Then locally (or in CI):

bash

 Copy code

```

nix build .#nixosConfigurations.truthdb.config.system.build.isoImage
# Output symlink: result/iso/*.iso

```

### 3. GitHub Actions: tag → ISO → Release

#### 3.1 Trigger on tags

In `.github/workflows/build-iso.yml`:

yaml

 Copy code

```

name: Build TruthDB OS ISO

on:
  push:
    tags:
      - 'v*' # v0.1.0, v0.2.0 etc.

jobs:
  build-iso:
    runs-on: self-hosted # your Ubuntu 24.04 runner
    steps:
      - name: Checkout
        uses: actions/checkout@v4

      - name: Install Nix
        uses: cachix/install-nix-action@v27

```



```

with:
  nix_path: nixpkgs=channel:nixos-unstable

- name: Build ISO
  run: |
    cd os
    nix build .#nixosConfigurations.truthdb.config.system.build.isoI
    ls -R
    # result/iso/*.iso should exist now

- name: Upload ISO as artifact (optional but nice)
  uses: actions/upload-artifact@v4
  with:
    name: truthdb-os-`${{ github.ref_name }}`
    path: os/result/iso/*.iso

- name: Create GitHub Release with ISO
  uses: softprops/action-gh-release@v2
  with:
    tag_name: `${{ github.ref_name }}`
    name: TruthDB OS `${{ github.ref_name }}`
    files: |
      os/result/iso/*.iso
  env:
    GITHUB_TOKEN: `${{ secrets.GITHUB_TOKEN }}`

```

What this gives you:

- Tag `v0.3.0` → workflow runs on your self-hosted runner
- Builds ISO via Nix
- Creates a GitHub Release `v0.3.0`
- Attaches `truthdb-os-v0.3.0.iso` (or whatever nix named it) as an asset

From a user/operator perspective, **“go to Releases, download the .iso, burn it, boot”**.

---

## 4. A couple of practical details

- **ISO size limits:** GitHub releases allow big assets (several GB), so a 300–800 MB appliance ISO is totally fine.
- **Checksums:** you probably want a `sha256sum` and maybe `sha512sum` file next to the ISO.

Add a step:

yaml

 Copy code

```
- name: Generate checksums
  run: |
    cd os/result/iso
    sha256sum *.iso > SHA256SUMS
    sha512sum *.iso > SHA512SUMS
```

And then include SHA256SUMS / SHA512SUMS in files: for the release.

- **Debug vs release ISOs:** if you later want a debug build, you can have:
  - truthdb-debug NixOS config, and
  - Trigger on tags like v\*-debug or separate workflow.

---

## 5. Answer to your core question

*"It should be automated. Maybe the main truthdb repo's releases will be the iso?"*

**Yes, that's a good model.**

The clean pattern is:

1. **Main TruthDB repo** contains:
  - app crates
  - OS definition (NixOS config).
2. You **only build and publish an ISO from tagged commits**.
3. The **GitHub Release for that tag is the OS version**, with the ISO attached.

If you want, next step I can:

- Sketch a **concrete** flake.nix + truthdb-service.nix that assumes your Rust server binary is built with Cargo and packaged into Nix.
- Or a **full example workflow file** with checksums and debug symbols separated.

    ...