AgriProvider Test Case Document

Project: AgriProvider

Date: 2026-11-09

Project status: Verified backend suite, lint, TypeScript checks, and local Expo web app startup.

Verification summary

? Backend tests: PASS (60/60)

? Mobile lint: PASS

? TypeScript compile: PASS

? Local web app: Running at http://localhost:8081

? Local API: Running at http://localhost:5000

Test cases

TC-01 - Provider registration

Valid provider sign-up creates a provider account and forces the role to provider. Invalid values fail cleanly.

TC-02 - Duplicate email prevention

A second registration with the same email must return a 409 duplicate error and not create a second user.

TC-03 - Provider login

A valid provider enters the application through API auth and session restoration.

TC-04 - Invalid credential rejection

Wrong email/password combinations return a generic 401 response without exposing account existence.

TC-05 - Admin assignment permission

Administrative assignment APIs must work only for admin role and remain blocked for provider/assessor/QA users.

TC-06 - Assessor review access

Assigned assessors can inspect only linked evidence and decision records.

TC-07 - Programme CRUD

Providers can create, retrieve, update, list, and archive programme records with proper ownership enforcement.

TC-08 - Learner registration and duplicate risk

Learner creation is provider-scoped; likely duplicate records require explicit confirmation.

TC-09 - Enrolment creation and uniqueness

Only one active enrolment may exist for a learner-programme pair at a time.

TC-10 - Attendance recording

Present, absent, and excused states are accepted; invalid states and out-of-scope records are rejected.

TC-11 - Evidence upload validation

Valid PDF/JPEG/PNG files under 5 MB are accepted; invalid or oversized files fail safely.

TC-12 - Evidence access control

Evidence remains private and provider-scoped; unauthorized access is denied.

TC-13 - Assessor correction flow

The assessor can request correction, and a provider may resubmit only after the correction state is recorded.

TC-14 - QA role restriction

The QA role has a clear informational-only placeholder state and is not presented as an operational workflow.

TC-15 - Web origin/session auth

Web cookie sessions only work for the configured origin and reject invalid origins.

TC-16 - Error and retry safety

Server errors remain safe, retryable when needed, and do not leak stack traces or internal details.

Notes and constraints

? QA workflow remains deliberately informational-only until the approved backend verification workflow is implemented.

? Certification and milestone eligibility remain explicitly out of scope for this milestone.

? Production storage, live payments, and external integrations are not included in this project build.