

TOP 10 SQL INTERVIEW QUESTIONS



MySQL Delete Duplicate Rows but keep one

- Delete the duplicate rows but keep latest: **using GROUP BY and MAX**
- Delete the duplicate rows but keep latest: **using JOINS**
- Delete the duplicate row but keep oldest: **using JOINS**
- Delete the duplicate row but keep oldest: **using ROW_NUMBER()**



Build Composite Index (Multiple-Column Indexes)

- Can have indexes on multiple columns in Mysql?
- What is Composite Index? Give a relevant example.



- In Mysql, An index may consist of up to how many columns?
- Multiple column index is built to support which primary use case in Mysql?

Clustered and Non Clustered Index

- Differentiate between the two with an example?
- When to Use a Clustered Index? Show with an example.
 - When to Use a Non-clustered Index? Show with an example.
- How many clustered indexes & non clustered indexes are allowed per table?
- Should Primary Keys be Clustered or Non-clustered Index?
- Which is Faster: Clustered or Non-clustered Index?



What is the difference between delete, truncate & drop?

- Which of these is DDL & DML command?
- Can we use the "where" clause with each one of them?
- Which of the above is executed by taking table lock?
- In which of the three one can "not" retrieve data even after the rollback is performed?
- Which of the above is executed by taking row-level lock?
- What is the primary use case of each one of the above mentioned?



Employees Earning More Than Their Managers

Table: Employee

Column Name	Type
id	int
name	varchar
salary	int
managerId	int

id is the primary key column for this table.

Each row of this table indicates the ID of an employee, their name, salary, and the ID of their manager.

Example 1:

Input:

Employee table:

id	name	salary	managerId
1	Joe	70000	3
2	Henry	80000	4
3	Sam	60000	Null
4	Max	90000	Null

Output:

Employee
Joe

Explanation: Joe is the only employee who earns more than his manager.



Rank Scores

Table: Scores

Column Name	Type
id	int
score	decimal

id is the primary key for this table.

Each row of this table contains the score of a game. Score is a floating point value with two decimal places.

Write an SQL query to rank the scores. The ranking should be calculated according to the following rules:

- The scores should be ranked from the highest to the lowest.
- If there is a tie between two scores, both should have the same ranking.
- After a tie, the next ranking number should be the next consecutive integer value. In other words, there should be no holes between ranks.

Return the result table ordered by `score` in descending order.

Example 1:

Input:

Scores table:

id	score
1	3.50
2	3.65
3	4.00
4	3.85
5	4.00
6	3.65

Output:

score	rank
4.00	1
4.00	1
3.85	2
3.65	3
3.65	3
3.50	4

Trips & Users

Table: Trips

Column Name	Type
id	int
client_id	int
driver_id	int
city_id	int
status	enum
request_at	date

id is the primary key for this table.

The table holds all taxi trips. Each trip has a unique id, while client_id and driver_id are foreign keys to the users_id at the Users table.

Status is an ENUM type of ('completed', 'cancelled_by_driver', 'cancelled_by_client').

Table: Trips

Column Name	Type
id	int
client_id	int
driver_id	int
city_id	int
status	enum
request_at	date

id is the primary key for this table.

The table holds all taxi trips. Each trip has a unique id, while client_id and driver_id are foreign keys to the users_id at the Users table.

Status is an ENUM type of ('completed', 'cancelled_by_driver', 'cancelled_by_client').

The **cancellation rate** is computed by dividing the number of canceled (by client or driver) requests with unbanned users by the total number of requests with unbanned users on that day.

Write a SQL query to find the **cancellation rate** of requests with unbanned users (**both client and driver must not be banned**) each day between "2013-10-01" and "2013-10-03". Round Cancellation Rate to **two decimal** points.

Return the result table in **any order**.



Consecutive Numbers

Table: Logs

Column Name	Type
id	int
num	varchar

id is the primary key for this table.

Write an SQL query to find all numbers that appear at least three times consecutively.

Return the result table in **any order**.

The query result format is in the following example.

Example 1:

Input:

Logs table:

id	num
1	1
2	1
3	1
4	2
5	1
6	2
7	2

Output:

ConsecutiveNums
1

Explanation: 1 is the only number that appears consecutively for at least three times.



Duplicate Emails

Table: Person

Column Name	Type
id	int
email	varchar

id is the primary key column for this table.
Each row of this table contains an email. The emails will not contain uppercase letters.

Write an SQL query to report all the duplicate emails.

Return the result table in **any order**.

Example 1:

Input:

Person table:

id	email
1	a@b.com
2	c@d.com
3	a@b.com

Output:

Email
a@b.com

Explanation: a@b.com is repeated two times.



Customer who never orders

Table: Customers

Column Name	Type
id	int
name	varchar

id is the primary key column for this table.
Each row of this table indicates the ID and name of a customer.

Table: Orders

Column Name	Type
id	int
customerId	int

id is the primary key column for this table.
customerId is a foreign key of the ID from the Customers table.
Each row of this table indicates the ID of an order and the ID of the customer who ordered it.

Write an SQL query to report all customers who never order anything.

Return the result table in **any order**.

