

AppSealer:

Automatic Generation of Vulnerability-Specific Patches
for Preventing Component Hijacking Attacks in Android
Applications

Mu Zhang

Heng Yin


Department of Electrical Engineering and Computer Science,
Syracuse University



Motivation: Component Hijacking Attacks in Android

“A class of attacks that seek to
gain **unauthorized access** to protected or
private resources
through **exported components** in
vulnerable Android apps.”
(L. Lu et al. CHEX, *CCS'12*)

Motivation: Component Hijacking Attacks in Android



Motivation: Current Countermeasures



- **Detection: Static Dataflow Analysis**
 - Conservative
- **Fix: Manual Effort**
 - Inexperienced
 - Not easy to confirm vulnerability

16 Reported in **Oct. 2012**

13 Not fixed until **Aug. 2013**


AppSealer: Automatic Patch Generation



- **Goal:** to automatically generate a patch that is specific to the discovered component hijacking vulnerability.

Design Requirements:

- No source code access.
- Vulnerability-specific patching.
- Minimal performance overhead.
- Minimal impact on usability.



Related Work: Automatic Patch Generation



- **Data Patch**

- W. Cui et al. ShieldGen, *Oakland*'07
- D. Brumley et al. *Oakland*'06
- M. Costa et al. Vigilante, *SOSP*'05
- M. Costa et al. Bouncer, *SOSP*'07
- J. Caballero et al. *RAID*'09


- **Code Patch**

- Z. Lin et al. AutoPaG, *ASIACCS*'07
- C. Zhang et al. IntPatch, *ESORICS*'10
- Sidiroglou and Keromytis, *IEEE Security and Privacy*
- J. Newsome et al. VSEF, *NDSS*'06

Technical Approach



- Key: to place *minimally* required code into the vulnerable program to *accurately* keep track of dangerous information.





A Running Example



```
1 public class VulActivity extends Activity{
2     private String DEFAULT_ADDR = "http://default.url";
3     private byte DEFAULT_KEY = 127;
4
5     private String addr;
6     private static Location location;
7     private byte key;
8
9     /* Entry point of this Activity */
10    public void onCreate(Bundle savedInstanceState){
11        this.key = DEFAULT_KEY;
12
13        this.addr = getIntent().getExtras().getString("url");
14        if(this.addr == null){
15            this.addr = DEFAULT_ADDR;
16        }
17    }
18
19    public void onStart(){
20        VulActivity.location = getLocation();
21    }
22
23    public void onDestroy(){
24        String location =
25            Double.toString(location.getLongitude())
26            + "," + Double.toString(location.getLatitude());
27
28        byte[] bytes = location.getBytes();
29        for(int i=0; i<bytes.length; i++)
30            bytes[i] = crypt(bytes[i]);
31        String url = this.addr;
32        post(url, bytes);
33    }
34
35    public byte crypt(byte plain){
36        return (byte)(plain ^ key);
37    }
38
39    public Location getLocation(){
40        Location location = null;
41        LocationManager locationManager = (LocationManager)
42            getSystemService(Context.LOCATION_SERVICE);
43        location = locationManager.getLastKnownLocation
44            (LocationManager.GPS_PROVIDER);
45        return location;
46    }
47
48    public void post(String addr, byte[] bytes){
49        URL url = new URL(addr);
50        HttpURLConnection conn =
51            (HttpURLConnection)url.openConnection();
52        ...
53        OutputStream output = conn.getOutputStream();
54        output.write(bytes, 0, bytes.length);
55        ...
56    }
57 }
```


Taint Slice Computation



Patch Statement Placement



```
1  public class VulActivity extends Activity{
    ...
5  private String addr;
P  public boolean addr_s0_t;
6  private static Location location;
P  public static boolean location_s1_t;
    ...
10 public void onCreate(Bundle savedInstanceState){
    ...
13 this.addr=getIntent().getExtras().getString("url");
P  if(isExternalIntent()){
P    this.addr_s0_t = true;
P  }else{
P    this.addr_s0_t = false;
P  }
14 if(this.addr == null){
15   this.addr = DEFAULT_ADDR;
P  this.addr_s0_t = false;
16 }
17 }
18
19 public void onStart(){
20   VulActivity.location = getLocation();
P  VulActivity.location_s1_t = true;
21 }
22 }
```

```
23 public void onDestroy(){
    ...
29 String url = this.addr;
P  BoolWrapper bytes_s1_w = new BoolWrapper();
P  bytes_s1_w.b = VulActivity.location_s1_t;
P  BoolWrapper url_s0_w = new BoolWrapper();
P  url_s0_w.b = this.addr_s0_t;
30 post(url, bytes, url_s0_w, bytes_s1_w);
31 }
    ...
44 public void post(String addr, byte[] bytes,
    BoolWrapper addr_s0_w, BoolWrapper bytes_s1_w){
P  boolean output_s0_t = addr_s0_w.b;
P  boolean bytes_s1_t = bytes_s1_w.b;
48 OutputStream output = conn.getOutputStream();
P  if(output_s0_t == true && bytes_s1_t == true)
P    promptForUserDecision();
49 output.write(bytes, 0, bytes.length);
50
51 }
52 }
```

Patch Optimization



```
public byte crypt(byte, BoolWrapper, BoolWrapper) BoolWrapper {  
    r0 := @this: VulActivity;  
    b0 := @parameter0: byte;  
  
    w_p0 := @parameter1: BoolWrapper;  
    w_t := @parameter2: BoolWrapper;  
    w_r := @parameter3: BoolWrapper;  
  
    r0_t = w_t.<BoolWrapper: boolean b>;  
    b0_t = w_p0.<BoolWrapper: boolean b>;  
    $b2_t = w_r.<BoolWrapper: boolean b>;  
  
    $b1 = r0.<VulActivity: byte key>;  
    $b2 = b0 ^ $b1;  
    $b2_t = b0_t | 0;  
  
    w_t.<BoolWrapper: boolean b> = r0_t;  
    w_p0.<BoolWrapper: boolean b> = b0_t;  
    w_r.<BoolWrapper: boolean b> = $b2_t;  
  
    return $b2;  
}
```

O1: Removing Redundant BoolWrapper Statements

O2: Removing Redundant Function Parameters

Patch Optimization



```
public byte crypt(byte, BoolWrapper, BoolWrapper) {  
    r0 := @this: VulActivity;  
    b0 := @parameter0: byte;  
    w_p0 := @parameter1: BoolWrapper;  
    $b3 := virtualInvoke r0.<VulActivity: byte crypt(byte)>($b2);  
    b0_t1 = w_p0.<BoolWrapper: boolean b>;  
    $b1 = r0.<VulActivity: byte key>;  
    $b2 = b0 ^ $b1;  
    $b2_t1 = b0_t1 | 0x;  
    $b3.<BoolWrapper: boolean b> = $b2_t1;  
    return $b2;  
}
```

O3: Inlining Instrumentation Code


O4: Soot Built-in Optimizations

Evaluation: Overview



- **16 real-world apps with component hijacking vulnerabilities**

- Increase of Program Size
 - Average: 2%
 - Worst Case: 9.6%
- Performance of Patch Generation
 - Average: 2%
 - Worst Case: 9.6%
- Runtime Overhead
 - Benign Context: No Interruption
 - Under Attack: Warning



Evaluation: Case Study



- 6 apps with **Pop-up Dialogs**
- 3 apps with **Selection Views**
- 3 apps with **Multiple Threads**

Related Work



- [1] W. Cui, M. Peinado, and H. J. Wang, “ShieldGen: Automatic Data Patch Generation for Unknown Vulnerabilities with Informed Probing,” in Proceedings of Oakland’07.
- [2] D. Brumley, J. Newsome, D. Song, H. Wang, and S. Jha, “Towards Automatic Generation of Vulnerability-Based Signatures,” in Proceedings of Oakland’06.
- [3] M. Costa, J. Crowcroft, M. Castro, A. Rowstron, L. Zhou, L. Zhang, and P. Barham, “Vigilante: End-to-End Containment of Internet Worms,” in Proceedings of SOSP’05.
- [4] M. Costa, M. Castro, L. Zhou, L. Zhang, and M. Peinado, “Bouncer: Securing Software by Blocking Bad Input,” in Proceedings of SOSP’07.
- [5] J. Caballero, Z. Liang, Poosankam, and D. Song, “Towards Generating High Coverage Vulnerability-Based Signatures with Protocol-Level Constraint-Guided Exploration,” in Proceedings of RAID’09.
- [6] Z. Lin, X. Jiang, D. Xu, B. Mao, and L. Xie, “AutoPaG: Towards automated Software Patch Generation with Source Code Root Cause Identification and Repair,” in Proceedings of ASIACCS’07.
- [7] C. Zhang, T. Wang, T. Wei, Y. Chen, and W. Zou, “IntPatch: Automatically Fix Integer-Overflow-to-Buffer-Overflow Vulnerability at Compile-Time,” in Proceedings of ESORICS’10.
- [8] S. Sidiroglou and A. D. Keromytis, “Countering Network Worms Through Automatic Patch Generation,” IEEE Security and Privacy, vol. 3, no. 6, pp. 41–49, Nov. 2005.
- [9] J. Newsome, D. Brumley, and D. Song, “Vulnerability-specific execution filtering for exploit prevention on commodity software,” in Proceedings of NDSS’06.

Conclusion



- We developed a technique to *automatically* generate patch for Android applications with **component hijacking vulnerability**.
- The key is to place *minimally* required code into the vulnerable program to *accurately* keep track of dangerous information and effectively block the attack at the security sensitive APIs.

Questions?

Discussion



- **Soundness of Patch Generation**
 - Static analysis: standard, FP
 - Taint tracking: taint policy of TaintDroid, FP
 - Optimization: compiler algorithms
 - In theory, FP; In practice, no FP observed.