Dynamic Scheduling of Network Updates

Xin Jin

Hongqiang Harry Liu, Rohan Gandhi, Srikanth Kandula, Ratul Mahajan, Ming Zhang, Jennifer Rexford, Roger Wattenhofer









Dynamic Scheduling of Network Updates

Xin Jin

Hongqiang Harry Liu, Rohan Gandhi, Srikanth Kandula, **Ratul Mahajan**, Ming Zhang, Jennifer Rexford, **Roger Wattenhofer**









Ratul Mahajan



C.-Y. Hong, S. Kandula, R. Mahajan, M. Zhang, V. Gill, M. Nanduri, and R. Wattenhofer, "Achieving high utilization with software-driven WAN," in ACM SIGCOMM, 2013.

Roger Wattenhofer



R. Mahajan and R. Wattenhofer, "On consistent updates in software defined networks," in ACM SIGCOMM HotNets Workshop, 2013.

Research

SDN: Paradigm Shift in Networking

 Direct, centralized updates of forwarding rules in switches




- Many benefits
 - Traffic engineering [B4, SWAN]
 - Flow scheduling [Hedera, DevoFlow]
 - Access control [Ethane, vCRIB]
 - Device power management [ElasticTree]

Update the data plane state


- Scenarios
 - Periodically traffic engineering
 - Failure recovery
- The state
 - a set of rules
 - how switches forward packets






Network Update is Challenging


- Requirement 1: fast
 - The agility of control loop
- Requirement 2: consistent
 - No congestion, no blackhole, no loop, etc.



What is Consistent Network Update




What is Consistent Network Update




- Asynchronous updates can cause congestion
- Need to carefully order update operations

Existing Solutions are Slow


- Existing solutions are static [ConsistentUpdate'12, SWAN'13, zUpdate'13]
 - Pre-compute an order for update operations





Existing Solutions are Slow


- Existing solutions are static [ConsistentUpdate'12, SWAN'13, zUpdate'13]
 - Pre-compute an order for update operations



- Downside: Do not adapt to runtime conditions
 - Slow in face of highly variable operation completion time

Operation Completion Times are Highly Variable


Measurement on commodity switches




Operation Completion Times are Highly Variable


Measurement on commodity switches

- Contributing factors
 - Control-plane load
 - RPC delays
 - Number of rules
 - Priority of rules
 - Type of operations (insert vs. modify)







Static Schedules can be Slow




No static schedule is a clear winner under all conditions!

Dynamic Schedules are Adaptive and Fast








Adapts to actual conditions!

No static schedule is a clear winner under all conditions!


- Exponential number of orderings
 - Integer Linear Programming: slow
- Cannot completely avoid planning
 - Constraint: consistent and feasible




- Exponential number of orderings
 - Integer Linear Programming: slow
- Cannot completely avoid planning
 - Constraint: consistent and feasible




- Exponential number of orderings
 - Integer Linear Programming: slow
- Cannot completely avoid planning
 - Constraint: consistent and feasible




- Exponential number of orderings
 - Integer Linear Programming: slow
- Cannot completely avoid planning
 - Constraint: consistent and feasible




- Exponential number of orderings
 - Integer Linear Programming: slow
- Cannot completely avoid planning
 - Constraint: consistent and feasible





- Exponential number of orderings
 - Integer Linear Programming: slow
- Cannot completely avoid planning
 - Constraint: consistent and feasible





Dionysus Pipeline

























- Supported scenarios
 - Tunnel-based forwarding: WANs
 - WCMP forwarding: data center networks
- Supported consistency properties
 - Loop freedom
 - Blackhole freedom
 - Packet coherence
 - Congestion freedom
- Check paper for details

WAN: Tunnel-based forwarding

- The ingress switches
 - match on packet headers and tag packets with tunnel ids
- Blackhone freedom
 - Tunnels fully established before ingress sws puts any traffic
 - All traffic removed from tunnels before tunnels deleted




WAN: Tunnel-based forwarding



Index	Operation
A	Add p_3 at S1
В	Add p_3 at S4
С	Add p_3 at S5
D	Change weight at S1
Е	Delete p_2 at S1
F	Delete p_2 at S2
G	Delete p_2 at S5

Table 1: Operations to update f with tunnel-based rules. tunnel-based rules (Table 1)




(c) Dependency graph using tunnel-based rules (Table 1)


DC: WCMP forwarding

- Switches at every hop
 - match on packet header
- Packet coherence
 - No packet should see a mix of old and new rules
 - Using version numbers

Transition from old traffic distribution to new traffic distribution




DC: WCMP forwarding




Index	Operation
X	Add weights with new version at S2
Y	Change weights, assign new version at S1
Z	Delete weights with old version at S2

Table 2: Operations to update f in WCMP forwarding.




(d) Dependency graph using WCMP-based rules (Table 2)

Dionysus Pipeline




Dionysus Scheduling


Scheduling as a resource allocation problem





Dionysus Scheduling

Scheduling as a resource allocation problem













- Scheduling as a resource allocation problem
- Finding a feasible update is NP-complete under link capacity and switch table size constraints
- Approach
 - Directed acyclic graph (DAG): always feasible, critical-path
 - General case: covert to a virtual DAG
 - Rate limit flows to resolve deadlocks


Critical-Path Scheduling

Calculate critical-path length (CPL) for each node

$$CPL_i = w_i + \max_{j \in children(i)} CPL_j$$

 $w_i = \begin{cases} 1, & if i \text{ is operation node} \\ 0, & otherwise \end{cases}$

- Extension: assign larger weight to operation nodes if we know in advance the switch is slow
- Resource allocated to operation nodes with larger CPLs




Critical-Path Scheduling

Calculate critical-path length (CPL) for each node

$$CPL_{i} = w_{i} + \max_{j \in children(i)} CPL_{j}$$


$$w_{i} = \begin{cases} 1, if \ i \ is \ operation \ node \\ 0, otherwise \end{cases}$$

- Extension: assign larger weight to operation nodes if we know in advance the switch is slow
- Resource allocated to operation nodes with larger CPLs




Scheduling DAGs

Dynamically schedule




Handling Cycles

- Convert to virtual DAG
 - Consider each strongly connected component (SCC) as a virtual node




- Critical-path scheduling on virtual DAG
 - Weight w_i of SCC: number of operation nodes




Handling Cycles

- Convert to virtual DAG
 - Consider each strongly connected component (SCC) as a virtual node




- Critical-path scheduling on virtual DAG
 - Weight w_i of SCC: number of operation nodes



Evaluation


- Implementation
 - Prototype: 5,000+ lines of C# code
- Datasets
 - WAN
 - interconnects O(50) sites
 - 288 traffic matrices on a day
 - DC
 - 3 layers with several hundred switches

Evaluation: Traffic Engineering




Evaluation: Traffic Engineering







Improve 50th percentile update speed by 80% compared to static scheduling (SWAN), close to OneShot

Evaluation: Failure Recovery



Evaluation: Failure Recovery





Reduce 99th percentile link oversubscription by 40% compared to static scheduling (SWAN)

Improve 99th percentile update speed by 80% compared to static scheduling (SWAN)

Conclusion

- Dionysus provides fast, consistent network updates through dynamic scheduling
 - Dependency graph: compactly encode orderings
 - Scheduling: dynamically schedule operations

Dionysus enables more agile SDN control loops

Thanks!

