

OpenNF: Enabling Innovation in Network Function Control



WISCONSIN
UNIVERSITY OF WISCONSIN-MADISON

Aaron Gember-Jacobson, Chaithan Prakash,
Raajay Viswanathan, Robert Grandl,
Junaid Khalid, Sourav Das, Aditya Akella

Network functions (NFs)

- Perform sophisticated *stateful* actions on packets/flows



WAN optimizer



Caching proxy




Intrusion detection system (IDS)

NF trends


- NFV → dynamically allocate NF instances



- SDN → dynamically reroute flows




Dynamic reallocation
of packet processing



Example: elastic NF scaling

1. Satisfy performance SLAs
2. Minimize operating costs
3. Accurately monitor traffic



Example: Elastic Networking

To simultaneously...

1. Satisfy performance SLAs
2. Minimize operating costs
3. Accurately monitor traffic




CPU

Cannot effectively implement
new services or abstractions!




Packet loss

Why NFV + SDN falls short



SLAs + cost + accuracy: What do we need?

- Quickly move, copy, or share internal NF state alongside updates to network forwarding state



- Guarantees: loss-free, order-preserving, ...



Also applies to other scenarios

Outline


- Motivation and requirements
- Challenges
- OpenNF architecture
 - State export/import
 - State operations
 - Guarantees
- Evaluation

Challenges


1. Supporting many NFs with minimal changes




2. Dealing with race conditions



3. Bounding overhead




OpenNF overview




NF state taxonomy

State created or updated by an NF applies to either a **single flow** or a **collection of flows**




NF API: export/import state

- Functions: get, put, delete




No need to expose/change internal state organization!

Control operations: move



Also provide copy and share


Lost updates during move



Loss-free: All state updates should be reflected in the transferred state, and all packets should be processed

- ✗ Split/Merge [NSDI '13]: pause traffic, buffer packets
 - Packets in-transit when buffering starts are dropped


NF API: observe/prevent updates using events



Only need to change an NF's receive packet function!


Use events for loss-free move

1. `enableEvents(red, drop)` on Bro_1
2. `get/delete` on Bro_1
3. Buffer events at controller
4. `put` on Bro_2
5. Flush packets in events to Bro_2
6. Update forwarding



Re-ordering of packets

- False positives from Bro's weird script



Order-preserving: All packets should be processed in the order they were forwarded by the switch

OpenNF: SLAs + cost + accuracy

1. Dealing with diversity

Export/import state based
on its association with flows

2. Dealing with race conditions

Events

+

Lock-step forwarding updates

Implementation

- Controller (*3.8K lines of Java*)
- Communication library (2.6K lines of C)
- Modified NFs (3-8% increase in code)



Bro IDS



iptables



Squid Cache



PRADS



Overall benefits for elastic scaling

- Bro IDS processing 10K pkts/sec
 - *At 180 sec:* move HTTP flows (489) to new IDS
 - *At 360 sec:* move back to old IDS
- SLAs: 260ms to move (loss-free)
- Accuracy: same log entries as using one IDS
 - VM replication: incorrect log entries
- Cost: scale down after state is moved
 - Stratos: scale down delayed 25+ minutes



[arXiv:1305.0209]

Evaluation: state export/import





**Serialization/deserialization
costs dominate**

**Cost grows with
state complexity**

Evaluation: operations


- PRADS asset detector processing 5K pkts/sec
- Move per-flow state for 500 flows



Operations are efficient, but guarantees come at a cost!

Conclusion

- Dynamic reallocation of packet processing enables new services
- Realizing SLAs + cost + accuracy requires quick, safe control of internal NF state
- OpenNF provides flexible and efficient control with few NF modifications



<http://opennf.cs.wisc.edu>




Backup

- Related work
- Copy and share
- Order-preserving move
- Bounding overhead
- Example control application
- Evaluation: controller scalability
- Evaluation: importance of guarantees
- Evaluation: benefits of granular control

Existing approaches

- Virtual machine replication
 - Unneeded state → incorrect actions
 - Cannot combine → limited reallocation
- Split/Merge *[NSDI'13]*
 - State allocations and accesses occur via library
 - Addresses a specific problem → limited suitability
 - Packets may be dropped or re-ordered → wrong NF behavior



Copy and share operations

- Used when multiple instances need some state
- Copy – no or eventual consistency
 - Once, periodically, based on events, etc.
- Share – strong or strict consistency
 - Events are raised for all packets
 - Events are released one at a time
 - State is copied before releasing the next event

Copy (multi-flow): 111ms
Share (strong): 13ms/packet




- from last)
 Note:
-
- Diagram illustrating a packet scheduling scenario:
- Inst₂ sends packets B1 (red) and B3 (blue).
 - Inst₁ sends packets B2 (blue) and B4 (blue).
 - A buffer (Buf) contains packets B1, B2, B3, and B4.
 - Packets B1 and B2 are shown being sent from the buffer to Inst₂.
 - Packets B3 and B4 are shown being sent from the buffer to Inst₁.


Bounding overhead

Applications decide (based on NF & objectives):


1. Granularity of operations



2. Guarantees desired




Example app: elastic NF scaling



```
movePrefix(prefix, oldInst, newInst):  
    copy(oldInst, newInst, {nw_src: prefix}, multi)  
    move(oldInst, newInst, {nw_src: prefix}, per, LF+OP)  
    while (true):  
        sleep(60)  
        copy(oldInst, newInst, {nw_src: prefix}, multi)  
        copy(newInst, oldInst, {nw_src: prefix}, multi)
```



Evaluation: controller scalability



Improve scalability with P2P state transfers



Evaluation: importance of guarantees

- Bro₁ processing malicious trace @ 1K pkts/sec
- After 14K packets: move active flows to Bro₂

Alert	Baseline	NF	LF	LF+OP
Incorrect file type	26	25	24	26
MHR Match	31	28	27	31
MD5	116	111	106	116
Total	173	164	157	173



Evaluation: benefits of granular control

- HTTP requests from 2 clients (40 unique URLs)
- Initially: both go to Squid₁
- 20s later: reassign Client₁ to Squid₂

	Ignore	Copy-client	Copy-all
Hits @ Squid ₁	117	117	117
Hits @ Squid ₂	Crash!	39	50
State transferred	0 MB	4 MB	54 MB

