

HTML Text Formatting Tags

Formating Styles

Style Name	HTML Tague
Bold	,
Italic	<i>,
Underlined	<u>
Strikethrough	<s>,
Superscript	<sup>
Subscript	<sub>
Monospaced	<code>,<pre>
Highlighted	<mark>
Small Text	<small>

Bold Text

Tag	purpose	Example
	Bold text without emphasis (for visual styling only)	This is bold
	Semantically important bold text	Important!

- Use when the bold text has meaning (e.g. alerts).
- is just visual. No meaning for screen readers.

Italic / Emphasized Text

Tag	purpose	Example
<i>	Italic text (styling only)	<i>This is italic</i>
	Emphasized content (semantics)	Pay attention!
<ul style="list-style-type: none">➤ Use for emphasis understood by screen readers.➤ <i> is for stylistic use (e.g. foreign words ,names).		

Underlined Text

Tag	purpose	Example
<u>	Underlines text	<u>This is underlined</u>
<ul style="list-style-type: none">➤ Underlines can confuse users(like links),so use them with caution		

Strikethrough / Deleted / Inserted Text

Tag	purpose	Attributes	Example
<s>	Renders text as incorrect	None	<s>Old price</s>
	Marks content as deleted	cite,datetime	<del datetime="2025-07-19">Removed
<ins>	Marks content as added	cite, datetime	<ins datetime="2025-07-20">New!</ins>
<ul style="list-style-type: none">➤ and <ins> are semantic used in document versioning.			

Superscript and Subscript

Tag	purpose	Example
<sup>	Superscript(above text line)	A=a²
<sub>	Subscript (below text line)	H₂o
<ul style="list-style-type: none">➤ Common in math/science formulas.		

Code and Monospaced Text

Tag	purpose	Example
<code><code></code>	Inline code snippet	<code><code>console.log()</code></code>
<code><pre></code>	Preserves formatting	<code><pre>Line1\n Line2</pre></code>
<code><kbd></code>	Keyboard input	<code><kbd>Ctrl +c</kbd></code>
<code><samp></code>	Output from a program	<code><samp>File saved.</samp></code>

- Use `<pre>` + `<code>` for code blocks.

Quotations and Citations

Tag	purpose	Attributes	Example
<code><q></code>	Short quote	Cite	<code><q cite="source">quote</q></code>
<code><blockquote></code>	Long block quote	Cite	<code><blockquote cite="book">Full quote</blockquote></code>
<code><cite></code>	Citation source(title of work)		<code><cite>Hamlet</cite></code>

- `<q>` wraps in quotation marks; `<blockquote>` indents.

Highlighted and Small Text

Tag	purpose	Example
<code><mark></code>	Highlighted text	<code><mark>Important!</mark></code>
<code><small></code>	Small, de-emphasize text	<code><small>Fine print</small></code>

- Great for alerts, notes, or footnotes.

Summary Table of Formating Text styles

Formatting types	Tag	used for
Bold	,	style only, Emphasis
Italic	<i>,	style only, Emphasis
Underlined text, Strikethrough	<u>,<s>	style/strike
Deleted, Inserted text	,<ins>	Version tracking
Superscript, subscript	<sup>,<sub>	Maths /Chemistry
Code and Monospaced text	<code>,<kbd>,<samp>,<pre>	Programming
Quotations and Citations	<q>,<blockquote>,<cite>	Quotes
Highlighted, Small text	<mark>,<small>	Highlight/notes