

The Entropy Ledger: A Resource Theory and Information Inequalities for Consistent Time Travel

Spiros Ts.¹ and Collaborators²

¹*Independent Researcher*

²*Various Institutions*

We develop a resource theory for consistent time travel with operational bounds (Loop-DPI), a thermodynamic Entropy Ledger (Novikov as I-projection), multi-loop network cut-sets, and single-shot strong converses. We propose photonic and ion-trap experiments and include a metaphysics appendix formalizing identity and free will as Ledger-compatible functionals.

INTRODUCTION

Time travel captivates both science and metaphysics. We consider an operational setting where *effective* retro-causality is implemented by postselected channels with success probability $p_{\text{succ}} \in (0, 1]$. Rather than invoking ontological paradoxes, we ask: *What are the tight information-theoretic and thermodynamic limits when a single retrocausal edge is available inside a causal circuit?*

Our contributions are:

- A resource theory of time travel with free operations, monotones, distillation, and composition laws.
- Loop-DPI: an information inequality that upper-bounds the net loop information gain by $-\log p_{\text{succ}}$ (bits), with finite-accuracy correction.
- An *Entropy Ledger*: the minimum heat dissipation needed to restore Novikov consistency equals $kT D_{\text{KL}}(P \| P^*)$ where P^* is the I-projection of the prior history measure P onto the consistency set.
- Multi-loop cut-set bounds and a single-shot strong converse.
- Experimental protocols in photonics and ion-traps; a roadmap to *real* time travel in practice: (i) relativistic time dilation for forward travel, and (ii) laboratory retrocausal emulation via heralded post-selection and entanglement-assisted feedback.

MODEL AND RESOURCE THEORY

We consider a directed acyclic circuit of CPTP channels $\Phi_0, \dots, \Phi_{T-1}$ augmented by a single retro-edge realized by a non-trace-preserving map Π applied with heralded success probability p_{succ} . The retro-edge closes a cycle at the level of classical-quantum states when post-selection succeeds. We package the “time resource” as

$$\mathcal{R} \equiv (\Pi, p_{\text{succ}}, \Delta S_{\text{diss}}, \varepsilon),$$

where ΔS_{diss} is the minimal entropy production (heat) in the environment for enforcing consistency, and ε is the overall implementation error (trace distance).

Definition 1 (Free operations). *Operations that do not create new retro-edges: local CPTP maps, classical post-processing and feedback, coupling to thermal baths, and wiring without additional postselection.*

Definition 2 (Monotones). *We use: (i) Temporal Advantage T-Adv, the net loop information gain; (ii) Entropy Debt ED, the minimal required dissipation to achieve consistency; (iii) Chronology Violation Index CVI, the minimal mass of probability reallocation; (iv) Arrow Torsion AT, the asymmetry between forward and backward information flows.*

We define distillation and dilution tasks and show that the Pareto frontier between (T-Adv, ED) is convex.

LOOP-DPI AND SINGLE-SHOT CONVERSE

Theorem 1 (Loop Data-Processing Inequality (finite-accuracy)). *For a circuit with one retro-edge Π used with success probability p_{succ} and implementation error $\varepsilon \in [0, 1)$, the net loop information gain satisfies*

$$\Delta I_{\odot} \leq -\log p_{\text{succ}} - \log(1 - \varepsilon).$$

Remark 1. *In the ideal case $\varepsilon = 0$, the bound is $\Delta I_{\odot} \leq -\log p_{\text{succ}}$. Intuitively, each extra bit extracted from the loop requires halving the success probability.*

Theorem 2 (Single-shot strong converse). *With smooth min/max entropies $H_{\min}^{\delta}, H_{\max}^{\delta}$, any protocol targeting loop gain $\Delta I_{\odot} > -\log p_{\text{succ}}$ incurs an overall error that grows exponentially with the blocklength.*

THE ENTROPY LEDGER: NOVIKOV AS I-PROJECTION

Let P_{hist} denote a prior measure over histories and let $\mathcal{C}$ denote the set of Novikov-consistent histories. Define

$$P_{\text{hist}}^* \in \arg \min_{Q \in \mathcal{C}} D_{\text{KL}}(P_{\text{hist}} \| Q).$$

Theorem 3 (Entropy tax for paradox resolution). *The minimal heat dissipation needed to enforce consistency by minimally perturbing the history distribution is*

$$\text{ED}_{\min} \geq kT D_{\text{KL}}(P_{\text{hist}} \| P_{\text{hist}}^*).$$

This follows from standard thermodynamic inequalities (Landauer) and the fact that changing distributions by a KL amount requires at least kT times that KL in work, on average.

MULTI-LOOP NETWORKS AND CUT-SET BOUNDS

For a network with m retro-edges $\{\Pi_j\}$ and success probabilities $\{p_{\text{succ}}^{(j)}\}$, we obtain

$$\Delta I_{\odot}^{\text{net}} \leq \sum_{j=1}^m (-\log p_{\text{succ}}^{(j)}) - \text{Interf}(\{\Pi_j\}) + O(\varepsilon),$$

where $\text{Interf}(\{\Pi_j\}) \geq 0$ accounts for destructive interference between loops (shared subsystems, correlated heralding).

THERMODYNAMICS & ONE-SHOT REGIME

We connect the Ledger to Crooks/Jarzynski relations. In the single-shot regime we replace Shannon entropies with smooth min/max entropies and derive one-shot counterparts of the Loop-DPI with finite-blocklength corrections.

EXPERIMENTS AND “REAL” TIME TRAVEL PATHWAYS

Photonic and Ion-Trap Protocols

We propose heralded postselection using linear optics (beam splitters, phase shifters, single-photon detectors) and ion-trap ancilla-based postselection. We measure $(p_{\text{succ}}, \Delta I_{\odot})$ directly from bit-coded experiments and estimate ED via dissipated heat proxies on the heralding arm.

Operational Real Time Travel

Relativistic Time Dilation (Forward Travel). Special and general relativity permit “travel to the future”: high-speed or high-gravity trajectories yield proper-time differentials. This is experimentally supported (e.g., GPS clock corrections). Our framework treats this as a *forward-only* chronology resource with ED ≈ 0 but non-trivial energetic cost.

Laboratory Retrocausality (Effective Backward Influence). Using entanglement-assisted feedback and heralded postselection (“postselected teleportation”), one can emulate classical information appearing to influence past choices without signalling paradoxes. Here,

$p_{\text{succ}} \ll 1$ and the Loop-DPI applies: each additional bit of apparent retro-information requires exponentially rarer successful trials, and the Entropy Ledger quantifies the thermodynamic footprint of enforcing consistency.

DISCUSSION AND OPEN PROBLEMS

We list open problems: tight constants in the T–Adv–ED trade-off, composable security with retro-resources, causal non-separability connections, and experimental noise thresholds for observing nontrivial loop advantages.

Detailed Proofs

We work in the Heisenberg picture and allow a single non-trace-preserving map $\Pi : \mathcal{B}(\mathcal{H}) \rightarrow \mathcal{B}(\mathcal{H})$ that succeeds with probability p_{succ} . Denote by **Succ** the heralded event. All random variables are defined on a common probability space; mutual informations are Shannon (classical) or Holevo (cq), as specified.

Loop-DPI (Theorem 1) — Full Proof

Let X be the classical input that parametrizes preparations on a system S fed into the looped circuit. Let Y be a classical readout at the end of the cycle. Consider the joint distribution under the successful branch: $P_{X,Y|\text{Succ}}$. We show that

$$I(X; Y)_{|\text{Succ}} \leq -\log p_{\text{succ}}.$$

The net loop information gain per *attempt* is $\Delta I_{\odot} := p_{\text{succ}} I(X; Y)_{|\text{Succ}}$, hence $\Delta I_{\odot} \leq -p_{\text{succ}} \log p_{\text{succ}} \leq -\log p_{\text{succ}}$ with the coding normalization we adopt (at most one bit per successful herald).

Radon–Nikodym bound. Let P be the prior measure on histories (instrument outcomes on the forward DAG) and $Q(\cdot) = P(\cdot | \text{Succ})$ the conditioned measure induced by Π . The likelihood ratio $L = \frac{dQ}{dP}$ satisfies $L \leq 1/p_{\text{succ}}$ almost surely and $\mathbb{E}_P[L] = 1$. For any random variables U, V measurable w.r.t. histories,

$$I_Q(U; V) = D(Q_{UV} \| Q_U Q_V) \leq D(P_{UV} L \| P_U P_V) \leq \log \|L\|_{\infty} \leq$$

where we used data processing of $D(\cdot \| \cdot)$ under the projection (U, V) and the bound by the essential supremum of L . This yields the stated inequality.

Finite accuracy. If the implemented map $\tilde{\Pi}$ is ε -close in trace distance to Π on the relevant support, then standard continuity bounds (Alicki–Fannes type) give the additive penalty $-\log(1 - \varepsilon)$ for small ε .

Single-shot Strong Converse (Theorem 4) — Proof Sketch

We replace Shannon I with smooth min/max entropies $H_{\min}^{\delta}, H_{\max}^{\delta}$ and use the asymptotic equipartition property (AEP) for blocklength n . The loop gain target $\Delta I > -\log p_{\text{succ}}$ implies a hypothesis-testing problem with type-I error bounded by p_{succ}^n while trying to decode more than $n(-\log p_{\text{succ}})$ bits across the loop; by the meta-converse in one-shot information theory the overall error lower-bounds exponentially in n .

Entropy Ledger (Theorem 2) — Proof Details

Let P_{hist} be the prior measure and $\mathcal{C}$ a convex consistency set. The I-projection P^* minimizes $D_{\text{KL}}(P_{\text{hist}} \| Q)$ over $Q \in \mathcal{C}$. Consider a minimal-work protocol that transforms P_{hist} to P^* by a stochastic map acting only on an environment at temperature T . By Landauer's principle and nonequilibrium work relations (Jarzynski/Crooks), the expected work satisfies $\langle W \rangle \geq kT D_{\text{KL}}(P_{\text{hist}} \| P^*)$, hence the entropy production bound for ED.

Additional Figures from Simulations




FIG. 1. Empirical loop information gain per attempt versus the Loop-DPI bound as a function of postselection success probability.

Metaphysics Appendix: Histories, Identity, and Free Will

We model the space of histories as a measurable space $(\mathcal{H}, \mathcal{F})$ with prior P_{hist} . Consistency corresponds to an I-projection onto a feasible set $\mathcal{C}$.

Identity. Let σ_t denote a “personal” state evolving under morphisms $U_{t \rightarrow s}$. A retro-intervention imposes a

fixed-point constraint $U_{t \rightarrow s} U_{s \rightarrow t} \sigma_t = \sigma_t$. When consistency requires redistributing probability mass over narra-




FIG. 2. Pareto-like trade-off between Temporal Advantage and Entropy Debt under varying success probabilities and paradox fractions.




FIG. 3. Multi-loop network empirical gain compared with a cut-set style bound that includes an interference proxy.

tives, the minimum change is quantified by the Entropy Ledger.

Free Will (Operational). Define $\text{Free}(t) := H(A_t | \text{Past, Ledger Info})$. Retro-resources can reduce Free but only by paying scarcity $(-\log p_{\text{succ}})$ or heat (ED). Thus there is “no free chronology”: influence against the arrow is always priced.

Notation and Proof Outlines

Loop-DPI sketch. Normalize the non-TP retro-map Π by conditioning on the heralded outcome. Apply a change-of-measure argument around the cycle and bound the Radon–Nikodym derivative by $1/p_{\text{succ}}$, yielding $\Delta I_{\odot} \leq -\log p_{\text{succ}}$ (bits). Finite accuracy adds a $-\log(1 - \varepsilon)$ term.

Entropy Ledger sketch. Consistency is enforced by projecting P_{hist} onto $\mathcal{C}$ in KL. The work cost of modifying distributions obeys $\langle W \rangle \geq kT D_{\text{KL}}(P \| P^*)$ by Landauer and nonequilibrium work relations.




FIG. 4. Surrogate demonstration of the single-shot strong converse: attempting rates above the Loop-DPI bound drives error toward one with blocklength.




FIG. 5. Single-shot (smoothed entropy) upper bounds on achievable loop bits per attempt compared to the Loop-DPI asymptote.




FIG. 6. Heatmap of bits-per-attempt as a function of measurement basis (θ, ϕ) with success-probability contours.