

Hexaware Practice Question Bank

(Aptitude + Coding + Technical + HR)

All questions below include answers/solutions so you can self-check without any paid tool. Use plain paper for aptitude, any free code editor (VS Code, or even an online compiler like programiz.com/onlinecompiler) for coding.

PART 1: APTITUDE

A. Quantitative Aptitude

Q1. A shopkeeper marks an item 40% above cost price and gives a 10% discount. Find his profit %. *Solution:* Let CP = 100. Marked price = 140. Discount 10% of 140 = 14. SP = 126. Profit = 26%. **Answer: 26%**

Q2. The simple interest on a sum for 3 years at 8% p.a. is ₹1,200. Find the sum. *Solution:* $SI = P \times R \times T / 100 \rightarrow 1200 = P \times 8 \times 3 / 100 \rightarrow P = 1200 \times 100 / 24 = 5000$. **Answer: ₹5,000**

Q3. A and B can do a piece of work in 12 and 15 days respectively. They work together for 4 days, then A leaves. In how many days will B finish the remaining work? *Solution:* A's rate = $1/12$, B's rate = $1/15$. Combined 4 days work = $4 \times (1/12 + 1/15) = 4 \times (9/60) = 36/60 = 3/5$. Remaining = $2/5$. B alone: $(2/5) / (1/15) = 6$ days. **Answer: 6 days**

Q4. A train 150m long crosses a pole in 15 seconds. Find its speed in km/hr. *Solution:* Speed = $150/15 = 10$ m/s = $10 \times 18/5 = 36$ km/hr. **Answer: 36 km/hr**

Q5. Find the average of first 50 natural numbers. *Solution:* Sum = $n(n+1)/2 = 50 \times 51/2 = 1275$. Average = $1275/50 = 25.5$. **Answer: 25.5**

Q6. In a mixture of 60 litres, milk and water are in ratio 2:1. How much water must be added to make the ratio 1:2? *Solution:* Milk = 40L, Water = 20L. Let x litres added: $40/(20+x) = 1/2 \rightarrow 20+x = 80 \rightarrow x = 60$. **Answer: 60 litres**

Q7. A sum of money doubles itself in 8 years at simple interest. In how many years will it become 4 times? *Solution:* Doubling means SI = P in 8 years $\rightarrow$ Rate = $100/8 = 12.5\%$. To become 4x, SI needed = 3P. Time = $3P \times 100 / (P \times 12.5) = 24$ years. **Answer: 24 years**

Q8. What is the probability of getting a sum of 8 when two dice are thrown?

Solution: Favorable outcomes: (2,6)(3,5)(4,4)(5,3)(6,2) = 5. Total = 36. Probability = $\frac{5}{36}$. **Answer: $\frac{5}{36}$**

Q9. If the price of sugar falls by 20%, by how much % should consumption increase to keep expenditure same? *Solution:* Increase % = $\frac{20}{(100-20)} \times 100 = 25\%$.

Answer: 25%

Q10. A boat goes 30 km upstream in 6 hours and 30 km downstream in 3 hours. Find speed of boat in still water and speed of stream. *Solution:* Upstream speed = 5 km/hr, Downstream = 10 km/hr. Boat speed = $\frac{(10+5)}{2} = 7.5$ km/hr. Stream = $\frac{(10-5)}{2} = 2.5$ km/hr. **Answer: Boat 7.5 km/hr, Stream 2.5 km/hr**

B. Logical Reasoning

Q11. Find the next number in series: 2, 6, 12, 20, 30, ? *Solution:* Differences: 4, 6, 8, 10, 12 → pattern $n(n+1)$. Next = 42. **Answer: 42**

Q12. If CODING is written as DPEJOH, how is FLYING written in the same code? *Solution:* Each letter shifted +1. F→G, L→M, Y→Z, I→J, N→O, G→H. **Answer: GMZJOH**

Q13. Blood relation: Pointing to a man, a woman says "His mother is the only daughter of my mother." How is the woman related to the man? *Solution:* Woman's mother's only daughter = the woman herself. So the man's mother is the woman. Woman is the man's **mother**.

Q14. Statement: All pens are pencils. All pencils are erasers. Conclusion: All pens are erasers. Valid or invalid? *Solution:* Valid (direct syllogism chain). **Answer: Valid**

Q15. Five friends A, B, C, D, E sit in a row. B is to the left of C but right of A. D is to the right of E and left of A. Find the order left to right. *Solution:* D, E constraint: D right of E, D left of A → E, D, A. A...B...C with B right of A, left of C → E, D, A, B, C. **Answer: E, D, A, B, C**

Q16. Odd one out: 3, 5, 7, 9, 11, 13 *Solution:* All are odd numbers except 9 is not prime (rest are prime). **Answer: 9**

Q17. A is facing north. He turns 90° clockwise, then 180°, then 90° anticlockwise. Which direction is he facing now? *Solution:* North→East(90cw)→West(180)→South(90 acw). **Answer: South**

C. Verbal Ability

Q18. Choose the correctly spelled word: (a) Recieve (b) Receive (c) Recievee (d) Receve **Answer: (b) Receive**

Q19. Find the error: "Neither of the two boys were present in the class." *Solution:* "Neither...nor" takes a singular verb. Should be "was." **Answer: "were" → "was"**

Q20. Synonym of "Meticulous": (a) Careless (b) Precise (c) Lazy (d) Rapid **Answer: (b) Precise**

Q21. Antonym of "Benevolent": (a) Kind (b) Generous (c) Malevolent (d) Charitable **Answer: (c) Malevolent**

PART 2: CODING PRACTICE (Easy-Medium, 2-3 problems expected in test)

Write these yourself in C/C++/Java/Python before checking the approach below. Use any free online compiler.

C1. Check if a number is prime

```
def is_prime(n):
    if n < 2:
        return False
    for i in range(2, int(n**0.5) + 1):
        if n % i == 0:
            return False
    return True
```

C2. Print all primes in a range (1 to N)

```
def primes_in_range(n):
    return [i for i in range(2, n+1) if is_prime(i)]
```

C3. Reverse a string without built-in reverse

```
def reverse_string(s):
    result = ""
    for ch in s:
        result = ch + result
    return result
```

C4. Check palindrome

```
def is_palindrome(s):  
    return s == s[::-1]
```

C5. Find the second largest element in an array

```
def second_largest(arr):  
    first = second = float('-inf')  
    for num in arr:  
        if num > first:  
            second = first  
            first = num  
        elif first > num > second:  
            second = num  
    return second
```

C6. Count vowels and consonants in a string

```
def count_vowels_consonants(s):  
    vowels = "aeiouAEIOU"  
    v = sum(1 for ch in s if ch in vowels and ch.isalpha())  
    c = sum(1 for ch in s if ch.isalpha() and ch not in vowels)  
    return v, c
```

C7. Check if two strings are anagrams

```
def is_anagram(s1, s2):  
    return sorted(s1) == sorted(s2)
```

C8. Find the factorial of a number (recursion)

```
def factorial(n):  
    if n == 0 or n == 1:  
        return 1  
    return n * factorial(n - 1)
```

C9. Fibonacci series up to N terms

```
def fibonacci(n):  
    a, b = 0, 1  
    result = []  
    for _ in range(n):  
        result.append(a)  
        a, b = b, a + b  
    return result
```

C10. Find duplicate elements in an array

```
def find_duplicates(arr):
    seen = set()
    duplicates = set()
    for num in arr:
        if num in seen:
            duplicates.add(num)
        seen.add(num)
    return list(duplicates)
```

C11. Rotate an array by k positions

```
def rotate_array(arr, k):
    k = k % len(arr)
    return arr[-k:] + arr[:-k]
```

C12. FizzBuzz

```
def fizzbuzz(n):
    for i in range(1, n+1):
        if i % 15 == 0: print("FizzBuzz")
        elif i % 3 == 0: print("Fizz")
        elif i % 5 == 0: print("Buzz")
        else: print(i)
```

Tip for the actual test: get a brute-force working version submitted before trying to optimize — partial credit exists, a broken "clever" solution scores zero.

PART 3: TECHNICAL MCQ / INTERVIEW QUESTIONS

OOP Concepts

- **Q:** What are the four pillars of OOP? **A:** Encapsulation, Abstraction, Inheritance, Polymorphism.
- **Q:** Difference between overloading and overriding? **A:** Overloading = same method name, different parameters, resolved at compile time. Overriding = subclass redefines parent method, resolved at runtime.
- **Q:** What is a constructor? Can it be private? **A:** Special method that initializes an object when created; yes, can be private (used in Singleton pattern).

DBMS

- **Q:** What is normalization? Explain 1NF, 2NF, 3NF briefly. **A:** Process of organizing data to reduce redundancy. 1NF: atomic values, no repeating groups. 2NF: 1NF + no partial dependency on composite key. 3NF: 2NF + no transitive dependency.
- **Q:** Difference between primary key and foreign key? **A:** Primary key uniquely identifies a row in its own table; foreign key references a primary key in another table to establish a relationship.
- **Q:** Write a SQL query to find the second highest salary from an Employee table.

```
SELECT MAX(salary) FROM Employee  
WHERE salary < (SELECT MAX(salary) FROM Employee);
```

- **Q:** Difference between DELETE, TRUNCATE, DROP? **A:** DELETE removes rows (can be rolled back, WHERE clause allowed), TRUNCATE removes all rows fast (no WHERE, resets identity), DROP removes the entire table structure.

Operating Systems

- **Q:** What is a deadlock? Name its four necessary conditions. **A:** A state where processes wait indefinitely for resources held by each other. Conditions: Mutual Exclusion, Hold and Wait, No Preemption, Circular Wait.
- **Q:** Difference between process and thread? **A:** Process is an independent program in execution with its own memory space; thread is a lightweight unit within a process sharing the same memory.
- **Q:** What is paging? **A:** A memory management scheme that eliminates the need for contiguous allocation by dividing memory into fixed-size pages.

Computer Networks

- **Q:** Name the 7 layers of the OSI model. **A:** Physical, Data Link, Network, Transport, Session, Presentation, Application.
- **Q:** Difference between TCP and UDP? **A:** TCP is connection-oriented, reliable, ordered; UDP is connectionless, faster, no guarantee of delivery.

Data Structures

- **Q:** Difference between array and linked list? **A:** Array has contiguous memory, fixed size, $O(1)$ access; linked list has non-contiguous memory, dynamic size, $O(n)$ access but $O(1)$ insertion/deletion at known position.
- **Q:** What is the time complexity of binary search? **A:** $O(\log n)$.

- **Q:** What is the worst-case time complexity of Quick Sort, and when does it occur?
A: $O(n^2)$, occurs when the pivot chosen is always the smallest or largest element (e.g., already sorted array with first/last element as pivot).

Output-prediction style (be ready to explain reasoning aloud)

```
int x = 5;
printf("%d %d %d", x++, x, ++x);
```

A: This is undefined/compiler-dependent behavior due to unspecified evaluation order of function arguments in C — good answer is to explain *why* it's ambiguous, not guess a single number.

PART 4: HR INTERVIEW — QUESTIONS TO PREPARE ANSWERS FOR

Prepare a 60–90 second spoken answer for each (don't memorize word-for-word, know your key points):

1. Tell me about yourself.
2. Why do you want to join Hexaware?
3. What do you know about Hexaware? (*IT services company, founded 1990, HQ Mumbai, strong in application transformation, cloud, BI, enterprise solutions — "Automate Everything, Cloudify Everything, Transform Customer Experiences"*)
4. What are your strengths and weaknesses?
5. Where do you see yourself in 5 years?
6. Are you willing to relocate or work rotational shifts?
7. Describe a challenge you faced in a team project and how you resolved it.
8. Why should we hire you over other candidates?
9. What is your biggest achievement so far?
10. Do you have any questions for us? (*always prepare 1–2, e.g., "What does the training program for new joiners look like?"*)

Structure tip: Use Situation → Action → Result for any "describe a time when..." question. Keep it factual and specific, not vague.

10-Day Schedule Using This Bank

Day	Task
1	GD topics (from earlier guide) + Verbal Q18-21 style practice (10 more of your own)
2	Quant Q1-5, redo until no errors
3	Quant Q6-10 + Logical Q11-14
4	Logical Q15-17 + full timed 20-question mock
5	Technical: OOP + DBMS questions, write your own answers before checking
6	Technical: OS + Networks + DSA questions
7	Coding C1-C6, write and run yourself
8	Coding C7-C12 + full mock coding round (3 problems, 45 min timer)
9	HR Q1-10, record yourself answering each once
10	Light review: redo only questions you got wrong all week, rest well

Note: these are practice-style questions built from commonly repeated aptitude/CS fundamentals and past Hexaware interview themes — not leaked actual test questions (companies rotate their bank). Master the pattern and reasoning, not the exact numbers.