

# SUBMITTAL FOR CHARLOTTE PIPE® HUBLESS CAST IRON SOIL PIPE AND FITTINGS

Date:									
Job Name:			Loca	Location:					
Engineer:	Con	Contractor:							
Scope: This specific (DWV), sew  Specification Hubless Case CISPI Stand Institute manufacture shall conform  Installation: Company a hydrostatica store compre injury or dea	er, and storm dr en: st Iron pipe and lard 301. All pipe and listed by N ed in the United m to ASTM C 15 shall comply with and shall conform lly tested after in essed air or gas ath.  Standards:	fittings shall be e and fittings shall be e and fittings sh SF® Internation States, and be 640, shall be man the latest instanto all applicationstallation to 10 in Cast Iron pig	manufactured from all be marked with al. Hubless Coupli certified by NSF® I anufactured in the allation instructions ble plumbing, fire, and ft. of head (4.3 psecore fittings. Doing	couplings usis intended for gray cast in the collective of the col	or use in no on and sha e trademar nform to CIS Heavy Dut s, and shall y Charlotte code requir WARNING	all conformate of the Conforma	n to ASTM ast Iron Stard 310, dium Dut if indicated Foundry The systement of the rest with the est with the content of the re- trice of the re- ork conform to the	M A 88 Soil P shall by could be shall b	88 and ipe be uplings all be asport/severe
ASTM C 564 CISPI 301: CISPI 310: ASTM C 127 ASTM C 154	4: Rubber Hubless Hubless 77: Hubless	Cast Iron Soil I Couplings for C Couplings	st Iron Soil Pipe ar Pipe and Fittings Cast Iron Soil Pipe and Heavy Duty Co	and Fittings	Submittal #: CDC: Job #: Reviewed by: Date: Vendor: Product Description:	37 I-PLUI 424 EDUA 10/03/ REVIS		MADE IN	
1/4 Bend	1/8 Bend	Wye	Combination	DIME A Inside		Gasket			
San Tee	San Cross	Test Tee	Reducer	Barrel Diameter  Size  B  1 1/2  1.50 ± .0  2 1.96 ± .0  3 2.96 ± .0  4 3.94 ± .0	9 2.35 ± .09 9 3.35 ± .09 9 4.38 + .09	Outside Diameter Spigot  M  1.96 ± .06 2.41 ± .09 3.41 ± .09 4.44 ± .09	Spigot	of F Barrel	Positioning Lug  W 1.13 1.13 1.13 1.13
"P" Trap	Blind Plug	Figure Eight	Two-Way Cleanout	5 4.94 ± .0 6 5.94 ± .0 8 7.94 ± .1 10 10.00 ± .1	05 9	5.36 ± .09 6.36 ± .09 8.44 ± .09 10.62 ± .09	.31 .19 .31 .19 .31 .23 .31 .28	.15 .15 .17 .22	1.50 1.50 2.00 2.00
	Not all fitting	nigure Eigin	ivvo-vvay Cleanout	12 11.94 ± .0 15 15.11 ± .0		12.62 ± .13 16.12 ± .13	.31 .28 .31 .36	.22	2.75 2.75

Note: Charlotte Pipe does not recommend or warrant installations joined with unshielded hubless couplings.



# **Certifications**

This is to verify that products manufactured by Charlotte Pipe and Foundry, Cast Iron Division, are manufactured in the United States and conform to the following standards:

### **SERVICE HUB AND SPIGOT PIPE AND FITTINGS**

All cast iron soil pipe and fittings shall be marked with the collective trademark of the Cast Iron Soil Pipe Institute (CISPI). ASTM A 74

Listed by NSF® International to the UP Code ISO 9001:2008 Certified

# **EXTRA HEAVY HUB AND SPIGOT PIPE AND FITTINGS**

All cast iron soil pipe and fittings shall be marked with the collective trademark of the Cast Iron Soil Pipe Institute (CISPI). ASTM A 74

Listed by  $NSF^{\$}$  International to the UP Code ISO 9001:2008 Certified

#### **HUBLESS PIPE AND FITTINGS**

All cast iron soil pipe and fittings shall be marked with the collective trademark of the Cast Iron Soil Pipe Institute (CISPI). CISPI Standard 301
ASTM A 888
Listed by NSF® International to the UP Code
ISO 9001:2008 Certified

#### **HUBLESS COUPLINGS**

CISPI Standard 310 ASTM C 1277 Certified by NSF® International

## **HUBLESS HEAVY DUTY COUPLINGS**

Meets ASTM C 1540

#### **COMPRESSION GASKETS**

ASTM C 564 CISPI HSN 85

Very truly yours,

Hooper Hardison, President

Notary Public

My commission expires July 02, 2022

Verii L. Wilson

Jage Handrson

TERRI L WILSON NOTARY PUBLIC UNION COUNTY, NC My Commission Expires 7-2-2022

LC-CI (7-18-18)

