

Lập trình hướng đối tượng

Biên soạn: Nguyễn Thị Tuyết Hải

Email: tuyethai@ptithcm.edu.vn

Chapter 9: Collections

9.1 The Java Collections Framework

9.2 Concrete Collections

9.3 Maps

9.4 Views and Wrappers

9.5 Algorithms

9.6 Legacy Collections

9.1 The Java Collections Framework

9.1.1 Separating Collection Interfaces and Implementation

E.g.,

- Interface tells **nothing** about how the queue is **implemented**.

```
public interface Queue<E>{  
    void add(E element);  
    E remove();  
    int size();  
}
```


- Implementation:

```
public class CircularArrayQueue<E> implements Queue<E> ...
```

```
public class LinkedListQueue<E> implements Queue<E> ...
```

- When use a queue, don't need to know which implementation is actually used once the collection has been constructed.

```
Queue<Customer> expressLane = new CircularArrayQueue<>(100);  
expressLane = new LinkedListQueue<>();
```



9.1 The Java Collections Framework

9.1.2 The Collection Interface

Two fundamental methods:

```
public interface Collection<E> {  
    boolean add(E element);  
    Iterator<E> iterator();  
    ...  
}
```

9.1.3 Iterators

```
public interface Iterator<E> {  
    E next();  
    boolean hasNext();  
    void remove();  
    default void forEachRemaining(Consumer<? super E> action);  
}
```

9.1 The Java Collections Framework

9.1.3 Iterators

- inspect all elements in a collection:
 - request an iterator
 - keep calling the next method while hasNext returns true
- “for each” loop works with any object that implements the Iterable interface
 - collection interface extends the Iterable interface

```
Collection<String> c = . . . ;
Iterator<String> iter =
c.iterator();
while (iter.hasNext()){
    String element = iter.next();
    // do something with element
}

// OR
for (String element : c) {
    do something with element
}
```


9.1 The Java Collections Framework

9.1.3 Iterators

- Java iterators as being between elements.
- `next()`, the iterator
 - jumps over the next element,
 - returns a reference to the element that it just passed

```
// remove 1st element
Iterator<String> it = c.iterator();
// skip over the first element
it.next();
// now remove it
it.remove();
```

```
//remove two adjacent elements
it.remove();
it.next();
it.remove();
```




9.1.4 Generic Utility Methods

- Collection and Iterator interfaces are generic
- Collection interface declares quite a few useful methods that all implementing classes must supply.
- Class AbstractCollection leaves the fundamental methods size and iterator abstract


9.1.5 Interfaces in the Collections Framework

- The interfaces of the collections framework that implement the Collection interface
- Two fundamental interfaces for collections: Collection and Map.



9.2 Concrete Collections

- Classes in the collections framework: extend abstract classes.




9.2.2 Array Lists

- an ordered collection
- visiting the elements:
 - an iterator
 - random access with methods `get` and `set`

9.2.1 Linked Lists


- Removing/inserting an element from/in the middle of an array: so expensive
- In Java, all linked lists are doubly linked: link to next, previous element.



9.2.1 Linked Lists

```
List<String> staff = new LinkedList<>();  
// LinkedList implements List  
staff.add("Amy");  
staff.add("Bob");  
staff.add("Carl");
```


```
Iterator iter = staff.iterator();  
String first = iter.next(); // visit first element  
String second = iter.next(); // visit second element  
iter.remove(); // remove last visited element
```



9.2.1 Linked Lists

```
List<String> staff = new LinkedList<>();  
staff.add("Amy");  
staff.add("Bob");  
staff.add("Carl");
```

```
ListIterator<String> iter =  
staff.listIterator();  
iter.next(); // skip past first element  
iter.add("Juliet");
```




9.2.3 Hash Sets

Hash table helps to find objects quickly

In Java, hash tables are implemented as arrays of linked lists.

- each list is called a *bucket*.
- find the place of an object in the table:
 - compute its hash code
 - reduce it modulo the total number of buckets.



9.2.3 Hash Sets

HashSet class implements a set based on a hash table.

- add elements with **add()**.
- contains(): make a fast lookup to see if an element is already present in the set.
- iterator visits all buckets in turn in a random order.

Full code: `set/SetTest.java`

9.2.4 Tree Sets

- TreeSet class is similar to the hashset with one added improvement - a sorted collection.
- Every time an element is added to a tree, it is placed into its proper sorting position.
 - The elements must implement the Comparable interface for comparing them.
- Adding an element to a tree is slower than adding it to a hash table.

Table 9.3 Adding Elements into Hash and Tree Sets

Document	Total Number of Words	Number of Distinct Words	HashSet	TreeSet
<i>Alice in Wonderland</i>	28195	5909	5 sec	7 sec
<i>The Count of Monte Cristo</i>	466300	37545	75 sec	98 sec

9.2.5 Queues and Deques

- A queue allows efficiently to add elements at the tail and remove elements from the head.
- A double-ended queue, or *deque*, allows efficiently to add or remove elements at the head and tail.
- Adding elements in the middle is not supported.

9.2.6 Priority Queues

- A priority queue retrieves elements in sorted order after they were inserted in arbitrary order.
 - whenever calling the remove method, you get the smallest element currently in the priority queue.
- A priority queue can either hold elements of a class that implements the Comparable interface or a Comparator object
- A typical use for a priority queue is job scheduling.
 - Each job has a priority.
 - Jobs are added in random order.
 - Whenever a new job can be started, the highest priority job is removed from the queue.

9.3 Maps

- A set is a collection that lets you quickly find an existing element. However, you need to have an exact copy of the element to find.
- Usually, you have some key information, and you want to look up the associated element.

The map data structure serves that purpose.

9.3.1 Basic Map Operations

Two general-purpose implementations for maps: `HashMap` and `TreeMap`

A hash map hashes the keys whereas a tree map uses an ordering on the keys to organize them in a search tree.

Full code: `map/MapTest.java`

```
Map<String, Employee> staff = new HashMap<>();  
// HashMap implements Map  
Employee harry = new Employee("Harry Hacker");  
staff.put("987-98-9996", harry);
```

```
String id = "987-98-9996";  
e = staff.get(id);  
// gets harry
```

```
staff.forEach((k, v) ->  
System.out.println("key=" + k + ", value=" + v));
```

9.3.3 Map Views

- The collections framework does not consider a map itself as a collection.
- Obtain views of the map - objects that implement the Collection interface
- There are three views:
 - the **set** of keys: `Set<K> keySet()`
 - the collection of values (which is not a **set**): `Collection<V> values()`
 - the set of key/value pairs: `Set<Map.Entry<K, V>> entrySet()`

```
Set<String> keys = map.keySet();
for (String key : keys){
    // do something with key }

for (Map.Entry<String, Employee> entry :
staff.entrySet()) {
    String k = entry.getKey();
    Employee v = entry.getValue();
    // do something with k, v
}
```